

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/EH/2023/SZ/ / 9

Dated.1.7.1.0.1/2023

## FIRE SAFETY CERTIFICATE

Certified that the Restaurant in the Name & Style of M/s LAZEEZ AFFAIRE, located 6/48, Malcha Marg Market, Chankyapuri, New Delhi 110021 comprised of Basement (Storage) ground plus one upper floor, But Restaurant is at Ground & First Floor only) owned/occupied by Ms. Sunita Sukhija was issued Fire Safety Certificate by this department vide letter no. F6/DFS/MS/EH/SZ/2020/07 dated 03/01/2020. The restaurant premise was re-inspected by the officer concerned of this department on 05/01/2023 in the presence of Mr. Puneet Kumar and found that the said premise have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy Class D "Assembly Building" as above with effect from 1.7../.pl.../2023 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on [7 / 0] /2023 at New Delhi by

(SUNIL CHAWDHARY) DY. CHIEF FIRE OFFICER (SZ) DELHI FIRE SERVICE

Copy to: -


1. The Dy. Health Officer, Public Health Department, South Zone, Green Park, Delhi- 110016 (Ref. MHA Portal ID 202211220540 dated 23/11/2022)

## Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The basement shall be used as per the provisions of BBL /NBC Part- IV.
- 5. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 6. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

N25

9



INSPECTION REPORT Same & address of the building: M/s Lazeez Affaire, 6/48, Malcha Marg Market, Chankyapuri, Delhi Group D Assembly Building Inl type of Occupancy Comprised of : B+G+ One upper floor, restaurant at GF & FF only type of Case Details of Previous NOC : F6/DFS/MS/EH/SZ/2020/07 dated 03/01/2020 Fire Safety directives letter No : Nil Date of inspection : 05/01/2023 8 Name of Inspecting Officer : DO (South) & ADO (BCP) Name and designation of officers From the building side : Mr. Puneet Kumar 10. Year of Construction : 1999 11. Applicant's letter No. : MHA Portal ID 202211220540 dated 23/11/2022 Minimum Standards on fire prevention S. No. Old NOC Provided at site and fire safety U/R 33 Remarks Requirement MR/NMR 1. Access to building Road width Approachable 5m MR(old case) Gate width -NA--NA--NA-Width of internal road -NA--NA-Number, Width, Type & Arrangement of Exits -NA-2. a. Number of staircases Upper Floors Required 01 MR(old case) Basements Required 02 MR(old case) b. Width of staircases Upper Floor Required 1.20m MR(old case) **Basements** Required 1.10m & 1.05m MR(old case) c. Protection of exits Fire check door -NA--NA--NA-Pressurization -NA--NA--NAd. No. of continuous staircases to terrace e. -NA-One -NA-Width of Corridor -NA--NA--NA-Door Size Two Exit Provided at GF only MR(old case) 3. Compartmentation Fire check door -NA--NA--NA--NA-Sealing of electrical shafts -NA--NA--NA-Fire Rating of shaft door -NA--NA--NA-Water Curtain -NA--NA--NA--NA--NA-Fire Dampers 4. Smoke Management System Exhaust Fan provided 30 ACPH **Basements** MR Exhaust Fan provided 12 ACPH MR Upper floors 5. Fire Extinguishers 12-No's MR Total numbers Types ISI ABC-12 No's MR Marked IS marking CO<sub>2</sub>-Nil MR 6. First-Aid Hose Reels Total numbers on each floor Provided MR One MR Length of hose reel hose 30m Nozzle diameter 30m MR 5mm 5mm 7. Automatic fire detection and alarming system -NA-Type of detectors -NA-Smoke & Heat



	<ul> <li>Location of Main Panel</li> <li>Location of Repeater Panel</li> </ul>		A- Basen	
			ANA	
	Alternate source of power	-N.		
-	Hooters' Location	-NA		
8		Requi		141
9		-NA	-NA	N
1	0. Automatic Sprinkler System			
	Basement	Requi	red Provide	ed MI
	<ul> <li>Upper Floors</li> </ul>	-NA		
	<ul> <li>Sprinkler above false ceiling</li> </ul>	-NA	-NA-	
11	. Internal Hydrants			
	<ul> <li>Size of riser/down-comer</li> </ul>	100mi	n Provide	d MR
	<ul> <li>Number of hydrants per floor</li> </ul>	one	Provide	
1	Hose Box	one	Provided	d MR
12.		•		
	<ul> <li>Total number of hydrants</li> </ul>	-NA-	-NA-	-NA-
12	Hose Box	-NA-	-NA-	-NA-
13.		•		
	Ground Level			
	Discharge of main Pump	-NA-	-NA-	-NA-
	Head of Main pump	-NA-	-NA-	-NA-
	Number of main pumps	-NA-	-NA-	-NA-
	Jockey Pump out put	-NA-	-NA-	-NA-
	Jockey pump head	-NA-	-NA-	
	Standby Pump out put	-NA-	-NA-	-NA-
	Standby Pump Head	-NA-	-NA-	-NA-
	➤ Auto Starting/Manual Stopping	-NA-	-NA-	-NA-
		1111	-INA-	-NA-
	<ul> <li>Terrace level</li> <li>Discharge of pump</li> </ul>	Boosting	450 I DM 0 100	
	Head of the pump	Doosting	450 LPM & 180 LPM	MR
	Power Supply	-NA-	35m	MR
	Auto Starting of pump	Required	Provided	MR
4.	Captive Water Storage for fire fighting	Required	Provided	MR
	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> </ul>	-NA-	-NA-	-NA-
	Fire service inlet	-NA-	-NA-	-NA-
	Access to tank	-NA-	-NA-	
	Overhead Tank capacity	-NA-	-NA-	-NA-
	Exit Signage.	5,000 Lts	5,000 Lts.	
	Provision of Lifts.	Required	Provided	MR MR
-				IVIK
	Pressurization of Lift Shaft	-NA-	-NA-	
	Pressurization of Lift lobby	-NA-		-NA-
	<ul> <li>Communication In lift Car</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Fireman's Grounding Switch</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Lift Signage</li> </ul>	-NA-	-NA-	-NA-
S	Standby power supply		-NA-	-NA-
R	Refuge Area.	Required	Provided	MR
	Total Area			17117
	> Location	-NA-	-NA-	
Fi	ire Control Room	-NA-	-NA-	-NA-
	or reduil		11/7-	-NA-
1	Detector System Panel			
1	a Pi	-NA-		
	Flow Switch Panel	-1 <b>V</b> / <b>A</b> -	-NA-	-NA-



• PA System Panel	-NA-	-NA-	-NA-
Battery backup Building Floor Plans	-NA-	-NA-	-NA-
	-NA-	-NA-	-NA-
ecial Fire Protection System for Protection	-NA -		

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/EH/SZ/2020/07 dated 03/01/2020, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspection Officer

Name: Sh. Manoj Kumar Sharma

Design: DO (South)

Signature of the Inspecting Officer

Name: Sh. Rajesh Kumar

Design: ADO (BCP)

Dy. CFO(SZ)

As approved, F.T. Letter û protub for Jene syndine Pl.

bloaded shah