GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2023/ 23

Dated: 2.4./.o.J../2023

FIRE SAFETY CERTIFICATE

Certified that the R. Continental Guest House located at 9966-71, Gali No.-4, Desh Raj Bhatia Marg, Multani Dhanda, Pahar Ganj, New Delhi, is comprised of stilt + ground + 03 floors, stilt – parking, ground floor to 3rd floor (04 guest rooms at each floor), total 16 guest rooms up to third floor. The FSC was earlier granted by this department vide letter No.F6/DFS/MS/GH/2020/NDZ/16 dated 10/01/20 for 16 guest rooms up to third floor only, Now, the premises was re-inspected by the officer concerned of this department on 18/01/23 in the presence of Sh. Kamal and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, (Sub Division-A-1) stilt – parking, ground floor to 3rd floor (04 guest rooms at each floor) total 16 guest rooms up to third floor only, with effect from .2.4../2023 for period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued **2.4**./.**0.1**./2023 at New Delhi by.

Dy. Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Commissioner of MCD, Civic Centre, New Delhi. to kindly ensure the occupancy as detailed above.
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi online ID No. 2022120721127 dated 04/01/23. Email id < tishalamba25@gmail.com> dated 10/01/23.
- 3. The Manager, R. Continental Guest House, 9966-71, Gali No.-4, Desh Raj Bhatia Marg, Mulatani Dhanda, Pahar Ganj, New Delhi.

Condition for the validity of Fire Safety Certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- The trained fire fighting staff should be available round the clock.
- The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.
- 9. Any flammable material for interior decoration is prohibited.

1/1/6

	\sim	110	
INSPEC	ΤI	ON	REPORT

 Name & address of the building R. Continental Guest House located at 9966-

71, Gali No.-4, Desh Raj Bhatia Marg, Mulatani Dhanda, Pahar Ganj, New Delhi

Residential, Sub Division-A-1 2. Type of occupancy:-

Stilt +G + 03 floors (total 16 Guest rooms) Stilt – parking, Gr. to 03rd floor (04 guest room at

each floor)

Renewal 3. Type of case:-

No. F6/DFS/MS/GH/2020/NDZ/16 dated 4. Details of previous FSC:-

10/01/20.

5. Fire safety directives No.-N/A 18/01/23

6. Date of inspection:-Sh. Ravinder Singh (ADO/CC) 7. Name of the inspecting officer:-

8. Name & designation of officer

From the building side:-9. Year of construction:-

10. Applicant's letter No:-

Sh. Kamal

2006

ID No. 2022120721127 dated 04/01/23.

Email id < tishalamba25@gmail.com> dated 10/01/23.

r 11 0 2 r I

3,

11/

cat ictio ilab ins fied eate lara vaila ystru newa S Ce Jecon

		Email iu < u.	Silalailibazo@g.iia	Old Case
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building			MR
	1) Road width	N/A	06 mtr. Approx.	N/A
	2) Gate width	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Ari	angement of E	Cxits	
	A. Number of staircases			MR
	1. Upper floors	01 Nos.	01 Nos.	N/A
	2. Basements	N/A	N/A	IN/A
	B. Width of staircase		1.40 to 1.50 mtr.	MR
	1. Upper floors	0.80 mtr.	N/A	N/A
	2. Basements	N/A	N/A	IVA
	C. Protection of exits	DI/A	N/A	N/A
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	01	MR
	D. No. of continuous	01	01	l Milk
	staircase to terrace	N/A	N/A	N/A
	E. Width of corridor	N/A	206 cms x	N/A
	F. Door size	14/14	80cms	
3.	Compartmentation			
3.	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System			
	1) Basements	30 ACPH	N/A	N/A
	2) Upper floors	12 a/c per hour	Natural/exhaust fan	MR

NIT

Fire Extinguishers			
2) Tymes		10 Nos	MR
	ABC & CO		2 MR
3) 1SI marking	Required		MR
First-Aid Hose Reel		Trovided	IVIK
1) Total number of each	01	0.1	MR
			IVIX
2) Length of hose reel hose	30 mtr.	30 mtr.	MR
3) Nozzle diameter	05 mm	0.5	MR
Automatic Fire Detection & Alarming System			IVIIC
1) Type of detectors Co type	Required		MR
2) Location of main panel	Ground floo		MR
3) Location of repeater pane	l N/A		N/A
4) Alternate source of power	· Required	Provided	MR
5) Hooter's Location	At each floor		MR
MOEFA	Required		MR
Public Address System	Required		MR
Automatic Sprinkler System	m	Tiovided	IVIK
1) Basement		N/A	N/A
2) Upper floors			N/A N/A
3) Sprinkler above false			N/A N/A
ceiling	1	13/74	III/A
Internal Hydrants			
1) Size of riser/down-comer	N/A	N/A	N/A
2) Number of hydrants per			N/A
floor		1	
3) Hose box	N/A	N/A	N/A
Yard Hydrants			1
1) Total number of hydrants	N/A	N/A	N/A
2) Hose box	N/A	N/A	N/A
Pumping Arrangement			
Ground level	N/A	N/A	N/A
a) Discharge of main	N/A		N/A
	N/A	N/A	N/A
		N/A	N/A
		N/A	N/A
	450 LPM	450 LPM	MR
/			MR
		Provided	MR
0) 10::010:1	1 Coquinou	Provided	MR
	1100		
Janting Water Storage for Ein	e Fighting	ı	
Captive Water Storage for Fire	e Fighting	N/A	N/A
	2) Location of main panel 3) Location of repeater pane 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box Yard Hydrants 1) Total number of hydrants 2) Hose box Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump output g) Stand by pump head f) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump	2) Types 3) ISI marking First-Aid Hose Reel 1) Total number of each floor 2) Length of hose reel hose 3) Nozzle diameter Automatic Fire Detection & Alarming Sy: 1) Type of detectors Co type 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box Vard Hydrants 1) Total number of hydrants N/A 2) Hose box N/A Pumping Arrangement 1) Ground level A) Discharge of main pump b) Head of main pump b) Head of main pump b) Ground by pump out put c) Number of main pump b) Head of main pump b) Head of main pump b) Head of main pump c) N/A c) Number of main pump b) Head of main pump c) N/A c) Number of main pump b) Head of main pump c) N/A c) Number of main pump b) Head of pump out put c) N/A c) Number of main pump b) Head of pump out put c) N/A c) Number of main pump b) Head of pump out put c) N/A c) Number of main pump b) Head of pump out put c) N/A c) Number of main pump b) Head of pump out put c) N/A c) Number of main pump b) Head of pump out put c) N/A	2) Types 3) ISI marking Required First-Aid Hose Reel 1) Total number of each floor 2) Length of hose reel hose 3) Nozzle diameter 1) Type of detectors Co type 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location Automatic Sprinkler System 1) Basement 2) Upper floors Automatic Sprinkler System 1) Basement 1) Basement 1) Basement 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box N/A

2/18

	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	5000 ltr.	5000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any: 01 CO ₂ & 01 Al near electric panel.	tion of special uisher provided	MR	

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved, we may renew the FSC issued vide letter no. No. F6/DFS/MS/GH/2020/NDZ/16 dated 10/01/20, up to third floor only, under rule 35 of the Delhi Fire Service rules 2010. Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Designation :- ADO (CC)

MR MR MR