



## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/EH/2023/SZ/ 2 8

Dated. 3.0.10 1./2023

## FIRE SAFETY CERTIFICATE

Certified that the Restaurant in the Name & Style of M/s DIABLO located at D-1, Blk-D, H-5/12, Kalka Das Marg, Mehrauli, New Delhi 110030 comprised Ground Floor only owned/occupied by Unit of First Fiddle F & B Pvt Ltd was issued Fire Safety Certificate by this department vide letter no. F6/DFS/MS/EH/2020/SZ/08 dated 06/01/2020. The restaurant premise was re-inspected by the officer concerned of this department on 21/01/2023 in the presence of Mr. Mahinder and found that the said premise have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy Class D "Assembly Building" (Restaurant is running at Ground floor only) as above with effect from 3.0./.b.l../2023 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 30 / 1 /2022 at New Delhi by

(SUNIL CHAWDHARY) DY. CHIEF FIRE OFFICER (SZ) DELHI FIRE SERVICE

## Copy to: -

 The Dy. Health Officer, Public Health Department, South Zone, Green Park, Delhi- 110016 (Ref. MHA Portal 2023010900300 dated 09/01/2023)


## Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 5. The basement shall be used as per the provisions of BBL /NBC Part- IV.
- 6. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of 2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

17

	INSPECTIO	N REPORT			
1	Name & Address of the Building		Init of First Fig. 7. a	*Hilliani	
			Init of First Fiddle F &	B Pvt Ltd) a	
2	Type of Occupancy	D-1, Blk-D, H-5/12, Kalka Das Marg, Mehrauli New Delhi 110030			
3	Building Comprised of	Group-D Assembly Building (Eating House)			
4	Type of Case	Ground floor only			
5	Details of Previous NOC	Renewal			
6	Fire Safety Directives Letter No	F6/DFS/MS/EH/	2020/SZ/08 dated 06/	01/2020	
7	Date of Inspection	Nil			
8		21/01/2023			
9	Name of the Inspecting Officers	Sh. Rajesh Kumar ADO (BCP)			
	Name & Designation of Officers from the building side	Mr. Mahinder			
10	Year of construction				
11	Applicant letter No.	2013 Restt. Running at Ground Floor only			
	Applicant letter No.	MHA Portal 2023010900300 dated 09/01/202			
S. No.	Minimum standards on Fire Prevention			Remarks	
	and Fire Safety U/R 33	Requirements	1 Tovided at Site	MR/NMR	
1	Access to Building.			MICHAIN	
	Road width	06 mtr	06 mtr	MR	
	Gate width	N/A	About on road	N/A	
	Width of internal road	N/A	N/A	N/A	
2	Number, width, type & arrangement of ex		IV/A	IV/A	
	a) Number of Staircase				
	<ul><li>Upper floors.</li><li>Basement floor.</li></ul>	N/A	N/A	N/A	
	b) Width of Staircase	N/A	N/A	N/A	
	<ul><li>Upper floors</li><li>Basement floor</li></ul>	NA	N/A	N/A	
	Basement Hoor	N/A	N/A	N/A	
	c) Protection of exits				
	Fire check door	N/A	N/A	N/A	
	Pressurization	N/A	N/A	N/A	
	d) No. of continuous staircase to terrace	N/A	N/A	N/A	
	e) Width of corridor	N/A	N/A	N/A	
	f) Door size	02 m & 1.0 mtr	02 mtr each	MR	
3	Compartmentation.				
	Fire check door.	Required	Provided	MR	
	Sealing of electrical shafts.	N/A	N/A	N/A	
	Fire rating of shaft door.	N/A	N/A	N/A	
	Water curtain	N/A	N/A	N/A N/A	
	Fire dampers.	N/A	N/A	-	
4	Smoke Management system.	1471	IV/A	N/A	
	Basement	NA	N/A	N/A	
	Upper floors	12 ACPH	Provided	MR	
5	Fire Extinguishers.				
	Total numbers	Required	06 Nos	MR	
	<ul> <li>Types</li> </ul>	ABC/CO <sub>2</sub>	ABC- & CO <sub>2</sub>	MR	
	ISI Marking	ISI marked	Provided	MR	
6	First Aid Hose Reels.				
•					
	<ul> <li>Total numbers on each floor.</li> </ul>	One			

M



1	a Langth of has small have	•		-
	Length of hose-reel hose.	30m	Provided	MR
_	Nozzle Diameter	5mm	Provided	MR
7	Automatic fire detection & alarming system	1.		
	Type of detectors	N/A	Smoke type	N/A
	Location of Main Panel	N/A	Ground floor	N/A
	Location of Repeater Panel	N/A	N/A	N/A
	Alternate source of power	N/A	Provided	N/A
	Hooter's location	N/A	Near exit	N/A
8	MOEFA	Required	Provided	MR
9	Public Address System	N/A	N/A	N/A
10	Automatic Sprinkler System			IVA
	Basement	N/A	N/A	N/A
	<ul> <li>Ground/ upper floors.</li> </ul>	N/A	N/A	N/A
	<ul> <li>Sprinkler above false ceiling</li> </ul>	N/A	N/A	N/A
11	Internal Hydrants.	1471	IN/A	IN/A
	Size of Riser/Down-comer	100 mm	Dravidid	) (D
	Number of Hydrant per floor	One	Provided	MR
	Hose box.		Provided	MR
12	Yard Hydrants.	One	Provided	MR
	Total number of hydrants.	27/4		
	Hose box.	N/A	N/A	N/A
13	Pumping arrangements.	N/A	N/A	N/A
	Ground Level			
	Discharge of main pump.	NT/ A		
	<ul><li>Head of main pump.</li></ul>	N/A N/A	N/A	N/A
	> Number of main pumps.		N/A	N/A
	> Jockey Pump output.	N/A N/A	N/A	N/A
	> Jockey Pump head.	N/A	N/A N/A	N/A
	Standby Pump output.	N/A	N/A N/A	N/A
	Standby Pump head.	N/A	N/A	N/A
	Auto Starting/Manual Stopping.	N/A	N/A	N/A
	Pump house access.	N/A	N/A	N/A N/A
	Terrace Level	14/11	11//A	IN/A
	> Discharge of pump.	450 LPM	Provided	MD
	<ul><li>Head of pump.</li></ul>	40m	Provided	MR
	Power supply.	Required	Provided	MR
	Auto starting of pump.	Required		MR
14	Captive water storage for fire fighting.	Required	Provided	MR
14		NI/A	N/4	
	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> </ul>	N/A N/A	N/A	N/A
	Fire Service Inlet.	N/A N/A	N/A	N/A
	Access to tank.	N/A N/A	N/A	N/A
	Overhead tank capacity.		N/A	N/A
15		20,000 Ltrs	Provided	MR
16	Exit Signage.  Provision of Lifts.	Required	Provided	MR
10				
	Pressurization of lift shaft.	N/A	N/A	N/A
	<ul><li>Pressurization of lift lobby.</li><li>Communication in lift car.</li></ul>	N/A	N/A	N/A
	• Fireman's switch.	N/A	N/A	N/A
	<ul> <li>Lift signage.</li> </ul>	N/A	N/A	N/A
17		N/A	N/A	N/A
17	Standby Power Supply	Required	Provided	MR

N/9

Homer My France

18	Refuge Area	/ ( )	·HAQ	1 section.
	Total area			
	• Location	N/A	N/A	
19	Fire Control Room.	N/A		N/A
			N/A	N/A
	Beteetor system panel	N/A		
	riow switch panel		N/A	N/A
	PA system panel.	N/A	N/A	N/A
	<ul> <li>Battery backup.</li> </ul>	N/A	N/A	N/A
	Building floor plan.	N/A	N/A	N/A
20	Special Fire Protection System for the	N/A	N/A	N/A
	Protection of special Risk, if any.	N/A	N/A	N/A

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Rajesh Kumar Designation: ADO / BCP

DO (SD)

mill minn

m6-145

ero(dr). F.

A DO (1317)

to approved, F.T. tettel.

Your synature

protop for

27/1/2013

DycFols2

Uploaded

A.

M.S. Cell