

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE : NEW DLEHI - 110 001

No. F.6/DFS/MS/Motel/2023/SZ/ 109

Dated: 97/02/2023

## **FIRE SAFETY CERTIFICATE**

Certified that **The Nitesh** located at Gate No-2, NH-8, Near Shiv Murti, Khasra no 22/23 (4-16) 24 (4-16) 22/2 (3-16) 33/4 (4-16), 7 (0-8) Village Samalkha, Delhi comprised of Basement (Storage & Service), Ground (Restaurant, Banquet, Bar & 15 Guest Rooms) & 1<sup>st</sup> Floor (15 Guest Rooms) Total 30 Guest Rooms owned/occupied by A Unit of J.J.V Marketing & Hotels Pvt Ltd was issued FSC by this department vide letter No. F6/DFS/MS/Motel/SZ/2018/352 dated 06/03/2018. The premise was re-inspected by the officer concerned of this department on 15/02/2023 in the presence of Ms. Anjali (GM) and found to have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010and that the building is fit for occupancy **class A "Residential Building "(Motel) Building** with effect  $\frac{1}{2}$  /  $\frac{02}{2}$  /2023 for a period of **three years** in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010.

Issued on 27 02 2023 at New Delhi by.

(SUNIL CHAWDHARY) CHIEF FIRE OFFICER

Copy to:-

1. The Joint. C.P. (Lic/Branch), 1<sup>st</sup> Floor P. S. Defence Colony, New Delhi-110049. (Ref. MHA Portal ID 2022120721124 dated 07/12/2022)

## Conditions for the validity of fire safety certificate:

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. The basement shall be used as per the provisions of BBL /NBC Part- IV
- 5. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="http://delhi.gov.in/wps/wcm/connect/doit\_fire/FIRE/Home/Forms">http://delhi.gov.in/wps/wcm/connect/doit\_fire/FIRE/Home/Forms</a>
- 6. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."



**INSPECTION REPORT** Name & address of the building

The Nitesh (A Unit of J.J. V Marketing & Hotels Pvt Ltd,

Gate No-2, NH-8, Near Shiv Murti, Kh. No 22/23 (4-16) 24 (4-16) 22/2 (3-16) 33/4 (4-16, 7 (0-8) Village Samalkha, Delhi

Type of Occupancy : Group A "Residential" (Motel) Building

Comprised of : Basement + GF + 1st Floor

4. Type of Case : Renewal

5. Details of Previous NOC : F6/DFS/MS/2019/Motel/1735 dated 06/09/2019

6. Fire Safety directives letter No : F6/MS/DFS/GH/2002/995 Dated 24/06/2002 7. Date of inspection

8. Name of Inspecting Officer : 15/02/2023

: DO (South) & ADO (BCP)

9. Name and designation of officers From the building side


10. Year of Construction : Ms. Anjali (GM) : 2009

11. Applicant's letter No. : MHA Portal ID 2022120721124 dated 07/12/2022

No	and	imum Standards on fire prevention fire safety U/R 33	Old NOC Requirement	Provided at site	Remarks MR/NMR	
l	Acc	ess to building	•		WINNIK	
		Road width				
		• Gate width	9m	Provided	MR	
		Width of internal road	5m	Provided	MR	
2.	Nui	mber, Width, Type & Armon	-NA-	NA	-NA-	
	a. N	umber of staircases	Exits			
		Upper Floors	D'			
		Basements	Five	Provided	MR	
	b. V	Vidth of staircases	Five	Provided	MR	
		Upper Floor	1.25	-		
		Basements	1.25 mtr	Provided	MR	
	c. P	rotection of exits	1.25 mtr	Provided	MR	
		Fire check door	Dogwing 1	7		
		Pressurization	Required -NA-	Provided	MR	
	d.	No. of continuous staircases to terrace	02 Nos	-NA-	-NA-	
	e.	Width of Corridor	NA NA	Provided	MR	
		Door Size	1 mtr	NA To the last of	NΑ	
			1 mu	1m (Final Exit)	MR	
•	Compartmentation					
	ľ	Fire check door	Required	Provided	MR	
		Sealing of electrical shafts	Required	Provided	MR	
	•	Fire Rating of shaft door	-NA-	-NA-		
		Water Curtain	-NA-		-NA-	
		Fire Dampers	-NA-	-NA-	-NA-	
	Smo	ke Management System	-11//-	-NA-	-NA-	
		Basements	20 A ODIT	<b>D</b>		
-			30 ACPH	Ex. Fan provided		
_		Upper floors	12 ACPH	Natural ventilation	-NA-	
	Fire	Extinguishers		•		
	•	Total numbers	Portable Fire	30 No's	MR	
- 1	•	Types	Extinguishers	ABC/W.Co <sub>2</sub> /Co <sub>2</sub> .	MR	
		IS marking	ISI Marked	15/15/-		
+	Fire	Aid Hose Deals		Yes	MR	
-	TITSL	-Aid Hose Reels	T			
	1	Total numbers on each floor	Hose Reels	B-4, GF-5 & FF-2		
	1	Length of hose reel hose		30m	MR	
	A 1-4	Nozzle diameter		5mm	MR	
-	Automatic fire detection and alarming system					
	1	Type of detectors	-NA-	-NA-	-NA-	
	•	Location of Main Panel	-ŅA-	-NA-	-NA-	

The fire br

	, , , , ,			Specie			
	a1/20						
	*		Surv	70. Zo.			
	Location of Repeater Panel	-NA-	-NA-				
	Alternate source of power	-NA-	-NA-	-NA-			
	Hooters' Location	-NA-	-NA-	-NA-			
	MOEFA	Required	Provided	MR			
).	Public Address System	Required	Provided	MR			
0.	Automatic Sprinkler System						
	<ul> <li>Basement</li> </ul>	Required	Provided	MR			
	<ul> <li>Ground Floor</li> </ul>	Required	Provided	MR			
	<ul> <li>Sprinkler above false ceiling</li> </ul>	-NA-	-NA-	-NA-			
11.	Internal Hydrants						
	<ul> <li>Size of riser/down-comer</li> </ul>	Required	100mm	MR			
	<ul> <li>Number of hydrants per floor</li> </ul>	Required	B-4, GF-5 & FF-2	MR			
	Hose Box	Required	B-4, GF-5 & FF-2	MR			
12.	Yard Hydrants						
	<ul> <li>Total number of hydrants</li> </ul>	Required	5 No's provided	MR			
	Hose Box	Required	5 No's provided	MR			
13.	Pumping Arrangements						
	Ground Level	2200 1 DM	Provided	MR			
	Discharge of main Pump	2280 LPM	Provided Provided	MR			
	Head of Main pump	60m		MR			
	Number of main pumps	01 Nos	Provided	MR			
	Jockey Pump out put	180 LPM	Provided				
	Jockey pump head	60m	Provided	MR			
	Standby Pump out put	2280 LPM	Provided	MR			
	Standby Pump Head	60m	Provided	-NA-			
	Auto Starting/Manual Stopping	Required	Provided	MR			
	Pump House Access	Required	Provided	MR			
	Terrace level						
	Discharge of pump	-NA-	-NA-	-NA-			
	Head of the pump	-NA-	-NA-	-NA-			
	Power Supply	-NA-	-NA-	-NA-			
	Auto Starting of pump	-NA-	-NA-	-NA-			
		Cantivo Water Storage for fire fighting					
14	Captive Water Storage for fire fighting		1				
14.	Captive Water Storage for fire fighting	1.00.000 Lts	1,00,000 Lts	MR			
14.	Underground tank capacity	1,00,000 Lts Required	1,00,000 Lts Provided				
14.	•	Required	1,00,000 Lts Provided Provided	MR MR MR			
14.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> </ul>		Provided	MR			
14.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> </ul>	Required Required	Provided Provided	MR MR			
	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> </ul>	Required Required Required	Provided Provided Provided	MR MR MR			
15.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> </ul>	Required Required Required 10,000 Lts	Provided Provided Provided 10,000 Lts	MR MR MR MR			
15.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> </ul> Exit Signage. Provision of Lifts.	Required Required Required 10,000 Lts	Provided Provided Provided 10,000 Lts	MR MR MR MR			
15.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> </ul>	Required Required Required 10,000 Lts Required	Provided Provided Provided 10,000 Lts Provided	MR MR MR MR MR			
15.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> </ul>	Required Required 10,000 Lts Required -NA-	Provided Provided Provided 10,000 Lts Provided -NA-	MR MR MR MR MR			
15.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> </ul>	Required Required 10,000 Lts Required -NA-	Provided Provided Provided 10,000 Lts Provided -NANA-	MR MR MR MR MR -NA-			
15.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> </ul>	Required Required 10,000 Lts Required -NANANANA-	Provided Provided Provided 10,000 Lts Provided  -NANANANA-	MR MR MR MR MR -NANANA-			
15.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> </ul>	Required Required 10,000 Lts Required -NANANANANA-	Provided Provided Provided 10,000 Lts Provided  -NANANANANA-	MR MR MR MR MR MR -NANANANA-			
15. 16.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> <li>Standby power supply</li> </ul>	Required Required 10,000 Lts Required -NANANANA-	Provided Provided Provided 10,000 Lts Provided  -NANANANA-	MR MR MR MR MR -NANANA-			
15. 16.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> <li>Standby power supply</li> <li>Refuge Area.</li> </ul>	Required Required Required 10,000 Lts Required  -NANANANANA- Required	Provided Provided Provided 10,000 Lts Provided  -NANANANA- Provided	MR MR MR MR MR MR -NANANANA-			
15. 16.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> <li>Standby power supply</li> <li>Refuge Area.</li> <li>Total Area</li> </ul>	Required Required Required 10,000 Lts Required  -NANANANANANANAN	Provided Provided Provided 10,000 Lts Provided  -NANANANANA-	MR MR MR MR MR MR -NANANANANANA-			
15. 16.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> <li>Standby power supply</li> <li>Refuge Area.</li> <li>Total Area</li> <li>Location</li> </ul>	Required Required Required 10,000 Lts Required  -NANANANANA- Required	Provided Provided Provided 10,000 Lts Provided  -NANANANANANANAN	MR MR MR MR MR MR -NANANANANANANA-			
15. 16.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> <li>Standby power supply</li> <li>Refuge Area.</li> <li>Total Area</li> <li>Location</li> <li>Fire Control Room</li> </ul>	Required Required Required 10,000 Lts Required  -NANANANANANANAN	Provided Provided Provided 10,000 Lts Provided  -NANANANANANANAN	MR MR MR MR MR MR -NANANANANANANA-			
15. 16.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> <li>Standby power supply</li> <li>Refuge Area.</li> <li>Total Area</li> <li>Location</li> <li>Fire Control Room</li> <li>Detector System Panel</li> </ul>	Required Required Required 10,000 Lts Required  -NANANANANANANAN	Provided Provided Provided 10,000 Lts Provided  -NANANANANANANAN	MR MR MR MR MR MR -NANANANANANANANA			
15. 16.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> <li>Standby power supply</li> <li>Refuge Area.</li> <li>Total Area</li> <li>Location</li> <li>Fire Control Room</li> <li>Detector System Panel</li> <li>Flow Switch Panel</li> </ul>	Required Required Required 10,000 Lts Required  -NANANANANANANAN	Provided Provided Provided 10,000 Lts Provided  -NANANANANANANAN	MR MR MR MR MR MR -NANANANANANANANA			
15. 16.	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> <li>Standby power supply</li> <li>Refuge Area.</li> <li>Total Area</li> <li>Location</li> <li>Fire Control Room</li> <li>Detector System Panel</li> </ul>	Required Required Required 10,000 Lts Required  -NANANANANANANAN	Provided Provided Provided 10,000 Lts Provided  -NANANANANANANAN	MR MR MR MR MR MR -NANANANANANANANA			



	20.	Spe	Building Floor Plans	-NA-	-NA-	-NA-	
3	20. Special Fire Protection System for Protection of special Risks, if any:						

The Nitesh (A Unit of J.J. V Marketing & Hotels Pvt Ltd) at Gate No-2, NH-8, Near Shiv Murti, Kh. No 22/23 (4-16) 24 (4-16) 22/2 (3-16) 33/4 (4-16, 7 (0-8) Village Samalkha, Delhi

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

nell

Signature of the Inspection Officer Name: Sh. Manoj Kumar Sharma

Design: DO (South)

15/2/223

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

**CFO** 

K.f.

ADGATE

As opporoved

2012

is puly for

21/2/223

CF

M,5,011

25/5/5) NBJarged