GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6./DFS/MS/2023/Banquet/WZ/

Dated: 27/02/2023

FIRE SAFETY CERTIFICATE

Certified that the Laxmi Radhey Shyam Charitable Club, Community Hall, (Grand Utsav Bhawan) located at Pkt-B-10, Sector-3, Delhi-85, comprised of Basement + Ground + 02 upper floors owned/ occupied by Grnad Utsav Bhawan (A unit of Laxmi Radhey Shyam Charitable Club) has already been issued FSC by this department vide letter No F.6/DFS/MS/2019/WZ/347 dated 08.02.2019. The premises was re-inspected by the officer concerned of this department on 09.02.2023 in the presence of Mr. Ankush and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class "Assembly Group D-5" with effect from 2702 203 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subjected to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on $27 \left[02 \right] 2 023$ at New Delhi by

(Dhrampal Bhardwaj) **Dy.Chief Fire Officer** Tel;-01123414250

S/L

Conditions for the validity of fire safety certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Fire+Safety+Acts+and +Rules/ http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Forms

C.V

/	-								
D			INSPECTION REPORT						
	1.	Nai	ne & address of the building : Laxmi Radhey Shyam Charitable Club, Community Hall,						
			3, Delhi-85						
			e of Occupancy	: Assembly	nbly				
	3.	Туг	tails of Previous NOC : F Safety directives letter No : F.	Renewal (B + Gr. + 02 upper floors) Basement -Storage, Gr. & 1 st floor-Banquet, 2 nd floor -7 Bridal rooms F.6/DFS/MS/2019/WZ/347 dated 08.02.2019.					
	4	Dat							
					F.6/DFS/Ms/2011/548 dated 25.03.2011.				
				09.02.2023					
					Sharma ADO(Rohini)				
			ne and designation of officers						
			U	Mr. Ankush					
				2009					
					il dated 04.02.2023	1			
S. I	No.		nimum Standards on fire pr	evention	BBL/NBC	Provided at site	Remarks		
		-	d fire safety U/R 33		Requirement		MR/NMR		
1.		Ac	cess to building				1 (D		
			Road width		Accessible	Accessible	MR		
			• Gate width		Accessible	4m	MR(Old case		
			• Width of internal road		NA	NA	NA		
2.		Nu	mber, Width, Type & Arrar	ngement of E	Exits				
		d. 1	Number of staircases						
			 Upper Floors 		02	02	MR		
			 Basements 		02	02	MR		
		e. '	Width of staircases						
			 Upper Floor 		1.5m	1.50 & 1.45m	MR(Old case		
			 Basements 		1.5m	1.50m & 1.45m	MR(Old case		
		f. I	rotection of exits						
		F	ire check door		Required in	Provided	MR		
					Basement				
			 Pressurization 		NA	NA	NA		
		d.	No. of continuous staircases to	o terrace	01	01	MR		
		e. 🏻	Width of Corridor		NA	NA	NA		
		f.	Door Size		1.5m x 2	Provided	MR		
3.		Con	partmentation						
			Fire check door		Required	Provided in	MR		
						basement			
		ŀ	Sealing of electrical shafts		Required	Provided	MR		
		ŀ	Fire Rating of shaft door		Required	Provided	MR		
		ŀ	Water Curtain		NA	NA	NA		
		ľ	Fire Dampers		NA	NA	NA		
	S	m ol	ke Management System				1		
		•	Basements		30 a/c per hour	Exhaust fan	MR		
		•	Upper floors		12 a/c per hour	Natural ventilated	MR		
	F	ire	Extinguishers		F				
	T.		Total numbers		10	10			
		I			10nos.	12nos.	MR		
		Ī	Types IS marking		ABC/CO2	ABC-12nos.	MR		
	-	-			ISI marked	Yes	MR		
	Fi	rst-,	Aid Hose Reels						
		•	Total numbers on each floor	r	01	Provided	MR		
		•	Length of hose reel hose		30mm	Provided	MR		
		•	Nozzle diameter	-	5m	Provided	MR		
			atic fire detection and alar			1011000	IVIIX		

MA

I

n 1 I t

1 b

M/28

A Control of Control o

-

4

<u>8.</u> 9.	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power 	Required GF NA	Provided Provided NA	MR		
	Location of Repeater PanelAlternate source of power					
	 Alternate source of power 	NA NA	NIA			
				NA		
	 Hooters' Location 	Required	Provided	MR		
	MOEFA	NA	NA	NA		
<i>.</i>		Required	Provided	MR		
10.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System					
	Basement	Required	Provided	MR		
	Ground & Upper Floors	NA	NA	NA		
	• Sprinkler above false ceiling	NA	NA	NA		
11.	Internal Hydrants					
	• Size of riser/down-comer	100mm	Provided	MR		
	• Number of hydrants per floor	01	Provided	MR		
	Hose Box	01	Provided	MR		
12.	Yard Hydrants					
	• Total number of hydrants	NA	NA	NA		
	Hose Box	NA	NA	NA		
13.	Pumping Arrangements					
	Ground Level					
	Discharge of main Pump	2280lpm	2280lpm	MR		
	Head of Main pump	60m	60m	MR		
	Number of main pumps	01nos.	01nos.	MR		
	Jockey Pump out put	1801pm	1801pm	MR		
	Jockey pump head	60m	60m	MR		
	Standby Pump out put	2280lpm	2280lpm	MR		
	Standby Pump Head	60m	60m	MR		
	Auto Starting/Manual Stopping	Required	Provided	MR		
	Pump House Access	Required	Provided	MR		
	Terrace level					
	 Discharge of pump 	450lpm	450lpm	MR		
	 Head of the pump 	40m	40m	MR		
	 Power Supply 	Required	Provided	MR		
	 Auto Starting of pump 	Required	Provided	MR		
14.	Captive Water Storage for fire fighting					
14.	Underground tank capacity	50,000ltr	50,000ltr	MR		
	 Onderground tank capacity Draw-off connection 	Required	Provided	MR		
	 Fire service inlet 	Required	Provided	MR		
	 Access to tank 	Required	Provided	MR		
		5,000ltr	5,000ltr	MR		
	Overhead Tank capacity	Required	Provided	MR		
	Exit Signage.	Incquireu	11071000			
16.	Provision of Lifts.	NT 4		NT A		
	Pressurization of Lift Shaft	NA	NA	NA		
	 Pressurization of Lift lobby 	NA Device 1	NA	NA		
	Communication In lift Car	Required	Provided	MR		
	Fireman's Grounding Switch	Required	Provided	MR		
	Lift Signage	Required	Provided	MR		
7.	Standby power supply	Required	Provided DG set	MR		
	Refuge Area.					
	> Total Area	NA	NA	NA		

M 29

$\langle \rangle$	1º	Τ	> Location			
$\searrow \lambda$	17.	F	re Control Room	NA	NA	NA
N'a	am		Detector System Panel	NA		
100 a			Flow Switch Panel		NA	NA
			PA System Panel	NA	NA	NA
			Battery backup	NA	NA	NA
			Building Floor Plans	NA	NA	NA
ł	20.	Sp	ecial Fire Protection System for	NA	NA	NA
		Pr	otection of special Risks, if any:	NA	NA	NA
-	Acc	ord	ingly the f			

Accordingly, the fire protection systems provided in the building were tested/ checked randomly and found in working condition at the time of inspection.

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and fire safety required as stipulated in NBC Part-4, and removal of shortcomings issued vide letter no. 188 dated 01.02.2023, the FSC issued vide letter no. F.6/DFS/MS/2019/WZ/347 dated **08.02.2019**, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

DO (NW)

18/1/10 Signature of the Inspecting Officer

Name Ajay Kumar Sharma Designation ADO(Rohini)

20

13/02)7 to with FT letter 6 prut up for Kind Demsal and Signature please. 17/1/ 1022 Please upload on Mus portal after dispatch on CAF 20 2022112020 UPD Wy 24/2/13 Ms Cel