

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No. F6/DFS/MS/School/WZ/2023/ 178

Dated: 14/03/2023

FIRE SAFETY CERTIFICATE

Certified that the New Solanki Model Public School Located at Jai Vihar, Nangloi-Najafgarh Road, New Delhi-110043, comprised of Ground + 02 Upper Floor only owned/occupied by New Solanki Model Public School was issued Fire Safety Certificate by this department Vide Letter No. F6/DFS/MS/School/02 Dated 01.01.2020. The said premise was re-inspected by the officer concerned of this department on 27.02.2023 in the presence of Sh. Joney Solanki and found that the premises / building have deemed complied with the fire prevention and fire safety requirements in accordance with D.O.E. Cr. No. 3298-3398 dated 01.03.2011 and that the premises/building is fit for occupancy class "Educational Building" Group B with effect from \(\frac{1}{2} \) for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rules, 2010, printed below

Issued on 19103123... at New Delhi by.

Director
Delhi Fire Service

Copy to: -

- 1. The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi 110054.
- 2. The Principal, New Solanki Model Public School, Jai Vihar, Nangloi-Najafgarh road, New Delhi-110043.

Following fire safety directives must be adhered to:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name and address of the building: New Solanki Model Public School Located at Jai Vihar, Nangloi-Najafgarh Road, New Delhi-110043.

2. Type of Occupancy

: Educational, Ground + 02 Upper Floors only

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/School/02 Dated 01.01.2020

5. Fire Safety directives Letter No.: D.O.E. Cr. No. 3298-3398 dated 01-03-2011

6. Date of inspection

: 27.02.2023

7. Name of the Inspecting Officer : Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side

: Sh. Joney Solanki

9. Year of Construction

: 1999

10. Applicant's letter No.

: NSMPS/23/2414 dated 01.02.2023

S	Minimum standards on fire	D.O.E. Circular N	100071002 21 21 21	t Remarks MR/NMR	
No	prevention and fire safety U/R 33	3298-3398 Dated	Accessed to	MR/NMR	
		01.03.2011/ as pe			
1.	Acces of hailding	dated 01.01.2020			
1.	Access of building	06 m	Provided	MR	
	Road width	4.5 m	Provided	MR	
	• Gate width	NA	NA	NA NA	
	Width of internal road	INA	, IVA	1421	
2.	Number, width, Type & Arrangements of exits				
	a. Number of staircases				
	 Upper floors 	01	02	MR	
-	Basements	NA	NA	NA	
	b. Width of staircases				
	Upper floors			(Old Case)	
	Basements	NA	NA	NA	
	c. Protection of exits				
	 Fire check door 	NA	NA	NA	
	 Pressurization 	NA	NA	NA	
	d. No of continuous	01	Provided	MR	
	staircase to terrace		151 /52- 61 500		
	e. Width Of Corridor	1.5 m	Provided	MR	
	f. Door Size	1 m	Provided	MR	
3.	Compartmentation		NA		
	Fire check door	NA	NA	NA	
	Sealing of electrical	NA	NA	NA	
	shafts	NA	NA	NA	
	 Fire Rating of shaft door 	NA	NA	NA	
	 Water Curtain 	NA	NA	NA	
	 Fire Dampers 			1421	
	Smoke managements System				
	Basements	NA	NA	NA	
	Upper floors	NA	NA	NA	
i.	Fire Extinguishers				
•	Total numbers	08 nos.	10 nos.	MR	
	• Types	ABC & CO ₂	Provided	MR	

	1
-1	15
H	11.

X

Total numbers on each floor Length of hose reel hose Nozzle diameter	01 30 m 5 mm	Provided Provided Provided	MR MR		
Length of hose reel hoseNozzle diameter	30 m	Provided	MR		
Nozzle diameter					
		Provided	MR		
Automatic fire detection and alarming sys		21011404	IVIIC		
Type of detectors	NA	NA	NA		
	NA		NA NA		
and the second of the second o			NA NA		
			NA NA		
-					
And the Annual Control of the Annual Control			NA		
			NA		
	INA	NA	NA		
D NA					
			NA		
* *			NA		
	INA	NA	NA		
	NIA				
			NA		
			NA		
2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	NA	NA	NA		
· · · · · · · · · · · · · · · · · · ·					
			NA		
	NA	NA	NA		
The state of the s					
• Discharge of main pump		NA	NA		
Head of main pump		NA	NA		
		NA	NA		
	NA	NA	NA		
Jockey pump head	NA	NA	NA		
Standby Pump out put	NA	NA	NA		
Standby Pump Head	NA	NA	NA		
Auto Staring/Manual	NA	NA	NA		
	NA	NA	NA		
	1	40.1	5		
	450 lpm	Provided	MR		
Power sumply	40 m	Provided	MR		
Auto starting of many	Required	Provided	MR		
	Required	Provided	MR		
Captive water Storage for fire fighting:					
Under ground tank capacity	NA	NA	NA		
	NA	NA	NA		
	NA	NA	NA		
	NA	NA	NA		
Overhead Tank capacity	10,000 ltrs.	Provided	MR		
	Required	Provided	MR		
Provision of Lifts					
Pressurization of Lift Shaft	NA	NA	NA		
Pressurization of lift lobby	NA	NA	NA		
Communication in lift Car	NA	NA	NA		
Fireman's Grounding Switch	NA		NA		
➤ Lift Signage	NA	NA	NA		
Standby nowar gunnly					
	NA	NA	NA		
Refuge Area > Total area					
	NA	NA	NA		
the same that th			1 17 1		
> Location	NA	NA	NA		
	 Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage 	• Location of Repeater Panel • Alternate source of power • Hooters' Location MOEFA Public Address System • Basements • Upper Floor • Sprinkler above false ceiling Internal Hydrants: • Size of riser/down-comer • Number of hydrants per floor • Hose Box Yard Hydrants • Total number of hydrants • Hose Box Pumping Arrangements: • Ground Level • Discharge of main pump > Head of main pump > Na > Jockey pump out put > Standby Pump out put > Standby Pump Head > Auto Staring/Manual stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power supply > Auto starting of pump Captive water Storage for fire fighting: • Under ground tank capacity > Draw off connection > Fire service inlet > Pressurization of Lift Shaft > Pressurization of Lift Shaft > Pressurization in lift Car > Fireman's Grounding Switch > Lift Signage NA NA NA NA NA NA NA NA NA N	• Location of Repeater Panel • Alternate source of power • Hooters' Location MOEFA NA N		

functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety requirements as per D.O.E. Circular no. 3298-3398 dated 01.03.2011, renewal of Fire Safety Certificate issued vide letter no. F6/DFS/MS/School/02 Dated 01.01.2020 is recommended.

Accordingly DFA is put up for approval please.

ADO (JWP)

\$ O(N

Fi dette is put-up for your signalure 12/

D.O. (WEST)/.5