FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE **NEW DELHI**

No. F6/DFS/MS/SZ/2023/ 148

Dated:/7 63/2023

FIRE SAFETY CERTIFICATE

Certified that the building GGSIP University Located at Sector 16 C, Dwarka, New Delhi (Type IV & V Quarters 1st & 2nd block) comprised of stilt plus nine & six upper floors was issued Fire Safety Certificate vide letter No. F6/DFS/MS/2012/1469, dated 24/04/2012. The premises was re - inspected by the officer concerned of this department on 02/03/2023 in the presence of Sh. Deepesh Singh Bhati A.E(E) & his team and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules 2010 and that the premises is fit for occupancy class "Residential" Group A (residential) with effect from $1+\frac{1}{202}$ for a period of five years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 17/03/2023... at New Delhi by.

Delhi Fire Serv

Copy to:

1. The Registrar (E&S), GGSIPU, Sector-16-C, Dwarka, New Delhi-170078.

2. The Astt. Registrar to the Hon'ble Vice Chancellor, GGSIPU, Sector-16-C, Dwarka, New Delhi-110078.

3. The Executive Engineer (UWD, GGSIPU) University Works Division, Ground Floor, Library Block, Guru Gobind Singh Indraprastha University, Sector 16-C, Dwarka New Delhi-110078.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. Basement shall be used strictly as per building bye laws.

7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delĥi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its

evniry

N/77 INSPECTION REPORT

 Name & address of the building: GGSIP University Located at Sector 16C, Type – IV & V Quarters, Dwarka, New Delhi.

2. Type of Occupancy : Educational

3. Type of Case : Renewal (Residential type IV & V= stit+9 UFs & Six UF)

4. Details of previous NOC: F6/DFS/MS/2012/1469, dated 24/04/2012

5. Fire Safety directives L. No.: F6/DFS/MS/BP/2006/1208, dated 25/05/2006

6. Date of inspection

: 02/03/2023

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side: Sh. Deepesh Singh Bhati A.E(E) & his team

9. Year of Construction

: 2010-11

10. Applicant's letter No.

:Email dated-25/12/2022

S	Minimum standards on fire	Requirement A	As per N/26,		Provide	100	Remarks	
No	prevention and fire safety U/R 3	and the second of the second o		29	at site	N	MR/NMR	
1.	Access of building							
	Road width	12 mtrs		Provided			/IR	
	Gate width	05 mtrs	Provided			MR being old case		
	Width of internal road	06 mtr		Old case	being			
2.	Number, width, Type & Arrangements of exits							
	a. Number of staircases							
	Upper floors	02 No's each block		Provided		-\	MR	
	Basements	NA	N	NA 1			NA	
	b. Width of staircases		н	HC				
	 Upper floors 	1.5mtr & 1.25 m Old case M				R being old case		
	 Basements 	NA NA				NA		
	c. Protection of exits	4						
	 Fire check door 	NA	N	Ά		N	A	
	 Pressurization 	NA	NA			NA		
	d. No of continuous	Required		Provide	d	M	IR	
	staircase to terrace e. Width Of Corridor	Required	Pı	rovided (Ol	d case)	-	IR .	
	f. Door Size	Required	Provided (Old case)			1 10000	MR	
3.	Compartmentation							
	Fire check door	NA	N.	A		N.	A	
	 Sealing of electrical 	Required	Se	ealed		M		
	shafts	•				IVIII		
	 Fire Rating of shaft door 	NA	N.	A		N.	Λ	
	 Water Curtain 	NA		NA		142	NA	
	 Fire Dampers 	NA	NA			N.		
4.	Smoke managements System					1112		
	 Basements 	NA	N	A		N	A	
	 Upper floors 	Required	Required Natural Ventilat		lation MR			
							7/6/	
		N						

ma

	Λ	N/78						4
	Fire Extinguishers							m
	 Total numbers 	02 nos	each floor	P	Provided			IR ·
	• Types	WCO2	2 & CO ₂	F	Provide	ed		IR C
	IS marking	ISI ma	arked	F	Provide	ed	N	IR
	First – Aid Hose Reels		2000					
	Total numbers on each flo	or 01 no each floor			I	Provided		IR
	• Length of hose reel hose	30m		Provided			IR	
	Nozzle diameter	51	nm			Provided	I M	IR
7.	Automatic fire detection and alarr	Jiiiii						
	Type of detectors		NA		1	NA NA		NA
	Location of Main Panel		NA		1			NA
	Location of Repeater Pane	el	NA Required Near Staircase			NA DG Set		NA
	Alternate source of power							MR
	Hooters' Location				e H	Provided		MR
8.	MOEFA		Required Pro			ed		MR
9.	Public Address System		Required	F	Provide	ed		MR
10.	Automatic Sprinkler System							
10.	Basements		NA	NA			NA	
	 Upper Floor		NA	NA			NA	
	 Sprinkler above false ceili 	ing	NA	1	NA		NA	
11	•	U	7.41				MR	
11	Size of riser/down- comer	:	100 ******		ET HENRY	ovided		
	Number of hydrants per fl		01 Nos.		Provid		MR MR	
	Hose Box		Required			Provided		
12							1.00	
	Total number of hydrants		Required			MR	_	
	Hose Box	9 10	Required		Provi	ded	MR	
13	. Pumping Arrangements:	15	10			-		
	Ground Level					n 111) (T)
	 Discharge of main pump 		Lpm	Provide		Provided	MD	MR
	Head of main pump	70 mt	r				MR	
	Number of main pumps	one	D) (ovided		MR MR	_
	Jockey pump out put	180 L		Provided Provided Provided Provided			MR	_
	> Jockey pump head	70 mt					MR	_
	> Standby Pump out put	2850					MR	_
	Standby Pump Head	70 mtr Required		Provided			MR	_
	> Auto Staring/Manual	Kequ	IICU	Provided			1,111	
	stopping > Pump House Access	Requ	ired			MR		
	Terrace level	Requ	IICU	11	Jilaca			
	 Terrace level Discharge of pump Head of the pump NA 		NA		A			
				NA		NA NA	_	
	> Power supply	NA NA		N		A 100 AND	NA	_
	> Auto starting of pump	NA NA		NA NA				
14				- 12				
12			2,00,000 ltr Provid		covided M		MR old	d Case
	• Under ground tank capacity	2,00,		- •			>	
	> Draw off connection	Requ	ired	Pr	rovideo	i	MR	
	> Fire service inlet	Requ		l Provid			MR	
	> Access to tank	Requ					MR	1
	Overhead Tank capacity	20,00					MR	
15		Requ		Provid				
1.	Zint Digingo	1						
1								



39			ı, J	179				
16.	Provision of Lifts		- PO 1	•				
	> Pressurization of Lift Shaft		NA	NA	N	A		
	> Pressurization of lift lobby		NA	NA	N	ΙA		
	Communication in lift Car		Required	Provided	N	1R	2	
	Fireman's Grounding Switch	٠	Required	Provided	N	1R		
	_		Required	Provided	N	1R		
	➤ Lift Signage		•		MR			
17.	Standby power supply		Required	Provided	IV			
18.	Refuge Area		n · 1	Provided	7	MR		
	Total area		Required	4 th & 7 th floor		MR		
	> Location		Required	4 & / 11001		1,127		
19.	Fire control room	_		n .:		MR		
	Detector system panel		Α	Provided		NA NA		
	Flow Switch Panel		A	1421				
	PA System Panel	R	equired	Provided	MR MR			
	Battery backup		equired	Provided				
	Building Floor Plans	R	equired	Provided		MR	NIA	
20.	Special Fire Protection Systems for	N	A	NA			NA	
20.	Protection of special Risks, if any;							
	Protection of special rusks, in may,		-					
Nam	ature of the Inspecting Officer e: Use Viv Synthesis Appendix							
_	Doke M 10/18/2	3						
	Director 13 2023		23					
	Graph latter	if	by by	op for Sil	The same of the sa	ple		