C16

Director

Delhi Fire Service.

FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE [Refer sub - rule (1) of rule 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE No.F6/DFS/MS/2023/ School / 188 NEW DELHI Dated: 17/03/2023

FIRE SAFETY CERTIFICATE

Certified that the building of Rajkiya Pratibha Vikas Vidhalaya, Located at Sector -10, Dwarka, New Delhi - 110075 (S.ID - 18211038) comprised of G+3 UFs was issued Fire Safety Certificate vide letter No. F6/DFS/MS/School/2015/SZ/970, dated 09/06/2015. The premises was re inspected by the officer concerned of this department on 06/03/2023 in the presence of Dr. Atul Kumar (HOS/V. Principal) and found that premises have deemed complied with the fire prevention and fire safety requirements in accordance with DOE Circular 3298-3398 Dated 01/03/2011 issued by Directorate of Education, Govt. of NCT of Delhi and that the building is fit for occupancy class B "Educational building" with effect from 17/03/2023 for a period of three years. In accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 17/03/2023 at New Delhi by.

Copy to:

)

10

- 1. The Principal, Rajkiya Pratibha Vikas Vidhalaya, Located & Sector 10, Dwarka, New Delhi - 110075 (S.ID - 18211038).
- 2. Directorate of Education Old Secretariat Delhi 110054

Following fire safety directives must be adhered to:-

- All the fire safety arrangements provided therein shall be maintained in good working 1 condition at all times.
- 2 Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- The trained staff should be available round the clock. 3
- 4 Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5 The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six 6 months prior to its expiry. www.dfs.delhigovt.nic.in.
- Basement shall be used strictly as per building bye laws. 7
- The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on 8 www.dfs.delhigovt.nic.in.

INSPECTION REPORT

NIII

- 1. Name & address of the building: Rajkiya Pratibha Vikas Vidhalaya, Located at Sector 10, Dwarka, New Delhi 110075 (S.ID 18211038).
- 2. Type of Occupancy : Educational Old building (G+3UFs)
- 3. Type of Case : Renewal
- 4. Details of previous NOC : F6/DFS/MS/School/2015/SZ/970, dated 09/06/15
- 5. Fire Safety directives Letter No. : DOE 3298-3398 dated 01-03-2011
- 6. Date of inspection : 06/03/2023
- 7. Name of the Inspecting Officer: Udai vir singh, ADO (DWK)
- 8. Name and designation of Officer

Total Area = 16036 sqm. Covered Area = 1935 sqm Class rooms = 44No. of students = 901

from the building side: Dr. Atul Kumar (HOS/V. Principal

- 9. Year of Construction : 2010
- Applicant's letter No.:23(5)/AE(E)/South-West/S.D-I/PWD/22-23/1095, dated 25/02/2023

S No	Minimum standards on fire prevention and fire safety U/		R 33 Requirement as per N/7, N/8 & N/9			Provided site			marks R/NMR		
1.	Access	s of building				1				MR	
	•	Road width					Provided				
	•	Gate width	4.5mtrs			provideo	d			MR	
	•	Width of internal	NA			NA				NA	
		road									
2.		er, width, Type & Arra	angement	s of exi	its						
	a.	Number of									
		staircases								D	
	•	 Upper floors 					4 Nos. + 01 Ramp			MR NA	
	•	Basements	NA NA			IN			1		
	b.	Width of staircases	10.00	·1		27140-	1.147-		(D/D-		
	•	Upper floors	1.5m if			3X149cm, 1x147c & ramp 158 cm			MR(Being old case)		
			1.5m additional & ran staire case of			& ramp	imp 158 cm 010			case) -	
			75cm ii		od						
			NA	ricqui	cu	NA				NA	
	•	Basements	INA							Inn	
	с.		NTA		TA			NA			
	•	Fire check door	NA	NA		NA NA					
	•	Pressurization	NA NA Required Provid								
	d.	No of continuous	Require	ed P	rovic	lea		MR			
		staircase to terrace Width Of Corridor	1.10 m	p	rovic	led	MR				
	f.	Door Size	01 m		vided		MR				
			UIII	110	rucu						
3.	-	artmentation		N	JA		NA		NA		
	• Fire check door		4				NA				
	•	Sealing of electrical	shafts NA				NA NA			NA NA	
	•	Fire Rating of shaft of	loor NA				NA NA				
	•	Water Curtain	NA						NA		
	Fire Dampers				ΙA		NA 1		NA	NA	

	Smoke	managements			N/I				-
	System								
	•	Basements	NA			NA		NA	the second s
	•	Upper floors	Requ	ired	Natura			on	MR
5.	Fire E	xtinguishers							
	•	Total numbers	14 N	05.		361	Nos.	MR	
		Types		& CO ₂			vided	MR	
		IS marking		arked			vided	MR	
5.	First -	Aid Hose Reels	Carory/Incide						
	•	Total numbers on each floor	2 No	s.		Prov	vided	MR	
	•	Length of hose reel	30m			Provided		MR	
		Nozzle diameter	5mm			Pro	vided	MR	
7.	Autor	natic fire detection and	and the second second			110	vided	IVIIX	
•	Auton		alarini	-	11		NIA		NA
	•	Type of detectors	- 1	NA			NA NA		NA
	•	Location of Main Par		NA NA			NA		NA
	•	Location of Repeater		NA			NA		NA
	•	Alternate source of p	ower				NA		NA
	•	Hooters' Location		NA			INA		
3.	MOEI		NA			NA			NA
).	-	Address System	NA			NA			NA
0	Auton	natic Sprinkler System			NT 4			NT A	
	•	Basements	NA			NA		NA	
	•	Upper Floor	NA		NA		Ň		NA
	•	Sprinkler above	NA		NA			NA	
1102		false ceiling							
1	Interna	al Hydrants:						100	214
	 Size of riser/down- comer 			NA				100mm	NA
	•	Number of hydrants	per	NA		Provided	NA		
		floor			NIA			Provided	NA
	•	Hose Box		NA				riovided	INF
2	Yard I	Iydrants	274			NT A			NIA
	•	Total number of	NA	NA		NA		NA	
		hydrants	NT A	274		NA		NA	
	•	Hose Box	NA		NA				INA
3	Pumpi	ng Arrangements:	r						
	•	Ground Level		NA		NIA			NA
	•	 Discharge of main pump 				NA NA			NA
		Head of main pump							NA
	1 20	Number of main pumps		NA		NA			NA
		Jockey pump out put	-	NA NA				NA	
		Jockey pump head	.	NA				NA	
		Standby Pump out pu	it	NA	NA				NA
		Standby Pump Head		NA		NA			NA
		 Auto Staring/Manual stopping 		NA	NA			-	
		 Pump House Access Terrace level 			NA NA				NA
		 Discharge of pump 			450 lpm 2X450 lpm		1	MR	
	 Head of the pump 			450 lpm 40Mtr	Provided		7	MR	
	 Power supply 			Required		Provided			MR
	-	 Auto starting of pump 			Provided			MR	

Zr.

W C

-				NB					
14	Captive water Storage for fire fighting:								
	 Underground tank capacity 	NA	1.1	NA	NA				
	Draw off connection	NA		NA	NA				
	Fire service inlet	NA		NA	NA				
	Access to tank	NA		NA	NA				
	 Overhead Tank capacity 	10,000 ltrs		Provided	MR				
15	Exit Signage	Require	d	Provided	MR				
16	Provision of Lifts								
	Pressurization of Lif	t Shaft	NA	NA	NA				
	Pressurization of lift	lobby	NA	NA	NA				
	Communication in li	ft Car	NA	NA	NA				
	Fireman's Grounding	Fireman's Grounding Switch		NA	NA				
	Lift Signage	NA	NA	NA					
17	Standby power supply		NA	NA .	NA				
18	Refuge Area	- Constructions							
	Total area		NA	NA	NA				
		Location		NA	NA				
19	Fire control room								
	Detector system pan	NA	NA	NA					
	Flow Switch Panel				NA				
	PA System Panel				NA				
	Battery backup			NA	NA				
	Building Floor Plans		NA	NA	NA				
20	Special Fire Protection Syst Protection of special Risks,	ems for if any;	NA	NA	NA				

NIA

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/School/2015/SZ/970, dated 09/06/2015 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer las Name Designation AD

10/6/23

enerta Da / own 0