

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/School/2023/SZ/ 20/

Dated: 21. /0.3. /2023

## FIRE SAFETY CERTIFICATE

Certified that the St. Paul's School at C-3, Safdarjung Development Area, New Delhi 110016 comprised of Basement, ground plus three upper floors owned/occupied by St. Paul's School was issued Fire Safety Certificate by this department vide letter no. F6/DFS/MS/School/2017/SZ/1542 Dt. 27/10/2017. The said premises was re-inspected by officer concerned of this department on 14/03/2023 in presence of Mr. Thomas P.T (Admin) and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with Directorate of Education Circular No 262-362 dated 17/01/2005 issued by Director of Education, Govt. of NCT of Delhi and that the building is fit for occupancy class "Educational Building Group – B" with effect from 21/03/2023 for a period of Three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rules 2010.

Issued on 21/03/2023 at New Delhi by

DIRECTOR
DELHI FIRE SERVICE

OI IN

Copy to: -

- 1. The Principal, St. Paul's School at C-3, Safdarjung Development Area, New Delhi 110016.
- 2. Directorate of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054

## Conditions for the validity of Fire Safety Certificate:

- All the means of escape/entry/exit shall be kept unlocked and free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The basement shall be used as per the provisions of BBL /NBC Part- IV.
- 4. All the staff members must know the correct method of operation of fire fighting system.
- The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."



INSPECTIO	N REPORT			
Name & Address of the Building	St. Paul's School at C-3, Safdarjung Development			
Type of Occupancy				
Building Comprised of				
Type of Case				
	F6/DFS/MS/Sc	hool/2020/SZ/206 dated	26/06/2020	
Fire Safety Directives Letter No				
	14.03.2023			
Name of the Inspecting Officers	ADO (BCP) Mr Thomas P T (Admin)			
from the building side				
Year of construction	2006			
Applicant letter No.	Outdoor diary n	o 10902 dated 06-02-20	23	
Minimum standards on Fire Prevention and Fire Safety U/R 33	Old NOC	Provided at Site	Remarks MR/NMR	
Access to Building.				
Road width	Accessible	10 m	MR	
Gate width	Required	3.6 mtr	NA	
<ul> <li>Width of internal road</li> </ul>	NA	NA	NA	
Number, width, type & arrangement of exits.				
a. Number of Staircase				
Upper floors.	04 Nos	05 Nos	MR	
N. P. S.	02 Nos	02 Nos	MR	
		And the second s		
	Required 1.50m, 1.45m, 1.45m,		ı, MR	
5.5	redailed		8	
Basement Hoor	Required 1.45m & 1.45m		MR	
c. Protection of exits				
	NA	NA	NA	
F 7	NA	NA	NA	
	Required	Three	MR	
	NA	NA	NA	
	1.0 mtr	Provided	MR	
	1.0 ma			
	NA	NA	NA	
		in the second se	NA	
			NA	
		NA	NA	
		NA	NA	
	12 ACPH	Exhaust fan provided	MR	
Basement     Upper floors	NA	NA	NA	
Fire Extinguishers.			100	
Total numbers	A STATE OF THE PARTY OF THE PAR		MR	
1 Section 1 Section 1 Section 1 Section 2 Sect			MR	
ISI Marking	Required	Provided	MR	
First Aid Hose Reels.				
A 11 V 1 M 1 M 1 M 1 M 1 M 1 M 1 M 1 M 1	03 No	03 Nos	MR	
<ul> <li>Total numbers on each floor.</li> </ul>	05 110			
Total numbers on each floor.  Length of hose-reel hose.	30 mtr	provided	MR	
<ul> <li>Total numbers on each floor.</li> <li>Length of hose-reel hose.</li> <li>Nozzle Diameter</li> </ul> Automatic fire detection & alarming system.		provided provided	MR	
	Type of Occupancy Building Comprised of Type of Case Details of Previous NOC Fire Safety Directives Letter No Date of Inspection Name of the Inspecting Officers Name & Designation of Officers from the building side Year of construction Applicant letter No. Minimum standards on Fire Prevention and Fire Safety U/R 33 Access to Building.  Road width Gate width Width of internal road Number, width, type & arrangement of exits.  Number of Staircase Upper floors. Basement floor  b. Width of Staircase Upper floors Basement floor  c. Protection of exits Fire check door Pressurization d. No. of continuous staircase to terrace e. Width of corridor f. Door size Compartmentation. Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system.  Basement Upper floors Fire Extinguishers. Total numbers Types	Type of Occupancy Building Comprised of Type of Case Details of Previous NOC Fire Safety Directives Letter No Date of Inspection Name of the Inspecting Officers Name & Designation of Officers from the building side Year of construction Applicant letter No. Minimum standards on Fire Prevention and Fire Safety UR 33 Access to Building.  Road width Width of internal road Number, width, type & arrangement of exits.  A. Number of Staircase Upper floors Basement floor  Building General Required C. Protection of exits Fire check door Fire chec	Type of Occupancy Building Comprised of Building Comprised of Basement + Ground + 3 upper floors. Type of Case Petails of Previous NOC Pire Safety Directives Letter No Date of Inspection Name of the Inspecting Officers Name & Designation of Officers from the building side Year of construction Applicant letter No. Minimum standards on Fire Prevention and Fire Safety UR 33 Access to Building. Required Width of internal road Number, width, type & arrangement of exits.  a. Number of Staircase Wupper floors Basement floor Basement floor Provided at Site Required  1.50m, 1.45m, 1.45m Required 1.1.45m & 1.45m NA	

1

M

आजादी हा अमृत महोत्सव

T	Location of Main Panel	NA	NA	NA
	<ul> <li>Location of Repeater Panel</li> </ul>	NA	NA	NA
	<ul> <li>Alternate source of power</li> </ul>	NA	NA	NA
	Hooter's location	NA	NA	NA
3.	MOEFA	NA	Provided	NA
9.	Public Address System	NA	Provided	NA
0.	Automatic Sprinkler System	.,,,		
0.	Basement	Required	Provided	MR
	Upper floors	NA	NA	NA
		NA	NA	NA
	Sprinkler above false ceiling	1471		
11.	Internal Hydrants.	100mm	Provided	MR
	Size of Riser/Down-comer	03 Nos	Provided	MR
	Number of Hydrant per floor		Provided	MR
	Hose box.	03 Nos	Provided	VIK
12.	Yard Hydrants.	N	NA	NA
	Total number of hydrants.	NA	NA NA	NA
	Hose box.	NA	NA	NA.
13.	Pumping arrangements.			
	A. Ground Level			AT A
	Discharge of main pump.	NA	NA	NA
	Head of main pump.	NA	NA	NA
	Number of main pumps.	NA	NA NA	NA
	> Jockey Pump output.	NA	NA NA	NA
	> Jockey Pump head.	NA	NA	NA
	<ul> <li>Standby Pump output.</li> <li>Standby Pump head.</li> </ul>	NA	NA NA	NA
	> Auto Starting / Manual Stopping.	NA	NA NA	NA
	> Pump house access.	NA	NA	NA
		NA	NA	NA
	<ul> <li>B. Terrace Level</li> <li>Discharge of pump.</li> </ul>	450 & 180 LPM	450 LPM x 2 & 180 LPM	MR
	Head of pump.	35 mtr each	Provided	MR
	> Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.			
	Underground tank capacity.	NA	NA	NA
	> Draw-off connection.	NA	NA	NA
	> Fire Service Inlet.	NA	NA	NA
	Access to tank.	NA	NA	NA
	Access to tank.			_
15.	<ul> <li>Access to tank.</li> <li>Overhead tank capacity.</li> </ul>	5,000 Ltr	NA 15,000 ltr Provided	NA MR
15. 16.	<ul> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> </ul>		15,000 ltr	NA
15. 16.	Access to tank. Overhead tank capacity.  Exit Signage. Provision of Lifts.	5,000 Ltr	15,000 ltr	NA MR
	Access to tank. Overhead tank capacity.  Exit Signage. Provision of Lifts. Pressurization of lift shaft.	5,000 Ltr Required	15,000 ltr Provided	NA MR MR
	Access to tank.     Overhead tank capacity.  Exit Signage.  Provision of Lifts.  Pressurization of lift shaft. Pressurization of lift lobby.	5,000 Ltr Required NA	15,000 ltr Provided	NA MR MR
	Access to tank.     Overhead tank capacity.  Exit Signage.  Provision of Lifts.  Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car.	5,000 Ltr Required NA NA	15,000 ltr Provided NA NA	NA MR MR NA
	Access to tank. Overhead tank capacity.  Exit Signage. Provision of Lifts.  Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch.	5,000 Ltr Required NA NA NA	15,000 ltr Provided  NA NA NA	NA MR MR NA NA
16.	Access to tank. Overhead tank capacity.  Exit Signage. Provision of Lifts.  Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage.	5,000 Ltr Required NA NA NA NA	15,000 ltr Provided  NA NA NA NA NA	NA MR MR NA NA NA NA
16.	Access to tank. Overhead tank capacity.  Exit Signage. Provision of Lifts.  Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage.  Standby Power Supply	5,000 Ltr Required NA NA NA NA NA	NA NA NA NA NA NA	NA MR MR NA NA NA
16.	Access to tank. Overhead tank capacity.  Exit Signage. Provision of Lifts.  Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply Refuge Area	5,000 Ltr Required NA NA NA NA NA	NA NA NA NA NA NA	NA MR MR NA NA NA NA
16.	Access to tank. Overhead tank capacity.  Exit Signage. Provision of Lifts.  Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply Refuge Area Total area	5,000 Ltr Required  NA	15,000 ltr Provided  NA	NA MR MR NA NA NA NA NA
16. 17. 18.	Access to tank.  Overhead tank capacity.  Exit Signage.  Provision of Lifts.  Pressurization of lift shaft.  Pressurization of lift lobby.  Communication in lift car.  Fireman's switch.  Lift signage.  Standby Power Supply  Refuge Area  Total area  Location	NA	15,000 ltr Provided  NA	NA MR MR NA NA NA NA
16.	Access to tank.  Overhead tank capacity.  Exit Signage.  Provision of Lifts.  Pressurization of lift shaft.  Pressurization of lift lobby.  Communication in lift car.  Fireman's switch.  Lift signage.  Standby Power Supply  Refuge Area  Total area  Location  Fire Control Room.	5,000 Ltr Required  NA	15,000 ltr Provided  NA	NA MR MR NA NA NA NA NA
16. 17. 18.	Access to tank.  Overhead tank capacity.  Exit Signage.  Provision of Lifts.  Pressurization of lift shaft.  Pressurization of lift lobby.  Communication in lift car.  Fireman's switch.  Lift signage.  Standby Power Supply  Refuge Area  Total area  Location	5,000 Ltr Required  NA	15,000 ltr Provided  NA	NA MR MR NA NA NA NA NA

M





		1 214	NA	NA	
	<ul> <li>PA system panel.</li> </ul>	NA		NA	
	<ul> <li>Battery backup.</li> </ul>	NA	NA	NA	
	Building floor plan.	NA	NA	NA NA	
	· · · · · · · · · · · · · · · · · · ·				
20.	Special Fire Protection System for the Protection of special rusk, it and				

The fire protection system provided in the building were randomly checked and found

functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/School/2017/SZ/1542 Dt. 27/10/2017, renewal under rule 37 of the Delhi Fire Service rules 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspection Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

DO (8D) signature Pl. 1912