

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2023/ 77

Dated : 11/04/2023

FIRE SAFETY CERTIFICATE

Certified that the Hotel Gaylord International located at 7973, Arakashan Road, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (Reception + 05 guest rooms), 1st floor to 3rd floor (09 guest rooms at each floor) and 4th floor not in use as per affidavit dated 10.10.2019 total 32 guest rooms up to third floor only. The FSC was earlier granted by this department vide letter No.F6/DFS/MS/GH/2020/98 dated 13/03/2020 for 32 guest rooms up to third floor only. Now, the premises was re-inspected by the officer concerned of this department on 28/03/2023 in the presence of Manager and found that the guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, (Sub Division-A-1) Ground floor (Reception + 05 guest rooms), 1st floor to 3rd floor (09 guest rooms at each period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 11/04/102 3at New Delhi by

Copy to:-

- 1. The Commissioner of North, MCD, Civic Centre, New Delhi. Kindly to ensure the occupancy in the building as detailed above.
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi online id no.2023021502114 dated 11/03/23,
- 3. The Manager, Hotel Gaylord International 7973, Arakashan Road, Pahar Ganj, New Delhi

Conditions for the validity of Fire Safety Certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the
- The trained fire fighting staff should be available round the clock
- 4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7 The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'I' (sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry
- 9. Any flammable material for interior decoration is prohibited.

NIPE

INSPECTION REPORT 1. Name & address of the building Hotel Gaylord International

at 7973, Arakashan Road, Pahar Ganj,

New Delhi

Residential, Sub Division-A-1 Type of occupancy:-

Gr. + 04 Upper floors (total 32 Guest rooms) Ground floor (Reception + 05 guest rooms). I" floor to 3rd floor (09 guest rooms at each) 4th

floor (given an affidavit dated 10.10.2019 regarding not to use any floor above third floor)

Renewal 3. Type of case:-

No. F6/DFS/MS/GH/2020/98 dated 4. Details of previous FSC:-

13/03/2020

Manager

N/A 5. Fire safety directives No.-

28/03/2023 Date of inspection -

Name of the inspecting officer:-

Name & designation of officer From the building side:-

10. Applicant's letter No -

Sh. Ravinder Singh (ADO/CC)

2000 9. Year of construction:-

online id no 2023021502114 dated 11/03/23,

10.	Applicant stetter 110			Old Case
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building			
	1) Road width	N/A	09 mtr.	N/A
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arr	angement of I	exits	
-	A. Number of staircases			
	1. Upper floors	02 Nos.	02 Nos.	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase		/	1.00
	1. Upper floors	1.25 mtr.	1.20 & 1.30 mtr	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits	E. 11-		
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	01	01	MR
	E. Width of corridor	01 mtr	01 mtr	MR
	F. Door size	01 mtr	01 mtr	MR
3.	Compartmentation			
٥.	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System		1	N/A
	1) Basements	30 ACPH	N/A	The Sales Annual Control of the Cont
	2) Upper floors	12 ACPH	Natural/Exhaust fan	MR
5.	Fire Extinguishers	12 Nos	14 Nos.	MR
	1) Total numbers	12 Nos	14 1403	





N121

	NID			-	
	2) Types	ABC & CO2	ABC & CO2	MR (
	2) Types 3) ISI marking	Required	Provided	MR	
0	First-Aid Hose Reel	required		900	
5.	1) Total number of each	02	02	MR	
	floor		02 /		
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR	
	3) Nozzle diameter	05 mm	05 mm	MR	
7.	Automatic Fire Detection &	and the second second	em		
1.	1) Type of detectors CO	Required	Provided	MR	
	2) Location of main panel	Gr. floor	Provided	MR	
	3) Location of repeater panel	N/A	N/A	NA	
	4) Alternate source of power	Required	Provided	MR	
	5) Hooter's Location	Gr. floor	Provided	MR	
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System				
10.	1) Basement	N/A	N/A	NA	
	2) Upper floors	N/A	N/A	NA	
	3) Sprinkler above false	N/A	N/A	NA	
	ceiling				
11.	Internal Hydrants		-		
11.	1) Size of riser/down-comer	100 mm	100 mm	MR	
	2) Number of hydrants per	01	01	MR	
	floor		/		
	3) Hose box	01	01	MR	
12.	Yard Hydrants	•		12/4	
	1) Total number of hydrants	N/A	N/A	NA	
	2) Hose box	N/A	N/A	N/A	
13.	Pumping Arrangement			- 1	
13.	1) Ground level	N/A	N/A	N/A	
	a) Discharge of main	N/A	N/A	N/A	
	b) Head of main pump	N/A	N/A	N/A	
	c) Number of main	N/A	N/A	N/A	
	160	3300			
	d) Jockey pump out put	N/A	N/A	N/A	
	e) Jockey pump head	N/A	N/A	NA	
		N/A	N/A	NA	
		1.7.225.69			
	g) Stand by pump head	N/A	N/A	NA	
		N/A	N/A	NA	
	h) Auto starting/Manual	10000			
	stopping 2) Terrace level			() 0	
	The second second	450 LPM	450 LPM	MR	
	a) Discharge of pump	30 mtr.	30 mtr.	/ MR	
	b) Head of pump	Required	Provided	MR	
	c) Power supply	Required	Provided	MR	
	d) Auto starting of pump				
		Pt- Et-kel-			
14.	Captive Water Storage for	r Fire Fightin	N/A	NA	
1.4.	Under ground tank capaci	ty N/A	1.00.0		



NIZS

	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	e) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	10,000 ltr.	10,000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	Pressurization of lift shaft	N/A	N/A	N/A
	 b) Pressurization of lift lobby 	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any: ABC & CO ²			MR

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved, we may renew the FSC issued vide letter no F6/DFS/MS/GH/2020/98 dated 13/03/2020, up to third floor only under rule 35 of the Delhi Fire Service rules 2010. Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)