



# FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE

#### [See sub-rule (1) of rule 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/NDZ/2023/EH 125

Dated: 13 /04/2023

### FIRE SAFETY CERTIFICATE

Certified that The Platinum Lounge Restaurant running at shop no. G-17, ground floor of Star City Mall, Plot No. 01-A, Distt Centre, Mayur Vihar-1, Delhi building comprised of basement, ground floor & two upper floors, owned / occupied by Platinum Lounge Restaurant (A unit of True Blue Resto Bar Pvt. Ltd.), was earlier issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/EH/2020/NDZ/30 Dated 28/01/2020. The premises was re-inspected by the officer concerned of this department on 31/03/2023 in the presence of Sh. Dharambir Singh and observed that all the Fire prevention and Fire Safety arrangements provided in the premises found in good working condition. The premises have therefore, deemed complied with rule 33 of the Delhi Fire Service rules, 2010 and that the building / premises is fit for occupancy Class "Assembly" (Group-D) (Restaurant) with effect from 13 /04/2023 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of conditions under 38 of the Delhi Fire Service rules, 2010.

Issued on ......13.104. 20.23 ..... at New Delhi.

DELHI FIRE SERVICE.

Copy to :-

- 1. Joint Commissioner of Police (Lic.) P. S.: Defence Colony, New Delhi-110024 w.r.t. MHA portal ID-2023031303531 dated 15/03/2023.
- 2. Authorized Signatory, The Platinum Lounge Restaurant, shop no. G-17, ground floor of Star City Mall, Plot No. 01-A, Distt Centre, Mayur Vihar-1, Delhi.

## Conditions for the validity of Fire Safety Certificate:-

- 1. Fire Safety Certificate is valid for Ground Floor only.
- All the fire safety arrangement provided there in shall be maintained in good working conditions at all times.
- 3. Loss of life or property due to non- functional fire safety measure shall be at the responsibility of the
- The trained fire- fighting staff should be available round the clock.
- 5. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning
- This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 7. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

#### INSPECTION REPORT

1. Name & address of the building : Platinum Lounge Restaurant at G-17, Star City

Mall, Plot No. 01-A, Distt Centre, Mayur Vihar-1, Delhi.

2. Building is comprised of Basement, Ground & 2nd Floor only (Restaurant at Ground Floor only) 3. Type of Occupancy

: Assembly Type of Case

: Renewal 5. Details of previous NOC : F6/DFS/MS/EH/2020/NDZ/30 Dated 28/01/2020

: Mr. Dharambir Singh

Fire Safety directives Letter No. : F6/DFS/MS/BP/2004/1969 dated 30/08/2004

7. Date of inspection : 31/03/2023 8. Name of the Inspecting Officer

: A.K. Jaiswal (D.O. East)

Name and designation of Officer from the building side

10. Year of Construction : 2004 11. Applicant's MHA Portal No. : 2023031303531 dated 15/03/2023

S No	Minimum standards on fire prevention and fire safety U/R 33	NBC (Part-IV) Requirements	Provided at site	Remarks MR/NMR		
1.	Access of building					
	Road width	12 m	13 mtr	MR		
	Gate width	4.5 m	6 m ,	MR		
	Width of internal road	6 m	6 m	MR		
2.	Number, width, Type & Arrangements of exits					
	<ul> <li>a. Number of staircases</li> </ul>					
	Upper floors	NA	NA	NA		
	<ul> <li>Basements</li> </ul>	NA	NA	NA		
	<ul> <li>b. Width of staircases</li> </ul>					
	<ul> <li>Upper floors</li> </ul>	NA	NA	NA		
	<ul> <li>Basements</li> </ul>	NA	NA	NA		
	<ul> <li>Protection of exits</li> </ul>	NA		-		
	<ul> <li>Fire check door</li> </ul>	NA	NA	NA		
	<ul> <li>Pressurization</li> </ul>	NA	NA	NA		
	d. No of continuous staircase to terrace	NA	NA /	NA		
	e. Width Of Corridor	2.5 m	2.5 m /	MR		
	f. Door Size	2.00 m	2.00 m x 2	MR		
3.	Compartmentation					
	<ul> <li>Fire check door</li> </ul>	NA	NA	NA		
	<ul> <li>Sealing of electrical shafts</li> </ul>	Required	Seamed	MR		
	Fire Rating of shaft door	NA	NA	NA		
1	Water Curtain	NA	NA	NA		
	Fire Dampers	NA	NA	NA		
1.	Smoke managements System			100,000		
-	Basements	NA	NA	NA		
	Upper floors	Required	Provided	MR		
j.	Fire Extinguishers					
	Total numbers	2	4	MR _		
	• Types	ISI marked ABC/CO <sub>2</sub>	Provided	MR		
	IS marking	Required	Provided	MR		
	c Alb	507				

6.	First - Aid Hose Reels						
	<ul> <li>Total numbers on</li> </ul>	1	1	MR (			
	each floor     Length of hose reel	30 mtr.	30 mtr.	MR /			
	hose	Jo ma.					
	Nozzle diameter	5mm.	5mm.	MR /			
7.	Automatic fire detection and alarming system						
	Type of detector	Heat	Provided	MR (Old Case			
	Location of Main Panel	Control Room in Basement	Provided				
	Location of Repeater Panel	Security Room	Provided	Provided MR			
	Alternate source of power	Battery / DG Set	Provided MR				
	Hooters' Location	Different Location	Provided	MR			
8.	MOEFA	Required	Provided	MR			
9.	Public Address System	Required	Provided	MR			
10.	Automatic Sprinkler System						
	Basements	NA	NA	NA			
	Upper Floor	Required	Provided	MR			
	Sprinkler above false ceiling	Required	Provided MR				
11.	Internal Hydrants						
• • •	Size of riser/down- comer	100 mm	Provided	MR /			
	Number of hydrants per floor	1	Provided	Provided MR			
	Hose Box	2	Provided	MR			
12.	Yard Hydrants						
	Total number of	NA	1	NA			
	hydrants     Hose Box	NA	1	NA			
13.			1-7	1,			
	Pumping Arrangements Terrace Level	(All the pump are n	lounted on ter	racej			
•	The second secon	4500 LPM	4500 LPM	MR (			
•	Discharge of main pump Head of main pump	50 m	50 m	MR (			
-;		2	2	MR /			
-;		450 LPM	450 LPM	MR			
-;		50 m	50 m	MR			
-		4500 LPM	4500 LPM	MR			
7		50 m	50 m	MR /			
>	Auto Staring/Manual	Required	Provided	MR /			
Þ	stopping Pump House Access	Required	Provided	MR			
•	Ground level						
P	Discharge of pump	NA	NA	NA			
×	Head of the pump	NA	NA	NA			
×	Power supply	NA	NA	NA			
×		NA	NA	NA			
4.	Captive water Storage for fire	fighting					
	Underground tank capacity	2,00,000 ltr	2,00,000 ltr	MR			
-	> Draw of connection	Required	Provided	MR			
-	Fire service inlet	Required	Provided	MR			
	> Access to tank	NA	NA	NA			
	Overhead Tank	25,000 lts.	Provided	MR			
	• Overnead rank capacity	<b>1</b>	<b>***</b>	w			

15	Exit Signage	Required	Provided	MR	
16.					
	<ul> <li>Pressurization of Lift Shaft</li> </ul>	NA	NA	NA	
	Pressurization of lift lobby	NA	NA	NA	
	<ul> <li>Communication in lift Car</li> </ul>	NA	NA	NA	
	<ul> <li>Fireman's Grounding Switch</li> </ul>	NA	NA	NA	
	➤ Lift Signage	NA	NA	NA	
17.	Standby power supply	NA	NA	NA	
18.	Refuge Area				
	> Total area	NA	NA	NA	
	> Location	NA	NA	NA	
19.	Fire control room				
	Detector system panel	NA	NA	NA	
j	> Flow Switch Panel	NA	NA	NA	
1	> PA System Panel	NA	NA	NA	
İ	> Battery backup	NA	NA	NA	
t	> Building Floor Plans	NA	NA	NA	
20.	Special Fire Protection Systems for Protection of special Risks, if any;	Required	HT & LT Panel protected with local CO2	MR	

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. MCB and Conduit Metal Wiring has also been provided.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. F6/DFS/MS/ EH/2020/NDZ/30 Dated 28/01/2020 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

> Signature of the Inspecting Officer : A.K. Jaiswal Name

Designation: D.O. (East)