

FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/SZ/2023/ 909

Dated:04 /01/2023

FIRE SAFETY CERTIFICATE

Certified that the building of Shree Ganesh CGHS Ltd located at Plot no - 12 B, Sector - 7, Dwarka, New Delhi - 110075, having 3 blocks, comprised of Ground/Stilt + 09 /10 Upper Floors Fire Certificate this vide was issued Safety by department letter No. F6/DFS/MS/CGHS/2016/SZ/1304, dated 23/08/16. The premise was re inspected by the officer concerned of this department on 27/04/2023 in the presence of. Mr Parmod (Manager) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Residential Building" Group A-4 with effect from 6405 2013 for a period of five years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 04 05 7073 at New Delhi by.

Delhi Fire Service.

Copy to:

1. The President, Shree Ganesh CGHS Ltd located at Plot no - 12 B, New Delhi - 110075.

The Joint Director (Building) DDA, Vikas Sadan, INA, Delhi-110023.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

The trained staff should be available round the clock.

- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

Basement shall be used as per building bye laws.

7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. www.dfs.delhigovt.nic.in.

8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on

INSPECTION REPORT

- 1. Name & address of the building: Shree Ganesh CGHS Ltd located at Plot no-12 B, Sector-7, Dwarka, New Delhi - 110075.
- 2. Type of Occupancy

: Residential Building"A" (Apartment)

- Type of Case :- Renewal 03 Blocks (Ground/Stilt + 09 /10 U.FS)
- Details of previous NOC :F6/DFS/MS/CGHS/2016/SZ/1304 dated 23/08/16
- Fire Safety directives L. No.: F6/MS/DFS/CGHS/2001/488 dated 21/03/01

Date of inspection

: 27/04/2023

7. Name of the Inspecting Officer: Udai vir Singh. ADO (DWK)

8. Name and designation of Officer

from the building side

: Mr Parmod (Manager)

9. Year of Construction

10. Applicant's letter No. : Nil dated 02/04/2023

S No	Minimum standards on fire prevention and fire safety U/R 33	As per N/ & N/11	0			Remarks MR/NMR			
1.	Access of building								
	Road width	Required	tequired			MR			
1	Gate width	4.5 mtrs			Provided	MR			
	Width of internal road	Required Old C		Case	Case MR (Being o		d case)		
2.	Number, width, Type & Arrangements of exits								
	 a. Number of staircases 						1 dD		
	 Upper floors 	2 Nos.			rovided		MR		
	 Basements 	N/A	N/A			N/A			
	 b. Width of staircases 					1 m m			
	Upper floors	1.25 m	1.25 m & 1.2 m		250 DOMEST CONTRACTOR OF THE PROPERTY OF THE P		MR (Being old ase)		
	Basements	N/A	N/A N/A			N/A			
	c. Protection of exits								
	Fire check door	N/A	N/A N		N/A		N/A		
	Pressurization		N/A		N/A		N/A		
	d. No of continuous staircase terrace		Required		Provided		MR		
	e. Width Of Corridor	01 mtr	01 mtr		Provided		MR		
	f. Door Size	01 mtr			Provided		MR		
3.	Compartmentation								
	Fire check door	N/A			N/A		N/A		
	Sealing of electrical shafts Fire Rating of shaft door Water Curtain	Require	d	Sealed			MR		
		N/A		N/A			N/A		
		N/A			N/A		N/A		
	Fire Dampers	N/A	N/A		N/A		N/A		
4.	Smoke managements System								
	Basements				N/A		N/A		
	 Upper floors 	12 a/c pe	12 a/c per hour		Natural Ventilation		MR		



5.	Fire Extinguishers		7	117				
	 Total numbers 	2 nos anak flass		r Provided	M	1R		
	Types		2 nos. each floor		Provided		ſR	
	IS marking	CO ₂ & WCO ₂		Provided	lucu			
6.	First-Aid Hose Reels		ISI marked		Provided			
		1	L11. T		M	IR		
	 Total numbers on each floor Length of hose reel hose 		The second second second	block Provided		MR		
	Nozzle diameter	30 m 30 m				IR		
7.			5 mm	5 m	m	147		
	Automatic fire detection and Type of detectors			1500		V/A		
	 Type of detectors Location of Main Par 	N/A		N/A		V/A		
		N/A		N/A	N/			
	Eccution of Repeater	Panel	N/A		N/A	N/		
	restricted of p	N/A N/A			11111			
8.	Trooters Location			N/A		V/A		
o. 9.	MOEFA		Requir		Provided	MR		
10.	Public Address System	Requir	ed	Provided	\	ИR		
10.	Automatic Sprinkler System Basements			-1 0 1 1 2 2 2 2	37/4	137	/ A	
		N/A			N/A		N/A N/A	
	Upper Floor Sprinkler of the Column	N/A			N/A			
	Sprinkler above false	N/A	4		N/A	N/	A	
11.	ceiling							
11.	Internal Hydrants	ъ .				1 (D		
	Size of riser/down- co		Requir 1 each				MR	
		nber of hydrants per floor			Provided		MR	
10	Hose Box		Requir	ed Prov	vided		MR	
12.	Yard Hydrants	- 1-				1		
	 Total number of 	Rec	quired	Provide	d	MR		
	hydrants	-						
12	Hose Box	Rec	quired	. Pro	vided :		MR	
13.	Pumping Arrangements				North Herrison		_	
	Ground Level	200	0.1		20501	2.40		
	Discharge of main pu		0 lpm		2850 lpm	MR		
	➤ Head of main pump	70 1	mtr	-1252 8888	70 mtr	MR		
	 Number of main pum Jockey pump out put 	*3577	1		01	MR		
	 Jockey pump out put Jockey pump head 		lpm		450 lpm	MR		
	Standby Pump out pu	70 1			70 mtr	MR		
	Standby Pump Head		0 lpm		2850 lpm	MR		
	> Auto Staring/Manual		70 mtr		70 mtr	MR		
	stopping	Req	Required		Provided	MR	e.	
	> Pump House Access	Pag	Required		Descrided	Provided MR		
	Terrace level	Req	Required		Provided	MR		
	Discharge of pump	450	IDM	Provi	dad	MR		
	➤ Head of the pump	-	450 LPM Pro 40 mtrs Pro					
	> Power supply	-					MR	
	 Auto starting of pump 		Required Provide Required Provide					
14.	Captive water Storage for fire	Req				MIK		
	Under ground tank		2,00000 ltrs 2000001		Mitre	MR	(D	
	capacity	2,00			VIIIS	MIK		
	> Draw of connection	Reg	Required		Provided	MR		
	Fire service inlet	-	uired		Provided	MR		
	> Access to tank		uired		Provided	MR		
	Access to tank				1 I U TIUUU			
		-			Provided	MP		
5	Overhead Tank capaci Exit Signage	ty 10,0	00 Itr	Prov	Provided vided	MR MR		



16.	Provision of Lifts	_		N/18				
	 Pressurization of Lift Shaf Pressurization of lift lobby 		N/A		N/A			
	 Communication in lift Car Fireman's Grounding Switch Lift Signage 		Required		N/A		N/A N/A	
17.					Provided	-	MR	
		ch R	equire	d	Provided	-	MR	
	Ct., II		equire	d	Provided	MR	MR	
18.	Standby power supply Refuge Area	R	equire	d	DG Set	MR		
19.	Total areaLocation		I/A		N/A N/A			
	Fire control room	1	N/A		N/A	N/A		
	 Detector system panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans 	N/A N/A			N/A	N/A		
		N/A			N/A N/A	N/A		
		N/A			N/A	N/A N/A		
		Required			Provided	MR		
20.	Special Fire Protection Systems for Protection of special Risks, if any;	NA CO2 fire extinguisher provided				MR		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety required under the rules the NOC issued vide F6/DFS/MS/CGHS/2016/SZ/1304, dated 23/08/16 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer abolibles if

Designation