GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

F.6/DFS/MS/GH/2023/SZ/ 8.3 No.

Dated: 04.1.05.72023

FIRE SAFETY CERTIFICATE

Certified that the Guest House in the Name & Style of M/s Hotel Swapnil International located at RZA-43, NH-8, Mahipalpur Extn., New Delhi 110037 comprised of Basement (Storage only), Ground floor (rec. & 04 rooms) 1st Floor (10 Guest Room) and 2nd Floor Owner Residence Total 14 Guest Rooms was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/GH/2018/SZ/2376 dated 22/10/2018. The premise was re-inspected by the officer concerned of this department on 24/04/2023 in the presence of Ms. Saroj Singh and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential, Group-A" (Guest House with 14 Guest rooms upto 1st floor) as above and valid upto 31/03/2026 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 04/05 /2023 at New Delhi by

DELHI FIRE SERVICE

Copy to: -

opy to:
1. The Addl. Commissioner of Police (Lic.), 1st Floor, P.S. Defence Colony, New Delhi-110049 (Ref. MHA Portal ID 2023041406450 dated 16/04/2023)

2. The Executive Enginner MCD, Najafgarh Zone, Building Department, , Najafgarh Delhi 110043.

Conditions for the validity of Fire Safety Certificate: -

All the means of escape/entry/exit shall be kept free from any obstruction.

- All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The basement shall be used as per the provisions of BBL /NBC Part- IV.

All the staff members must know the correct method of operation of fire fighting system.

The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any

"The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."



,	INSPECTION	ON REP	ORT		
1	Name & Address of the Building	M/s Hotel Swapnil International at RZA-43, NH-8, Mahipalpur Extn., New Delhi 110037			
2	Type of Occupancy	Residential, "Group-A" (Guest House)			
3	Building Comprised of	Basement, Ground + 02 upper floors			
4	Type of Case	Renewal			
5	Details of Previous NOC	F6/DFS/MS/GH/2018/SZ/2376 dated 22/10/2018			
6	Fire Safety Directives Letter No	Nil			
7	Date of Inspection	24/04/2023			
8	Name of the Inspecting Officers	DO (South) & ADO (BCP)			
9	Name & Designation of Officers from the building side	Ms. Saroj Singh			
10	Year of construction	2000 Basement (Storage only) Gd Floor (Rec. & 04 Guer Rooms, 1st (10 guest room) and 2st floor (owner residence) total 14 Guest Rooms			
11	Applicant letter No.	MHA Po		2023041406450 dated 1	6/04/2023
S. No.	Minimum standards on Fire Prevention and Fire Safety U/R 33	Old !	NOC	Provided at Site	Remarks MR/NMF
1	Access to Building.				
	 Road width 	06 mtr		12 mtr	MR
	Gate width	-N		-NA-	-NA-
	Width of internal road	-N	A-	-NA-	-NA-
2	Number, width, type & arrangement of exits.				1
	a) Number of Staircase				
	Upper floors.	0110	Nos	Provided	MR
	> Basement floor.	02	200609	Provided	MR
	b) Width of Staircase	02	10	Tiovided	IVIIC
	> Upper floors	1.26		1.05 mtr	MR
	> Basement floor	1.25	mtr		(old case)
		1.25	mtr	1.30m & 0.95 mtr	MR (old case)
	c) Protection of exits	As per clause 7.31 in UBBL 2016			
	Fire check door	Required		Provided	MR
	> Pressurization	Requ		Provided	MR
	d) No. of continuous staircase to terrace	Or		Provided	MR
	e) Width of corridor			-NA-	-NA-
	f) Door size	-NA- lm		1.20mtr (Final Exit)	MR
3	Compartmentation.			1.20mm (1 mar Exit)	MIK
-	Fire check door	-N	Α.	-NA-	-NA-
	Sealing of electrical shafts.	-N		-NA-	-NA-
	- Bearing of electrical situits			-NA-	-NA-
		-N	^-		
	 Fire rating of shaft door 	-N			_
	Fire rating of shaft door Water curtain	-N	Α-	-NA-	-NA-
	 Fire rating of shaft door Water curtain Fire dampers 	-N	A- A-	-NA-	_
4	Fire rating of shaft door Water curtain Fire dampers Smoke Management system.	-N -N As per c	A- A- lause 7.3	-NA- -NA- 31 in UBBL 2016	-NA-
4	 Fire rating of shaft door Water curtain Fire dampers 	-N -N As per c 30 A	A- A- lause 7.3	-NA- -NA-	-NA-
4	Fire rating of shaft door Water curtain Fire dampers Smoke Management system. Basement Upper floors Fire Extinguishers.	-N -N As per c 30 A 12 A	A- A- lause 7.3 CPH CPH	-NANA- I in UBBL 2016 Exhaust fan provided Exhaust fan provided	-NA- -NA- MR MR
	Fire rating of shaft door Water curtain Fire dampers Smoke Management system. Basement Upper floors	-N -N As per c 30 A 12 A	A- A- lause 7.3 CPH CPH	-NANA- Bl in UBBL 2016 Exhaust fan provided Exhaust fan provided	-NANAMR
	Fire rating of shaft door Water curtain Fire dampers Smoke Management system. Basement Upper floors Fire Extinguishers.	-N -N As per c 30 A 12 A	A- lause 7.3 CPH CPH Nos	-NANA- I in UBBL 2016 Exhaust fan provided Exhaust fan provided Provided ABC & CO2	-NANAMR MR MR MR
	Fire rating of shaft door Water curtain Fire dampers Smoke Management system. Basement Upper floors Fire Extinguishers. Total numbers	-N -N As per c 30 A 12 A	A- lause 7.3 CPH CPH Nos	-NANA- Bl in UBBL 2016 Exhaust fan provided Exhaust fan provided	-NANAMR
	Fire rating of shaft door Water curtain Fire dampers Smoke Management system. Basement Upper floors Fire Extinguishers. Total numbers Types	-N -N As per c 30 A 12 A	A- lause 7.3 CPH CPH Nos	-NANA- I in UBBL 2016 Exhaust fan provided Exhaust fan provided Provided ABC & CO2	-NANAMR MR MR MR
5	Fire rating of shaft door Water curtain Fire dampers Smoke Management system. Basement Upper floors Fire Extinguishers. Total numbers Types ISI Marking	-N. As per c 30 A 12 A 10 1 ABC ISI m	A-A-A-Ilause 7.3 CPH CPH Nos CO2 arked	-NANA- I in UBBL 2016 Exhaust fan provided Exhaust fan provided Provided ABC & CO2 Provided	-NANAMR MR MR MR MR
5	Fire rating of shaft door Water curtain Fire dampers Smoke Management system. Basement Upper floors Fire Extinguishers. Total numbers Types ISI Marking First Aid Hose Reels.	-N -N As per c 30 A 12 A	A-A-A-Ilause 7.3 CPH CPH Nos / CO2 arked	-NANA- I in UBBL 2016 Exhaust fan provided Exhaust fan provided Provided ABC & CO2	-NANAMR MR MR MR

2112	ALC: I	PET 1
-3	ITTEL	THE PARTY

7	Automatic fire detection & alarming system. As per clause 7.31 in UBBL 2016			
5.05	Type of detectors			
	Location of Main Panel	Co/Mo/type	Provided	MR
	Location of Repeater Panel	Required	Provided	MR
	Alternate source of power	-NA-	-NA-	-NA
	Hooter's location	Required	Provided	MR
8	MOEFA	Required	Provided	MR
9	Public Address System	Required	Provided	MR
10	Automatic Sprinklan S	Required	Provided	MR
	Automatic Sprinkler System Basement			
		Required	Provided	MR
	• Upper floors.	-NA-	-NA-	-NA-
11	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11	Internal Hydrants.			1
	 Size of Riser/Down-comer 	Required	100 mm	MR
	Number of Hydrant per floor	-NA-	-NA-	-NA-
12	Hose box.	-NA-	-NA-	-NA-
12	Yard Hydrants.			-14/1-
	 Total number of hydrants. 	-NA-	-NA-	-NA-
	Hose box	-NA-	-NA-	-NA-
13	Pumping arrangements.		· · · ·	-NA-
	Ground Level			
	Discharge of main pump.	-NA-	-NA-	I NA
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output	-NA-	-NA-	-NA-
	Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head Auto Starting/Menual Standing	-NA-	-NA-	-NA-
	> Pump house access.	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
	Terrace Level			-NA-
	Discharge of pump.	450 LPM	Provided	MR
	Head of pump. Power supply. Auto starting of pump.	40m	Provided	MR
		Required	Provided	MR
		Required	Provided	MR
14	Captive water storage for fire fighting.			WIK
	Underground tank capacity	-NA-	-NA-	-NA-
	> Draw-off connection	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	. recess to talk.	-NA-	-NA-	-NA-
	Overhead tank capacity.	10,000 ltrs	10,000 ltrs	MR
15	Exit Signage.	Required	Provided	
16	Provision of Lifts.	12	Tiovided	MR
	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	Communication in lift car	-NA-	-NA-	-NA-
	Fireman's switch.	-NA-	-NA-	-NA-
	Lift signage.	-NA-	-NA-	-NA-
17	Standby Power Supply	Required	Provided	MR
18	Refuge Area		11071000	MIK
	Total area	-NA-	-NA-	-NA-
	Location	-NA-	-NA-	
19	Fire Control Room.		-WW-	-NA-

m



20	Special Fire Protection System for the Protection of special Risk, if any.			-NA-
	Building floor plan	-NA-	-NA-	-NA-
	Battery backup	-NA-	-NA-	-NA-
	PA system panel.	-NA-	-NA-	-NA-
	 Flow switch panel 	-NA-	-NA-	-NA-
	 Detector system panel. 	-NA-	-NA-	-NA-

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Further, the party has complied all the observation / Shortcoming already issued &

communicated by this department vide letter of even no 94 dated 28/02/2023.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/GH/2018/SZ/2376 dated 22/10/2018, renewal under rule 37 of the Delhi Fire Service rules 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspection Officer Name: Sh. Manoj Kumar Sharma

Design: DO (South)

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

yolard 1-L