

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No. F6/DFS/MS/School/WZ/2023/29 8

Dated:

03/05/2023

FIRE SAFETY CERTIFICATE

Certified that the Rose Valley Public School Located at RZ-20, Nathan Vihar, Nangloi-Najafgarh Road, Ranhola Village, New Delhi-110041, comprised of Ground + 02 Upper Floors only owned / occupied by Rose Valley Public School was issued Fire Safety Certificate by this department Vide Letter No. F6/DFS/MS/School/2020/90 dated 02.03.2020. The said premise was re-inspected by the officer concerned of this department on 20.04.2023 in the presence of Sh. P. C. Deswal (Director) and found that the premises/building have deemed complied with the fire prevention and fire safety requirements in accordance D.O.E. Cr. No. 3298-3398 dated 01.03.2011 and that the premises/building is fit for occupancy class "Educational Building" Group B with effect from 63/05/2023 for a period of three years, subject to compliance of the conditions, printed below.

Issued on 43. 45. 2023. at New Delhi by.

hi Fire Service

Copy to: -

The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi – 110054.

 The Principal, Rose Valley Public School, RZ-20, Nathan Vihar, Nangloi-Najafgarh Road, Ranhole Village, New Delhi-110041.

Following fire safety directives must be adhered to:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

 Name and address of the building: Rose Valley Public School Located at RZ-20, Nathan Vihar, Nangloi-Najafgarh road, Ranhola Village, New Delhi-110041

2. Type of Occupancy : Educational, (Ground + 02 Upper floors)

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/School/2020/90 Dated 02.03.2020

5. Fire Safety directives Letter No.: D.O.E. Cr. No. 3298-3398 dated 01-03-2011

6. Date of inspection : 20.04.2023

7. Name of the Inspecting Officer: Aman Kumar Lathar, ADO (JWP)

Name and designation of Officer

from the building side : Sh. P. C. Deswal (Director)

9 Year of Construction : 2006

10. Applicant's letter No. : Form "J" dated nil

S No	Minimum standards on fire prevention and fire safety U/R 33	D.O.E. Circular No 3298-3398 Dated 01.03.2011/ as per I dated 02.03.2020	site	at Remarks MR/NMR			
1.	Access of building						
	 Road width 	06 m	Provided	MR			
	Gate width	4.5 m	Provided	MR			
	 Width of internal road 	NA	NA	NA			
2.	Number, width, Type & Arrangements of exits						
	a. Number of staircases						
	 Upper floors 	02	Provided	MR			
	 Basements 	NΛ	NA	NΛ			
	 b. Width of staircases 			N/D			
	Upper floors	Old Case	1.5 m x 1 & 1.05 m x 1	MR			
	 Basements 	NA	NA	NA			
	c. Protection of exits						
	 Fire check door 	NΛ	NΛ	NA			
	 Pressurization 	NA	NA	NA			
	d. No of continuous staircase to terrace	01	Provided	MR			
	e. Width Of Corridor	NA	NΛ	NA			
	f. Door Size	1 m	Provided	MR			
3.	Compartmentation		NΛ				
	Fire check door	NΛ	NΛ	NΛ			
	 Sealing of electrical 	NA	NΛ	NΛ			
	shafts	NA	NΛ	NA			
	 Fire Rating of shaft door 	NA	NA	NA			
	Water CurtainFire Dampers	NΛ	NA	NA			
1.	Smoke managements System						
	Basements	NA	NΛ	NA			
	Upper floors	NΛ	NA	NΛ			

	Fire Extinguishers	04	06	1.45				
	Total numbers	04 nos.	06 nos.	MR				
	• Types	ABC & CO ₂	Provided	MR				
	IS marking	ISI marked	Provided	MR				
6.	First – Aid Hose Reels							
	 Total numbers on each floor 	01	Provided	MR				
	 Length of hose reel hose 	30 m	Provided	MR				
	 Nozzle diameter 	5 mm	Provided	MR				
7.	Automatic fire detection and alarming system							
	 Type of detectors 	NA	NΛ	NA				
	 Location of Main Panel 	NΛ	NA	NA				
	 Location of Repeater Panel 	NΛ	NA	NA				
	 Alternate source of power 	NΛ	NΛ	NA				
	 Hooters' Location 	NΛ	NA	NA				
8.	MOEFA	NΛ	NΛ	NΛ				
9.	Public Address System	NΛ	NA	NA				
10.	Automatic Sprinkler System							
	 Basements 	NΛ	NΛ	NA				
	Upper Floor	NΛ	NΛ	NA				
,.	Sprinkler above false ceiling	NΛ	NΛ	NA				
11.	Internal Hydrants:	1000						
	 Size of riser/down-comer 	NΛ	NΛ	NΛ				
	Number of hydrants per floor		NA	NΛ				
12	Hose Box	NΛ	NA	NA				
12.	Yard Hydrants	1						
	Total number of hydrants	NA	NA	NA				
13.	Hose Box	NA	NA	NΛ				
13.	Pumping Arrangements:							
	Ground Level							
	 Discharge of main pump Head of main pump 	NA NA	NA	NΛ				
	Number of main pumps	NA NA	NA NA	NA				
	> Jockey pump out put	NA NA	NA NA	NA				
	> Jockey pump head	NA NA	NA NA	NA NA				
	Standby Pump out put	NA	NA NA	NA NA				
	Standby Pump Head	NΛ	NA NA	NA				
	Auto Staring/Manual	NΛ	NA	NA				
	stopping		1	NA.				
	Pump House Access	NΛ	NA	NA				
	Terrace level							
	Discharge of pump	450 lpm	Provided	MR				
	Head of the pump Power supply	40 m	Provided	MR				
	Power supplyAuto starting of pump	Required	Provided	MR				
		Required	Provided	MR				
14.	Captive water Storage for fire fighting:							
	Under ground tank capacity	NA	NA	NA				
	 Draw off connection Fire service inlet 	NA NA	NA	NA				
	Access to tank	NA Parada	NA D	NA				
	Overhead Tank capacity	Required	Provided	MR				
15	Exit Signage	5,000 ltrs.	Provided	MR				
16.	Provision of Lifts	Required	Provided	MR				
10.	➤ Pressurization of Lift Shaft	NA	NA	NA				
	> Pressurization of lift lobby	NA NA	NA NA	NA NA				
	Communication in lift Car	NA NA	NA NA	NA				
	The state of the s	The second secon						
	Fireman's Grounding Switch	NA						
	Fireman's Grounding SwitchLift Signage	NA NA	NA NA	NA NA				

I

A

8.	Refuge Area		NA	NA		
	> Total area	NA	NA	NA NA		
	> Location	NA	NA			
19.	Fire control room					
	Detector system panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans	NA	NA			
		NA	NA	NA		
		NA	NΛ	NA		
		NA	NA	NA		
		NA NA	NA	NA		
20.		NA	NA	NA		

Fire protection systems provided in the building were checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety requirements as per D.O.E. Circular no. 3298-3398 dated 01.03.2011, renewal of Fire Safety Certificate issued vide letter no. F6/DFS/MS/School/2020/90 Dated 02.03.2020 is recommended.

Accordingly DFA is put up for approval please.

ADO (JWP)

TED TI John 2.2

Dineter

F.I. Sutter is produp for your mignature po