## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No F6/DFS/MS/2023/ 233

Dated 16 A 1 72023

## FIRE SAFETY CERTIFICATE

Certified that the Manakalya Bhawan located at 9, Bahadur Shah Zafar Marg, New Delhi - 110002, is comprised of Basement + Ground + 04 Upper floors owned/occupied by Manak Bhawan was issued earlier FSC by this department F6/DFS/MS/2003/NDZ/2689 dated 31/10/2003. Now, the premises was re-inspected by the officer concerned of this department on 04/05/22 in the presence of Sh. Anuj. Dy. Director and found that the said building has deemed complied with the fire prevention and fire safety requirements in in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 6 55 2023 at New Delhi by.

Delhi Fire Service

Copy to:-

1. The Executive Engineer (E), CPWD, Safdarjung Hospital Electrical Division, New Delhi

2. Sh. Sakuram Gugulothu ,Project management and works department, Room No 308-09. BIS Manakalya Bhawan 9, Bahadur Shah Zafar Marg, New Delhi - 110002.

## Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

9. Any flammable material for interior decoration is prohibited.

2

INSPECTION REPORT 1. Name & address of the building : Manakalya Bhawan 9, Bahadur Shah Zafar Marg, New Delhi - 110002. Type of occupancy : Business Building B + G + 04 upper floor Type of case:-: Renewal 4. Details of previous NOC : F6/DFS/MS/2003/NDZ/2689 dated 31/10/2003 Fire safety directives No. : 12 point inspection 6. Date of inspection:-04/05/2023. 7. Name of the inspecting officer : Sh. Ravinder Singh ADO/CC Sh. Rajinder Atwal, DO (CD) 8. Name & designation of officer From the building side : Sh. Anuj. Dy. Director 9. Year of construction : 1957 10. Applicant's letter No : mail id pmwd@bis.gov in dated 19 .04.2023 Old Case ( renewal ) Minimum Standards on fire Requirement S.No. Provided at Remarks Existing fire MR/NMR Prevention and fire safety site safety U/R 33 arrangements ١. Approach to Building 1) Road width 06 mtr. 06 Mtr. MR NA 2) Gate width NA NA NA NA NA 3) Width of internal road Number, Width Type & Arrangement of Exits 2. A. Number of staircases MR 1. Upper floors 02 Nos. 02 Nos. 02 Nos. 02 Nos. MR 2. Basements B. Width of staircase 1.5 mtr & MR 1.25 mtr & .75 1. Upper floors 1.10 mtr mtr 1.5 mtr. & MR 1.25 mtr.&.75 2. Basements 1.10 mtr mtr C. Protection of exits NA Provided NA 1. Fire check door NA NA NA 2. Pressurization D. No. of continuous 02 02 MR staircase to terrace NA NA NA E. Width of corridor 01 mtr. MR F. Door size 01 mtr. Compartmentation 3. Provided MR 1) Fire check door Required MR 2) Sealing of electrical shafts Required Provided NA NA NA 3) Fire rating of shaft door NA NA NA 4) Water curtain NA NA NA Fire Dampers 4. Smoke Management System 30 ACPH Provided MR 1) Basements 12 ACPH Natural MR 2) Upper floors Fire Extinguishers 5 20 Nos. 20 Nos. MR 1) Total numbers



ABC, CO2

Provided

MR

MR

ABC, CO2

Required

Types

3) ISI marking

		N/23		1
6.	First-Aid Hose Reel			
	1)Total number	01	Provid	ed MR
1	2) Length of hose reel hose	30 m	30 m	MR
	3) Nozzie diameter	5 mm	5 mm	MR
7.	Automatic Fire Detection &	Alarming Sys	tem	1.100
	Type of detectors(heat/sm )	oke Require		ded MR
l	2) Location of main panel	Gr. Flo	or Provid	led MD
	3) Location of repeater panel	NA NA	NA NA	The second secon
	4) Alternate source of power	D.G set		NA M
	5) Hooter's Location	Ground	Provid	
8.	MOEFA	Require		
9.	Public Address System	Require		The second secon
10.	Automatic Sprinkler System	1 Keduire	Provide	ed MR
	1) Basement	Required	f Provide	d MR
	2) Upper floors	NA	Provide	
		133	ground fourth f	&
	3) Sprinkler above false ceiling	. NA	NA NA	the first of the f
11.	Internal Hydrants	101/0	IVA	NA.
	1) Size of riser/down-comer	100 MM	100 MN	1 MR
	2) Number of hydrants floor	01	01	MR
	3) Hose box each floor	01	01	MR
12.	Yard Hydrants/external hydrant		1.93	Harix
	1) Total number of hydrants	02	Provided	MR
	2) Hose box	02	Provided	
3.	Pumping Arrangement		1	1 741
	1) Ground level			
	a) Discharge of main pump	1800 LPN	1 1800 LPM	I MR
	b) Head of main pump	70 mtr.	70 mtr.	MR
	c) Number of main pump	01	01	MR
-	d) Jockey pump out put	180 LPM	180 LPM	MR
	e) Jockey pump head	70 mtr.	70 mtr	MR
-	f) Stand by pump output	1800 LPM	1800 LPM	MR
	g) Stand by pump head	70 mtr.	70 mtr.	MR
	h) Auto starting/Manual stopping	Required	Provided	MR
	2) Terrace level			
-	a) Discharge of pump	900 LPM	Provided	MR
F	c) Power supply	Required	Provided	MR
- (	d) Auto starting of pump Captive Water Storage for Fire Fig.	Required	Provided	MR
	Under ground tank capacity		1,00,000 itr.	1.00
	a) Draw-off connection	Required	Provided	MR MR
	b) Fire service inlet	Required	Provided	MR
	c) Access to tank	Required	Provided	MR
	d) Over head tank capacity	20,000 litr.	40,000 litr.	MR
	xit Signage.	Required	Provided	MR
P	rovision of Lifts	And the second		
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	NA	N/A	N/A
	c) Communication in lift car	Required	Provided	MIR

	NIZM			
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	NA	NA	NA
	Total area location	NA	NA	NA
19	Fire Control Room	NA	NA	NA
	a) Detector system panel	Required	Provided	MR
	b) Flow switch panel	NA	NA	NA
	c) PA system panel	Required	Provided	MR
	d) Battery backup	Required	Provided	MR
	c) Building floor plan	NA	NA	NA
20.	Special Fire Protection System for Protection of special Risk, if any:			

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection. Further, shortcomings issued vide letter No.F6/DFS/MS/2021/NDZ/1957 dated 24.09.2021 found complied.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved, we may renew the FSC issued vide letter no F6/DFS/MS/2003/NDZ/2689 dated 31/10/2003, under rule 35 of the Delhi Fire Service rules 2010. Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name :- Sh. Rajinder Atwal Designation :- DO (CD)

Signature of the Inspecting Officer

Name :- Sh. Ravinter Singh Designation : ADO (CC)

A

1R

Pl. spik about earlier FSC mentioned

DO(CD) + ABO(CE)

- Spoken with DO(CD)

- Nowlast file is attached with mainfile.