GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2023/ \ CO

Dated :- 02/ 06 /2023

FIRE SAFETY CERTIFICATE

Certified that the M/s Lord Krishna Palace Guest House located at 2304-06, Laxmi Narayan Street, Chuna Mandi, Pahar Ganj, New Delhi comprised of Basement + Stilt + Ground + 03 Upper floors, Basement (Storage), stilt (parking), Ground floor to 3rd floor (07 guest rooms at each floor), total 28 guest rooms up to third floor only. The FSC was earlier granted by this department vide letter No. F6/DFS/MS/GH/NDZ/2020/93 dated 13.03.2020 for 28 guest rooms up to third floor only, Now, the premises was re-inspected by the officer concerned of this department on 23/05/23 in the presence of Sh. Manish Arora (Owner) and found that the said guest house building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, (Sub Division-A-1) Basement (Storage), stilt (parking), Ground floor to 3rd floor (07 guest rooms at each floor), total 28 guest rooms up to third floor only, and valid up to 31.03.2026 from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below

Issued 02/6/2023 at New Delhi by

Delhi Fire Service



1. The Commissioner, MCD, Civic Centre, New Delhi, to kindly ensure the occupancy as detailed above and deviation if any

2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi online ID No. online id no.2023051709106 dated 18:05 2023

3. Sh. Manish Gupta, M/s Lord Krishna Palace Guest House, 2304, 2305, 2306, Laxmi Narayan Street, Chuna Mandi, Pahar Ganj, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times
- 2 Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the

The trained fire fighting staff should be available round the clock.

4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned. Stilt floor shall be used strictly for parking only.

This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovi.nic.in

7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry

9. Any flammable material for interior decoration is prohibited

10. The basement shall be used strictly as per BBL concerned.

INSPECTION REPORT

M/s Lord Krishna Palace Guest House 1. Name & address of the building -

at 2304/2305/2306, Laxmi Naryan Street,

Chuna Mandi, Pahar Ganj, New Delhi

Residential, Sub Division-A-1 Type of occupancy -

B + Solt + Ground + 03 Upper floors

(total 28 Guest rooms)

Basement (Storage), Stilt floor (Parking), Ground Floor to 3rd floor (07 guest rooms at each floor)

3. Type of case:renewal

F6/DFS/MS/GH/NDZ/2020/93 dated 4. Details of previous FSC -

13 03 2020

5. Fire safety directives No.-

N/A

Date of inspection:-

23/05/23

7. Name of the inspecting officer -

Sh. Rajinder Atwal (DO/CD) &

Sh. Ravinder Singh, ADO

Name & designation of officer From the building side:-

Sh. Manish Arora (Owner)

2015

9. Year of construction:-10. Applicant's letter No online id no 2023051709106 dated 18.05 2023

| | Applicant's letter No | And the second section of the second section is a second section of the section of the second section of the sectio | 3021/03100 03(60.19 | | |
|-------|---|--|-------------------------|-------------------|--|
| S.No. | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement as per previous FSC | Provided at site | Remarks MR/NMF | |
| I. | Access to Building | | | | |
| | 1) Road width | N/A | 06 mtr. | MR | |
| | 2) Gate width | N/A | N/A | N/A | |
| | 3)Width of internal road | N/A | N/A | N/A | |
| 2. | Number, Width Type & Arr | | | | |
| 4. | A. Number of staircases | | T | | |
| | 1. Upper floors | 02 Nos. | 02 Nos. | MR | |
| | 2 Basements | 02 Nos. | 02 Nos | MR | |
| | B. Width of staircase | 14-13-4 | | | |
| | 1. Upper floors | 1.5 mtr. & 1.35 mtr. | 1.5 mtr. & 1.35 mtr. | MR | |
| | 2. Basements | 1.5 mtr. & 1.35 mtr. | 1.5 mtr. & 1.35 mtr. | MR | |
| | C. Protection of exits | | | | |
| | 1. Fire check door | N/A c | N/A | N/A | |
| | 2 Pressurization | N/A | N/A | N/A | |
| | D. No. of continuous staircase to terrace | 01 | 01 | MR | |
| | E. Width of corridor | 1.2 mtr. | 1.2 mtr. | MR | |
| | F Door size | 1 mtr. | 1 mtr | MR | |
| 3. | Compartmentation | | | | |
| | 1) Fire check door | N/A | N/A | N/A | |
| | 2) Sealing of electrical shafts | Required | Provided | MR | |
| | 3) Fire rating of shaft door | N/A | N/A | N/A | |
| | 4) Water curtain | N/A | N/A | N/A | |
| | 5) Fire Dampers | N/A | N/A | N/A | |
| 4. | Smoke Management System | | | | |
| | 1) Basements | 12 ACPH | Provided | MR | |
| | 2) Upper floors | 12 a/c per hour | Natural | MR | |
| 5. | Fire Extinguishers | 1 | | | |

V 6 00

MIR

| | I) To a l | 1010 | | | |
|-----|--|--|----------|------------|--|
| | 1) Total numbers | 20 Nos. | 20 Nos. | MR | |
| | 2) Types | ABC & CC | | | |
| | 3) ISI marking | Required | Provided | MR | |
| 6. | First-Aid Hose Reel | | rioridea | Wilk | |
| | Total number of eachflo | or 01 | 01 | MR | |
| | Length of hose reel hose | 30 m | 30 m | | |
| | 3) Nozzle diameter | 05 mm | 05 mm | MR MR | |
| 7. | Automatic Fire Detection & Alarming System | | | | |
| | | | | | |
| | 2) Location of main panel | At ground | Provided | MR | |
| | | floor | Provided | MR | |
| | Location of repeater pane | I N/A | N/A | N/A | |
| | 4) Alternate source of power | r At each floor | | MR | |
| | Hooter's Location | Required | Provided | MR | |
| 8. | MOEFA | Required | Provided | MR | |
| 9. | Public Address System | Required | Provided | | |
| 10. | Automatic Sprinkler Syste | m | Trovided | MR | |
| | 1) Basement | Required | Provided | 140 | |
| | 2) Upper floors | N/A | N/A | MR | |
| | 3) Sprinkler above false | N/A | N/A | N/A | |
| | ceiling | i i i | N/A | N/A | |
| 1. | Internal Hydrants | | | + | |
| | 1) Size of riser/down-comer | 100 mm | 100 mm | MR | |
| | Number of hydrants per floor | Required | Provided | MR | |
| | 3) Hose box | Required | Provided | MR | |
| 12. | Yard Hydrants | | | | |
| | 1) Total number of hydrants | N/A | N/A | N/A | |
| | 2) Hose box | N/A | N/A | N/A | |
| 3. | Pumping Arrangement | | 1074 | IN/A | |
| | Ground level | N/A | N/A | N/A | |
| | a) Discharge of main pump | N/A | N/A | N/A N/A | |
| | b) Head of main pump | N/A | N/A | | |
| | c) Number of main | N/A | N/A | N/A | |
| | pump | N/A | N/A | N/A | |
| | d) Jockey pump out put | N/A | N/A | N/A | |
| | e) Jockey pump head | N/A | N/A | N/A | |
| | Stand by pump output | N/A | N/A | N/A | |
| | g) Stand by pump head | The state of the s | N/A | N/A | |
| | h) Auto starting/Manual stopping | | N/A | N/A | |
| | 2) Terrace level | | | | |
| | a) Discharge of pump | 450 LPM 4 | 150 LPM | MR | |
| | | | 0 mtr | MR | |
| | | | Provided | MR | |
| | d) Auto starting of pump | Required P | rovided | MR | |
| 1. | Captive Water Storage for Fire Fighting | | | | |
| | Under ground tank capacity | The second secon | VA | N/A | |
| | a) Draw-off connection | N/A N | /A | N/A | |
| | b) Fire service inlet | The Control of the Co | | N/A | |



| | c) Access to tank | Required | Provided | |
|---------|--|-------------|-------------|-----|
| | d) Over head tank | 10,000 ltr. | 10,000 ltr | MR |
| | capacity | 10,000 111. | 10,000 ltr. | MR |
| 15. | Exit Signage. | Required | Provided | |
| 16. | Provision of Lifts. | required | rrovided | MR |
| | Pressurization of lift shaft | N/A | N/A | N/A |
| | Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | Required | Provided | MR |
| | d) Fireman's switch | Required | Provided | MR |
| | e) Lift signage | Required | Provided | MR |
| 17. | Stand by Power Supply | Required | Provided | MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| C = LJE | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection System for Protection of special Risk, if any: | | | N/A |

The original file is not teachable at MS cell, accordingly, the fire protection systems provided in the guest house building as per previous FSC inspection report, were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules 35(6), if approved, we may renew the FSC issued vide letter no F6/DFS/MS/GH/NDZ/2020/93 dated 13.03.2020, up to third floor only, under rule 35(6) of the Delhi Fire Service Rules 2010. Accordingly, DFA is put up for kind perusal/approval and signature please.

Signature of ipspecting officer

Name :- Sh. Rajinder Atwal Designation :- DO (CD)

Signature of the Inspecting Officer

Sh:- Ravinder Singh Designation :ADO/CC