## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI - 110001

No. F6/DFS/MS/EH/NDZ/2023/ \76

Dated: 0 77 0 6/2023

## FIRE SAFETY CERTIFICATE

Certified that the Eating House in the Name & Style of M/S Aslam Chicken Corner located at 972, 973 and 985, Ground & First Floor, Bazar Matia Mahal, Jama Masjid, Delhi, in the building comprised of Ground + 03 upper floor owned/ occupied by Aslam Chicken Corner have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of this department on 23.05.2023 in the presence of Mohd. Arbaaz (Owner) and that the premises is fit for occupancy class "Group - D Assembly" (Restaurant Running at Ground & 1" floor only) with effect from . 1 1 1 2023 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to conditions under Rule 38 of Delhi Fire Service Rules, 2010 printed below.

Issued on 07/06/2023 at New Delhi by

Délhi Fire Service Tel: 011-23414000

## Copy to:-

- The Joint Commissioner of Police (Licensing), 1st Floor, Police Station Defence Colony, New Delhi: - Ref. MHA Portal ID. No. 2023051508949 dated 15.05.2023.
- The Commissioner, Municipal Corporation of Delhi, Minto Road, New Delhi.
- The Manager, M/S Aslam Chicken Corner at 972, 973 and 985, Ground & First Floor, Bazar Matia Mahal, 3. Jama Masjid, Delhi.

## Condition for the validity of fire safety certificate

- This FSC is valid for ground & first floor only.
- All the fire safety arrangements provided therein shall be maintained in good working condition at all times. 1.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the 2 3. management
- The trained fire fighting staff should be available round the clock.
- Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority. 4\_ 5
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in. 7
- The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub Rule (I) of Rule 37] along with a copy of this Certificate, six month prior to its expiry. Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.

		The second of th	CTION REPOR	Corner locate	d at 972, 973 &		
	Name	e & address of the building	M/S Aslam Chiken Corner located at 972, 973 & 985, Ground & First Floor, Bazaar Matia Mahal Jama Masjid, Delhi -06.				
	Building is comprised of		Ground + 03 upper floors (Restaurant Running at GF & FF floor only)  2nd & 3nd floor- Owner's residence				
1	Турс	of occupancy	Assembly Building (Group-D)				
	Type of case		New Case				
_	Deta	ils of previous FSC	NA				
5	Deta	safety direction letter no.	UBBL-2016/ NBC Part-IV-2016				
5	Fire	Salety direction return	22.06.2023				
8	Nam	of inspection e of the inspecting officers	Rajinder Atwal DO (CD) & Sumit Kumar ADC (SPM)				
9	Nam	ne of the designation of officer in the building side	10 )				
10		r of construction	2002				
11		licant's letter no.	Online application no. 2023051508949 dated				
S.N o	Pre	nimum Standards on fire vention and fire safety uirements U/R 33	UBBL/ NBC Part-IV-2016	Provided at Site	Remarks MR NMR		
1	-	ess To Building:					
•		d width	06	Provided	MR		
	Gate width		NA	NA	NA		
	Width of internal road		NA	NA	NA		
2	Nu	mber, Width, Type and Arran	gement of Exits:				
	A	Number of staircases					
		a Upper floor	02 nos	02 nos.	MR -		
		b Basement	NA	NA	NA		
8	В	Width of staircases			1		
		- Hanne floor	1 6 mts aach	1.5 mtrs. each	MR V		
		a Upper floor	1.5 mtr. each				
		b Basement	NA NA	NA	NA		
	C	b Basement Protection of exits	NA	NA	NA		
	c	b Basement Protection of exits a Fire check door	NA NA	NA NA	NA NA		
		b Basement Protection of exits a Fire check door b Pressurization	NA NA NA	NA NA NA	NA NA NA		
	C	b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircases	NA NA	NA NA	NA NA		
	D	b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircases to terrace	NA NA NA 01 nos.	NA NA NA 01 nos.	NA NA NA MR ✓		
		b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircases	NA NA NA	NA NA NA	NA NA NA		
3	D E F	b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircases to terrace Width of corridor	NA NA 01 nos. NA 1.5 mtrs. – 02	NA NA NA 01 nos. NA	NA NA NA MR /		
3	D E F	b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircases to terrace Width of corridor Door size	NA NA 01 nos. NA 1.5 mtrs. – 02	NA NA NA 01 nos. NA Provided	NA NA NA MR  NA MR		
3	D E F	b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircases to terrace Width of corridor Door size  mpartmentation:	NA NA 01 nos. NA 1.5 mtrs 02 nos.	NA NA NA 01 nos. NA	NA NA NA MR  NA MR  NA MR		
3	D E F Co	b Basement  Protection of exits a Fire check door b Pressurization  No. of continuous staircases to terrace  Width of corridor  Door size  mpartmentation:  Fire check door	NA NA OI nos. NA 1.5 mtrs 02 nos.	NA NA NA 01 nos. NA Provided	NA NA NA NA NA NA NA NA		
3	D E F Co A B	b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircases to terrace Width of corridor Door size  mpartmentation: Fire check door Sealing of electrical shafts	NA NA OI nos. NA 1.5 mtrs. – 02 nos. NA NA	NA NA NA 01 nos. NA Provided NA NA NA	NA NA NA MR  NA MR  NA NA NA NA		
3	D E F Co A B C	b Basement  Protection of exits a Fire check door b Pressurization  No. of continuous staircases to terrace  Width of corridor  Door size  mpartmentation:  Fire check door  Sealing of electrical shafts  Fire rating of shaft door	NA NA OI nos. NA 1.5 mtrs. – 02 nos. NA NA	NA NA NA Ol nos. NA Provided  NA NA NA NA NA	NA NA NA NA MR  NA NA NA NA NA NA		
3	D E F Co A B C D E	b Basement  Protection of exits a Fire check door b Pressurization  No. of continuous staircases to terrace  Width of corridor  Door size  mpartmentation:  Fire check door  Sealing of electrical shafts  Fire rating of shaft door  Water curtain	NA NA OI nos. NA 1.5 mtrs. – 02 nos. NA NA NA NA	NA NA NA 01 nos. NA Provided NA NA NA	NA NA NA MR  NA MR  NA NA NA NA		
	D E F Co A B C D E	b Basement  Protection of exits a Fire check door b Pressurization  No. of continuous staircases to terrace Width of corridor Door size  mpartmentation: Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire dampers	NA NA OI nos. NA 1.5 mtrs. – 02 nos. NA NA NA NA	NA NA NA Ol nos. NA Provided  NA NA NA NA NA	NA		

0

8. M 20

5.	_	xtinguisher:	Lia	10 nos.	MR		
	A	Total numbers	10 nos.		-		
	В	Types	ABC & Co2	ABC & Co2	MR		
	C	ISI marking	Required	Provided	MR		
6	First-Aid-Hose Reels:						
	A	Total numbers of each floor	01 nos.	01 nos.	MR		
	В	Length of hose reel hose	30 mtrs.	30 mtrs.	MR /		
	C	Nozzle diameter	5 mm	5 mm	MR		
7	Automatic Fire Detection And Alarming System:						
	A	Type of detectors	NA	NA	NA		
	В	Location of main panel	NA	NA	NA		
	С	Location of repeater panel	NA	NA	NA		
	D	Alternate source of power		NA	NA		
8	E	Hooters Location	NA	NA	NA		
0.00	MOEF		Required	Provided	MR		
9		Address System:	NA	NA	NA		
10		atic Sprinkler System:					
	A	Basement	NA	NA	NA		
	В	Upper floor	NA	NA	NA		
	С	Sprinkler above false ceiling	NA	NA	NA		
11		l Hydrants:			-		
	A	size of riser/down-comer	100 mm	Provided	MR		
	В	Number of hydrants per floor	01 no.	01 no.	MR		
	C	Hose box	01 no.	01 no.	MR		
12		ydrants:					
	A	Total number of hydrants	NA	NA	NA		
	В	Hose box	NA	NA	NA		
13		g Arrangements:					
	A	Ground level					
	a)	Discharge of main pump	NA	NA	NA		
	b)	Head of main pump	NA	NA	NA		
	c)	Number of main pumps	NA	NA	NA		
	d)	Jockey pump out put	NA	NA	NA		
	e) f)	Jockey pump head	NA	NA	NA		
	g)	Standby pump out put	NA	NA	NA		
	h)	Standby pump head Auto starting /manual	NA	NA	NA		
		stopping /manual	NA	NA	NA		
	В	Terrace level					
	a)	Discharge of pump	450 LD) 4	400			
	b)	Head of the pump	450 LPM 40 mtrs.	10	MR (		
	c)	Power supply	Required	D	MR /		
	d)	Auto starting of pump	Required		MR		
	-		reduned	Provided	MR		

Pi 20

14	Captive Water Storage For Fire Fighting:					
	A	Underground tank capacity	NA	NA	NA	
1	В	Draw-off connection	NA	NA	NA	
1	C	Fire service inlet	Required	Provided	MR	
	D	Access to tank	NA	NA	NA	
	E	Overhead tank capacity	20,000 ltrs.	Provided	MR	
15	-	t Signage:	Required	Provided	MR	
16	Provision of Lifts:					
	A	Pressurization of lift shaft	NA	NA	NA	
	В	Pressurization of lift lobby	NA	NA	NA	
	C	Communication in lift car	NA	NA	NA	
	D	Firemen's grounding switch	NA	NA	NA	
	E	Lift signage	NA	NA	NA	
17		andby Power Supply:	Required	Provided	MR	
18	Defense Areas					
10	-	Total area	NA	NA	NA	
	A	Location	NA	NA	NA	
10	The Control of the Co					
19	-		NA	NA	NA	
	A	Detector system panel	NA	NA	NA	
	B	Flow switch panel	NA	NA	NA	
	C	Pa system panel	NA	NA	NA	
	D	Battery backup	NA	NA	NA	
	E	Building floor plans		NA	NA	
20	Sp	pecial Fire Protection Systems I pecial Risks, If Any:	ere tested, check	al as more		

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspections. Building is comprised of Ground plus four upper floors and terrace of fourth floor has been punctured at few locations and undertaking submitted that fourth floor will not be used for any purpose and the building is now comprised of ground plus three upper floors out of which second and third floor are being used as residence. Restaurant is running at ground and first floor only.

Keeping in view of the substantially satisfactory compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, it is recommended to grant Fire Safety Certificate to restaurant (Assembly Occupancy) at ground and first floor only under Rules 35(3) of the Delhi Fire Service Rules, 2010.

Signature of the Inspecting Officer

Name

Rajinder Atwal

Designation

DO (CD)

Signature of the Inspecting Officer

Name

Sumit Kumar

Designation

ADO (SPM)

Dy.CFO (NDZ)

NY SON

31 51 302

Dinector

106/20