Dated: 12/06/2023



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

No.F.6/DFS/MS/EH/2023/SZ/ / \$/

FIRE SAFETY CERTIFICATE

Certified that the M/s KD FOODS running at second floor only in a building comprised of basement, ground plus three upper floors located at D-4, Rajouri Garden, New Delhi-110027, owned/occupied by M/s KD FOODS have complied with the fire prevention and fire safety requirements in accordance with the Rule 33 of the Delhi Fire Service Rule 2010 and verified by the officers concerned of this department on 02/06/2023 in the presence of Sh. Juned (Maintance) and found that the building (Second floor only) is fit for occupancy 'Class D "Assembly Building" (Restaurant) ' for with effect from 12/06/2023 for a period of three years in accordance with the Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on 12/06/2023 at New Delhi by

Director

Delhi Fire Service

or he

Copy to:-

- 1. M/s KD FOODS, D-4, Second Floor, Rajouri Garden, New Delhi-110027
- The Joint Commissioner of Police, Licensing Unit, First Floor, Police Station, Defence Colony, New Delhi.

Following fire safety directives must be adhered to:-

- The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- All the means of escape shall be kept free of all the type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc. may be got verified from the authorities concerned.
- This Fire Safety Certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
 - The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: M/s KD FOODS, D-4, Second floor, Rajouri Garden, New Delhi-

110027.

Building comprised of : Basement, ground plus three upper floors but eating house at

second floor only.

3. Type of Occupancy : Assembly
4. Type of Case : New Case

5. Details of Previous NOC : F6/DFS/MS/Mercantile/2023/SZ/76 Dated 13/02/2023 (for entire

building)

6. Fire Safety directives letter No : F6/MS/DFS/BP/2019/242 dated 21/06/2019

7. Date of inspection : 02/06/2023

8. Name of Inspecting Officers : A.D.O. R.K. Yadav and D.O. Vedpal Chhikara

9. Name and designation of officers

From the building side : Sh. Juned (Maintance)

10. Year of Construction : 2022

11. Applicant's letter No. : ID No. 2023052309470 dated 23/05/2023

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Requirement	Provided at site	Remarks MR/NMR			
1.	Access to building						
Tile I	Road width	12 m	provided	MR			
	Gate width	N/A	On road	MR			
	Width of internal road	N/A	N/A	N/A			
2.	Number, Width, Type & Arrangement of Exits						
	a. Number of staircases		EIPLINE PARM				
	Upper Floors	Two	Provided	MR			
	Basements	N/A	N/A	N/A			
	b. Width of staircases						
	Upper Floor	2 m &1.5 m	2 m &1.5 m	MR			
	Basements	N/A	N/A	N/A			
	c. Protection of exits • Fire check door	Required	Provided	MR ~			
	Pressurization	N/A	N/A	N/A			
	Tressurization						
	d. No. of continuous staircases to	Two	Provided	MR			
	terrace	N/A	N/A	N/A			
	e. Width of Corridor f. Door Size	2 m &1.5 m	2 m &1.5 m	MR			
3.	Compartmentation			CO. C. C.			
die	Fire check door	Required	Provided	MR /			
	Sealing of electrical shafts	Required	Sealed	MR /			
	Fire Rating of shaft door Water Curtain	N/A	N/A	N/A			
	Water Curtain Fire Dampers	N/A	N/A	N/A			
	The Bampers	N/A	N/A	N/A			
4.	Smoke Management System						
	Basements	N/A	N/A	N/A			
	Upper floors	Required	Provided	MR			
5.	Fire Extinguishers						
	Total numbers Types	04 no.'s	Provided	MR			
	IS marking	ABC & CO _{2 Type}	Provided	MR			
The second		ISI marked	Provided	MR			

	Deale			MR		
6.	First-Aid Hose Reels Total numbers on each floor	One	Provided			
	Chara reel hose	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
	Automatic fire detection and alarming	system				
	T -C detectors	N/A	Provided	N/A		
	Location of Main Panel	N/A	N/A	N/A		
	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power Hooters' Location	Required	Provided	MR		
		Required	Provided	MR		
	MOEFA	Required	Provided	MR		
i. I.	Public Address System	N/A	N/A	N/A		
^	Automatic Sprinkler System					
0.	Basement	N/A	N/A	N/A		
	Ground Floor	N/A	Provided	N/A		
	Sprinkler above false ceiling	N/A	N/A	N/A		
1.	Internal Hydrants					
	Size of riser/down-comer	100 MM	Provided	MR		
	Number of hydrants per floor	One	Provided	MR		
	Hose Box	One	Provided	MR		
2.	Yard Hydrants					
	Total number of hydrants	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
3.	Pumping Arrangements Fire fighting system is common for entire building					
	Ground Level					
	 Discharge of main Pump Head of Main pump 	2280 LPM	Provided	MR		
	 Number of main pumps Jockey Pump out put 	60 m	Provided	MR		
		one	Provided			
				MR		
	Jockey pump head	180 LPM	Provided	MR		
	 Jockey pump head Standby Pump out put 	180 LPM 40 m	Provided Provided	SHEGGE		
	Jockey pump head	180 LPM 40 m 2280 LPM	Provided Provided Provided	MR		
	 Jockey pump head Standby Pump out put Standby Pump Head 	180 LPM 40 m 2280 LPM 60 m	Provided Provided Provided Provided	MR MR		
	 Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/Manual 	180 LPM 40 m 2280 LPM 60 m Required	Provided Provided Provided Provided Provided	MR MR MR		
	> Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access	180 LPM 40 m 2280 LPM 60 m	Provided Provided Provided Provided	MR MR MR MR		
	> Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level	180 LPM 40 m 2280 LPM 60 m Required Required	Provided Provided Provided Provided Provided Provided Provided	MR MR MR MR MR MR MR		
	> Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump	180 LPM 40 m 2280 LPM 60 m Required Required	Provided Provided Provided Provided Provided Provided Provided Provided	MR MR MR MR MR MR MR MR		
	> Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply	180 LPM 40 m 2280 LPM 60 m Required Required 900 LPM 40 m	Provided Provided Provided Provided Provided Provided Provided Provided Provided	MR MR MR MR MR MR MR MR		
	> Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump	180 LPM 40 m 2280 LPM 60 m Required Required	Provided	MR MR MR MR MR MR MR MR MR		
	> Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply	180 LPM 40 m 2280 LPM 60 m Required Required 900 LPM 40 m Required Required	Provided Provided Provided Provided Provided Provided Provided Provided Provided	MR MR MR MR MR MR MR MR		
1.	> Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump Captive Water Storage for fire fighting • Underground tank capacity	180 LPM 40 m 2280 LPM 60 m Required Required 900 LPM 40 m Required Required Required	Provided	MR		
	Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/Manual Stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting Underground tank capacity Draw-off connection	180 LPM 40 m 2280 LPM 60 m Required Required 900 LPM 40 m Required Required 2,00,000 ltrs.	Provided	MR M		
	Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/Manual Stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting Underground tank capacity Draw-off connection Fire service inlet	180 LPM 40 m 2280 LPM 60 m Required Required 900 LPM 40 m Required Required Required	Provided	MR M		
1.	Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/Manual Stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting Underground tank capacity Draw-off connection Fire service inlet Access to tank	180 LPM 40 m 2280 LPM 60 m Required Required 900 LPM 40 m Required Required Required Required	Provided	MR M		
4.	Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/Manual Stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting Underground tank capacity Draw-off connection Fire service inlet	180 LPM 40 m 2280 LPM 60 m Required Required 900 LPM 40 m Required Required Required Required Required	Provided	MR M		

U W

1	Provision of Lifts				
9	Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage	Required	Provided	MR	
		Required	Provided	MR	
		Required	Provided	MR	
		Required	Provided	MR	
		Required	Provided	MR	
17.	Standby power supply	Required	Provided	MR	
18.	Refuge Area.				
	Total Area Location	N/A	N/A	N/A	
		N/A	N/A	N/A	
19.	Fire Control Room				
	Detector System Panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans	N/A	N/A	N/A	
		N/A	N/A	N/A	
		N/A	N/A	N/A	
		N/A	N/A	N/A	
-		N/A	N/A	N/A	
20.	Special Fire Protection System for Protection of special Risks, if any:	Required	LT & HT Panel provided	MR	

The FSC was already issued vide letter No. F6/DFS/MS/Mercantile/2023/SZJ76 dated 13/02/2023 for mercantile part only.

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. The shortcomings issued vide letter No. F6/DFS/MS/EH/2023/SZ/264 dated 19/05/2023 has been complied.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under Rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer

Name

: R.K. Yadav

Designation: ADO (JKP)

Signature of the Inspecting Officer

Name

Vedpal Chhikara

Designation:

DO (SW)

CFO (HQ)

Dinester / 06/27

FIPT

ADODNO=onch

FT letter is put up for roge of

DIRECTOR DESMAN

9/6/23

00/2.0)