ming -

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELIII HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No F 6 DFS/MS/School/2023/SZI 395

Dated 07/06 / 2023

FIRE SAFETY CERTIFICATE

Certified that the Rao Ganga Ram Public School, at Old Delhi Gurgaon Road, Kapashera, New Delhi-110037 comprised of Ground plus two upper floor owned/occupied by Rao Ganga Ram Public School was issued Fire Safety Certificate by this department vide letter No F.6/DFS/MS/School/2020/SZ/125 Dated 18/03/2020. The said premise was re-inspected by officer concerned of this department on 31/05/2023 in presence of Mr Satish Kumar and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules 2010 and that the building is fit for occupancy class "Educational Building Group – B" with effect from 07/06/2023 for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under/Rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rule 2019

Issued on 07/06 2023 at New Delhi by

DIRECTOR DELHI FIRE SERVICE

Copy to: -

- The Principal, Rao Ganga Ram Public School, at Old Delhi Gurgaon Road, Kapashera, New Delhi-110037
- 2. The Directorate of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi- 110054

Conditions for the validity of Fire Safety Certificate

- All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 2. All the staff members must know the correct method of operation of firefighting system.
- 3. This certificate cannot be treated as regularization of unauthorized construction, if any
- The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

4/19

months interes

| | INSPECTIO | N REPORT | C.L. L. OHDAIL | Courgaon | |
|--------|--|--|------------------------------|----------|--|
| 1 | Name & Address of the Building | Rao Ganga Ram Public School, at Old Delin Gurgacat Road Kanashera, New Delhi-110037 | | | |
| | | Educational Building, "Group-B" (School) | | | |
| 2 | | Ground plus two u | pper floors | | |
| 3 | Bulluing Comprises C. | P-maral | | | |
| 4 | Type of Case Details of Previous NOC | F 6/DFS/MS/School/2020/SZ/125 Dt 18/03/2020 | | | |
| 5 | Fire Safety Directives Letter No | Nil | | | |
| 6 | | 31/05/2023 | | | |
| 7 | Date of Inspection Name of the Inspecting Officers | Sh Rajesh Kumar ADO (BCP) | | | |
| 9 | Name & Designation of Officers | Mr Satish Kumar | | | |
| 9 | from the building side | | | | |
| 10 | Year of construction | 2005 & 2012 | | | |
| 11 | Applicant letter No | RGRPS/2023/276 | dated 22/05/2023 | Remarks | |
| S. No. | the second secon | Requirements | Provided at Site | MR/NMR | |
| 1 | Access to Building. | | (-tr | MR | |
| • | Road width | Required | 6 mtr | MR | |
| | Gate width | Required | 5 mtr | -NA- | |
| | Width of internal road | -NA- | -NA- | -14/4- | |
| 2 | Number, width, type & arrangement of ex | cits. | | | |
| - | a) Number of Staircase | | 02 1/2 | MR | |
| | Upper floors. | 02 Nos | 02 Nos | -NA- | |
| | > Basement floor | -NA- | -NA- | -NA- | |
| | b) Width of Staircase | | | 1/0 | |
| | > Upper floors | 1 50 mtr | 1 60 mtr & 1 50 mtr | MR | |
| | Basement floor | -NA- | -NA- | -NA- | |
| | c) Protection of exits | | | -NA- | |
| | Fire check door | -NA- | -NA- | -NA- | |
| | | -NA- | -NA- | -NA- | |
| | > Pressurization | | 05 Nos | MR | |
| | d) No. of continuous staircase to terrace | -NA- | -NA- | -NA- | |
| | e) Width of corridor | 1 mtr | Provided | MR | |
| | f) Door size | 1 1110 | | | |
| 3 | Compartmentation. | -NA- | -NA- | -NA- | |
| | Fire check door | -NA- | -NA- | -NA- | |
| | Sealing of electrical shafts | -NA- | -NA- | -NA- | |
| | Fire rating of shaft door | -NA- | -NA- | -NA- | |
| | Water curtain | -NA- | -NA- | -NA- | |
| | Fire dampers. | -Jun- | 44.4 | | |
| 4. | Smoke Management system. | 30 ACPH | -NA- | -NA- | |
| | Basement | | | -NA- | |
| | Upper floors | 12 ACPH | -NA- | -WV- | |
| 5. | Fire Extinguishers. | 2222 | 20.51.1 | 110 | |
| | Total numbers | 20 No's | 20 No's | MR | |
| | Types | ABC / CO ₂ | ABC-26 & CO ₂ -14 | MR | |
| | ISI Marking | ISI marked | Provided | MR | |
| 6. | First Aid Hose Reels. | | | 1 100 | |
| - | Total numbers on each floor | 02 No's | 02 No's | MR | |
| | Length of hose-reel hose | 30m | 30m | MR | |
| | - Landing or more | 5mm | 5mm | ME | |

a

g



| 7 | Automatic fire detection & alexander | M2 -5-04 ST-5-5-5 | | वादी :: स्मृत घहोता |
|-------|---|--|------------|------------------------|
| 20010 | Automatic fire detection & alarming system. Type of detectors | | | |
| | Location of Main Panel | -NA- | -NA- | -NA- |
| | Location of Repeater Panel | -NA- | -NA- | -NA- |
| | Alternate source of power | -NA- | -NA- | -NA- |
| | Hooter's location | -NA- | -NA- | -NA- |
| 8. | MOEFA | -NA- | -NA- | -NA- |
| 9. | Public Address System | -NA- | -NA- | -NA- |
| 10. | Automatic Sprinkler System | -NA- | -NA- | -NA- |
| | Basement | -NA- | | |
| | Upper floors | -NA- | -NA- | -NA- |
| •• | Sprinkler above false ceiling | -NA- | -NA- | -NA- |
| 11. | internal Hydrants. | -NA- | -NA- | -NA- |
| | Size of Riser/Down-comer | -NA- | 212 | |
| | Number of Hydrant per floor | -NA- | -NA- | -NA- |
| 12. | • Hose box | -NA- | -NA- | -NA- |
| 14. | Yard Hydrants. | -in- | -NA- | -NA- |
| | Total number of hydrants | -NA- | 214 | |
| 13. | Hose box | -NA- | -NA- | -NA- |
| 15. | Pumping arrangements. | TATAL T | -NA- | -NA- |
| | Ground Level | 7 1 7 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | | |
| | Discharge of main pump | -NA- | 214 | |
| | Head of main pump | -NA- | -NA- | -NA- |
| | Number of main pumps | -NA- | -NA- | -NA- |
| | Jockey Pump output Jockey Pump head | -NA- | -NA- | -NA- |
| | Standby Pump output | -NA- | -NA- | -NA- |
| 7 | Standby Pump output Standby Pump head | -NA- | -NA- | -NA- |
| y | Auto Starting/Manual Storming | -NA- | -NA- | -NA- |
| 7 | > Pump house access. | -NA- | -NA- | -NA- |
| 7 | Terrace Level | -NA- | -NA- | -NA- |
| 7 | > Discharge of pump | | | -NA- |
| 1 | - Discharge of pump | 450 LPM | 450 LPM | T MD |
| - 1 | Head of pump Power supply | 40m | 40m | MR |
| | - Power supply | Required | Provided | MR |
| 4. | Auto starting of pump | Required | Provided | MR |
| - | Captive water storage for fire fighting. | | Tioridea | MR |
| 1 | Underground tank canacity | -NA- | -NA- | T NA |
| | Draw-off connection | -NA- | -NA- | -NA- |
| | Fire Service Inlet Access to tank | -NA- | -NA- | -NA- |
| | Access to tank | -NA- | -NA- | -NA- |
| . 1 | Overhead tank capacity Exit Signage. | 10,000 Ltr | 10,000 Ltr | -NA- |
| _ | Provision of Lifts. | Required | Provided | MR |
| + | | | | MR |
| | Pressurization of lift shaft | -NA- | -NA- | T NA |
| | Pressurization of lift lobby | -NA- | -NA- | -NA- |
| 1 | Communication in lift car | -NA- | | -NA- |
| | Fireman's switch | No. of the last of | -NA- | -NA- |
| | Lift signage | -NA- | -NA- | -NA- |
| S | | -NA- | -NA- | -NA- |
| _ | Standby Power Supply | -NA- | -NA- | - |
| R | Refuge Area | | -NA- | -NA- |
| | Total area | -NA- | MA | 1 200 |
| | Location | | -NA- | -NA- |
| - | ire Control Room. | -NA- | -NA- | -NA- |

7

~ C



| | -NA- | -NA- | -NA- |
|---------------------------------------|--|---|---|
| Flow switch panel PA system panel | -NA- | -NA- | -NA- |
| | -NA- | -NA- | -NA- |
| Ballery backup | -NA- | -NA- | -NA- |
| Special Firm P | -NA- | -NA- | -NA- |
| riotection of special Risk, if any | -NA- | -NA- | -NA- |
| 4 | PA system panel. Battery backup Building floor plan Special Fire Protection System for the Protection of special Risk if any. | PA system panel Battery backup Building floor plan Protection System for the Protection of special Risk, if any | PA system panel Battery backup Building floor plan PA |

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire as required under DOE circular, FSC issued F 6/DFS/MS/School/2020/SZ/125 Dt.18/03/2020, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name Sh. Rajesh Kumar Designation ADO (BCP)

DO (8D)

Any ports
As approved, F.T. Letter in pritup for