HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2023/ 113

Dated: 14/0.6/2023

FIRE SAFETY CERTIFICATE

Certified that the Prince Palace Dx. located at 5115, Gali Thanedar Wali, Main Bazar, Pahar Ganj, New Delhi is comprised of Ground + 03 Upper floors, Ground floor (reception + 02 offices) and 1st floor to 3rd floor (05 guest rooms at each floor), total 15 guest rooms up to third floor only. The FSC was earlier granted by this department vide letter No.F6/DFS/MS/GH/2019/2348 dated 20/12/19 for 15 guest rooms up to third floor only. Now, the premises was re-inspected by the officer concerned of this department on 06/06/23 in the presence of Manager and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, (Sub Division-A-1) Ground floor (reception + 02 offices) and 1st floor to 3rd floor (05 guest rooms at each floor), total 15 guest rooms up to third floor only, and valid up to 31.03.2026 from the date of issue in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 14 106/23at New Delhi by.

(Atu) Garg) DIRECTOR Pelhi Fire Service

Copy to:-

- 1. The Commissioner, MCD, Civic Centre, New Delhi. to kindly ensure the occupancy as detailed above.
- The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi online ID No.2023053009954 dated 31.05.2023.
- 3. The Manager, Prince Palace Dx. located at 5115, Gall Thanedar Wall, Main Bazar, Pahar Ganj, New

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any,
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi
 Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.
- 9. Any flammable material for interior decoration is prohibited.

N/28

INSPECTION REPORT

1. Name & address of the building Prince Palace Dx. located at 5115,

Gali Thanedar Wali, Main Bazar, Pahar

Ganj, New Delhi

Residential, Sub Division-A-1 2. Type of Occupancy:-

Gr. + 03 Upper floors (total 15 Guest rooms) Ground floor (reception + 02 offices) and 1st floor to 3rd floor (05 guest rooms at each floor), RI

W

12

in

F

Renewal Type of case:-

No.F6/DFS/MS/GH/2019/2348 dated 4. Details of previous FSC:-

20/12/19.

Manager

5. Fire safety directives No.-

N/A 06/06/23 6. Date of inspection:-

Sh. Ravinder Singh (ADO/CC) 7. Name of the inspecting officer:-

8. Name & designation of officer

from the building side:-

2001 9. Year of construction:-


ID No 2023053009954 dated 31.05.2023.

10. Applicant's letter No:-Old Case Remarks Provided at site Requirement Minimum Standards on fire S.No. MR/NMR Prevention and fire safety Existing fire safety U/R 33 arrangements Access to Building 1. MR 1.80 mtr. N/A 1) Road width N/A N/A N/A 2) Gate width N/A N/A N/A 3)Width of internal road Number, Width Type & Arrangement of Exits 2. A. Number of staircases MR 01 No. 01 No. 1. Upper floors N/A N/A N/A 2. Basements B. Width of staircase MR 1.18 mtr. 80 cms. 1. Upper floors N/A N/A N/A 2. Basements C. Protection of exits N/A N/A N/A 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A D. No. of continuous staircase to terrace N/A N/A N/A E. Width of corridor MR 01 mtr. 01 mtr. F. Door size Compartmentation 3. N/A N/A N/A 1) Fire check door N/A N/A Sealing of electrical shafts N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers Smoke Management System 4. N/A N/A 30 ACPH 1) Basements MR Natural 12 n/e per hour 2) Upper floors Fire Extinguishers 5. MR 08 Nos. 08 Nos. 1) Total numbers ABC & CO2 MR ABC & CO2 2) Types MR Required Provided 3) ISI marking

(so)

NEA

| | 7. | | | | |
|-----|------------------------------------|---|--|--|--|
| 6. | First-Aid Hose Reel | | | 64 | |
| | 1) Total number of eachfloor | 01 | 01 | MR | |
| | 2) Length of hose reel hose | 30 mtr. | 30 mtr. | MR | |
| | 3) Nozzle diameter | 05 mm | 05 mm | MR | |
| 7. | Automatic Fire Detection & | | | | |
| | 1) Type of detectors Co type | Required | Provided | MR | |
| | 2) Location of main panel | At ground floor | Provided | MR | |
| | 3) Location of repeater panel | N/A | N/A | N/A | |
| | 4) Alternate source of power | At each floor | Provided | MR | |
| | 5) Hooter's Location | Required | Provided | MR | |
| 8. | MOEFA | N/A | N/A | N/A | |
| 9. | Public Address System | Required | Provided | MR | |
| 10. | Automatic Sprinkler System | | | | |
| | 1) Basement | N/A | N/A | N/A | |
| | 2) Upper floors | N/A | N/A | N/A | |
| | Sprinkler above false ceiling | N/A | N/A | N/A | |
| 11. | Internal Hydrants | J 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | | | |
| | 1) Size of riser/down-comer | N/A | N/A | N/A | |
| | 2) Number of hydrants per floor | N/A | N/A | N/A | |
| | 3) Hose box | N/A | N/A | N/A | |
| 12. | Yard Hydrants | | 10/14 | IIVA | |
| | 1) Total number of hydrants | N/A | N/A | N/A | |
| | 2) Hose box | N/A | N/A | N/A | |
| 13. | Pumping Arrangement | | THE STATE OF THE S | INA | |
| | 1) Ground level | N/A | N/A | NUA | |
| | a) Discharge of main | N/A | N/A | N/A | |
| | pump | | N/A | N/A | |
| | b) Head of main pump | N/A | N/A | N/A | |
| | c) Number of main pump | N/A | N/A | N/A | |
| | d) Jockey pump out put | N/A | N/A | N/A | |
| | e) Jockey pump head | N/A | N/A | N/A | |
| | f) Stand by pump output | N/A | N/A | N/A | |
| | g) Stand by pump head | N/A | N/A | N/A | |
| | h) Auto starting/Manual stopping | N/A | N/A | N/A | |
| | 2) Terrace level | | 1 | | |
| | a) Discharge of pump | 225 LPM | 225 LPM | MR | |
| | b) Head of pump | 25 mtr. | 25 mtr. | MR | |
| | c) Power supply | Required | Provided | MR | |
| | d) Auto starting of pump | Required | Provided | MR | |
| 14. | Captive Water Storage for F | Tivik | | | |
| | Under ground tank capacity | N/A | N/A | N/A | |
| | a) Draw-off connection | N/A | N/A | N/A | |
| | b) Fire service inlet | N/A | N/A | N/A | |
| | c) Access to tank | N/A | N/A | The state of the s | |
| | d) Over head tank | 2,500 ltr. | THE RESIDENCE OF THE PARTY OF T | N/A | |
| 15. | capacity Exit Signage. | 2,500 Itr. | 2,500 ltr. | MR | |



MP M

| 16 | Provision of Lifts. | | | N/A |
|-----|--|--------------|--|---------------|
| 16. | Pressurization of lift shaft | N/A | N/A | N/A |
| | | | N/A | N/A |
| | b) Pressurization of lift | N/A | 14/74 | 31/4 |
| | c) Communication in | N/A | N/A | N/A |
| | lift car | | N/A | N/A |
| | d) Fireman's switch | N/A | The second secon | N/A |
| | e) Lift signage | N/A | N/A | MR |
| | Stand by Power Supply | Required | Provided | |
| 17. | | N/A | N/A | N/A |
| 18. | Refuge Area | The sections | N/A | N/A |
| | Total area location | N/A | III.C | |
| | 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | N/A | N/A | N/A |
| 19. | Fire Control Room | | N/A | N/A |
| | a) Detector system panel | N/A | 10000 | |
| | | 12114 | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | IN/A | 1 2 2 2 2 2 2 |
| | | | N/A | N/A |
| | e) Building floor plan | N/A | 1.00 | N/A |
| 20. | Special Fire Protection System for Protection of special Risk, if any: | | | SCO COVERED |

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved, we may renew the FSC issued vide letter no F6/DFS/MS/GH/2019/2348 dated 20/12/19, up to third floor only, under rule 35(6)of the Delhi Fire Service rules 2010. Accordingly, DFA is put up for kind perusal and signature please. Signature of the Inspecting Officer

Name :- Ravinger Singh Designation :- ADO (CC)