No.F6/DFS/MS/School/NDZ/2023/442

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELIII HEADQUARTERS: DELIII FIRE SERVICE: NEW DELIII- 110001



Dated: 27/ 06/2023

## FIRE SAFETY CERTIFICATE

Certified that the Sarvodaya Kanya Vidyakaya located at Pocket- IV, Mayur Vihar- I, Delhi-110091 (School I.D- 1002036), building comprised of Ground + 3 upper floors. (B- block), owned / vide letter No. occupied by Sarvodaya Kanya Vidyakaya, was issued FSC F6/DFS/MS/School/2019/NDZ/565 dated 15.03.2019. The School building was re-inspected by the officer concerned of this department on 15/06/2023 in presence of Mrs. Neeraj Kumari (Principal) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with rule 33 of Delhi Fire Service Rules, 2010 and that the building is fit for occupancy class "Educational" (Group-B) with effect from .27 06 12023. for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rule 2010.

Issued on 27/06/2023 at New Delhi by.

Copy to:-

- 1. The Principal, Sarvodaya Kanya Vidyakaya located at Pocket- IV, Mayur Vihar- I, Delhi-110091.
- 2. The Dy. Director of Education, located at D- Block, Anand Vihar, Delhi-110054.

## Conditions for the validity of Fire Safety Certificate

- 1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule(1) of rule 37] along with a copy of this certificate, six months prior to its expiry
- 2 All the means of escape shall be kept free of all the type of obstruction all the time
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- 6 This Fire Safety Certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic in
- 8. Fire Safety Certificate is valid for Block- B of Ground & 3 upper floors only.

	1			TION REPORT			
L	Name & address of the building			Sarvodaya Kanya Vidyakaya located at Pcoket- IV, Mayur Vihar- I, Delhi-110091 (School I.D- 1002036)			
2			ng is comprised of	Ground + 3 upper flo		1002000	
3			f occupancy	Educational Building			
4			f case	Renewal _	<u> </u>		
5			of previous FSC	The state of the s	2010/NDZ/565 dat	~4.15.03.2010	
6			fety directives letter no.	F6/DFS/MS/School/2019/NDZ/565 dated 15.03 2019 NBC (Part- IV)			
7			finspection	15.06.2023			
8	Name of the inspecting officers			22.4 Strate Sept. 5(5)	an ADOUL NI		
9	Nan	om the building side  Yaswant Singh Meena, ADO (L.N)  Mrs. Neeraj Kumari (Principal)					
10			f construction	1994			
11			ant's letter no.	Outdoor Diary No.26	621 dated 08 06 20	133	
S.No	Mii	nim even	num standard of fire ntion and fire safety U/R 33	Requirement 1	Provided at site		
1	1		s to Building:			The second live of the second	
1 /	A	-	oad width	10 mtrs	10 mtrs	MR	
	В	-	iate width	4.5 mtrs.	4.5 mtrs.	MR	
	C		Vidth of internal road	NA	NA	NA	
2		mb	er, Width, Type and Arrange	ment of Exits:		10000	
	A	N	lumber of staircases				
		a	Upper floor	02 nos.	02 nos	MR	
		b	ROSE CONTROL OF CONTRO	NA	NA	NA	
	В	V	Width of staircases			115003	
		а	Upper floor	1.5 mtrs each.	1.7 mtrs each.	MR	
		ь	Basement	NA	NA	NA	
	C	P	Protection of exits	NA	NA	NA	
		а	Fire check door	NA	NA	NA	
		ь	Pressurization	NA	NA	NA.	
	D		No. of continuous staircases to	L. I. (1) (2) (2)	02 no.	MR	
	E	V	Width of corridor	1.5 mtrs	1.5 mtrs.	MR	
	F	Γ	Door size	1.0 mtrs (for class room)	C. S. SHOOMAGNED	MR	
3	Compartmentation:						
	A	I	Fire check door	NA	NA	NA	
	В	5	Sealing of electrical shafts	NA	NA	NA	
	C		Fire rating of shaft door	NA	NA	NA	
	D		Water curtain	NA	NA	NA	
	E	-	Fire dampers	NA	NA	NA.	
4	Sr	nol	ke Management System:		1	1777	
	A	-	Basement	NA	NA	NA	
4	B	7	Upper floor	NA	NA	NA	

9,	-	re Extinguisher:						
	A	Total numbers	20 nos	20 nos	MR			
	B	Types	CO <sub>2</sub> & ABC	CO2& ABC	MR			
_	C	ISI marking	ISI Marked	Provided	MR			
6	First-Aid-Hose Reel:							
	A	Total numbers of each floor	02 nos	02 nos	MR			
	B	Length of hose reel hose	30 mtrs	30 mtrs	MR			
_	C	Nozzle diameter	5 mm	5 mm	MR			
7	Au	tomatic Fire Detection and Al	arming System:					
	٨	Type of detectors	NA	NA	NA			
	B	Location of main panel	NA	NA	NA			
	c	Location of repeater panel	NA	NA	NA			
	D	Alternate source of power	NA	NA	NA			
_	E	Hooters	NA.	NA	NA			
8	-	OEFA:	NA	NA	NA			
9	Pu	blic Address System:	NA	NA	NA			
10	Au	tomatic Sprinkler System:	4	122.2	Tiestor.			
	A	Basement	NA	NA	NA			
	B	Upper floor	NA	NA	NA			
	C	Sprinkler above false ceiling	NA	NA NA	NA			
11	Int	ernal Hydrants:	0.507	11898	INA			
	A	Size of riser/down-comer	NA	NA	Tay a			
	В	Number of hydrants per floor	NA	NA NA	NA NA			
	C	Hose box	NA	NA NA	-			
12	Ya	rd Hydrants:	1	Livor	NΛ			
	A	Total number of hydrants	NA	NA	TXC			
	В	Hose box	NA NA	100.000	NA			
13	Pu	mping Arrangements:		NA	NA			
		Ground level						
	A	Discharge of main pump	NA	Tar	f			
	В	Head of main pump		NA	NA			
	C	Number of main pumps	NA	NA	NA			
	D	Jockey pump out put	NA	NA	NA			
	E	Jockey pump head	NA	NA	NA			
	F	Standby pump out put	NA NA	NA	NA			
	G	The state of the s	NA	NA	NA			
	Н	Standby pump head Auto starting /manual	NA	NA	NA			
	725.	stopping	NA	NA	NA			
	1	Pump house access	NA	NA	31.			
	Ter	race Level		INA	NA			
	A	Discharge of pump	450 LPM	2 X 450 LPM	Liver			
	В	Head of the pump	40 mtrs	40 mtrs	MR			
	C	Power supply	Required	Provided	MR MR			
	D	Auto starting of pump	Required	Provided	MR			

14	Captive Water Storage for Fire Fighting:						
	A	Underground tank capacity	NA	NA	NA.		
	В	Draw-off connection	NA	NA	NA		
	C	Fire service inlet	NA	NA	NA		
	Ð	Access to tank	NA	NA	NA		
	E	Overhead tank capacity	10,000 Ltrs	10,000 Ltrs	MR		
15	Ex	it Signage:	Required	Provided	MR		
16	1 2007 111222 1 200 1 202 1 202						
	A	Pressurization of lift shaft	NA NA	NA	NA		
	В	Pressurization of lift lobby	NA	NA:	NA		
	C	Communication in lift car	NA	NA	NA		
	D	Firemen's grounding switch	NA	NA	NA		
	E	Lift signage	NA	NA	NA		
17	Sta	indby Power Supply:	NA	NA	NA		
18	Refuge Area:						
	A	Total area	NA	NA	NA		
	В	Location	NA	NA	NA		
19	I I I I I I I I I I I I I I I I I I I						
	A	Detector system panel	NA	NA	NA		
	В	Flow switch panel	NA	NA	NA		
	C	PA system panel	NA	NA	NA		
	D	Battery backup	NA	NA	NA		
	E	Building floor plans	NA	NA	NA		
20	Sp	ecial Fire Protection systems for otection of special Risks, if any:	NA	NA	NA		

Note: - FSC is valid for B, Block only which is ground + 3 upper floor, "A" block is written wrongly in previous I/R & FSC.

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspections.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required in NBC (Part-IV) the FSC issued vide letter no. F6/DFS/MS/School/2019/NDZ/565 dated 15.03.2019 is recommended to beyonewed

> Signature of the Inspecting Officer Yaswant Singh Meena Name Designation ADO (L.N)

DGA is not correct Put up new DGA
renewal case.

o Lax Sign. Pleasy