

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No. F6/DFS/MS/School/WZ/2023/ 464

Dated: 10-7-2023

FIRE SAFETY CERTIFICATE

Certified that the Govt. Sarvodaya Kanya Vidyalaya Located at Ashok Vihar, Phase-II, New Delhi-110052, comprised of 03 Blocks (BL-1=Ground + 02 Upper Floors & BL-2 & 3=Ground + 01 Upper Floors each owned/occupied by Govt. Sarvodaya Kanya Vidyalaya was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/School/2017/1070 Dated 26.04.2017. The said premise was re-inspected by the officer concerned of this department on 28.06.2023 in the presence of Ms. Neena Popli (H.O.S) and found that the premises / building have deemed complied with the fire prevention and fire safety requirements in accordance D.O.E., GNCT of Delhi, Circular no. 3298-3398 dated 01-03-2011 and that the premises/building is fit for occupancy class "Educational Building" Group B with effect from 10-07-2023 for a period of three years, subject to compliance of the conditions, printed below.

Issued on 10-07-2023 at New Delhi by.

Copy to: -

1. The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi - 110054.

2. The Principal, Govt. Sarvodaya Kanya Vidyalaya, Ashok Vihar, Phase-II, New Delhi-110052.

Following fire safety directives must be adhered to:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

A Principle of the Parket

INSPECTION REPORT

1. Name and address of the building: Govt. Sarvodaya Kanya Vidyalaya Located at Ashok Vihar, Ph-II, New Delhi-110052.

2. Type of Occupancy : Educational, 03 Blocks (BL-1=G+2 UFs & BL-2,3= G+01 UF)

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/School/2017/1070 Dated 26.04.2017

5. Fire Safety directives Letter No.: D.O.E Cr.no.3298-3398 dated 01-03-2011

6. Date of inspection : 28.06.2023

7. Name of the Inspecting Officer: Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side : Ms. Neena Popli (H.O.S)

9. Year of Construction : 1976

10. Applicant's letter No. : email dated 15.06.2023

No	Minimum standards on fire prevention and fire safety U/R 33	D.O.E. Circular No. 3298-3398 Dated 01.03.2011/ as per FSC dated 26.04.2017		Provided at site		Remarks MR/NMR		
1.	Access of building							
	Road width	Accessible	08 m 3.60 m MI NA		MR R(Old Case) NA			
	Gate width	Accessible						
	 Width of internal road 	NA						
2.	Number, width, Type & Arrangements of exits							
	a. Number of staircases	The state of the s	Dir Der					
	Upper floors	BL-1=2, BL-2=1 & BL-3=1	BL-1=3, BL-2=1 & BL-3=1 NA			MR		
	Basements	NA			NA			
	b. Width of staircases	Land and		100				
Carlo Company	Upper floors	1.5 m	BL-	BL-1=1.4 m x 1, 1.25 m x 2 BL-2=1.5 m x 1 BL-3=1.6 m x 1		MR		
	Basements	NA		NA		NA		
1	c. Protection of exits			The state of the s				
	Fire check door	NA	T	NA		NA		
	Pressurization	NA		NA		NA		
1	d. No of continuous staircase to terrace	01	11/4	Provided	w/J	MR		
	e. Width Of Corridor	1.5 m		Provided	l	MR		
	f. Door Size	1 m		Provided	ed MR			
3.	Compartmentation		NA					
1	Fire check door	NA	NA		NA			
	 Sealing of electrical 	NA	NA		NA			
	shafts	NA		NA		NA		
	Fire Rating of shaft door	NA		NA		NA		
	Water CurtainFire Dampers	NA	1 100	NA		NA		
4.	Smoke managements System	rather or house						
	Basements	NA	o de la	NA		NA		
	Upper floors	NA	NA			NA		

5.	Fire Extinguishers	20 ===	27	10			
	Total numbers	20 nos.	27 nos.	MF			
1	• Types	ABC & CO ₂	Provided	MI			
1771	IS marking	ISI marked	Provided	MI			
6.	First-Aid Hose Reels						
	 Total numbers on each floor 	03 in BL-1	Provided	M			
	 Length of hose reel hose 	30 m	Provided	M			
10	Nozzle diameter	05 mm	Provided	M			
7.	Automatic fire detection and alarmin	ng system					
	Type of detectors	NA	NA	N.			
	 Location of Main Panel 	NA	NA	N.			
	 Location of Repeater Panel 	NA	NA	N.			
	Alternate source of power	NA	NA	N/			
	Hooters' Location	NA	NA	N/			
8.	MOEFA	NA	NA	N/			
9.	Public Address System	NA NA	NA	N/			
10.	Automatic Sprinkler System	IVA	BL-1	111/			
10.		NA Provided		N/			
	Basements Unner Floor	NA NA	Provided	N/			
	Upper Floor		Provided	NA NA			
	Sprinkler above false ceiling	INA	Provided	INA			
11.	Internal Hydrants:	N14	I NIA I	NIA			
	Size of riser/down-comer	NA	NA NA	NA NA			
	Number of hydrants per floor		NA NA	NA NA			
	Hose Box	NA	NA	INA			
12.	Yard Hydrants	T 374 T	274	NA			
	Total number of hydrants	NA	NA	NA			
	Hose Box	NA	NA	NA			
13.	Pumping Arrangements:	-					
	Ground Level	NA	T NA T	NIA			
	Discharge of main pump	NA NA	NA NA	NA			
	> Head of main pump	NA	NA NA	NA			
	Number of main pumpsJockey pump out put	NA NA	NA NA	NA NA			
	> Jockey pump head	NA NA	NA NA	NA NA			
	Standby Pump out put	NA NA	NA NA	NA			
	> Standby Pump Head	NA NA	NA NA	NA			
	> Auto Staring/Manual	NA	NA NA	NA			
	stopping	144	1374	1471			
	Pump House Access	NA	NA	NA			
	Terrace level						
	Discharge of pump	450 lpm	Provided	MR			
	> Head of the pump	40 m	Provided	MR			
	> Power supply	Required	Provided	MR			
	> Auto starting of pump	Required	Provided	MR			
14.	4. Captive water Storage for fire fighting:						
	 Under ground tank capacity 	NA	NA	NA			
	Draw off connection	NA	NA	NA			
	> Fire service inlet	NA	NA	NA			
	Access to tank	NA	Provided	NA			
1.5	Overhead Tank capacity Fig. 4.6: Output St. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	10,000 ltrs.	Provided	MR			
15	Exit Signage	Required	Provided	MR			
16.	Provision of Lifts						
	 Pressurization of Lift Shaft Pressurization of lift lobby 	NA	NA	NA			
	 Pressurization of lift lobby Communication in lift Car 	NA	NA NA	NA			
	Fireman's Grounding Switch	NA	NA NA	NA			
	➤ Lift Signage	NA	NA NA	NA			
		NA	NA	NA			
17.	Standby power supply	NA	NA	NA			

18.	Refuge Area > Total area > Location				
			NA NA	NA NA	NA NA
9.	Fire control room				INA
- Commence of the Commence of	 Detector system panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans 	NA NA NA NA NA	NA NA NA NA NA		NA NA NA NA
20.	Special Fire Protection Systems for Protection of special Risks, if any;	NA	NA		NA

Fire protection systems provided in the building were checked and found functional at the time of inspection. Shortcomings issued vide letter no. F6/DFS/MS/WZ/2020/91 dated 07.02.2020 are rectified.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety requirements as per D.O.E. Circular no. 262-362 dated 17.01.2005, renewal of Fire Safety Certificate issued vide letter no. F6/DFS/MS/School/2017/1070 Dated 26.04.2017 is recommended.

Accordingly DFA is put up for approval please.

ADO (JWP)

ADD BMI

F. F. Letter is added for your signalure pl.

With apples

Sports

Apples

Ap