GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No. F6/DFS/MS/Ind./WZ/2023/ 337

FIRE SAFETY CERTIFICATE

Dated: 14/07/2023

Certified that the M/s. Relaxo Footwears Limited, Located at F-7, Udyog Nagar, Rohtak Road, New Delhi-110041, comprised of Basement + Ground + Mezzanine floor + 1st floor only was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/88/BP/854 dated 20.06.1988. The said premises was re inspected by the officer concerned of this department on 06.07.2023 in the presence of Sh. Sudhir (Deputy Manager, HR) and found that the premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the building/premises is fit for occupancy class " Industrial" Group G with effect from 1407 2023 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed below,

Issued on .14 0.7 2023. at New Delhi by.

Copy to: -

1. Sh. Manoj Kumar Goel, M/s. Relaxo Footwears Limited, F-7, Udyog Nagar, Rohtak Road, New Delhi-110041.

Following Fire Safety Directive must be adhered to :-

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities. In case of deviation the NOC be treated as Null & Void.

5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.

6. All comments / directions of licensing Department shall always be permitted and followed. 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first

schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

9. The Basement shall be used as per BBL.

INSPECTION REPORT

1. Name & address of the building

: M/s. Relaxo Footwears Limited Located at F-7, Udyog Nagar, Rohtak Road, New Delhi- 41

2. Type of Occupancy

: Industrial, Group-G

3. Type of Case

: Renewal (B + G + Mezz. floor + 1^{st} floor)

4. Details of previous NOC

: F6/DFS/MS/88/BP/854 dated 20.06.1988

5. Fire Safety directives Letter No.

: F6/DFS/MS/84/374 dated 03.05.1984

6. Date of inspection

: 06.07.2023

7. Name of the Inspecting Officer

: Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side

: Sh. Yogesh (Electrical Engineer) & Sandeep

Arora (GM-HR)

9. Year of Construction

: 1984

10. Applicant's letter no.

: email dated 17.03.2023

S No	Minimum standards on fire prevention and fire safety U/R 33			Provided at site	Remarks MR/NMR
1.	Access of building	×25.5020 1-	the can		MD
	Road width	09 m		rovided	MR
-1	Control data	As per guideline not mentioned	P	rovided	MR
	Gate width Width of internal road	NA	3/4 - 2	NA	NA
-	Number, width, Type & Arrange	ments of exits	11.576	1916/15	
2.			nmi II	DANIEL S	
	a. Number of staircasesUpper floors	As per guideline not mentioned	15	02	MR
	Basement	As per guideline not mentioned	127	03	MR
- 1				The state of the s	
		As per guideline	1.5 m	x 1 & 1.20	MR being
	 Upper floors 	not mentioned	1	m x 1	old case
	D	As per guideline	1.5 m	x 1, 1.20 m	MR being
	 Basements 	not mentioned	x1&	1.10 m x 1	old case
	c. Protection of exits			100	
	Fire check door	Required	I	Provided	MR
	Pressurization	NA	1	NA	NA
	d. No of continuous	01	yann	02	MR
	staircase to terrace	NA	1111	NA	NA
	e. Width Of Corridor	Required	2001	Provided	MR
-	f. Door Size	Required	-		
. 1	Compartmentation	NA	N THE PARTY	NA	NA
	Fire check door Carling of electrical			NA	NA
	 Sealing of electrical shafts 	NA	TI	INA	INA
	Fire Rating of shaft door	NA		NA	NA
1	Water Curtain	NA		NA	NA
1	11,717	NA NA		NA	NA
	Fire Dampers System	IVA		INA	1471
	Smoke managements System	Required	91.1	Provided	MR
	BasementsUpper floors	Required	100000000000000000000000000000000000000	xhaust Fan)	MIK
	оррег шеез	Required	Ope	nable Window	MR
. 1	Fire Extinguishers				
1	Total numbers	15 nos.		Provided	MR
	• Types	ABC, foam & CO2		Provided	MR
	• IS marking	ISI marked		Provided	MR

		Total numbers on each floor	02	Provided		MR
	40.0		30 m	Provided		MR
	94.84	Length of hose reel hose	05 mm	Provided		MR
7.	At	Nozzle diameter		Provided		WIK
/.	Autor	natic fire detection and alarmi		ot Smoke/He	-4	MF
	•	Type of detectors	As per guideline ne mentioned	Smoke/He	at	MIF
	made	Location of Main Panel	As per guideline no mentioned			
	0.10	Location of Repeater Panel	NA	NA	-	NA
		Alternate source of power	NA	NA		NA
		Hooters' Location	NA	NA		NA
8.	MOE	FA	NA	NA		NA
9.		c Address System	NA	NA		NA
10.		natic Sprinkler System				
100		Basements	NA	NA		MR
		Upper Floor	NA	NA		NA
		Sprinkler above false ceiling		NA		NA
11.	Intern	al Hydrants:				
	•	Size of riser/down- comer	NA	Provided		NA
		Number of hydrants per	NA	Provided		NA
		floor	and the state of			
		Hose Box	NA	Provided		NA
12.	Yard	Hydrants				
	•	Total number of hydrants	NA	. NA		NA
		Hose Box	NA	NA		NA
13.	Pump	ing Arrangements:	4			
		Ground Level	e in	District States 1 - 9		
		Discharge of main pump	NA	NA		NA
	>	Head of main pump	NA	NA		NA
		Number of main pumps	NA	NA		NA
		Jockey pump out put	NA	NA		NA
		Jockey pump head	NA	NA		NA
	1 20	Standby Pump out put	NA	NA		NA
	-		NA	NA		NA
	-	Auto Staring/Manual	NA	NA		NA
	>	stopping Pump House Access				
		Terrace level	NA	NA		NA
	>		As per guideline not mentioned	450 lpm		MR
	>	Head of the pump	NA	10		1.75
		Power supply	NA NA	40 m		MR
	>	Auto starting of pump	NA	Provided Provided		MR
14.	Captiv	e water Storage for firefighting		Fiovided		MR
	•	Underground tank capacity	50,000 ltrs.	Provided	-	MD
	>	Draw off connection	NA	NA		MR
	>	Fire service inlet	NA	NA NA		NA NA
	>	Access to tank	Required	Provided		NA MR
	•	Overhead Tank capacity	As per guideline not	5000 ltrs.		MR
15	Exit Si	The same of the sa	mentioned	and the second of the second		
16.		ion of Lifts	Required	Provided		MR
-11	>	Pressurization of Lift Shaft	NA	IN.		
	>	Pressurization of lift lobby	NA NA	NA	NA	
1	>	Communication in lift Car	NA NA	NA	N/	
	2	Fireman's Grounding Switch	NA NA	NA	N/	
	-	Lift Signage	NA NA	NA	NA	
17.	Standb	y power supply	NA NA	NA NA	NA	
18.	Refuge	Area	MA	INA	NA	
	>	Total area	NA	NA		N1 4
- 1	2	Location	NA	NA NA		NA

		1.15				
19.	Fire control room					
	Detector system panel	NΛ	NΛ	NΛ		
	➤ Flow Switch Pancl ➤ PA System Pancl	NA	NA	NA		
		NΛ	NA	NΛ		
	> Battery backup	NΛ	NΛ	NΛ		
	> Building Floor Plans	NΛ	NA	NA		
20.	Special Fire Protection Systems for Protection of special Risks, if any;	NΛ	NΛ	NΛ		
	The fire protection systems provided in the building were checked and for					
	functional at the time of inspection.					

In view of the deemed compliance of minimum standards on fire prevention

and fire safety requirements under the rules, renewal of Fire Safety Certificate issued vide letter no. F6/DFS/MS/88/BP/854 dated 20.06.1988 is recommended under rule 37 of the Delhi Fire Service Rule, 2010 under DFS Act 2007.

Accordingly DFA is put up for approval please.

ADO (JWP)

DOG (MKG)
M.K. CHATTOPADHYAY

7/202

Anybull

CT. Letter is port-up for your rignature HO.

Dillto II

Lindon 6wp 1