GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

o. F6/DFS/MS/SZ/2023/Dc/338

Dated: 18/07/2023

FIRE SAFETY CERTIFICATE

Certified that the Gopala Tower located at Plot No. 25, Rajendra Place, New Delhi-110008. comprised of Basement, Ground, Mezzanine floor plus thirteen upper floors was issued No Objection Certificate by this department vide letter No. F.6/ DFS/MS/2016/SZ/385 dated 10.02.2016 for occupancy of building and building was re-inspected by the officers concerned of this department on 11.07.2023 in presence of Mr. Rajkumar (Estate Manager) and found that the said business building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi fire service Rules 2010 and that the building/premises is fit for occupancy class Group E (Business Building) with effect from 18 07 2023 for a period of 03 (three) years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on 18 7 223 at New Delhi by.

Director Delhi Fire Service

Copy to: -

1. Sh. Rajkumar (Estate Manager), Gopala Tower, 25, Rajendra Place, New Delhi- 08.

2. The Joint Director (Building) C&I, DDA, Building Section, DDA, Vikas Sadan, INA, New Delhi.

Following Fire Safety Directives Must Be Adhered To:-

- 1. Providing of fire safety measures does not give any guarantee that there will be No fire. These equipments/installation can minimize the losses if maintained in good working condition and handled efficiently in case of fire.
- All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- The means of escape arrangements shall be kept unlocked & unobstructed for speedy evacuation of occupants in case of an emergency.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 5. The trained staff should be available round the clock.
- 6. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 7. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

INSPECTION REPORT

Name & address of the building

: Gopala Tower, Plot No. 25, Rajindra Place, New Delhi-110008.

2. Type of Occupancy

: Business (Class- E)

3. Type of Case

: Renewal 12 Points (Basement, Ground, Mezzanine floor plus thirteen Upper floors)

4. Details of previous NOC

: F.6/ DFS/MS/2016/SZ/385 dated 10.02.2016

5. Fire Safety directives letter No

: Old case

6. Date of inspection

: 11.07.2023

7. Name of the Inspecting Officers

: Vedpal Chhikara, DO (SW) & P.V. Rathee, ADO (SRD)

8. Name and designation of officers from the building side

: Mr. Rajkumar (Estate Manager)

9. Year of Construction

: 1980-81

2 No a. b. c. ten g. h.	• Road width • Gate width • Width of internal road umber, Width, Type & Arrangeme Number of staircases • Upper Floors • Basements Width of staircases • Upper Floors • Basements Protection of exits • Fire check door	Accessible Required N/A ent of Exits - 02 02 - Old Case Old Case		06 mts. rect accessible fi N/A - 02 02	MR bein	MR MR N/A		
a. b. c. ter g. h.	 Gate width Width of internal road umber, Width, Type & Arrangeme Number of staircases Upper Floors Basements Width of staircases Upper Floors Basements Protection of exits 	Required N/A ent of Exits - 02 02 - Old Case		rect accessible fi N/A	MR bein	MR N/A		
a. b. c. ter g. h.	 Width of internal road umber, Width, Type & Arrangeme Number of staircases Upper Floors Basements Width of staircases Upper Floors Basements Brotection of exits 	N/A ent of Exits - 02 02 - Old Case		N/A - 02	MR bein	N/A		
a. b. c. ter g. h.	Number, Width, Type & Arrangeme Number of staircases Upper Floors Basements Width of staircases Upper Floors Basements Protection of exits	- 02 02 02 - Old Case		- 02				
a. b. c. ter g. h.	Number of staircases Upper Floors Basements Width of staircases Upper Floors Basements Protection of exits	02 02 - Old Case		A STATE OF THE STA		- ig old case		
b. c. ter g. h.	 Upper Floors Basements Width of staircases Upper Floors Basements Protection of exits 	02 - Old Case		A STATE OF THE STA		- ig old case		
c. e. ter g. h.	 Basements Width of staircases Upper Floors Basements Protection of exits 	02 - Old Case		A STATE OF THE STA		g old case		
c. e. ter g. h.	 Basements Width of staircases Upper Floors Basements Protection of exits 	- Old Case	i Gid T Ha	02	1/01	MR being old case		
c. e. ter g. h.	Upper FloorsBasementsProtection of exits	The second secon			MR being old case			
e. tei g. h.	Basements Protection of exits	The second secon						
e. tei g. h.	Protection of exits	Old Case	1.35 & 0.92 mts		MR being old case			
e. tei g. h.	377 3 300 300 300	Old Case	2.2:	5 & 1.02 mts	MR bein	MR being old case		
g. h.	- Fire check door	-	100		May 1	#		
g. h.	 Fire check door Pressurization No. of continuous staircases terrace Width of Corridor 	Required		Provided	MR			
g. h.		N/A	1 200	N/A	N/A			
g. h.		01		01	MR			
h.		Old Case	2.60,	2.32 & 1.45 mts	MR being old case			
3 C	Door Size	Old Case	E103771050	to 2.08 mts & 5 to 2.04 mts	MR being old case			
	Compartmentation.							
	Fire check door	Required		Provided	MR			
	Sealing of electrical shafts	Required		Sealed	MR			
1	Fire Rating of shaft door	N/A		N/A	N/A			
	Water Curtain	N/A		N/A	N/A			
	Fire Dampers	N/A		N/A	N/A			
4 Sr	Smoke Management System.							
	• Basements 3	30 a/c per hour	Exhaust fans are Provided		vided	MR		
		2 a/c per hour	Natural Ventilation		MR			
5 Fi	ire Extinguishers							
	• IOM IMMORIS	04 Nos. at each floo			MR			
	Types	NCO2 ABC & CO2 IS ISI marked			MR			
	IS marking	151 marked			MR			

_		109		15
	DT 1 + -			
_	Total numbers on each floor	N-36	Provided	MR
	CONTROL OF THE CONTRO	30 m each	Provided	MR
	Length of hose reel hoseNozzle diameter	5 mm each	Provided	MR
	Automatic fire detection and alarmin		Tiovided	10.743
		N/A	N/A	N/A
	Type of detectors	N/A N/A	N/A	N/A
	Location of Main Panel Control of M	N/A	N/A	N/A
	Location of Repeater Panel	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
	Hooters' Location		Provided	MR
-	MOEFA	Required Required	Provided	MR
0	Public Address System.	Required	Provided	IVIIC
0	Automatic Sprinkler System.	Required	Provided	MR
	Basement		Provided	MR
	Upper Floor/Ground Floor Sprinkler shows false asiling	Required	Company of the section	
	Sprinkler above false ceiling	N/A	N/A	N/A
l	Internal Hydrants	T 100	100 MM	MR
	Size of riser/down-comer	100 mm	100 MM	MR
	Number of hydrants per floor	01	01	MR
,	Hose Box Variable Park	01	01	MK
2	Yard Hydrants.	04	04	MR
	Total number of hydrants	04	04	MR
	Hose Box	04	04	MIK
;	Pumping Arrangements.			d Course
	Ground Level	2850 LPM	2850 LPM	MR
	Discharge of main Pump		Provided	MR
	Head of Main pump Number of main pumps	Required 01	01	MR
	Jockey Pump out put	450 LPM	450 LPM	MR
	Jockey pump head		Provided	MR
	Standby Pump out put	Required 2850 LPM	2850 LPM	MR
	Standby Pump Head	Required	Provided	MR
	- Auto Starting/ Manual	Required	Provided both	
	stopping	Required	Provided botti	MR
	Pump House Access	Required	Provided	MR
	Terrace level			<i>A</i>
	Discharge of pump	N/A	N/A	N/A
	Head of the pump	N/A	N/A	N/A
	Power Supply	N/A	N/A	N/A
	 Auto Starting of pump 	N/A	N/A	N/A
	Captive Water Storage for fire fighting	ng.	100000000000000000000000000000000000000	
	Underground tank capacity	2,00,000 ltr.	2,00,000 ltr.	MR
	 Draw-off connection 	Required	Provided	MR
	Fire service inlet	Required	Provided	MR
	- Access to tank	Required	Provided	MR
	Overhead Tank capacity	50,000 ltr.	50,000 ltr.	MR
	Exit Signage.	Required	Provided	MR
	Provision of Lifts.	3 1		
	Pressurization of Lift Shaft	N/A	N/A	N/A
	Pressurization of Lift lobby	N/A	N/A	N/A
	Communication In lift Car	Required	Provided	MR
200	Fireman's Grounding Switch	Required	Provided	MR
	 Lift Signage 	Required	Provided	
- 1	- Lift Signage	required	riovided	MR

	V		N-37,				
17	Standby power supply	Required	Provided	MR			
18	Refuge Area.						
J	- Total Area	N/A	N/A	N/A			
	- Location	N/A	N/A	N/A			
19	Fire Control Room						
	Detector System Panel	Required	Provided	MR			
	Flow Switch Panel	N/A	N/A	N/A			
	PA System Panel	Required	Provided	MR			
	Batter backup	Required	Provided	MR			
	Building Floor Plans	N/A	N/A	N/A			
20	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	CO ₂ fire extinguisher provided near electric Panel	MR			

The fire protection systems provided in the building were test checked at random and found satisfactory at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the Rules, the NOC issued vide letter No. F.6/ DFS/MS/2016/SZ/385 dated 10.02.2016, renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly. DFA is put up for approval & signature please

Signature of the Inspecting Officer

Name- Vedpal Chhikara Divisional Officer (SW)

Signature of the Inspecting Officer Name- P.V. Rathee Divisional Asstt. Div. Officer (S.Rd)

Rall 13/7/23.

S.T. Letter to put up fin Stan please Dinector My