



C-47

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No.F.6 DFS/MS/School/2023/SZ/ 507

Dated: 25/07/2023

## FIRE SAFETY CERTIFICATE

Certified that the **Deepalaya School** located at A-14, Kalkaji Extn. New Delhi 110019 comprised of Basement, Ground plus Two Upper floors owned/occupied by Deepalaya School was issued Fire Safety Certificate by this department vide letter no. F6/DFS/MS/School/2020/SZ/382 dated 29/09/2020. The said premise was re-inspected by officer concerned of this department on 18/07/2023 in presence of Mr. AJI George and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010 and that the building is fit for occupancy class "Educational Building Group – B" with effect from 25/07/2023 for a period of Three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rules 2010.

Issued on 25/12023 at New Delhi by

DIRECTOR

DELHI FIRE SERVICE

Copy to: -

1. The Principal, Deepalaya School located at A-14, Kalkaji Extn. New Delhi 110019

2. The Directorate of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi- 110054

## Conditions for the validity of Fire Safety Certificate

- All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 2. All the staff members must know the correct method of operation of firefighting system.
- 3. This certificate cannot be treated as regularization of unauthorized construction, if any.
- 4. The basement shall be used as per the provisions of BBL /NBC Part- IV.
- The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

of N)6

/		
आज	ादी क	
अ	मृत महोत्सव	Į

	INSPECTION	ON REPORT	100		
1	Name & Address of the Building	Deepalaya School, A-14, Kalkaji Extn. New Delhi			
2	Type of Occupancy	Educational, Gro	up_B (School)		
3	Building Comprised of	Basement Groun	d + 02 upper floors		
4	Type of Case	Basement, Ground + 02 upper floors.			
5	Details of Previous NOC	F6/DFS/MS/School/2020/SZ/382 dated 29/09/2020			
6	Fire Safety Directives Letter No	F6/DFS/MS/BP/96/329 dated 08/03/1996			
7	Date of Inspection	18-07-2023			
8	Name of the Inspecting Officers	DO (South) & ADO (BCP)			
9	Name & Designation of Officers from the building side	Mr. AJI GEORGE			
10	Year of construction	1998			
11	Applicant letter No.	Outdoor diary no 3566 dated 06-07-2023			
. No.	Minimum standards on Fire Prevention	As per old noc	Provided at Site	Remarks	
	and Fire Safety U/R 33	requirements	200000000000000000000000000000000000000	MR/NMR	
1	Access to Building.				
	Road width	Required	06 mtr	MR	
- 1	Gate width	Required	4.5mtr	MR	
	Width of internal road	-NA-	-NA-	-NA-	
2	Number, width, type & arrangement of ex	its.	Company to the second		
	a) Number of Staircase	240-1	at all of		
9.03	➤ Upper floors.	Required	03 Nos	MR	
No.	> Basement floor.	Required	03 Nos	MR	
1000	b) Width of Staircase	lug bo	mad wheat is		
ATT.	> Upper floors	Required	1.35m x 2 & 1.31 m	MR	
	Basement floor	Required	1.35m x 2 & 1.31 m	MR	
301	Daschell Not				
77.77	c) Protection of exits  > Fire check door	-NA-	-NA-	-NA-	
917	> Pressurization	-NA-	-NA-	-NA-	
11.		Required	03 Provided	MR	
414	to the state of th	-NA-	-NA-	-NA-	
76.		1m	Provided	MR	
	f) Door size		ruit .	VIP	
3	Compartmentation.  • Fire check door.	-NA-	-NA-	-NA-	
100	Fire check door.     Sealing of electrical shafts.	-NA-	-NA-	-NA-	
1.94	Fire rating of shaft door.	-NA-	-NA-	-NA-	
4.1	Water curtain	-NA-	-NA-	-NA-	
30	Fire dampers.	-NA-	-NA-	-NA-	
-	Smoke Management system.		THE LAND THE	(1 8)	
4.	Basement	30 ACPH	Exhaust fan provided	MR	
	Upper floors	12 ACPH	Natural ventilation	MR	
		ma (El in	posting a ser 7 *		
5.	Fire Extinguishers.  • Total numbers	20 Nos	20 Nos	MR	
		ABC / CO2	ABC & Co2	MR	
	Types     ISI Marking	ISI mark	Provided	MR	
1.6	First Aid Hose Reels.		nin Z. sguted	I IIII	
6.	Total numbers on each floor.	U2 Nos	Provided	MR	
151	Length of hose-reel hose.	30m	Provided	MR	
-1775	Nozzle Diameter	5mm	Provided	MR	
	Nozzie Diameter  Automatic fire detection & alarming system.	1200-200			
7	Automatic lire detection & alai ming system.	-NA-	-NA-	-NA-	

~





	Location of Main Panel	-NA-	-NA-	-NA
district to	Location of Repeater Panel	-NA-	-NA-	-NA
	Alternate source of power	-NA-	-NA-	-NA
	Hooter's location	-NA-	-NA-	-NA-
8.	MOEFA	-NA-	NA	-NA-
	Public Address System	Required	Provided	MR
	Automatic Sprinkler System	Required	Tiovided	WIII
10.	Basement	Required	Provided	MR
	Upper floors	-NA-	-NA-	-NA-
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11.	Internal Hydrants.	-IVA-	-11/1-	-NA-
	Size of Riser/Down-comer	Required	100 mm	MR
	Number of Hydrant per floor	-NA-	-NA-	-NA-
	Hose box.	-NA-		
12.	Yard Hydrants.	-NA-	-NA-	-NA-
100		DTA	LICAR MARSH	T NA
	<ul> <li>Total number of hydrants.</li> <li>Hose box.</li> </ul>	-NA-	-NA-	-NA-
13.	Pumping arrangements.	-NA-	-NA-	-NA-
10.	Ground Level			
4.00	Discharge of main pump.	274	The state of the s	1 224
	Head of main pump.	NΛ	NΛ	NA
	Number of main pumps.	-NA-	-NA-	-NA-
12101	Jockey Pump output.	-NA-	-NA-	-NA-
934	> Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
7.	> Standby Pump head.	-NA-	-NA-	-NA-
916	Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
ACK.	Terrace Level		English - NA-	-NA-
12	Discharge of pump.	Old case	900 & 180 LPM	MR
SEA	➤ Head of pump.	Old case	35m	MR
12.	Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.		2500000	I.II.
ALL:	Underground tank capacity.	50,000 ltr	50,000 ltr	MR
7	Draw-off connection.	-NA-	-NA-	-NA-
W.	Fire Service Inlet.	-NA-	-NA-	-NA-
- L	Access to tank.	-NA-	-NA-	-NA-
15. 1	Overhead tank capacity.      Signature	20,000 ltrs	20,000 ltrs	MR
	Exit Signage. Provision of Lifts.	Required	Provided	MR
10.	Pressurization of lift shaft.	N/A I	115 V A 2011 A	
12.2	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	Communication in lift car.	-NA-	-NA-	-NA-
1	Fireman's switch.	-NA-	-NA-	-NA-
N I	Lift signage.	-NA-	-NA-	-NA-
	tandby Power Supply	-NA-	-NA-	-NA-
	Refuge Area	-11/14-	MARKET NA	-NA-
1/	Total area	-NA-	-NA-	-NA-
	• Location	-NA-	-NA-	
	Location	-IVA-	-IVA-	-NA-

W

W

Fire Control Room.			
Detector system panel.     Flow switch panel.	-NA-	-NA-	-NA-
	-NA-	-NA-	-NA-
	-NA-	-NA-	-NA-
PA system panel.	-NA-	-NA-	-NA-
Battery backup.      Goog plan	-NA-	-NA-	-NA
Building floor plan.  Special Fire Protection System for the Protection of special Risk, if any.	-NA-	-NA-	-NA

The fire protection system provided in the building were randomly checked and found

Keeping in view of the deemed compliance of the minimum standard on fire prevention and functional at the time of inspection. safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/School/2020/SZ/382 dated 29/09/2020, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspection Officer Namq: Sh. Manoj Kumar Sharma

Design: DO (South)

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

CFO (HQ)