GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

No. F.6/DFS/MS/Industry/2023/SZ/ 373

Dated: 07/08/2013

FIRE SAFETY CERTIFICATE

Certified that the M/s Bharat Adhesives, A-36, Mayapuri Industrial Area, Phase-II, New Delhi-110064 comprised of basement and ground floor only owned/occupied by M/s letter department vide this by FSC issued Adhesives was Bharat F.6/DFS/MS/Industry/2020/SZ/333 dated 25/08/2020. The Industrial building was reinspected by the officers concerned of this department on 24/07/2023 in the presence of Sh. Prankul Nijhawan (Partner) and found that the industrial building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class Group "G" "Industrial Building" w.e.f. the date of issue of this certificate for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule-38 of the Delhi Fire Service Rules, 2010 printed below.

Issued on 07 08 2023 at New Delhi.

Atul Garg)
Director
Delhi Fire Service

Copy to:-

 The Executive Eingineer (Bldg.), HQ-II, SDMC, 8th Floor, Dr. SPM Civic Centre, E-Wing, J.L. Nehru Marg, New Delhi-110002

2. The Partner, M/s Bharat Adhesives, A-36, Mayapuri Industrial Area, Phase-II, New Delhi-110064.

Following fire safety directives must be adhered to:-

- All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement shall be used as per the building bye laws.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

10/1-

INSPECTION REPORT

1. Name & address of the building: M/s Bharat Adhesives, A-36, Mayapuri Industrial Area, Phase-II, New

Delhi-110064

2. Building comprised of : Basement & ground floor only

3. Type of Occupancy : Industrial Building.

4. Type of Case : Renewal

5. Details of Previous NOC : F.6/DFS/MS/Industry/2020/SZ/333 dated 25/08/2020

6. Fire Safety directives letter No : F.6/DFS/MS/BP/2003/617 dated 24.03.03

7. Date of inspection : 24/07/2023

8. Name of Inspecting Officer : A.D.O. R.K. Yadav & D.O Vedpal Chhikara

9. Name and designation of officers

From the building side : Sh. Prankul Nijhawan (Partner)

10. Year of Construction : Before 2003

11. Applicant's letter No. : E-mail dated 12/07/2023

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirements	Provided at site	Remarks MR/NMR				
1.	Access to building	- Diam-						
100	 Road width Gate width Width of internal road 	09 m 05 m N/A	Provided Provided N/A	M/R M/R N/A				
2.	Number, Width, Type & Arrangement of Exits							
	a. Number of staircases Upper Floors Basements b. Width of staircases	N/A Two	N/A Two	N/A M/R				
		N/A	N/A	N/A				
	Upper Floor Basements	1.25 m	1.33 & 1.35 n	n M/R				
	c. Protection of exits • Fire check door • Pressurization	N/A N/A	N/A N/A	N/A N/A				
		a Volume	service 4.					
	d. No. of continuous staircases to terrace e. Width of Corridor f. Exit Door Size	N/A	N/A	N/A M/R				
		1.25 m	Provided	-T267 AV40				
		1.0 m	Provided	M/R				
3.	Compartmentation	The same of						
	Fire check door	Required	Provided	M/R				
	Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers	N/A	N/A	N/A				
		N/A	N/A	N/A				
		N/A	N/A	N/A				
	Solution in the second	N/A	N/A	N/A				
4.	Smoke Management System							
	Basements	Required	Exhaust fans a provided					
	Upper floors	N/A	N/A	N/A				
5.	Fire Extinguishers							
	Total numbersTypesIS marking	05 no.'s W/CO ₂ / CO ₂ type	Provided	M/R				
			Provided	M/R				
		ISI marked	ISI marked	M/R				

5



N/13

	First-Aid Hose Reels			-			
	 Total numbers on each floor 	One	Provided	1.40			
	Length of hose reel hose		Provided	M/R			
		36 mtrs.		MR			
	Nozzle diameter	5 mm	Provided	MR			
	Automatic fire detection and alarming						
	Type of detectors	N/A	N/A	N//A			
	 Location of Main Panel 	N/A	- Contract of	N/A			
	Location of Repeater Panel	N/A	N/A	N/A			
	Alternate source of power	N/A	N/A	N/A			
	Hooters' Location	N/A	N/A	N/A			
	MOEFA		N/A	N/A			
The second second	Public Address System	Required	Provided	M/R			
).	Automatic Sprinkler System	N/A	N/A	N/A			
	Basement	N/A	N/A	I NUA			
	Ground Floor	N/A	N/A	N/A N/A			
	Sprinkler above false ceiling	N/A	N/A	N/A N/A			
1.	Internal Hydrants	14//3	IVA	I N/A			
	 Size of riser/down-comer 	N/A	N/A	N/A			
	 Number of hydrants per floor 	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
2.	Yard Hydrants			72 (29 A)			
S. IEIV	Total number of hydrants	Required	Provided	M/R			
	Hose Box	Required	Provided	M/R			
3.	Pumping Arrangements			MIX			
	Ground Level						
	 Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put 	1620 LPM	Provided	M/R			
		55 mtrs.	Provided	M/R			
		One	Provided	M/R			
		180 LPM	Provided	M/R			
		55 mtrs.	Provided	M/R			
	➤ Standby Pump Head	1620 LPM	Provided	M/R			
	> Auto Starting/Manual	55 mtrs.	Provided	M/R			
	Stopping	Required	Provided	M/R			
		Required	Provided	SERVICE			
	Pump House Access Terrace level	Required	Frovided	M/R			
	Discharge of pump	450 LPM	Provided	14/0			
	> Head of the pump	30 Mtrs	Provided	M/R			
	➤ Power Supply	Required	Provided	M/R M/R			
	➤ Auto Starting of pump	Required	Provided	M/R			
14.	Captive Water Storage for fire fighting		are sport and				
	Underground tank capacity	35000 ltrs	Provided	M/D			
	Draw-off connection	Required	Provided	M/R			
	 Fire service inlet Access to tank Overhead Tank capacity 	Required	Provided	M/R			
		Required	Provided	M/R			
		10,000 Ltrs.	Provided	M/R			
of his area	to a stantage	Required	Provided	M/R M/R			
15.	Exit Signage.	- TA		IVI/IC			
16.	Provision of Lifts.						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication In lift Car Fireman's Grounding Switch	N/A	N/A	N/A			
	Lift Signage	N/A	N/A	N/A			
	I LIII Signage						

Standby power suppl	y	N/A	N/A	N/A
Defense A			N/A	
Refuge Area.				
> Total Area				
> Location	N	/A	N/A	N/A
	N	/A	N/A	N/A
Fire Control Room			20.00	
D				
Detector Syste		V/A	N/A	N/A
Flow Switch P PA System Pa		I/A	N/A	N/A
Battery backup		I/A	N/A	N/A
Building Floor Plans		I/A	N/A	N/A
	N	I/A	N/A	N/A

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the Fire Safety Certificate issued vide letter number F.6/DFS/MS/Industry/2020/SZ/333 dated 25/08/2020 renewal under rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of Inspecting Officer Name:-Vedpal Chhikara

Designation: Divisional Officer

Signature of Inspecting Officer

Name:- R.K. Yadav

Designation:- Asstt. Divisional Officer

(FO (52) | Mugh 2 181 (202)

Dinectar My

ADD) DK

FT better k

put up for size

1 8 202

DIRECTOR POOL