

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No.F.6 DFS/MS/School/2023/SZ/ 544

Dated: 09/08/2023

## FIRE SAFETY CERTIFICATE

Certified that the Bharat Vashisht Vidya Mandir at Khasra No 1599, 1600/1, Near Shiv Hansa Chowk, Aaya Nager Extension, Phase –V, New Delhi 110047 Comprised of Ground plus Two upper floors owned/occupied by Bharat Vashisht Vidya Mandir was issued Fire Safety Certificate by this department vide letter no. F6/DFS/MS/School/2020/SZ/229 Dt. 16/07/2020. The said premises was re-inspected by officer concerned of this department on 01/08/2023 in presence of Mr. Rajender Singh and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with Directorate of Education Circular No F.16//Estate/CC/Fire Safety/2011/3298 to 3398 dated 01/03/2011 issued by Director of Education, Govt. of NCT of Delhi and that the building is fit for occupancy class "Educational Building Group – B" with effect from <a href="#page-97/08/2023">97/08/2023</a> for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rules 2010.

Issued on 09/08.2023 at New Delhi by

DIRECTOR DELHIFIRE SERVICE

Copy to: -

 Bharat Vashisht Vidya Mandir at Khasra No 1599, 1600/1, Near Shiv Hansa Chowk, Aaya Nager Extension, Phase -V, New Delhi 110047

The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi- 110054.

## Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- All the staff members must know the correct method of operation of firefighting system.
- The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."



	INSPECTION DEPORT					
	Name & Address of the Building Bharat Vashisht Vidya Mandir, Khasra No 1599					
7	than to riddiess of the Building	1600/I, Near Shiv Hansa Chowk, Aaya Nager Extension, Phase -V, New Delhi 110047.				
2	Type of Occupancy	Educational, Group-B (School)				
3	Building Comprised of	Ground plus Two Upper Floor				
4	Type of Case	Renewal				
5	Details of Previous NOC	F6/DFS/MS/School/2020/SZ/229 Dt. 16/07/2020				
6	Fire Safety Directives Letter No	New case				
7	Date of Inspection	01-08-2023				
8	Name of the Inspecting Officers	Sh. Rajesh Kumar ADO (BCP)				
9	Name & Designation of Officers from the building side	Mr. Rajender Singh				
10	Year of construction	2008				
11	Applicant letter No.	BVVM/DFS/2023/2023-2024/21 dated 20/07/2023				
S. No	Minimum standards on Fire Prevention and Fire Safety U/R 33	As per Old NOC Requirement	Provided at Site	Remarks MR/NMF		
1	Access to Building.					
	Road width	Accessible	6mtr	MR		
	Gate width	-NA-	4.5mtr	-NA-		
	Width of internal road	-NA-	-NA-	-NA-		
2	Number, width, type & arrangement of exits.					
	a) Number of Staircase					
	Upper floors.	01 No	03 Nos & 01 ramp	MR		
	Basement floor.	-NA-	-NA-	-NA-		
	b) Width of Staircase		Control of the Control of the			
	➤ Upper floors	1.50mtr/0.75mtr	G To Terrace -0.90mtr & 1.80mtr (new SC) FF to SF- 1.20 mtr Ramp GF to FF 1.20 mtr	MR (old case)		
F *	➤ Basement floor	-NA-	-NA-	-NA-		
	c) Protection of exits			1,300		
	Fire check door	-NA-	-NA-	-NA-		
	> Pressurization					
		-NA-	-NA-	-NA-		
	d) No. of continuous staircase to terrace	Required	Provided	MR		
	e) Width of corridor	-NA-	-NA-	-NA-		
	f) Door size	1 mtr	Provided	MR		
3	Compartmentation.					
	<ul> <li>Fire check door.</li> </ul>	-NA-	-NA-	-NA-		
	<ul> <li>Sealing of electrical shafts.</li> </ul>	-NA-	-NA-			
	<ul> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door.</li> </ul>	-NA- -NA-		-NA-		
	<ul> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door.</li> <li>Water curtain</li> </ul>	-NA-	-NA-	-NA-		
	<ul> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door.</li> <li>Water curtain</li> <li>Fire dampers.</li> </ul>	-NA- -NA-	-NA-	-NA- -NA- -NA-		
4.	Sealing of electrical shafts.     Fire rating of shaft door.     Water curtain     Fire dampers.  Smoke Management system.	-NA- -NA- -NA-	-NA- -NA- -NA-	-NA-		
4.	Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement	-NA- -NA- -NA-	-NA- -NA- -NA-	-NA- -NA- -NA-		
	Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers.  Smoke Management system. Basement Upper floors	-NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA-		
	Sealing of electrical shafts.     Fire rating of shaft door.     Water curtain     Fire dampers.  Smoke Management system.     Basement     Upper floors  Fire Extinguishers.	-NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA-	-NA- -NA- -NA-		
	Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers.  Smoke Management system. Basement Upper floors	-NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA-		
	Sealing of electrical shafts.     Fire rating of shaft door.     Water curtain     Fire dampers.  Smoke Management system.     Basement     Upper floors  Fire Extinguishers.	-NA- -NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA- -NA- 08 Nos	-NA- -NA- -NA- -NA- -NA- MR		
5.	Sealing of electrical shafts.     Fire rating of shaft door.     Water curtain     Fire dampers.  Smoke Management system.     Basement     Upper floors  Fire Extinguishers.     Total numbers     Types     ISI Marking	-NANANANANA- Required ABC	-NANANANANANANANA-	-NA- -NA- -NA- -NA- -NA- MR		
5.	Sealing of electrical shafts.     Fire rating of shaft door.     Water curtain     Fire dampers.  Smoke Management system.     Basement     Upper floors  Fire Extinguishers.     Total numbers     Types	-NANANANANA- Required	-NA- -NA- -NA- -NA- -NA- 08 Nos	-NA- -NA- -NA- -NA- -NA- MR		
5.	Sealing of electrical shafts.     Fire rating of shaft door.     Water curtain     Fire dampers.  Smoke Management system.     Basement     Upper floors  Fire Extinguishers.     Total numbers     Types     ISI Marking	-NANANANANA- Required ABC ISI mark	-NANANANANANA-  08 Nos ABC & Co2 Type Provided	-NA- -NA- -NA- -NA- -NA- MR MR		
5.	Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers.  Smoke Management system. Basement Upper floors  Fire Extinguishers. Total numbers Types ISI Marking  First Aid Hose Reels.	-NANANANANA- Required ABC	-NANANANANANANANA-	-NA- -NA- -NA- -NA- -NA- MR		







7	Automatic fire detection & alarming system.	7777		371
	Type of detectors	-NA-	-NA-	-NA-
	<ul> <li>Location of Main Panel</li> </ul>	-NA-	-NA-	-NA-
-	<ul> <li>Location of Repeater Panel</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Alternate source of power</li> </ul>	-NA-	-NA-	-NA-
	Hooter's location	-NA-	-NA-	-NA-
	MOEFA	-NA-	-NA-	-NA-
9. 1 10. /	Public Address System	-NA-	-NA-	-NA-
10.	Automatic Sprinkler System  Basement			274
	Dascincia	-NA-	-NA-	-NA-
	epper noors	-NA-	-NA-	
11. I	Sprinkler above false ceiling nternal Hydrants.	-NA-	-NA-	-NA-
	Size of Riser/Down-comer			274
100		-NA-	-NA-	-NA-
10.1	<ul> <li>Number of Hydrant per floor</li> <li>Hose box.</li> </ul>	-NA-	-NA-	-NA-
12. Y	ard Hydrants.	-NA-	-NA-	-NA-
12. 1		374		1 324
	Total number of hydrants.     Hose box	-NA-	-NA-	-NA-
13. P	11000 00/1.	-NA-	-NA-	-NA-
10. P	umping arrangements.			
-	• Ground Level	***		4
	<ul> <li>Discharge of main pump.</li> <li>Head of main pump.</li> </ul>	-NA-	-NA-	-NA-
15	Number of main pumps.	-NA-	-NA-	-NA-
2	> Jockey Pump output.	-NA-	-NA-	-NA-
	> Jockey Pump head.	-NA-	-NA-	-NA-
10	Standby Pump output.	-NA-	-NA-	-NA-
100	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting / Manual Stopping.	-NA-	-NA-	-NA-
100	Pump house access.	-NA-	-NA-	-NA-
-		-NA-	-NA-	-NA-
-	Terrace Level	450 7 704		
	<ul> <li>Discharge of pump.</li> <li>Head of pump.</li> </ul>	450 LPM	Provided	MR
	Power supply.	40m	Provided	MR
	> Auto starting of pump.	-NA-	-NA-	-NA-
4 6	The state of the s	Required	Provided	MR
4. Ca	ptive water storage for fire fighting.	N		
	Underground tank capacity.	-NA-	-NA-	-NA-
	> Draw-off connection.	-NA-	-NA-	-NA-
*	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
	Overhead tank capacity.	10,000 ltrs	Provided	MR
	it Signage.	Required	Provided	MR
6. Pro	ovision of Lifts.			
	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	<ul> <li>Pressurization of lift lobby.</li> </ul>	-NA-	-NA-	-NA-
	Communication in lift car.	-NA-	-NA-	-NA-
4	Fireman's switch.	-NA-	-NA-	-NA-
	<ul> <li>Lift signage.</li> </ul>	-NA-	-NA-	-NA-
7. Sta	ndby Power Supply	-NA-	-NA-	-NA-
	uge Area			1112
	Total area	-NA-	-NA-	-NA-
	Location	2570000000		
		-NA-	-NA-	-NA-
	e Control Room.		self of self or	
	<ul> <li>Detector system panel.</li> </ul>	-NA	-NA-	-NA-

C