

GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI- 110001

No. F.6/DFS/MS/LPG/2023/SZ/ 390

Dated: 14/08/2023

FIRE SAFETY CERTIFICATE

Certified that the M/s Sarla Enterprises located at Site No-1, Sector 02, R.K Puram, New Delhi Comprised of Ground Floor only owned/occupied by M/s Sarla Enterprises Bharatgas, was issued FSC by this department vide letter no. F6/DFS/MS/LPG/2018/SZ/2285 Dated 09/10/2018. The premise was re-inspected by the officer concerned of this department on 07.08.2023 in the presence of Ms. Versha Sandeep of the said filling station and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Storage-H (LPG Godown) with effect from \(\frac{10}{2} \) / \(\frac{8}{2} \) / 2023 for a period of three years in accordance with rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010.

Issued on 14 /08 /2023 at New Delhi by

(ATUL GARG)
DIRECTOR
DELHI FIRE SERVICE

Copy to: -

1. M/s Sarla Enterprises located at Site No-1, Sector 02, R.K Puram, New Delhi

The Dy. Commissioner (Green Park Zone) Municipal Corporation of Delhi, Aurobindo Marg, Green Park, New Delhi 110016.

Conditions for the validity of Fire Safety Certificate: -

All the means of escape/entry/exit shall be kept free from any obstruction.

All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting system.

- 4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.



| | | INSPECTIO | ON REPORT | cana thre Describeral | iday' i | | |
|-------|--|--|--|-----------------------------------|-------------------|--|--|
| 1 1 | | e & Address of the Building | M/s Sarla Enterprises, LPG Godown at Site No 1 Sector-2, R.K Puram, New Delhi | | | | |
| 2 | Type | of Occupancy | Storage Building (LPG Godown) | | | | |
| 3 | Build | | 1 | | | | |
| 4 | Type of Case | | Ground floor only | | | | |
| 5 | Details of Previous NOC | | Renewal | | | | |
| (6(3) | - 1050-5 | | F6/DFS/MS/LPG/2018/SZ/2285 Dated 09/10/2018 | | | | |
| 7 | Date | Safety Directives Letter No | F6/DFS/MS/89/LPG/287 dated 23/02/1989 | | | | |
| 38% | | | 07/08/2023 | our Sudicke Succession | alad W | | |
| 8 | | ne of the Inspecting Officers | Sh. Rajesh Kumar (ADO BCP) | | | | |
| 9 | Nan | ne & Designation of Officers | Ms. Versha Sandeep | | | | |
| 10 | Ves | n the building side | sometimes with the continued as | | | | |
| 11 | _ | olicant letter No. | 1989 | | | | |
| S. No | | | Outdoor diary no 3957 dated 19-07-2023 | | | | |
| 1 | Minimum standards on Fire Prevention and Fire Safety U/R 33 | | Old NOC Requirement | Provided at Site | Remarks MR/NMF | | |
| - | A | ess to Building. Road width | | Manager of the same of the | | | |
| | | Koad width Gate width | Required | 09 mtr | MR | | |
| | | Width of internal road | -NA- | -NA- -NA- | -NA- | | |
| 2 | Nu | mber, width, type and arrangements | of exits. | -INA- | -NA- | | |
| - | | Number of Staircase | | | | | |
| | | Upper floors | -NA- | Alternatives has | analys I | | |
| | | Basement floor | -NA- | -NA- | -NA- | | |
| | b. | | 700000 | | -NA- | | |
| | | | 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | ort come to agents 201 | | | |
| | | Upper floors | -NA- | -NA- | -NA- | | |
| | 1 | Basement floor | -NA- | -NA- | -NA- | | |
| | C. | Protection of exits | | Brad gray - to | N | | |
| | NV | Fire check door | -NA- | -NA- | -NA- | | |
| | SP. | Pressurization | -NA- | -NA- | -NA- | | |
| | d. | No. of continuous staircase to terrace | -NA- | 17 may 25 de 193 m | - | | |
| | | Width of corridor | -NA- | -NA- | -NA- | | |
| | 0.00 | | -NA- | -NA- | -NA- | | |
| | f. | Door size | 1m | Provided | MR | | |
| 3 | C | ompartmentation. | 11-14-31- | of the character ments of | IVIX | | |
| | | | 4 | | 2-1- | | |
| | 0.24 | Fire check door. Sealing of electrical shafts. | -NA- | -NA- | -NA- | | |
| 1 | AV | Sealing of electrical shafts. Fire rating of shaft door. | -NA- | -NA- | -NA- | | |
| - | | Water curtain | -NA- | -NA- | -NA- | | |
| J. 11 | 1397 | Fire dampers. | -NA- | -NA- | -NA- | | |
| 4. | S | moke Management system. | 1 2 | 2,00(22,26,46) | Ed (m) 1.8 | | |
| | | Basement | -NA- | -NA- | -NA- | | |
| | | Upper floors | -NA- | -NA- | -NA- | | |
| 5. | F | ire Extinguishers. | THE PARTY OF THE P | a. 1180 a. d. SATUR, processor a. | * | | |
| | AN | Total numbers | Required | 04 No + 06 Nos + |) m | | |
| | 14 | • Types | | Send Buckets | MR | | |
| | 1476 | ISI Marking | ISI Marked | A STATE OF STREET | MR | | |
| | | | 11 | Provided | MR | | |
| 6. | I | First Aid Hose Reels. | | Matthew of Med. | THE PARTY | | |
| | | Total numbers on each floor. | -NA- | -NA- | -NA- | | |
| | | Length of hose-reel hose. | -NA- | -NA- | -NA- | | |
| | | Nozzle Diameter | -NA- | -NA- | -NA- | | |

we





| 7 | Automatic Fire Detection and Alarming | system. | | 1 374 |
|---|--|--------------------|--------------------|-------|
| | | -NA- | -NA- | -NA |
| 11.00 | Type of detectors | -NA- | -NA- | -NA |
| | Location of Main Panel | -NA- | -NA- | -NA |
| | Location of Repeater Panel | -NA- | -NA- | -NA |
| | Alternate source of power | -NA- | -NA- | -NA |
| | Hooter's location | -NA- | -NA- | -NA |
| 8. | MOEFA | | -NA- | -NA |
| 9. | Public Address System | -NA- | HIP OF THE | |
| 10. | Automatic Sprinkler System | | | -NA |
| | Basement | -NA- | -NA- | -NA |
| h 1 | Upper floorsSprinkler above false ceiling | -NA- | -NA- | -NA- |
| | Sprinkler above false ceiling | -NA- | -NA- | -NA |
| 11. | Internal Hydrants. | | 747 541 | NA |
| | Size of Riser / Down-comer | -NA- | -NA- | -NA- |
| Brown ! | Number of Hydrant per floor | -NA- | -NA- | |
| | 1 (AA) W (87) S (1) | -NA- | -NA- | -NA- |
| 12. | Hose box. Yard Hydrants. | | diam mais | |
| 2.7 | | -NA- | -NA- | -NA- |
| - | Total number of hydrants. | -NA- | -NA- | -NA- |
| | Hose box. | -NA- | 2-22-2-2 | |
| 13. | Pumping arrangements. | | ingi paga | - |
| 3.1 | Ground Level | NA T | -NA- | -NA- |
| | Discharge of main pump. | -NA- | -NA- | -NA- |
| | > Head of main pump. | -NA- | -NA- | -NA- |
| | ➤ Number of main pumps. | -NA- | -NA- | -NA- |
| <td>> Jockey Pump output.</td> <td>-NA-</td> <td>-NA-</td> <td>-NA-</td> | > Jockey Pump output. | -NA- | -NA- | -NA- |
| | Jockey Pump head. Standby Pump output. | -NA- | -NA- | -NA- |
| | > Standby Pump head. | -NA- | -NA- | -NA- |
| | > Auto Starting/Manual Stopping. | -NA- | -NA- | -NA- |
| | Terrace Level | | | 343 |
| | Discharge of pump. | -NA- | -NA- | -NA- |
| - | > Head of pump. | -NA- | -NA- | -NA- |
| 16.7 | > Power supply. | -NA- | -NA- | -NA- |
| | > Auto starting of pump. | -NA- | -NA- | -NA- |
| 14. | Captive water storage for fire-fighting. | | contraction of the | n 5 7 |
| - | Underground tank capacity. | -NA- | -NA- | -NA- |
| -1-1 | > Draw-off connection. | -NA- | -NA- | -NA- |
| | > Fire Service Inlet. | -NA- | -NA- | -NA- |
| | > Access to tank. | -NA- | -NA- | -NA- |
| | Overhead tank capacity. | -NA- | -NA- | -NA- |
| 15. | No Smoking signage | -NA- | -NA- | -NA- |
| 16. | Provision of Lifts. | | SAN 250 | |
| | Pressurization of lift shaft. | -NA- | -NA- | -NA- |
| | Pressurization of lift lobby. | -NA- | -NA- | -NA- |
| | Communication in lift car. | -NA- | -NA- | -NA- |
| | • Fireman's switch. | -NA- | -NA- | -NA- |
| | Lift signage. | -NA- | -NA- | -NA- |
| 7 | Standby Power Supply | -NA- | -NA- | |
| 8. | Refuge Area | 11 2 14 2 2 | | -NA- |
| 0. | | | rimina) | |
| | Total area Location | -NA- | -NA- | -NA- |
| | | | | |

red

P



| 20. | Special Fire Protection System for the Protection of special Risk, if any. | No electric Connection or point in godown area. No Smoking Sign boards provided. | | MR |
|-----|--|---|------|------|
| | A company of the same of the s | -NA- | -NA- | -NA- |
| | Building floor plan | -NA- | -NA- | -NA- |
| | PA system Panel. Battery backup | -NA- | -NA- | -NA- |
| | Flow Switch Panel. | -NA- | -NA- | -NA- |
| 1 | Detector System Panel. | -NA- | -NA- | -NA- |

The fire protection systems provided in the building were test checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under rules, renewal of the FSC issued vide letter No. F6/DFS/MS/LPG/2018/SZ/2285 Dated 09/10/2018, under rules 37 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly, DFA is put up for perusal and signature please.

Signature of the Inspecting Officer Name: Mr. Rajesh Kumar

Designation: ADO (BCP)

DO (8D)

Mell 71873

St 8 81 2023

Dinectar M/ 18/2

F1 15

As approved, F.I. tetta is putip for your

synature PI

091812023

m