FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/SZ/2023/ 421

Dated: 04/ 09/2023

FIRE SAFETY CERTIFICATE

Certified that the building of Upkari CGHS Ltd. Located at Plot No-09, Sector-12, Phase-1, Dwarka, New Delhi-110075 having 04 blocks, comprised of Basement + Ground/Stilt +Six/Seven UFs was issued No Objection Certificate for occupancy of the building by this department vide letter No. F6/DFS/MS/CGHS/2002/1525, dated 11/09/2002. The premise was re inspected by the officer concerned of this department on 26/08/2023 in the presence of Sh. Inderject Singh (Secretary) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Residential Building" Group A-4 with effect from 64/04/2023 for a period of five years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .04 09 2023 at New Delhi by.

fal Garg)

Director

Delhi Fire Service

Copy to:

1. The President, Upkari CGHS Ltd. Located at Plot No-09, Sector-12, Phase-1, Dwarka, New Delhi-110075.

2. The Joint Director (Building) DDA, Vikas Sadan, INA, Delhi-110023.

Following fire safety directives must be adhered to:-

 All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.

5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

Basement shall be used as per building bye laws.

7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. www.dfs.delhigovt.nic.in.

8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on

www.dfs.delhigovt.nic.in.



INSPECTION REPORT

 Name & address of the building: Upkari CGHS Ltd. Located at Plot No-09, Sector-12, Phase-1, Dwarka, New Delhi-110075.

2. Type of Occupancy : Residential Building "A" (Apartment)

3. Type of Case: Renewal (04 BL =Basement+Ground/Stilt +Six/Seven UFs)

4. Details of previous NOC : F6/DFS/MS/CGHS/2002/1525, dated 11/09/2002

 Fire Safety directives Letter No.: F6//DFS/MS/CGHS/97/1445, dated 08/10/1997 & F6//DFS/MS/CGHS/98/994, dated 25/05/1998

6. Date of inspection

: 26/08/2023

7. Name of the Inspecting Officer: Sh. Udai vir Singh ADO (DWK)

8. Name and designation of Officer

from the building side : Sh. Inderjeet Singh (Secretary)

9. Year of Construction

: 2001

10. Applicant's letter No.

: CGHS/Fire Deptt./2023-24/01, dated-21/08/2023

S No	Minimum standards on fire prevention and fire safety U/R 33		As Per- directive			Provided at site		at	Remarks MR/NMF			
1.	Access of building			LD	11.1			MR				
	Road width	09 mtrs 6 mtrs		Provided			MR (old case)					
- 1	Gate width					MD	(Old case)		130)			
	Width of internal road	6 mtrs	MA.	5.8	to 6m	10.	IVIK	(Old)	case)			
2.	Number, width, Type & Arranger	nents of exit	S	_		i h	-	3 33	-			
	a. Number of staircases Upper floors	1 no. each BL	Prov	rconn	Two Bluected a	locks t Ter	race	&	4	MR		
	Basements Width of staircases				Provide	ed MR						
		1.25 mtr each 115cm MR (Being of						ing ol	d case	:)		
	Upper floorsBasements	1.25 mu c		15m	16,19			Being old case)				
	c. Protection of exits Fire check door Pressurization d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size	/					- 1	· m				
		SCD N/A		11011000		MR						
				LUIL			N/A	CONTRACTOR OF THE PROPERTY OF				
		01 each block		Provided		Viet	MR					
		N/A		N/A			N/A					
		1m	e'		Provided	d	M	R				
	Compartmentation	N/A	N/	N/A			N/A	N/A				
	Fire check door	The state of the s		ovide	d			M		Ť.		
	 Sealing of electrical shafts 	Required N/A	N/		u	el PA	-	N/				
	 Fire Rating of shaft door 	N/A	N/	_			-	N/				
	Water Curtain	N/A	N/A			I N			V/A			
	 Fire Dampers 	IN/A	14/	TVA USELSON IS				41101				
	Smoke managements System	N/A	Exhaust Fan Pro			video	ed N/A					
	BasementsUpper floors	N/A N/A			Ventila		•		N/A			

N19

	Fire Extinguishers							15 -	
	Total numbers	1	2 nos. each floor		Provided	31		MF	
	Types		CO ₂ & ABC	1	CO ₂ , ABO	C, Water	Co2	MF	
	IS marking		SI marked		Provided			MF	
4	First – Aid Hose Reels						Log	М	
-	Total numbers on each	01 No. eac	01 No. each Floor Provided						
			30 m		30 m		MR		
	The second secon	Length of hose reel hoseNozzle diameter		5 mm		II III	MR		
	Automatic fire detection and	alarmin	5 mm						
7.		N/A	N/	A N/A					
	 Type of detectors Location of Main Pan 	ol.	N/A		//A		N/A		
			N/A	N/	Ά		N/A		
	South the first of	Location of Repeater Panel			Ά	ú ri e r	N/A		
	Alternate source of po	owei	N/A N/A		N/A		N/A	A	
	Hooters' Location		Required	Pro	ovided	- 1	MR	10	
	MOEFA		Required		ovided		MR		
	Public Address System	agu ly a la	Required	11	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
0.	Automatic Sprinkler System	NA.	V	Pro	ovided		M	ſR	
	Basements	N/A		N/A			N	/A	
	Upper Floor Glass	N/A		N/A		L 2	N/A		
	Sprinkler above false	18/2		1 "	IVA III				
	ceiling		100					11	
11.	Internal Hydrants	mer	100 mm	Provided			MR		
	Size of riser/down-comer					,,500	MR		
	Number of hydrants p	Required				MR			
-	Hose Box			7 7		4-			
2.	Yard Hydrants	ante	Required		F	rovided		MR	
	Total number of hydra Here Boy	anto	Required	Pro	vided		M	R	
^	Hose Box Description Agrangements				a market	14			
3.	Pumping Arrangements				20		LI		
	· · · · · · · · · · · · · · · · · ·	Ground Level Finding pump			14/21			/A -	
	 Discharge of main put Head of main pump 	шр	N/A N/A	N/A	A	N/A			
	Number of main pump	Number of main pumps			4	N/A			
	I THILLDOL OF THEMES PORTED				1	N/A			
	> Jockey pump out put	,	N/A	N/A	70		N/A		
	Jockey pump out putJockey pump head		N/A	N/A	1			- 7	
	 Jockey pump out put Jockey pump head Standby Pump out put 		N/A N/A	N/A	1		N/A		
	 Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head 		N/A N/A N/A	N/A N/A	1	20.00	N/A N/A		
	 Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual 		N/A N/A N/A N/A	N/A N/A N/A	1 1 1	. 20. 19. Dai 4	N/A N/A N/A		
	 Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual Pump House Access 		N/A N/A N/A	N/A N/A	1 1 1	. 20. 19. Dai 4	N/A N/A		
	 Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual Pump House Access Terrace level 		N/A N/A N/A N/A N/A	N/A N/A N/A N/A			N/A N/A N/A N/A	MP	
	 Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual Pump House Access Terrace level Discharge of pump 		N/A N/A N/A N/A N/A 450 lpm ea	N/A N/A N/A N/A	A A A A A A A A A A A A A A A A A A A	Provided	N/A N/A N/A N/A	MR	
	 Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual Pump House Access Terrace level Discharge of pump Head of the pump 		N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A	A A A A A A A A A A A A A A A A A A A	Provided	N/A N/A N/A N/A MR	MR	
	 Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual Pump House Access Terrace level Discharge of pump Head of the pump Power supply 	stopping	N/A N/A N/A N/A N/A N/A 450 lpm ea 40 mtr Required	N/A N/A N/A N/A N/A ach blo	A A A A A A A A A A A A A A A A A A A	Provided	N/A N/A N/A N/A MR	MR	
	 Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual Pump House Access Terrace level Discharge of pump Head of the pump 	stopping	N/A N/A N/A N/A N/A 450 lpm ea 40 mtr	N/A N/A N/A N/A N/A ach blo	A A A A A A A A A A A A A A A A A A A	Provided	N/A N/A N/A N/A MR	MR	
4.	 Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual Pump House Access Terrace level Discharge of pump Head of the pump Power supply 	stopping	N/A N/A N/A N/A N/A A50 lpm ea 40 mtr Required Required	N/A N/A N/A N/A ach blo	A A A A A A A A A A A A A A A A A A A	Provided	N/A N/A N/A N/A N/A MR MR	MR	
4.	 Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump 	fighting	N/A N/A N/A N/A N/A N/A 450 lpm ea 40 mtr Required Required	N/A N/A N/A N/A ach blo	A A A A A A A A A A A A A A A A A A A	Provided	N/A N/A N/A N/A N/A I MR MR	MR	
4.	 Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire Under ground tank 	fighting 2,00	N/A N/A N/A N/A N/A N/A 450 lpm ea 40 mtr Required Required	N/A N/A N/A N/A N/A Provid	A A A A A A A A A A A A A A A A A A A	Provided	N/A N/A N/A N/A N/A MR MR MR	MR	
14.	 Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire Under ground tank capacity Draw of connection Fire service inlet 	fighting 2,00 Req Req	N/A N/A N/A N/A N/A N/A 450 lpm ea 40 mtr Required Required 0,000 ltrs uired uired	N/A N/A N/A N/A N/A Provid	A A A A A A A A A A A A A A A A A A A	Provided MF	N/A N/A N/A N/A N/A MR MR MR	MR	
14.	 Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire Under ground tank capacity Draw of connection Fire service inlet Access to tank 	fighting 2,00 Req Req Req	N/A N/A N/A N/A N/A N/A 450 lpm ea 40 mtr Required Required 0,000 ltrs uired uired uired	N/A N/A N/A N/A N/A Provide	A A A A A A A A A A A A A A A A A A A	Provided	N/A N/A N/A N/A N/A MR MR R R	,	
14.	 Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire Under ground tank capacity Draw of connection Fire service inlet Access to tank Overhead Tank capaci 	fighting 2,00 Req Req Req 10,0	N/A N/A N/A N/A N/A N/A 450 lpm ea 40 mtr Required Required uired uired uired uired uired uired uired uired	N/A N/A N/A N/A N/A Provide	A A A A A A A A A A A A A A A A A A A	Provided MF	N/A N/A N/A N/A MR MR R R R	MR	
5	 Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire Under ground tank capacity Draw of connection Fire service inlet Access to tank 	fighting 2,00 Req Req Req 10,0	N/A N/A N/A N/A N/A N/A A50 lpm ea 40 mtr Required Required uired uired uired uired uired uired uired uired	N/A N/A N/A N/A N/A Provide	A A A A A A A A A A A A A A A A A A A	Provided MF	N/A N/A N/A N/A MR MR R R R		

6.	Provision of Lifts	•	1277	137/4	N/A		
	Pressurization of Lift Sha	N/A	N/A	N/A			
	 Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch 		N/A			N/A	
			Required	Provided	MR		
			Required	Provided	MR		
	➤ Lift Signage	Required	Provided	MR			
17.	Standby power supply		Required	DG Set 60 KVA	MR		
18.	Refuge Area					N/A	
	> Total area		N/A	N/A		N/A	
	> Location	N/A	N/A	IN/F			
19.	Fire control room		N/A				
	Detector system panel N/.		A	N/A		N/A	
	> Flow Switch Panel	N/A	4	N/A		MR	
	> PA System Panel	Rec	quired	Provided			
	> Battery backup		uired Provided		MR		
	> Building Floor Plans	N/A		N/A		N/A	
20.			Required	CO2 fire extinguisher near electric panel	provide	d MR	

The fire protection systems provided in the building were test checked and found functional

at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter No. F6/DFS/MS/CGHS/2002/1525, dated 11/09/2002 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended

Signature of the Inspecting Officer
Name Volumer Inspecting Officer
Designation Application

Defew Daylors

Directal 1/1 8/2023

Any melly

potop der

Prapa

"DIRECTORY DIDIZZ