

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No.F.6/DFS/MS/School/2023/NDZ/ 623

Dated: 07/09/2023

## FIRE SAFETY CERTIFICATE

Certified that the St. Krishna Bodh Shiksha Sadan (Govt. Recognised Middle School)
Located at 219, Village Mandoli, Near Bank Colony, Delhi-93, building comprised of Ground plus two upper floors only owned / occupied by St. Krishna Bodh Shiksha Sadan, was issued NOC vide letter No. F6/MS/DFS/2006/2895 Dated 28/09/2006. The School building was re-inspected by the officer concerned of this department on 30/08/2023 in presence of Smt. Anju Sharma (Principal) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with Circular No. 262-362 dated 17/01/2005 issued by Director of Education and that the building is fit for occupancy class "Educational" (Group-B) with effect from 07/09/2023 for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rule 2010.

Issued on 07/09/2023 at New Delhi by.

DIRECTOR DELHI FIRE SERVICE

Copy to :-

1. The Principal, St. Krishna Bodh Shiksha Sadan, 219, Village Mandoli, Near Bank Colony, Delhi-93.

2. Director of Education, B-Block, Yamuna Vihar, North East, Delhi-110053.

## Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided therein shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the Management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc. shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction, if any.
- 6. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.

## INSPECTION REPORT

1. Name & address of the building

: St. Krishna Bodh Shiksha Sadan

(Govt. Recognised Middle School).

219, Village Mandoli, Near Bank Colony, Delhi-93.

2. Building is comprised of

: G+2

3. Type of Occupancy

: Educational

4. Type of Case 5. Details of previous NOC

: Renewal

6. Fire Safety directives Letter No.

: F6/MS/DFS/2006/2895 Dated 28/09/2006 : Circular No. 262-362 dated 17/01/2005

7. Date of inspection

: 30/08/2023

8. Name of the Inspecting Officer

: D.O. (E.D.)

9. Name and designation of Officer

from the building side

: Smt. Anju Sharma (Principal)

: 2004

	O. Year of Construction : 1. Applicant's letter No. :	2004 ST.KBSS/OC/187/20	23 Dated 22/08/2	023
S	Minimum standards on fire	D.O.E. Circular	Provided at Site	Remarks MR/NMI
No	prevention and fire safety U/R 33	Req./ 262-362	Site	
1.	Access of building		Combin	MR C
	Road width	6 mtr	6 mtr	N/A
	Gate width	N/A	N/A	
	Width of internal road	N/A	N/A	N/A
2.	Number, width, Type & Arrangement	ts of exits		
	a. Number of staircases	VALUE OF THE RESERVE		140
	Upper floors	02 nos.	02 nos.	MR
	Basements	N/A	N/A	N/A
	b. Width of staircases	1	al Company	e · T
	Upper floors	1.50 mtrs.	1.10 & 1.00 m	MR
			(old accepted)	
	Basements	N/A	N/A	N/A /
	c. Protection of exits	al - Fall	Layer-Seve	
	Fire check door	N/A	N/A	N/A
	Pressurization	N/A	N/A	N/A
	d. No of continuous staircase to terrace	01 nos.	02 nos.	MR
	e. Width Of Corridor	1.50 mtrs.	1.20 mtr. (old accepted)	MR
	f. Door Size	1.00 m	0.90 m (old accepted)	MR
3.	Compartmentation			
	Fire check door	N/A	N/A	N/A
	Sealing of electrical shafts	N/A	N/A	N/A
	Fire Rating of shaft door	N/A	N/A	N/A
	Water Curtain	N/A	N/A	N/A
	Fire Dampers	N/A	N/A	N/A
4.	Smoke managements System	Part of the second		- 11
Ŧπ	Basements	N/A	N/A	N/A
	Upper floors	N/A	N/A	N/A
5.	Fire Extinguishers			
	Total numbers	06 nos.	06 nos.	MR
	• Types	ISI marked ABC/CO <sub>2</sub>	Provided	MR
	• IS marking	Required	Provided	MR

Т	Pinet Aid Hear Darle			
	First - Aid Hose Reels	01 nos.	01 nos.	MR
}	Total numbers on each floor	30 m	30 m	MR
	• Length of hose reel hose	6.5 mm	6.5 mm	MR
	Nozzle diameter	2.274	0.0	
7.	Automatic fire detection and alarmi		N/A	N/A
	Type of detector	N/A	N/A	N/A
	Location of Main Panel	N/A	N/A	N/A
	Location of Repeater Panel	N/A	N/A	N/A
	Alternate source of power	N/A N/A	N/A	N/A
	Hooters' Location	N/A	N/A	N/A
3	MOEFA	N/A	N/A	N/A
9.	Public Address System	IN/A	1.7.	
10.	Automatic Sprinkler System	N/A	N/A	N/A
	Basements	N/A	N/A	N/A
	Upper Floor     Consider above false cailing	N/A	N/A	N/A
	Sprinkler above false ceiling		A STATE OF THE STATE OF	
11.	Internal Hydrants			1 11 /4
11.	Size of riser/down- comer	N/A	N/A	N/A
	Number of hydrants	N/A	N/A	N/A
	• per floor			1
	Hose Box	N/A	N/A	N/A
12.	The second secon			T
12.	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
13.	And the second of the second o			
100	Ground Level		Tarat	NI/A
	<ul><li>Discharge of main pump</li></ul>	N/A	N/A	N/A N/A
77.11	Head of main pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A N/A	N/A
	Jockey pump out put	N/A	N/A	N/A
	> Jockey pump head	N/A N/A	N/A	N/A
Mark	> Standby Pump out put	N/A	N/A	N/A
	Standby Pump Head	N/A	N/A	N/A
	<ul><li>Auto Staring/Manual stopping</li><li>Pump House Access</li></ul>	N/A	N/A	N/A
	<ul> <li>Terrace level</li> <li>Discharge of pump</li> </ul>	220 LPM	220 LPM	MR.
	The state of the s	40 m	40 m	MR
	Head of the pump Power supply	Required	Provided	MR
		Required	Provided	MR
	Auto starting of pump	•	Trovided	
14.	Captive water Storage for fire fighting	N/A	N/A	N/A
	Underground tank capacity	N/A	N/A	N/A
	> Draw of connection	N/A N/A	N/A	N/A
	<ul><li>Fire service inlet</li><li>Access to tank</li></ul>	N/A N/A	N/A	N/A
		2500 ltrs	3000 ltrs	MR
	Overhead Tank capacity	Required	Provided	MR
.5.	Exit Signage.	Kequired	w w	

16.	Provision of Lifts.			
	Pressurization of Lift Shaft	N/A	N/A	N/A
	Pressurization of lift lobby	N/A	N/A	N/A
	Communication in lift Car	N/A	N/A	N/A
	Fireman's Grounding Switch	N/A	N/A	N/A
	• Lift Signage	N/A	N/A	N/A
17.	Standby power supply	N/A	N/A	N/A
18.	Refuge Area	.,,		N/A
	Total area	N/A	N/A	
	• Location	N/A	N/A	N/A
19.	Fire control room			N/A
	Detector system panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	PA System Panel	N/A	N/A	N/A
	Battery backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	
20.	Special Fire Protection Systems for	N/A	N/A were tested, check	N/A

The fire protection systems provided in the building were tested, checked and found

functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, The Fire Safety Certificate issued vide letter no. F6/MS/DFS/2006/2895 Dated 28/09/2006 renewal under circular No. 262-362 Dated 17/01/2005 is recommended.

> Signature of the Inspecting Officer Name: Ashok Kumar Jaiswal

Designation: D.O. (East Division)

etter is adoled for Segn. pl.