

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/Audi/NDZ/2023/ 457

Dated :- 29 / 6 9/2023

FIRE SAFETY CERTIFICATE

Certified that the Gandhi Memorial Hall located at Pearey Lal Bhawan, 2, Bahadur Shah Zafar Marg, New Delhi comprised of Ground floor + 03 Upper floor with Auditorium & Hall this department floor. earlier granted **FSC** by Ground was at No.F6/DFS/MS/Audi/NDZ/2020/445 dated 03/11/20. Now, the premises was re-inspected by the officer concerned of this department on 20/09/23 in the presence of Mr. Sita Ram and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises (Auditorium) is fit for occupancy class -Assembly Building with effect from 29/09/2023 for period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 29/09/2023 at New Delhi by.

DIRECTOR Delhi Fire Service

Copy to:-

- 1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- Sh. S.S.K. Shandilya , Secretary, Gandhi Memorial Hall at Pearey Lal Bhawan, 2, Bahadur Shah Zafar Marg, New Delhi.

Condition for the validity of Fire Safety Certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.

	INSPI	ECTION REPOR	PT .					
1.	Name & address of the building		orial Hall located a	at Pearey				
		, 2, Bahadur Shah Zafar Marg,						
		New Delhi.	, -,	Dara Marg,				
2.	Type of Occupancy	Ground floor +	round floor + 03 upper floor with Auditorium &					
3	Tyme of	d floor						
4	Type of case:-	Renewal	SAICH PAIRS					
•	4. Details of previous FSC:- No. F6/DFS/MS/Audi/NDZ/20 03/11/20.							
5.	Fire safety directives No Date of inspection:- Name of the inspecting officer:- Sh. Ravinder Singh (ADO/CC)							
6.								
7.								
8.	Name & designation of officer							
0	From the building side:-	Mr. Sita Rar	n					
	Year of construction:-	1981						
10.	Applicant's letter No:-	nil dated 16.0	8.23.					
.No.	Minima Grand			Old Case				
.110.	Minimum Standards on fire	Requirement/ Existing fire	Provided at site	Remarks				
	Prevention and fire safety U/R 33	safety		MR/NMR				
	Let the state of t	arrangements						
**	Access to Building	10						
	1) Road width	12 mtr.	12 mtr.	MR				
	2) Gate width	4.5 mtr.	4.5 mtr.	MR				
	3)Width of internal road	N/A	N/A	N/A				
·=	Number, Width Type & Arra	angement of Ex	its					
	A. Number of staircases	West of the second						
	1. Upper floors	03 Nos.	03 Nos.	MR				
	2. Basements	N/A	N/A	N/A				
	B. Width of staircase	ar jet nin se	ATT ET	LA SHI				
	1. Upper floors	1.6 mtr.	1.5, 1.6 & 0.80 Mtr.	MR				
	2. Basements	N/A	N/A	N/A				
	C. Protection of exits	- 1, 5, 10		Maria I said				
	1. Fire check door	N/A	N/A	N/A				
	2. Pressurization	N/A	N/A	N/A				
	D. No. of continuous	01	01	MR				
	staircase to terrace	TANKS THE SECOND	410 774	i i i i i i i i i i i i i i i i i i i				
	E. Width of corridor F. Door size	N/A	N/A	N/A				
	Compartmentation	01 mtr.	01 mtr.	MR				
•		I NOTE THE PARTY OF THE PARTY O	- whe	16 6				
	1) Fire check door	N/A	N/A	N/A				
	2) Sealing of electrical shafts	N/A	N/A	N/A				
	Fire rating of shaft door Water curtain	N/A	N/A	N/A				
		N/A	N/A	N/A				
	5) Fire Dampers	N/A	N/A	N/A				
4.	Smoke Management System							
	1) Basements	30 ACPH	N/A	N/A				
	2) Upper floors	12 ACPH	Exhaust fan	MR				
•	Fire Extinguishers							
	1) Total numbers	20	20	MR				
	2) Types	ABC & CO2	ABC & CO2	MR				

1		
11	7	L
NI	,	
1		

	NI /		427 (2)	555
	J	Required	Provided	MR
	3) ISI marking	Required	Tiovided	
6.	First-Aid Hose Reel	04	04	MR
	1) Total number	30 mtr.	30 mtr.	MR
	2) Length of hose reel hose	05 mm	05 mm	MR
	3) Nozzle diameter Automatic Fire Detection &	Alarming Syst		
7	Automatic Fire Detection &	Beam	Provided	MR
	1) Type of detectors	At Gr. floor	At Gr. floor	MR
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	Required	Provided	MR
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	The state of the s	Provided	MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	11.25
10.	Automatic Sprinkler System	27/4	N/A	N/A
	1) Basement	N/A	Provided Provided	MR
	2) Upper floors(stage)	Required	N/A	N/A
	3) Sprinkler above false ceiling	N/A	N/A	14/2
11.	Internal Hydrants		100	MR
	1) Size of riser/down-comer	100 mm	100 mm	MR
	2) Number of hydrants	04	04	MR
	3) Hose box	04	04	IVIIV
12.	Yard Hydrants		104	MR
	1) Total number of hydrants	04	04	MR
	2) Hose box	04	04	IVII
13.	Pumping Arrangement	101		-
	Ground level			MI
	a) Discharge of main pump	900 LPM	900 LPM	MI
	b) Head of main pump	70 mtr.	70 mtr.	MI
	c) Number of main pump	01	01	MI
	d) Jockey pump out put	450 LPM	450 LPM	MI
	e) Jockey pump head	70 mtr.	70 mtr.	MI
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/
	h) Auto starting/Manual stopping	Required	Provided	MI
	2) Terrace level			
	a) Discharge of pump	N/A	N/A	N/
	b) Head of pump	N/A	N/A	N/
	c) Power supply	N/A	N/A	N/
	d) Auto starting of pump	N/A	N/A	N/.
14.	Captive Water Storage for Fi			
14.	1) Under ground tank	50,000,&	50,000 \$52,500	M
	capacity	52,500 ltr.	ltr.	
	a) Draw-off connection	Required	Provided	M
	b) Fire service inlet	Required	Provided	M
			Provided	M
	d) Over head tank capacity	Required		M
	a liver near tank canacity	6500 ltr.	6500 ltr.	IVI

5.	Exit Signage.	Required	Provided	MR
6.	Provision of Lifts.	An Kitha I	0 2 A 118 Cl 29	1997
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20. Special Fire Protection System for Protection of s Risk, if any: Co2 & DCP				MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/Audi/NDZ/2020/445 dated 03/11/20 under rule 35 of the Delhi Fire Service rules 2010. Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Office

Name :- Ravinder Singh Designation :- ADO (CC)