C-25

Azadi _{Ka} Amrit Mahotsav

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F.6/DFS/MS/EH/2023/NDZ/ 297

Dated: 2709/2023

FIRE SAFETY CERTIFICATE

Certified that the Dominos Pizza (Jubilant Foods Works Ltd.) running at ground floor of the building comprised of two basements, ground plus two upper floors located at G-11. Ground floor. 29-31, Aggarwal Fun City Mall, Unity One, CBD Shahdara, Delhi-110032, owned/occupied M/s Jubilant Foods Works Ltd. was issued FSC vide letter No. F.6/DFS/MS/EH/2020/NDZ/162 dated 19/11/2020. The premises was re-inspected by the officers concerned of this department on dated 19/01/2023 in the presence of Ms. Aradhana (Manager) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with rule 33 of Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy Group 'D' "Assembly" with effect from 2012 2012 is valid upto 31/03/2026 in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 & also conditions printed below.

Issued on ... 2. 7. 09 2.2.3... at New Delhi by

(ATUL GARG)
DIRECTOR
OCCUPANTION
OCCUPANTI

To.

Sh. Yunus Khan, M/s Jubilant Foods Works Ltd. at G-11, Ground floor, 29-31, Aggarwal Fun City Mall, CBD Shahdara, Delhi-110032

Copy to:-

The Joint Commissioner of Police (Lic.), 1st Floor Police Station, Defense Colony, New Delhi MHA ID- 2023090315565 dated 04/09/2023

Conditions for the validity of Fire Safety Certificate

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.

6. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

NIP

1. Name & address of the building

: Dominos Pizza (Jubilant Foods Works Ltd.)

G-11, Ground floor, 29-31, Aggarwal Fun City Mall,

Unity One, CBD Ground, Shahdara Delhi

:02 basement, ground plus two upper floors

(Restaurant is running ground floor only)

3. Type of Occupancy

2. Building is comprised of

:Restaurant (Assembly) :Renewal

4. Type of Case

5. Details of Previous NOC letter

6. Fire Safety directive letter No

:F.6/DFS/MS/EH/2020/NDZ/162 dated 19/11/2020

:NBC Part IV

7. Date of Inspection

:18/09/2023

8. Name of the Inspecting officers

:DO(ED), A.K. Jaiswal& ADO(Shd.), Deepak Kumar

9. Name and designation of Officer from the building side

:Mr. Aradhana (Manager)

10. Year of Construction

:2005

11. Applicant's letter No

:2023090315565 dated 04/09/2023

Sr. No.	Minimum Standards on Fire Prevention and Fire Safety U/R33	NBC Part IV Requirement	Provided at Site	Remarks MR/NMR	
01	Access to Building	Te game a	MARKET WEST		
	Road width	12mtr.	26mtr.	MR	
	Gate width	4.50mtr.	05mtr.	MR	
	 Width of internal road 	N/A	N/A	N/A	
02	Number, Width, Type and Arrangen	nent of Exits	contractoris		
	a. Number of Staircases	N/A	N/A	N/A	
	Upper floor	N/A	N/A	N/A	
	Basement	N/A	N/A	N/A	
	B. Width of Staircases	7 16	Tall 1 18 18 2 4	1.2	
	Upper floor	N/A	N/A	N/A	
	Basement	N/A	N/A	N/A	
	c. Protection of Exits			1,,,,,	
	Fire check door	N/A	N/A	N/A	
	Pressurization	N/A	N/A	N/A	
	d. No. of Continuous Staircases to Terrace	N/A	N/A	N/A	
	e. Width of Corridor	N/A	2.5 mtr	MR	
	f. Door Size	02 mtr.	02 nos. (02 mtr&1.50mtr)	MR	
03	Compartmentation.				
	Fire check door	N/A	N/A	NIA	
	 Sealing of electrical shafts 	N/A	Sealed	N/A N/A	
	 Fire rating of shaft door 	N/A	N/A		
	Water curtain	N/A	N/A	N/A	
	 Fire dampers 	N/A	N/A	N/A	
04	Smoke Management System.				
	Basement	N/A	N/A	1 11/2	
	 Upper floor 	N/A	N/A	N/A	
)5.	Fire Extinguishers N/A N/A N/A				
	Total numbers	03nos.	02===	-	
	Types	ABC /CO ₂	03nos.	MR	
	IS marking	ISI marked	ABC /CO ₂	MR	
		.o. marked	ISI marked	MR	

1 NI7

	First-Aid-Hose Reels.			N. Z. T.			
	Total numbers	01 nos	01 nos	115			
	 Length of hose reel hose 	30 mtr	30 mtr	MR			
07	Nozzle diameter	OF	05 mm	MR			
07	Automatic Fire Detection and Alarming System 05 mm MR						
	Type of detectors	Heat & Smoke	Desvided				
	 Location of main panel 	Control Room	Provided	MR			
	 Location of repeater panel 	Security Room	Provided Provided	MR			
	Alternate source of power	Battery & DG Set	Provided	MR MR			
00	• Hooter	Different Location	Provided	MR			
80	MOEFA	Required	Provided	MR			
09	Public Address System.	Required	Provided				
10	Automatic Sprinkler System.		Trovided	MR			
	Basement	N/A		78.1			
	upper floor	N/A	Provided	N/A			
	sprinkler above false ceiling	N/A	Provided	N/A			
11	Internal Hydrants	N/A	Provided	N/A			
	size of riser/down-comer	100 mm	100 mm				
	 Number of hydrants per floor 	01 nos.	04 nos.	MR			
	Hose box	01 nos.	04 nos.	MR			
12	Yard Hydrants. 01 nos. 04 nos. MR						
To	Total number of hydrants	N/A	01 nos.	NIA			
	Hose box	N/A	01 nos.	N/A N/A			
13	Pumping Arrangements.						
	> Ground Level Common with Mall						
	Discharge of main pump Head of main pump	2280 lpm	2280 lpm	MR			
	Number of main pumps	60mtrs	60mtrs	MR			
	Jockey pump out put	01nos	01nos	MR			
	Jockey pump head	450 lpm	450 lpm	MR			
	Standby pump out put	60mtr	60mtr	MR			
	Standby pump head	2280 lpm	2280 lpm	MR			
	Auto starting /manual	60 mtr	60 mtr	MR			
	stopping	Required	Provided	MR			
	Pump house access	Required	Provided	MR			
	> Terrace Level MR						
	Discharge of pump	N/A	N/A	N/A			
	 Head of the pump 	N/A	N/A	N/A			
	Power supply	N/A	N/A	N/A			
	Auto starting of pump	N/A	N/A	N/A			
14	Captive Water Storage for Fire Common with Mall						
	Underground tank capacity	N/A	2,00, 000 ltrs	MR			
	 Draw-off connection 	N/A	Provided	MR			
	Fire service inlet	N/A	Provided	MR			
	 Access to tank 	N/A	Provided	MR			
15	Overhead tank capacity Exit Signage.	20,000 ltr	25,000 ltr	MR			





6	Provision of Lifts.		N/A	N/A
	Pressurization of lift shaft	N/A	J	N/A
	Pressurization of lift lobby	N/A	N/A	N/A
1	Pressurization of lift lobby	N/A	Provided	N/A
	Communication in lift car	N/A	Provided	
	 Firemen's grounding switch 		Provided	N/A
	Lift signage	N/A	Provided	N/A
17	Standby Power Supply	N/A	1.00	
18	Refuge Area.	2010	TN/A	
10	Keluge / Irou.	N/A	N/A	N/A
	Total area	N/A	N/A	14
	Location			
19	Fire Control Room		N/A	N/A
		N/A	N/A	N/A
	Detector system panel	N/A	N/A	N/A
	Flow switch panel	N/A	Provided	MF
	 PA system panel 	N/A	N/A	N/A
	Battery backup	N/A		N/A
	Duilding floor plans	N/A	N/A	1
20	Special Fire Protection Systems for Protection of Special Risks, if Any:			

The fire protection systems provided in the building were tested/checked and found

Keeping in view the deemed compliance of the minimum standards on fire functional at the time of inspection. prevention and fire safety measures as required under the rules the FSC issued vide letter no. F.6/DFS/MS/EH/2020/NDZ/162 dated 19/11/2020 renewal under rule 35 of the Delhi Fire Service Rule, 2010 is recommended.

Signature of the Inspecting Officer

Name Designation : Deepak Kumar

: A.D.O. (SHD)

Signature of the Inspecting Officer

Name: A.K. Jaiswal

Designation : D.O. (East)

Dinectar

Abol skald. Sir, F.T. Dodfer is pro up for your tind standarde pl.