आज़ादी का अमृत महोत्सव

C-29

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/GH/2023/SZ/ \56

Dated: 27.1.9.12023

## **FIRE SAFETY CERTIFICATE**

Certified that the M/s Hotel Airport Inn located at A-7, Road No 1, Mahipalpur Extension, New Delhi 110037 comprised of Basement Ground plus Three upper floor with 31 Guest Rooms & 4<sup>th</sup> floor Sealed with brick wall was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/GH/2018/SZ/2168 dated 20/09/2018. The premise was re-inspected by the officer concerned of this department on 13/09/2023 in the presence of Mr. Parash Sehrawat (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential, Group-A" (Guest House with 31 Guest rooms) and validity upto 31/03/2026 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 2 + 109 / 2023 at New Delhi by

DIRECTOR ELHI FIRE SERVICE

Copy to: -

 The Addl. Commissioner of Police (Lic.), 1st Floor, P.S. Defence Colony, New Delhi-110049 (Ref. MHA Portal ID 2023090615707 dated 06/09/2023)

## Conditions for the validity of Fire Safety Certificate: -

All the means of escape/entry/exit shall be kept free from any obstruction.

 All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.

3. The basement shall be used as per the provisions of UBBL /NBC Part- IV.

4. All the staff members must know the correct method of operation of fire fighting system.

5. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

6. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.

7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

8. The 4th floor is sealed with bricks wall. The occupancy above 3rd floor is not allowed.





1	Name & Address of the Building						
	107 107 C 17	M/s Hotel A:					
2	Type of Occupancy	M/s Hotel Airport Inn at A-7, Road No 1,					
3	Building Comprised of						
	APRIL DE LA CONTRACTION DEL CONTRACTION DE LA CO	Accidential, Group-A" (Guest House)					
4	Type of Case	Basement Ground plus 4 upper floors (4th Floor sealed with brick wall)					
5	Details of Previous NOC	Renewal					
6	Fire Safety Directives Letter No						
7	T TO OI HISDIPCTION	F6/DFS/MS/GH/2018/SZ/2168 dated 20/09/2018 Nil					
8	Name of the Inspecting Officers	13/09/2023					
9	Name & Designation of Officers	DO (South) & ADO (BCP)					
	from the building side	Mr. Paresh Sehrawat					
10	Year of construction	M. Laternal Hedrands .					
11	Applicant letter No.	2010 Total 31 Guest room					
S. No.	Minimum standard	MHA Portal ID 2023090615707 dated 06/09/2023					
	Minimum standards on Fire Prevention and Fire Safety U/R 33	Old NOC Provided at Site Remark					
1	Access to Building.	requirements	Attractive March	MR/NMR			
dr +	Road width	and the dis-	medicine beat a				
9	Gate width	Required	06 mtr	MR			
		-NA-	Israpic -NA-ignori	-NA-			
2	• Width of internal road	-NA-	leve I fra -NA-	-NA-			
-	Number, width, type & arrangement of exits.  a) Number of Staircase	umber of Sactor					
Win .	> Upper floors.	KUTHER ?	ran ender men				
4	Basement G	02 Nos	Provided	MR			
YE.	Basement floor.	1 + 1 ramp	Provided	MR			
Mr.	b) Width of Staircase	Jessu Q	State 1 - State 10 -	IVIK			
W- W-	> Upper floors	1.25 mtr	1.25-1.40 m & 0.90 m	1 M			
	➤ Basement floor	1.25 mtr	1.04 m & 2.5 m (ramp)				
	c) Protection of exits		1.04 iii & 2.3 m (ramp)	MR			
	➤ Fire check door	-NA-	AND THE PROPERTY AND THE PARTY				
	> Pressurization	-NA-	-NA-	-NA-			
1917	d) No. of continuous staircase to terrace	Production of the second	-NA-	-NA-			
El é	e) Width of corridor	Required	01 Provided	MR			
174	f) Door size	1.25 mtr	Provided	MR			
3	Compartmentation.	1m <sub>nissen</sub>	1.67 mtr (Final Exit)	MR			
	Fire check door.	of the same and the same of th					
M	Sealing of electrical shafts.	-NA-	-NA-	-NA-			
N.	Fire rating of shaft door.	Required	Provided	MR			
SV-	Water curtain	-NA-	-NA-	-NA-			
1	Fire dampers	-NA-	-NA-	-NA-			
1/4	Smoke Management system.	-ΝΛ-	-ΝΛ-	-ΝΛ-			
11/	Basement	As per clause 7.31 of UBBL 2016					
		30 ACPH	Exhaust fan	MR			
1	• Upper floors	12 ACPH	Exhaust fan	MR			
5	Fire Extinguishers.			IVIK			
Luc.	Total numbers	12 Nos	Provided	1			
	Types	ABC/CO2	ABC & CO2	MR			
	ISI Marking	ISI marked		MR			
6	First Aid Hose Reels.		Provided	MR			
8.50	<ul> <li>Total numbers on each floor.</li> </ul>	0-10-10-10-10-10-10-10-10-10-10-10-10-10					
-	<ul> <li>Length of hose-reel hose.</li> </ul>	One	Provided	MR			
M. F.	Nozzle Diameter	30 mtr	Provided	MR			
exe	Nozzie Diameter	5 mm	Provided	MR			



-	Automatic fire detection & alarming system.	As per clause 7.31 o	UBBL 2010	1 10
7	Type of detectors	Co. Mo. Det.	Provided	M
	Location of Main Panel	Required	Provided	M
TERM	Location of Repeater Panel	Required	Provided	M
	Alternate source of power	Required	Provided	_
	Hooter's location	Required	Provided	M
- 2011011		Required	Provided	M
8	MOEFA Public Address System	-NA-	NA	-N
9	Public Address System	The Part of the Land	100,913	
10	Automatic Sprinkler System	Required	Provided	M
	Basement	-NA-	-NA-	-N
	Upper floors.  Class calling	-NA-	-NA-	-Na
	Sprinkler above false ceiling		on the same and the same	
11	Internal Hydrants.	-NA-	-NA-	-N/
	Size of Riser/Down-comer	-NA-	-NA-	-N/
	Number of Hydrant per floor	-NA-	-NA-	-NA
o terror	Hose box.	16	Production of pain	
12	Yard Hydrants.	-NA-	-NA-	-N/
	Total number of hydrants	-NA-	-NA-	-NA
K/4	Hose box.	-NA-	Terrait by Miller 19	
13	Pumping arrangements.	12 YES 165 Y	Company of P	411
7	Ground Level	TO THE LAND OF THE LOCAL PROPERTY OF THE LOC	-NA-	-NA
	Discharge of main pump.	-NA-	-NA-	-N/
	Head of main pump.	-NA-	-NA-	-NA
	Number of main pumps.	-NA-	-NA-	-NA
	> Jockey Pump output.	-NA-	-NA-	-NA
	Jockey Pump head.	-NA-	-NA-	-NA
	> Standby Pump output.	-NA-	-NA-	-NA
	> Standby Pump head.	-NA-	-ΝΛ-	-N/
V	> Auto Starting/Manual Stopping.	-ΝΛ-	-NA-	-NA
	> Pump house access.	-NA-	-IVA-	1,1
	Terrace Level	000 1 70 (	Provided	MF
	Discharge of pump.	900 LPM	Provided	MI
	> Head of pump.	35m	Provided	MI
	➤ Power supply.	Required	Provided	MF
	Auto starting of pump.	Required	Provided	I
14	Captive water storage for fire fighting.		is dissolved to a	-NA
1000	Underground tank capacity.	-NA-	NA	-NA
	> Draw-off connection.	-NA-	-NA-	-NA
	> Fire Service Inlet.	-NA-	-NA-	_
	> Access to tank.	-NA-	-NA-	-NA
	<ul> <li>Overhead tank capacity.</li> </ul>	10,000 lu	Provided	Mi
10	E-it Signage	Required	Provided	MI
16	Exit Signage.  Provision of Lifts.		on the manual sections	
10	Pressurization of lift shaft.	-NA-	-NA-	-NA
	Pressurization of lift lobby.	-NA-	-NA-	-NA
	Communication in lift car.	-NA-	-NA-	-NA
6117	Fireman's switch.	-NA-	-NA-	-NA
		-NA-	-NA-	-NA
	Lift signage.  Standby Power Symply	Required	Provided	MF
17	Standby Power Supply	Required		
18	Refuge Area	-NA-	-NA-	-NA
	Total area	-NA-	-NA-	-NA
	Location	-INA-	-14/7-	

आज़ादी व्य अमृत महोत्सद

	Detector system panel.	-NA-	-NA-	-NA-
	<ul> <li>Flow switch panel.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>PA system panel.</li> </ul>	-NA-	-NA-	-NA-
	Battery backup.	-NA-	-NA-	-NA-
	Building floor plan.	-NA-	-NA-	-NA-
20	Special Fire Protection System for the Protection of special Risk, if any.			

Note: As per MHA Portal Application details per floor occupancy is below mentioned.

1. Ground floor 05 Room

06 Nos of Bed

2. First Floor: 09 Rooms

09 Nos of Bed

3. Second Floor: 09 Rooms

09 Nos of Bed

4. Third Floor: 08 Rooms

08 Nos of Bed

The occupancy per person at per floor is less than of 10 people hence the FCD requirements under clause 7.31 of UBBL is not applicable.

The fire protection system provided in the building were randomly checked and found functional at the time of inspection. The occupancy above 3<sup>rd</sup> floor not allowed as per clause 7.31 of UBBL 2016.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/GH/2018/SZ/2168 dated 20/09/2018, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspection Officer Name: Sh. Manoj Kumar Sharma

Design: DO (South)

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

CFO (HO)

91 2022

Director

Portol D

As approved, F.T. fett

fetter in

putup

Director M/19/2

My

03/0/53 2400959