

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI <u> HEAD QUARTERS : DELHI FIRE SERVICE : NEW DELHI - 110001</u>

No.F6/DFS/MS/NDZ/2023/ 4 60

Dated:-03/10./2023

FIRE SAFETY CERTIFICATE

Certified that Bank of Baroda located at 16, Sansad Marg, New Delhi, comprised of Basement + Ground + 13 upper floors, was earlier granted FSC by this department vide letter No. F.6/DFS/MS/GH/NDZ/2019/186 dated 13/04/20. Now, the premises was re-inspected by the officers concerned of this department on 14/09/23 in the presence of Sh. Praveen, Fire Safety Officer and found that the said business building has deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class- Business with effect from .0.3 ... 10 ... 2023... for period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 03 10 2023 at New Delhi by.

DIRECTOR Delhi Fire Service

Copy to:-

1. The Chief Architect, NDMC Palika Kendra, New Delhi.

2. Sh. B.S Gupta, Dy. General Manager - DZH, Bank of Baroda, 16, Sansad Marg, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of
- 3. The trained fire fighting staff should be available round the clock.
- 4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.

INSPECTION REPORT 1. Name & address of the building : Bank of Baroda Building, 16, Sansad Marg, New Delhi. 2. Type of occupancy : Business Building B + Gr. + 13 upper floors Type of case:-: Renewal (12 point inspection) 4. Details of previous FSC : F.6/DFS/MS/GH/NDZ/2019/186 dated 13/04/20 5. Fire safety directives No. : F6/DFS/MS/84/479 dated 28/06/1984 6. Date of inspection:-: 14/09/23 7. Name of the inspecting officer : Sh. Rajinder Atwal DO/CD & Sh. Ravinder Sigh ADO/CC 8. Name & designation of officer From the building side : Sh. Praveen Kumar, Fire safety Officer 9. Year of construction : 1986 10. Applicant's letter No : ZO:NDZ:SEC:2023-24/601 Dated 01/09/19. S.No. Minimum Standards on fire Requirement Provided at site Remarks Existing fire Prevention and fire safety MR/NMR safety U/R 33 arrangements 1. Approach to Building 1) Road width 6 Mtr. MR 6 mtr. MR 2) Gate width 6 Mtr. 06 mtr. N/A 3) Width of internal road N/A 06 mtr. one side only 2. Number, Width Type & Arrangement of Exits A. Number of staircases MR 1. Upper floors 01 01 2. Basements 02 02 MR B. Width of staircase 01 Nos. 1.4m . B to 2nd 1. Upper floors 1.25 mtr. MR floor & 01 Nos. ground to 13 upper floor 1.4 & 1.5 mtr. 2. Basements 1.25 mtr. MR C. Protection of exits 1. Fire check door N/A Provided N/A 2. Pressurization N/A N/A N/A D. No. of continuous 01 01 MR staircase to terrace E. Width of corridor NA NA NA F. Door size NA NA NA 3. Compartmentation 1) Fire check door Required Provided MR 2) Sealing of electrical shafts Required Provided MR 3) Fire rating of shaft door NA NA NA 4) Water curtain N/A N/A N/A 5) Fire Dampers N/A N/A N/A 4. Smoke Management System 1) Basements 30 ACPH Mechanical MR

~ W

Provided

Provided

45

MR

MR

MR

12 ACPH

ABC & CO2, WCo2

40

2) Upper floors

2) Types

Fire Extinguishers

1) Total numbers

5.

	/	NIC	_		
	3) ISI marking	Required	Provided	IVA	
6.	First-Aid Hose Reel				
	1)Total number of each	01	01		
	floor	A1505-5	A Comment	MR	
	2) Length of hose reel hose		30 mtr.	MR	
_	3) Nozzle diameter	05 mm	05 mm	IVIIC	
7.	Automatic Fire Detection &	: Alarming System		1 10	
	1) Type of detectors	Heat & Smoke	Provided	MR	
	2) Location of main panel	Main Exit	Main Exit	MR	
	3) Location of repeater pane		Provided	MR MR	
	4) Alternate source of power		Provided	MR	
	5) Hooter's Location	Each floor	Provided		
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System	_) (D	
	1) Basement	Required	Provided	MR	
	2) Upper floors	N/A	N/A	N/A	
	3) Sprinkler above false	N/A	N/A	N/A	
	ceiling				
11.	Internal Hydrants	1.50	150	MR	
	1) Size of riser/down-comer	150 mm	150 mm		
	2) Number of hydrants per	01	01	MR	
	floor	01	01	MR	
12	3) Hose box each floor	01	01	IVIK	
12.	Yard Hydrants	100	100	MR	
	1) Total number of hydrants	02	02	MR	
	2) Hose box	02	02	MR	
3.	Pumping Arrangement				
	1) Ground level			MD	
	a) Discharge of main	2280 LPM	2280 LPM	MR	
	pump	63 mtr.	62t-	, MD	
	b) Head of main pump		63 mtr.	/ MR	
	c) Number of main pump		02	MR	
	d) Jockey pump out put	180 LPM	180 LPM	MR	
	e) Jockey pump head	63 mtr.	63 mtr.	MR	
	f) Stand by pump output	1850 LPM	1850 LPM	MR	
	g) Stand by pump head	63 mtr.	63 mtr.	MR	
	h) Auto		Provided	MR	
	starting/Manual	Required	1 - 2 1		
	stopping	170000 7 170			
	2) Terrace level				
	a) Discharge of pump	N/A	N/A	N/A	
	b) Head of pump	N/A	N/A	N/A	
	c) Power supply	N/A	N/A	N/A	
	d) Auto starting of pump	N/A	N/A	N/A	
	Captive Water Storage for Fire Fighting				
111	 Under ground tank 	2,00,000 ltr. /	2,00,000 lt	. MR	
11	capacity				
	capacity a) Draw-off connection	Required	Provided	MR	

Jul.

	c) Access to tank	Required	Provided	110
	d) Over head tank capacity	20,000 ltr.	20,000 ltr.	MR MR
15.	Exit Signage.	Required	Provided	
16.	Provision of Lifts.	required	Flovided	MR
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Standby Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	Provided	N/A
	Total area location	N/A	Provided	N/A
19.	Fire Control Room	N/A	Provided	N/A
	a) Detector system panel	Required	Provided	MR
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	Required	Provided	MR
	d) Battery backup	Required	Provided	MR
	e) Building floor plan	Required	Provided	MR
20.	Special Fire Protection System for Protection of special Risk, if any: ABC & Co ₂			MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection. Further, the following points are not required in 12 points inspection, whereas in previous FSC inspection Performa same have been mentioned, however, same are not provided at the site. If approved, we may exempt the same.

1 Pressurization of staircases and lift lobby & shaft.

2 Sprinklers system at upper floors.

In view of the deemed compliance of the 12 minimum standards of fire prevention and fire safety measures as required under the rules, if approved, we may renew the FSC issued vide letter no F.6/DFS/MS/GH/NDZ/2019/186 dated 13/04/20, under 12 points . Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: - Rajinder Atwal Designation: - DO (CD) Signature of the Inspecting Officer

Name: - Ravinder Singh

Designation: - ADO (CC)