

GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

No. F.6/DFS/MS/School/2023/SZ/ 741

Dated: 16 /10 / 2023

FIRE SAFETY CERTIFICATE

Certified that the Bloom Public School located at C-8, Vasant Kunj, New Delhi110070, comprised of Ground plus three upper floors was issued Fire Safety Certificate by this
department vide letter No. F.6/DFS/MS/School/2020/SZ/311 dated 27/08/2020. The premises was reinspected by officer concerned of this department on 06/10/2023 in presence of Mr. Manmohan
Sharma (Admin Officer) of the school and found that the said school building have deemed
complied with the fire prevention and fire safety requirements in accordance with Directorate of
Education circular F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01/03/2011 issued by
Director of Education, Govt. of NCT of Delhi and that the school building is fit for occupancy
class "Educational Building" Group-B, with effect from the date of issue of this certificate for a
period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner
cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi
Fire Service Rules, 2010.

Issued on 16/10/2023 at New Delhi by

DIRECTOR

DELHI FIRE SERVICE

Copy to: -

1. The Admin Officer, Bloom Public School, C-8, Vasant Kuni, New Delhi-110070

2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi.

Conditions for the validity of Fire Safety Certificate: -

1. All the means of escape/entry/exit shall be kept free from any obstruction.

- All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."



100	11/1/2		-1-201	महोत्सव	
1,000	Name & Address of the Building	ON REPORT	Contrated No work		
2	or the Building	Bloom Public School, C-8, Vasant Kunj, New Delhi-110070			
3	Type of Occupancy	Educational Building "Group-B" (School)			
10-10-0	Building Comprised of	Ground plus three upper floors.			
4	Type of Case	Renewal	e upper floors.	1	
5	Details of Previous NOC	A GIDIE X			
6	Fire Safety Directives Letter No	F.6/DFS/MS/School/2020/SZ/311 dated 27/08/2020			
7	Date of Inspection	F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01/03/2011			
8	Name of the Inspecting Officers	06/10/2023			
9	Name & Designation of Officers	DO (South) & ADO (BCP) Mr. Manmohan Sharma (Admn. Officer)			
10	Year of construction	1999			
11	Applicant letter No.	CONTRACTORING DAILY			
S. No.	Minimum standards on Fire Prevention	E-mail dated 18/08/2023			
1	and Fire Safety U/R 33 Access to Building.			Remarks MR/NMF	
- 87/	Road width	participal in the last	od soczydowe family		
	Gate width	Required	12 mtr	MR	
	Width of internal road	Required	5.34, 3.32 & 0.89m	MR	
2	The second secon	-NA-	-NA-	-NA-	
- A M	Number, width, type & arrangement of ex	cits.	man to terreducit 4		
	> Upper floors.		mwg nambo beatt w		
	Basement floor.	Required	Two	MR	
	b) Width of Staircase	-NA-	MA- POL S	-NA-	
	> Upper floors		repurchasis despite		
	> Basement floor	Required	1.42 mtr each	MR(old case)	
	c) Protection of exits	-NA-	-NA-	-NA-	
	> Fire check door	-NA-	over ment ment 4		
	▶ Pressurization	-NA-	-NA-	-NA-	
	d) No. of continuous staircase to terrace		-NA-	-NA-	
NIK	e) Width of corridor	Required	Two	MR	
NIM 8	n Door size	-NA-	vhrr-NA-my 4	-NA-	
3	Compartmentation.	-NA-	III HEU-NA-	-NA-	
-			office mater storoge for	74. Car	
-AK-	Fire check door. Sealing of electrical shafts.	-NA-	Ann Irm -NA-	-NA-	
-AM-	Fire rating of shaft door.	-NA-	-NA-	-NA-	
464	Water curtain	-NA-	-NA-	-NA-	
MM.	Fire dampers.	-NA-	-NA-	-NA-	
200		-NA-	-NA-	-NA-	
4.	Smoke Management system.		4.11	T2 1	
-AV-	Basement Upper floors	-NA-	-NA-	-NA-	
5.	Upper floors Fire Extinguishers.	-NA-	-NA-	-NA-	
+25	Total numbers	Required	15 Nos.	100	
-10/-	Types	ABC / CO2	ABC & W.CO2	MR	
101-	ISI Marking	ISI marked	Provided	MR MR	
6.	First Aid Hose Reels.	151 Illai keu	Tiovided	IVIK	
	Total numbers on each floor.	One	Provided	MR	
AV	Length of hose-reel hose.	30m	Provided	MR	
-AM-	Nozzle Diameter	5mm	Provided	MR	
7	Automatic fire detection & alarming system.				





				_
	Type of detectors	-NA-	-NA-	-NA
	Location of Main Panel	-NA-	-NA-	-NA
	Location of Repeater Panel	-NA-	-NA-	-NA-
	Alternate source of power	-NA-	-NA-	-NA-
_		-NA-	-NA-	-NA-
	Hooter's location		-NA-	-NA-
8.	MOEFA	-NA-	-NA-	-NA-
9.	Public Address System	-NA-	-NA-	-11/24
0.	Automatic Sprinkler System		N14	-NA-
	Basement	-NA-	-NA-	
	Upper floors	-NA-	-NA-	-NA-
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11.	Internal Hydrants.		also got .	
	Size of Riser/Down-comer	Required	100 mm	MR
	 Number of Hydrant per floor 	Required	One	MR
	Hose box.	Required	One	MR
12.	Yard Hydrants.		TEN TOTAL	1975
	Total number of hydrants.	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13.	Pumping arrangements.		7.55	
	Ground Level			
	Discharge of main pump.	-NA-	-NA-	-NA-
	> Head of main pump.	-NA-	-NA-	-NA-
	> Number of main pumps.	-NA-	-NA-	-NA-
	> Jockey Pump output.	-NA-	-NA-	-NA-
	> Jockey Pump head.	-NA-	-NA-	-NA-
	> Standby Pump output.	-NA-	-NA-	-NA-
	> Standby Pump head.	-NA-	-NA-	-NA-
	> Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-
	> Pump house access.	-NA-	-NA-	-NA-
	100-100-100-100-100-100-100-100-100-100		the second second second	1,000,000
	Terrace Level		the state of the	1
	> Discharge of pump.	450 LPM	450 LPM	MR
	 Head of pump. Power supply. 	40m	40m	MR
	> Auto starting of pump.	Required	Provided	MR
		Required	Provided	MR
4.	Captive water storage for fire fighting.		- Marining Call	
	Underground tank capacity.	-NA-	-NA-	-NA-
	> Draw-off connection.	-NA-	-NA-	-NA-
	 Fire Service Inlet. Access to tank. 	-NA-	-NA-	-NA-
	Overhead tank capacity.	-NA-	-NA-	-NA-
5.		10,000 Ltrs	10,000 Ltrs	MR
6.	Exit Signage. Provision of Lifts.	Required	Provided	MR
0.		T		
	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	Communication in lift car.	-NA-	-NA-	-NA-
	Fireman's switch.	-NA-	-NA-	-NA-
	Lift signage.	-NA-	-NA-	-NA-
17.	Standby Power Supply	-NA-	-NA-	-NA-
18.	Refuge Area			
	Total area	-NA-	-NA-	-NA-
	Location	-NA-	-NA-	-NA-

4





-NA-
_
-NA-
-NA-
-NA-
-NA-

The fire protection system provided in the building / premises were test checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire issued vide letter No. safety NOC measures as required under the rules, the F.6/DFS/MS/School/2020/SZ/311 dated 27/08/2020, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspection Officer Name: Sh. Manoj Kumar Sharma

Design: DO (South)

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

As approved, F-1- fetter in Antrop or your signature of