## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI <u> HEAD QUARTERS : DELHI FIRE SERVICE : NEW DELHI – 110001</u>

NO. F.6/DFS /MS/NDZ/2023/ 492

Dated 7/10/2023

## FIRE SAFETY CERTIFICATE

Certified that the Alliance International Pvt. Ltd. located at 2E/21, Jhandewalan Extension, Pahar Ganj, New Delhi is comprised of Basement + Ground + Five Upper floors owned/occupied by M/s Alliance International Private Limited, was earlier granted FSC by this department vide letter No.F6/DFS/MS/2020/NDZ/349 dated 07.09.2020. Now, the premises was re-inspected by the officer concerned of this department on 09/10/2023 in the presence of Ms. Pratika Sharma and found that the said premises has deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and the premises is fit for occupancy class -Business Building with effect from. 1.7/10/23... for period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of Delhi Fire Service Rules 2010, printed below:

Issued on 17/10/2023 at New Delhi by.

Delhi Eire Service

Copy to:-

- 1. The Commissioner, MCD, Civic Centre, New Delhi. : To kindly ensure the occupancy as detailed above and deviation if any.
- 2. Mr. Dinesh Saini (Owner) Alliance International Pvt. Ltd., 2E/21, Jhandewalan Extension, Pahar Ganj, New Delhi-110055.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an

emergency. 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub

rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

9. Any flammable material for interior decoration shall strictly prohibited.

INSPECTION REPORT 1. Name & address of the building:- Alliance International Pvt. Ltd., 2E/21,

Jhandewalan Extension, Pahar Ganj, New

Delhi

2. Type of occupancy:-Business Building (B+ G+05 Upper Floors) 3. Type of case:-

Renewal

4. Details of previous FSC:-F6/DFS/MS/2020/NDZ/349 dated

07.09.2020 5. Fire safety directives No.-No.F6/BP/77/DFS-132 dated 05/05/1977 6. Date of inspection:-09/10/23

7. Name of the inspecting officer:-

Sh. Ravinder Singh (ADO/CC) 8. Name & designation of officer

From the building side:-

Ms. Pratika Sharma

1976

9. Year of construction:-

10. Applicant's letter No:letter no. nil dated 26/09/2023

S.No.	Minimum Standards on fire Requirement Provided at site						
	Prevention and fire safety U/R 33	/Exiting fire safety arrangements	riovided at site	Remarks MR/NMR			
1.	Access to Building						
	1) Road width	Adequate	Provided	MR			
	2) Gate width	NA	Directly approachable	NA			
	3)Width of internal road	NA	NA	NA			
2.	Number, Width Type & Arra	ngement of Exits					
	A. Number of staircases						
	1. Upper floors	02 Nos.	02 Nos.	MR			
	2. Basements	02 Nos.	02 Nos.	MR			
	B. Width of staircase						
	1. Upper floors	1.20 & 0.75 mtr.	1.20 & 0.90 mtr.	MR			
	2. Basements	1.20 & 0.75 mtr.	1.20 & 0.90 mtr.	MR			
	C. Protection of exits						
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous staircase to terrace	01	01	MR			
	E. Width of corridor	N/A	N/A	N/A			
	F. Door size	N/A	1 mtr.	MR			
	Compartmentation						
	1) Fire check door	Required	Provided	MR			
	2) Sealing of electrical shafts	Required	Provided	MR			
	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
•	Smoke Management System						
	1) Basements	Required	Provided/ exhaust fan	MR			
	2) Upper floors	N/A	Provided	N/A			

N/22

5.	Fire Extinguishers			- 20
	1) Total numbers	12 Nos.	14 Nos.	
	2) Types	ABC & CO2		MR
	3) ISI marking	Required	ABC & CO2	MR
6.	First-Aid Hose Reel	required	Provided	MR
	1)Total number of each	01	01	
	floor	01	01	MR
	2) Length of hose reel hose	30 m	20	
	3) Nozzle diameter	05 mm	30 m	MR
7.	Automatic Fire Detection & A	Alarming System	05 mm	MR
	1) Type of detectors	N/A		
	2) Location of main panel	N/A	Provided	N/A
	3) Location of repeater panel	N/A	Ground	N/A
	4) Alternate source of power		N/A	N/A
	5) Hooter's Location	N/A	Provided	N/A
8.	MOEFA	N/A	Provided	N/A
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	N/A	N/A	N/A
	1) Basement	Desire		
	2) Upper floors	Required	Provided	MR
47	Sprinkler above false	N/A	N/A	N/A
	ceiling	N/A	N/A	N/A
11.	Internal Hydrants	PA PARTITION	1 10 100	
	1) Size of riser/down-comer	100 mm	100 mm	MR
	<ol><li>Number of hydrants per floor</li></ol>	01 Nos.	01 Nos.	MR
	3) Hose box	01 Nos.	01 Nos.	MR
12.	Yard Hydrants	Good!	011103.	IVIK
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement			IIVA
	Ground level	N/A	N/A	N/A
	a) Discharge of main     pump	N/A	N/A	N/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	N/A	N/A	N/A N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/ Manual stopping	N/A	N/A	N/A
	2) Terrace level	A PARTY	200	-
	a) Discharge of pump	Required	900 & 450 LPM	MR
	1) ** 1 0		200010000000000000000000000000000000000	1
	b) Head of pump	40 m	40 m	MR

		Required	Provided	MR
-	d) Auto starting of	Required		
14.	Captive Water Storage for Fire  1) Under ground tank	50,000 Ltrs.	50,000 Ltrs.	MR
	canacity	1 1	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	25000 Ltr.	MR
	d) Over head tank capacity	Required		MR
		Required	Provided	MA
15.	Exit Signage. Provision of Lifts.			-5.07
	a) Pressurization of lift	N/A	N/A	N/A
	shaft b) Pressurization of lift	N/A	N/A	N/A
	lobby c) Communication in lift	N/A	N/A	N/A
		• "	, h	27/4
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17	Stand by Power Supply	N/A	N/A	N/A
17.	Refuge Area	N/A	N/A	N/A
19.	Total area location	N/A	N/A	N/A
	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System	for Protection of	f special Risk, if	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter no. F6/DFS/MS/2020/NDZ/349 dated 07.09.2020, under rule 35(6) of the Delhi Fire Service rules 2010. Accordingly, DFA is prepared and put up for kind perusal and approval / signature please

Signature of the Inspecting Officer

Name :- Ravinder Sir Designation :- ADO (CC)