

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110001**

No.F6/DFS/MS/School/NDZ/2023/764

Dated:-26.10.2023

FIRE SAFETY CERTIFICATE

Certified that the Atal Adarsh Vidyalaya located at Hanuman Lane, New Delhi comprises of Ground + 02 Upper floor was earlier granted FSC by this department vide letter No. F6/DFS/MS/School/NDZ/2020/217 dated 15/07/20. Now, the premises was re-inspected by the officer concerned of this department on 19-10-2023 in the presence of Ms. Puspa Kumari (Principal) and found that the said school building have complied with the fire prevention and fire safety requirements in accordance with Circular No. F.16/Estate/CC/Fire Safety/2011/3298-3398 dated 01/03/2011 and that the premises is fit for occupancy of class Group B "Educational Building" (Sub-Div. B-I) with effect from .. 26.1.16...2023 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 on the conditions printed below. Issued on2.6./1.0/.20.23..... at New Delhi by.

Belhi Fire Service

Copy to:-

1. Director of Education, Govt. of NCT, Delhi.

2. The Principal, Atal Adarsh Vidyalaya, Hanuman Lane, New Delhi.

3. Sh. N.K. Gaur, Fire Officer, Fire Department, NDMC, Palika Kendra, New Delhi.

Conditions for the validity of Fire Safety Certificate

1. All the means of escape shall be kept free of all types of obstruction all the time.

2. All the fire safety arrangements provided there in shall be maintained in good working condition at all time.

- 3. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.

5. Basement shall be used as per NBC/BBL 1983.

- 6. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.
- 7. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 8. Any flammable material for interior decoration is prohibited.

	3.11.09	74114				
"	IN	SPECTION REP	PORT			
1.	Name & address of the building	g:- Atal Adarsh	Vidyalaya located	at Hanuman		
		Lane, New	Delhi	at Handinan		
	Type of occupancy:-		Building, Gr. + 2	Floor		
	Type of case:-	Renewal				
4	. Details of previous FSC:-	F6/DFS/MS	S/School/NDZ/2020	1/217 dated		
	. Fire safety directives No Date of inspection:- N/A 19/10/23 Name of the inspecting officer:- Sh. Ravinder Singh (ADO/CC)					
7.						
8.	Name & designation of office					
	From the building side:-		Cumari (Principal)			
	Year of construction:-	1991				
10	. Applicant's letter No:-	mail id <fo@< td=""><td>ndmc.gov.in> date</td><td>d 27.09.2023</td></fo@<>	ndmc.gov.in> date	d 27.09.2023		
S.No.	Minimum 84 1 1 7	1.				
S.1NO.		Requirement Exiting fire	Provided at site	Remarks		
	Prevention and fire safety U/R 33	safety certificate	99	MR/NMR		
	Naviga and the second	arrangements				
1.	Access to Building	1 1 1				
	1) Road width	06 mtr.	09 mtr.	MR		
	2) Gate width	4.5 mtr.	05 mtr	MR		
	3)Width of internal road	NA	NA	NA		
2.	Number, Width Type & Arran	ngement of Exits				
	A. Number of staircases					
	1. Upper floors	02	02 & ramp	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase					
	1. Upper floors	1.5 mtr.	1.25 & 1.60 mtr. &	MR		
	2 Parray	100000	ramp			
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	01	1st Gr. to 2nd floor	MR		
	staircase to terrace	7 2 1	(terrace), 2 nd S/c			
			Gr. to 1st floor &			
			Ramp Gr. to 2 nd floor			
	E. Width of corridor	1 mtr.	1.05	MD		
	F. Door size	1 mtr.	1.25 mtr. /	MR		
	Compartmentation		1 mu	MR		
	1) Fire check door	N/A	NI/A	27/4		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain		N/A	N/A		
		N/A	N/A	N/A		
6	5) Fire Dampers	N/A	N/A	N/A		
	Smoke Management System	200		-2		
	1) Basements	N/A	N/A	N/A		
	2) Upper floors	12 ACPH	Natural	MR		
_	Fire Extinguishers	H2 2 16	922			
	1) Total numbers	07 Nos.	10 Nos. /	MR		
	2) Types	ABC & CO2	ABC, CO2	MR		

MIL

		5500		-
-	3) ISI marking	Required	Provided	MR 💞
6.	First-Aid Hose Reel			1
	1)Total number of each floor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr. (MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection & A	larming System	1	IVAL
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	Required	Provided	
10.	Automatic Sprinkler System	required	Tiovided	MR
	1) Basement	N/A	N/A	NI/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling		IVA	N/A
11.	Internal Hydrants			
	1) Size of riser/down-comer	100 mm	100 mm	100
	2) Number of hydrants per	01	01	MR
	floor	- A To select	01	MR
	3) Hose box	01	01	100
12.	Yard Hydrants	MR		
	1) Total number of hydrants	N/A	N/A	INVA
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement		1.071	N/A
	Ground level	N/A	N/A	NIA
	 a) Discharge of main 	N/A	N/A	N/A N/A
	pump	ROSE A TRACK		I
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main	N/A	N/A	N/A
	pump			I IVA
	d) Jockey pump out put	280 LPM	280 LPM (MR
	e) Jockey pump head f) Stand by pump	30 mtr.	30 mtr.	MR
	, pump	N/A	N/A	N/A
	output	Die N		1
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual stopping	N/A	N/A	N/A
	2) Terrace level	1		
	Be of builth	450 LPM	450 LPM	MR
	- Pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR
14.	Captive Water Stomas 6	Pili		1
sterning.	Captive Water Storage for Fir 1) Under ground tank			
	capacity	N/A	N/A	N/A
	Tapacity			

	- ortion	N/A	N/A	N/A	
	a) Draw-off connection	N/A	N/A	N/A	
	b) Fire service inlet	Required	Provided	MR	
5.5	c) Access to tank d) Over head tank capacity	5,000 ltr.	5,000 ltr.	MR	
	Cupana,		Provided	MR	
15.	Exit Signage.	Required	Flovides		
16.	Provision of Lifts.		27/4	N/A	
10.	a) Pressurization of lift shaft	N/A	N/A N/A	1,,,,,	
				N/A	
	b) Pressurization of lift	N/A			
	lobby		N/A	N/A	
	c) Communication in	N/A	IN/A		
	lift car		N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
	e) Lift signage	N/A	N/A	N/A	
17.	Stand by Power Supply	N/A	N/A	N/A	
18.	Refuge Area	N/A	- 5-86G	N/A	
10.	Total area location	N/A	N/A		
	Total area location	1	N/A	N/A	
10	Fire Control Room	N/A	II Chromate	N/A	
19.		N/A	N/A	IVA	
	a) Detector system panel		27/4	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	35000 E	
		27/4	N/A	N/A	
	e) Building floor plan	N/A	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	MR	
20.	Detection System for Protection of special Risk, II				

The fire protection system provided in the school building were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/School/NDZ/2020/217 dated 15/07/20, renewal under Rule 35 of the Delhi Fire Service rules 2010, Accordingly, DFA is put up for kind perusal and signature

Signature of the Inspecting Officer

Name :- Ravinder Sing

Designation :- ADO (CC)