GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No.F6/DFS/MS/School/NDZ/2023/765

Dated: 26/10/2023

FIRE SAFETY CERTIFICATE

Certified that the Dashmesh Public School at Vasundhara Enclave, Delhi-110096, now comprised of Basement + Ground + 03 upper floors only (Earlier it Basement + Ground + 02 upper floors only for which Fire Safety Certificate was issued by this department vide letter No. F6/DFS/MS/School/NDZ/2020/322 dated 02/09/2020), have complied with fire prevention & fire safety requirements in accordance with 33 of the Delhi Fire Service Rules, 2010/ NBC Part - IV and verified by the officer concerned of Fire Service on 13.09.2023 in presence of Mrs. Manpreet Kaur (Principal) and that the building /premises is fit for occupancy class "Educational" (Group-B) with effect from 26/10/2023 for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rule 2010.

Issued on 26/10/12023 at New Delhi by.

ATUL GARG)
DIRECTOR
DELHI FIRE SERVICE

Copy to:-

- 1. Director of Education, (GNCT of Delhi), Civil Lines, Old Secretariat Delhi-110054.
- 2. The Principal, Dashmesh Public School at Vasundhara Enclave, Delhi-110096.

Conditions for the validity of Fire Safety Certificate

- The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 2. All the means of escape shall be kept free of all the type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy
 and constructional deviation in building etc .may be got verified from the authorities concerned.
- This Fire Safety Certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7. Basement shall be used as per BBL.
- 8. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.

			INSPECT	TION REPOR	CI			
	Name & address of the balloting			Dashmesh Public School at Vasundhara Enclave, Delhi-110096.				
	Duildi	na	is comprised of	Basement + Ground + 03 upper floors only.				
	Madevocacute			Educational Building				
i - 2			ecupancy	N. Gara / Alteration				
1	2 Vi vivra letter no			F6/DFS/MS/School/NDZ/2020/322 dated 02.09.2020. Basement + Ground + 02 upper floors. F6/DFS/MS/BP/2020/352 dated 16.09.2020				
5								
6								
7	Date of inspection Name of the inspecting officers Name of the designation of officer			13.10.2023		- 4 ND		
8				Yashwant Sir	igh Me	ena ADO (L.N)		
9				Mrs. Manpreet Kaur (Principal)				
from the building side Year of construction			2020					
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			Email dated - 22/09/2023		Remarks		
1005055	11 Applicant's letter no. S.No Minimum standard of fire prevention and fire safety U/R 33		Requirement Pr		Provided at site	MR/NMR		
1	Access to Building:			Late D. T. H. Sansar		MR		
1	A Road width			6.0 mtrs.			MR	
			ate width	4.5 mtrs		4.5 mtrs	MR	
	1 15 1	G Width of internal road		N/A				
		11/	idth of internal road			6.0 mtrs	MK	
2		11/	idth of internal road		:	6.0 mtrs	MK	
2	C	W	idth of internal road er, Width, Type and Arrange					
2	C	W mb	idth of internal road er, Width, Type and Arrange umber of staircases		03 no	S.	MR	
2	C	W mb N a	idth of internal road er, Width, Type and Arrange	ment of Exits		S.		
2	C Nu A	W mb N a b	idth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement	03 nos. 03 nos.	03 no	s. s.	MR MR	
2	C	W mb N a b	idth of internal road er, Width, Type and Arrange umber of staircases Upper floor	ment of Exits 03 nos.	03 no 03 no 02 no	S.	MR MR	
2	C Nu A	W mb N a b	idth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement Vidth of staircases	03 nos. 03 nos.	03 no 03 no 02 no 01no.	s. s. of 1.7 mtrs & of 1.8 mtrs os. of 1.7 mtrs &/	MR MR MR	
2	C Nu A	Wmber N a b W a b	idth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement Vidth of staircases Upper floor Basement	03 nos. 03 nos. 1.50 mtrs.	03 no 03 no 02 no 01 no 02 no 01 no	s. s. of 1.7 mtrs & of 1.8 mtrs s. of 1.7 mtrs & of 1.8 mtrs s. of 1.8 mtrs	MR MR MR	
2	C Nu A	Wmber N a b W a b	ridth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement ridth of staircases Upper floor Basement	03 nos. 03 nos. 1.50 mtrs. Required	03 no 03 no 02 no 01no 02 no 01no Provi	s. s. of 1.7 mtrs & of 1.8 mtrs s. of 1.7 mtrs & of 1.8 mtrs ded	MR MR MR	
2	C Nu A B	Wmbe N a b w a b P a	ridth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement Vidth of staircases Upper floor Basement Protection of exits Fire check door	03 nos. 03 nos. 1.50 mtrs. Required Required	03 no 03 no 02 no 01 no 02 no 01 no Provi	s. s. of 1.7 mtrs & of 1.8 mtrs s. of 1.7 mtrs & of 1.8 mtrs ded	MR MR MR MR MR MR MR MR MR	
2	C Nu A B C C	Wmbe Nab b Waab	ridth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement Vidth of staircases Upper floor Basement Protection of exits Fire check door Pressurization	03 nos. 03 nos. 1.50 mtrs. Required Required N/A	03 no 03 no 02 no 01no 02 no 01no Provi	s. s. of 1.7 mtrs & for of 1.8 mtrs	MR MR MR MR MR	
2	C Nu A B C C D	Wmber N a b W a a b b P a b b t t	ridth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement Vidth of staircases Upper floor Basement Protection of exits Fire check door Pressurization No. of continuous staircases to	03 nos. 03 nos. 1.50 mtrs. Required Required N/A 0 02 nos.	03 no 03 no 02 no 01 no 01 no Provi Provi N/A	s. s. of 1.7 mtrs & of 1.8 mtrs s. of 1.8 mtrs ded ided os.	MR MR MR MR MR MR MR MR MR	
2	C Nu A B C C D E	Wmber Na b W a a b b P a b b t t	ridth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement Vidth of staircases Upper floor Basement Protection of exits Fire check door Pressurization No. of continuous staircases to errace Width of corridor	03 nos. 03 nos. 1.50 mtrs. Required Required N/A 0 02 nos. 1.50 mtrs.	03 no 03 no 02 no 01 no 01 no Provi Provi N/A 02 no	s. of 1.7 mtrs & / of 1.8 mtrs s. of 1.8 mtrs ded ided os.	MR MR MR MR MR MR MR MR MR N/A MR	
	C Nu A B C C D E F	Wmbbbbbbbbbbbbbbbbbbbbbbbbbbbbbbbbbbbb	ridth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement ridth of staircases Upper floor Basement rotection of exits Fire check door Pressurization No. of continuous staircases to errace Width of corridor Door size	03 nos. 03 nos. 1.50 mtrs. Required Required N/A 0 02 nos.	03 no 03 no 02 no 01 no 01 no Provi Provi N/A 02 no 2.0 no	s. of 1.7 mtrs & / of 1.8 mtrs s. of 1.8 mtrs ded ided os.	MR MR MR MR MR MR MR MR MR N/A MR	
3	C Nu A B C C D E F C C	Wmb/Nab waa b b Paa b b t t voom	ridth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement Vidth of staircases Upper floor Basement Protection of exits Fire check door Pressurization No. of continuous staircases to errace Width of corridor Door size partmentation:	03 nos. 03 nos. 1.50 mtrs. Required Required N/A 0 02 nos. 1.50 mtrs.	03 no 03 no 02 no 01 no 01 no Provi Provi N/A 02 no 2.0 no	s. of 1.7 mtrs & / of 1.8 mtrs s. of 1.8 mtrs ded ided os.	MR MR MR MR MR MR MR MR MR N/A MR	
	C Nu A B C C D E F C C A	Wmbb N a b W a b F a b t t I omp	ridth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement ridth of staircases Upper floor Basement rotection of exits Fire check door Pressurization No. of continuous staircases to errace Width of corridor Door size partmentation: Fire check door	03 nos. 03 nos. 1.50 mtrs. 1.50 mtrs. Required Required N/A 0 02 nos. 1.50 mtrs. 1.0 mtrs.	03 no 03 no 02 no 01 no 01 no Provi Provi N/A 02 no 2.0 no	s. s. of 1.7 mtrs & of 1.8 mtrs s. of 1.8 mtrs ded ided os. ntrs. Provided	MR MR MR MR MR MR MR MR MR N/A MR MR MR	
	C Nu A B C C D E F C C A B	Wmb/Naabbwaabbwaabbwaabbwaabbwaabbwaabbwaa	ridth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement Vidth of staircases Upper floor Basement Protection of exits Fire check door Pressurization No. of continuous staircases to errace Width of corridor Door size partmentation: Fire check door Sealing of electrical shafts	03 nos. 03 nos. 1.50 mtrs. 1.50 mtrs. Required Required N/A 02 nos. 1.50 mtrs. 1.50 mtrs.	03 no 03 no 02 no 01 no 01 no Provi Provi N/A 02 no 2.0 no	s. s. of 1.7 mtrs & of 1.8 mtrs os. of 1.7 mtrs & of 1.8 mtrs ded ided os. ntrs. Provided Sealed	MR	
	C Nu A B C C A B C C	Wmbe N a b W a a b b N t t V I I omp	ridth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement ridth of staircases Upper floor Basement rotection of exits Fire check door Pressurization No. of continuous staircases to errace Width of corridor Door size partmentation: Fire check door Sealing of electrical shafts Fire rating of shaft door	03 nos. 03 nos. 1.50 mtrs. 1.50 mtrs. Required Required N/A 0 2 nos. 1.50 mtrs. 1.0 mtrs. Required Required	03 no 03 no 02 no 01 no 01 no Provi Provi N/A 02 no 2.0 no	s. s. of 1.7 mtrs & of 1.8 mtrs s. of 1.8 mtrs ded ided os. ntrs. Provided	MR	
	C Nu A B C C A B C D	Wmbe N a b W a a b b t t v t t t t t t t t t t t t t t t	ridth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement Vidth of staircases Upper floor Basement Protection of exits Fire check door Pressurization No. of continuous staircases to errace Width of corridor Door size partmentation: Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain	03 nos. 03 nos. 1.50 mtrs. 1.50 mtrs. Required Required N/A 0 02 nos. 1.50 mtrs. 1.0 mtrs. Required Required N/A N/A	03 no 03 no 02 no 01 no 01 no Provi Provi N/A 02 no 2.0 no	s. s. of 1.7 mtrs & of 1.8 mtrs s. of 1.8 mtrs of 1.8 mtrs ided ided os. ntrs. Provided Sealed N/A	MR	
3	C Nu A B C C D E F C C D E E C D E E C D E E C D E E C D E E C D D E E E C D D E E E C D D E E E E	Wmb/Naabbwaabbwaabbwaabbwaabbwaabbwaabbwaa	ridth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement ridth of staircases Upper floor Basement rotection of exits Fire check door Pressurization No. of continuous staircases to errace Width of corridor Door size partmentation: Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire dampers	03 nos. 03 nos. 1.50 mtrs. 1.50 mtrs. Required Required N/A 0 2 nos. 1.50 mtrs. 1.0 mtrs. Required Required	03 no 03 no 02 no 01 no 01 no Provi Provi N/A 02 no 2.0 no	s. s. of 1.7 mtrs & for 1.8 mtrs s. of 1.8 mtrs ded ded ded sos. Provided Sealed N/A N/A	MR MR MR MR MR MR MR MR N/A MR MR MR MR MR MR MR MR	
	C Nu A B C C D E F C C D E E C D E E C D E E C D E E C D E E C D D E E E C D D E E E C D D E E E E	Wmb/Naabbwaabbwaabbwaabbwaabbwaabbwaabbwaa	ridth of internal road er, Width, Type and Arrange umber of staircases Upper floor Basement Vidth of staircases Upper floor Basement Protection of exits Fire check door Pressurization No. of continuous staircases to errace Width of corridor Door size partmentation: Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain	03 nos. 03 nos. 1.50 mtrs. 1.50 mtrs. Required Required N/A 0 02 nos. 1.50 mtrs. 1.0 mtrs. Required Required N/A N/A	03 no 03 no 02 no 01 no 01 no Provi Provi N/A 02 no 2.0 no	s. s. of 1.7 mtrs & for 1.8 mtrs s. of 1.8 mtrs ded ded ded sos. Provided Sealed N/A N/A	MR MR MR MR MR MR MR MR N/A MR MR MR MR MR MR MR MR	

(W)

5.	Fire Extinguisher:							
	Λ	Total numbers	24 nos.	30 nos.	MR			
	В	Types	CO ₂ & ABC	CO ₂ & ABC	MR			
	C	ISI marking	ISI Marked	Provided	MR			
6	First-Aid-Hose Reel:							
	A	Total numbers of each floor	04 nos.	04 nos.	MR			
	B	Length of hose reel hose	30 mtrs	30 mtrs	MR			
	С	Nozzle diameter	05 mm	05 mm	MR			
7	Automatic Fire Detection and Alarming System:							
	٨	Type of detectors	N/A	Provided	MR			
	В	Location of main panel	N/A	Provided	MR			
	C	Location of repeater panel	N/A	Provided	MR			
	D	Alternate source of power	N/A	Provided	MR			
	E	Hooters	N/A	Provided	MR			
8	M	DEFA:	Required	Provided	MR			
9	Pu	blic Address System:	Required	Provided	MR			
10	Automatic Sprinkler System:							
	A	Basement	Required	Provided	MR			
	В	Upper floor	N/A	N/A	N/A			
	C	Sprinkler above false ceiling	Required	Provided	MR			
11	Internal Hydrants:							
**	A Size of riser/down-comer		100 mm	100 mm	MR			
	B	Number of hydrants per floor	04 nos.	04 nos.	MR			
	C	Hose box	04 nos.	04 nos.	MR			
12	Yard Hydrants:							
-	A Total number of hydrants		04 nos. 04 nos.		MR			
	B	Hose box	04 nos.	04 nos.	MR			
13	1000							
1	Pumping Arrangements: Ground level							
1	A	Discharge of main pump	2280 LPM	2280 LPM	MR			
	B	Head of main pump	60 mtrs	60 mtrs (MR			
	С	Number of main pumps	01 no.	01 no.	MR			
	D	Jockey pump out put	180 LPM	180 LPM	MR			
	E	Jockey pump head	60 mtrs.	60 mtrs.	MR			
	F	Standby pump out put	2280 LPM	2280 LPM	MR			
	G	Standby pump head	60 mtrs.	60 mtrs.	MR			
	H	Auto starting /manual	Required	Provided	MR			
	1.0	stopping						
	I	Pump house access	Required	Provided	MR			
2	Terrace Level							
	A	Discharge of pump	900 LPM	900 LPM	MR			
	В	Head of the pump	40 mtrs	40 mtrs.	MR			
	C	Power supply	Required	Provided	MR			
	D	Auto starting of pump	Required	Provided	MR			

Dashmesh Public School at Vasundhara Enclave, Delhi-110096.



0.42

4	Captive Water Storage for Fire Fighting:							
	٨	Underground tank capacity	2,00,000 ltrs.	Provided	1	MR		
	B	Draw-off connection	Required	Provided		MR		
	C	Fire service inlet	Required	Provided		MR		
	D	Access to tank	Required	Provided		MR		
	E	Overhead tank capacity	25,000 ltrs.	25,000 ltrs:	25,000 ltrs.			
15	Exi	t Signage:	Required	Provided		MR		
16	Provision of Lifts:							
	٨	Pressurization of lift shaft	Required	Provided	M	IR		
	В	Pressurization of lift lobby	Required	Provided	M	4R		
	С	Communication in lift car	Required	Provided	Provided N			
	D	Firemen's grounding switch	Required	Provided	Provided N			
	E	Lift signage	Required	Provided	M	IR		
17	Standby Power Supply:		Required	Provided		MR		
18	Refuge Area:							
	٨	Total area	N/A	N/A	N	/A		
	B	Location	N/A	N/A	N	/A		
19	Fire Control Room:							
	Λ	Detector system panel	Required	Provided	N	1R		
	B	Flow switch panel	Required	Provided	N	1R		
	C	PA system panel	Required	Provided	N	1R		
	D	Battery backup	Required	Provided	N	1R		
	E	Building floor plans	Required	Provided	N	1R		
20	1 2	pecial Fire Protection systems for rotection of special Risks, if any:	Required	red Provided		1R		

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards of fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer
Name Yashwant Singh Meena

Designation ADO (L.N)

DORD DFA Blease

ph c20/(197)

20101323

23 /9 (20)

Directa / 91)