



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-1 10001

No. F.6/DFS/MS/Business/2023/SZ/ 537

Dated: ./.D./..J../2023

FIRE SAFETY CERTIFICATE

Certified that the **Jindal Stainless Ltd.** located at Plot No 12, Bhikaji Cama Place, New Delhi comprised of Basement, Lower Ground Floor, Upper Ground Floor plus 02 Upper Floors owned/occupied by Jindal Stainless Ltd was issued FSC by this department vide letter No F.6/DFS/MS/2014/SZ/232 Dated 14-12-2014. The premise was re-inspected by officer concerned of this department on 02/11/2023 in the presence of Mr. Divya Kumar Sharma and found that the said premise have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and that building is fit for occupancy class "Business Occupancy" with effect from 10/11/2023 for period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued ____/0 / 11 /2023 at New Delhi by

ATUL GARG) DIRECTOR DELHI FIRE SERVICE

Copy to: -

- 1. Jindal Stainless Ltd. located at Plot No 12, Bhikaji Cama Place, New Delhi.
- 2. The Dy. Director (Bldg) Building Section, DDA, Vikas Sadan, INA New Delhi.

Conditions for the validity of Fire Safety Certificate:

All the means of escape/entry/exit shall be kept free from any obstruction.

All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to nonfunctional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting

system.

4. The basement shall be used as per the provisions of UBBL-2016 /NBC Part- IV.

 The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

 This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL- 2016), if

any.

 The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.





1	Name & Adda INSPECTION REPORT					
2	Address of the Building	Jindal Stainless Ltd, at Plot No 12, Bhikaji Cama Place, New Delhi				
3	Type of Occupancy	Business "Group-E"				
	Building Comprised of	Basement, Lower Ground Floor & Upper Ground				
4	Type of Case	Floor plus 02 upper floors.				
5	Details of D	Renewal				
6	Details of Previous NOC	F.6/DFS/MS/2014/SZ/232 Dated 14-12-2014				
7	Pire Safety Directives Letter No Date of Inspection	F6/DFS/MS/BP/94/770 Dated 17/05/1994				
8	Name of the I	02/11/2023				
9	Name of the Inspecting Officers Name & Designation of Officers	DO (South) & ADO (BCP) Mr. Divya Kumar Sharma				
	from the building side					
10	Year of construction	The state of the s				
11	Applicant letter No.	1996 Frank 127/10/2022				
S. No.	Minimum standards on Fire Prevention	NBC/BBL	Email dated 27/10/2023 NBC/BBL Provided at Site Remarks			
	and Fire Safety U/R 33	requirements	Provided at Site	MR/NMR		
1	Access to Building.	- Cquin Custom	7 1 1 1 1 1 1	MANUTAN		
	Road width	12 mtr	Provided	MR		
	Gate width	Required	Provided	MR		
	 Width of internal road 	*NA*	≤NAs	*NA*		
2	Number, width, type & arrangement of exits.		machineror at	1		
	a) Number of Staircase	75-17	The state of the s			
	Upper floors.	Required	02 Nos	MR		
	> Basement floor.	Required	02 Nos	MR		
	b) Width of Staircase					
	➤ Upper floors	1.20 mtr	1.30m & 1.55 mtr each	MR		
V.	➤ Basement floor	1.20 mtr	1.30m & 1.55 mtr each			
	c) Protection of exits					
M 21 M	Fire check door	Required	Provided	MR		
	> Pressurization	-NA-	-NA-	-NA-		
	d) No. of continuous staircase to terrace	01 Nos	Provided	MR		
	e) Width of corridor	1.20 mtr	Provided	MR		
	Land and the state of the state	01 mtr	Provided			
-		O1 mir	Provided	MR		
3	Compartmentation.	The letter have	Carterial Control of			
-	Fire check door.	Required	Provided	MR		
	Sealing of electrical shafts.	-NA-	-NA-	-NA-		
1.	Fire rating of shaft door.	-NA-	-NA-	-NA-		
	Water curtain	-NA-	-NA-	-NA-		
	• Fire dampers.	-NA-	-NA-	-NA-		
-	Smoke Management system. Basement	30 ACPH	P. L) (D		
	Upper floors	L. ASSOCIATION CONTRACTOR	Exhaust fan provided	MR		
+	25 200 T 200 (200 (200 (200 (20) (20) (20) (20)	12 ACPH	Exhaust fan provided	MR		
+	Fire Extinguishers. • Total numbers	50 Nos	CON-	100		
			50 Nos	MR		
	Types	ABC/W.CO2	CO2, W.CO2 & ABC	MR		
	ISI Marking	ISI marked	Provided	MR		
П	First Aid Hose Reels.					
	 Total numbers on each floor. 	02 Nos each floor	Provided	MR		
	Length of hose-reel hose.	30m	Provided	MR		
	Nozzle Diameter	5mm	Provided	MR		
1	Automatic fire detection & alarming system.	ATTENDED	1101100	IVII		





	Type of detectors			र्व गहोत्सर
	Location of Main Panel	Required	Provided	MR
	Location of Repeater Panel	Required	Provided	MR
	Alternate source of power	-NA-	-NA-	-NA-
	Hooter's location	Required	Provided	MR
8.	MOEFA	Each floor	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	-NA-	-NA-	-NA-
	Basement			
	Upper floors	Required	Provided	MR
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11.	Internal Hydrants.	-NA-	-NA-	-NA-
	Size of Riser/Down-comer	100	and the second second	2.1
	Number of Hydrant per floor	100 mm	Provided	MR
ne.	Hose box.	02 No	Provided	MR
12.	Yard Hydrants.	02 No	Provided	MR
	Total number of hydrants.	N/A	110	
	Hose box.	-NA-	-NA-	-NA-
13.	Pumping arrangements.	-NA-	-NA-	-NA-
	Ground Level		and a control of	The second second
	Discharge of main pump.	2000 7 7	Company and the same of the	1 7
	Head of main pump.	2280 LPM	Provided	MR
	Number of main pumps.	50 mtr	Provided	MR
	> Jockey Pump output.	01 No	Provided	MR
	> Jockey Pump head.	180 LPM	Provided	MR
	Standby Pump output.	50m	Provided	MR
	Standby Pump head.	-NA-	-NA-	
	Auto Starting/Manual Stopping	-NA-	-NA-	-NA-
	> Pump house access.	Required	Provided	MR
	Terrace Level	Required	Provided	MR
	Discharge of pump.			MIK
	Head of pump	900 LPM	Provided	MR
	Power supply.	40m	Provided	
	Auto starting of pump.	Required	Provided	MR
14.		Required	Provided	MR
	Captive water storage for fire fighting. Underground tank capacity.	and-		MR
	Draw-off connection.	50,000 Ltrs	Provided	
	Fire Service Inlet.	Required	Provided	MR
	Access to tank	Required	Provided	MR
	Overhead tank capacity.	Required	Provided	MR
15.	Exit Signage.	10,000 Ltrs	Provided	MR
16.	Provision of Lifts.	Required	Provided	MR
	Pressurization of lift shaft.	1 1	Danison	MR
	Pressurization of lift shaft.	Required	Provided	3
	Pressurization of lift lobby. Communication in lift car.	Required	Provided	MR
	Fireman's switch.	Required	Provided	MR
	Lift signage	Required	Provided	MR
7.	Standby Power Supply	Required	Provided	MR
18.	A CONTRACTOR OF THE CONTRACTOR	Required		MR
	Refuge Area		Provided	MR
	Total area			



	Location	-NA-	-NA-	-NA-
19.	Fire Control Room.			
	Detector system panel.	-NA-	-NA-	-NA-
	 Flow switch panel. PA system panel. Battery backup. Building floor plan. 	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
20.	Special Fire Protection System for the Protection of special Risk, if any.	-NA-	-NA-	-NA-

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and safety measures as required under the rules, the FSC issued vide letter no F.6/DFS/MS/2014/SZ/232 Dated 14-12-2014, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspection Officer Name: Sh. Manoj Kumar Sharma

Design: DO (South)

Signature of the Inspecting Officer

Name: Sh. Rajesh Kumar Design: ADO (BCP)

CFO (HO)

.1. lettre in pritip for