



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F.6/DFS/MS/Storage/SZ/2023/ 550

Dated: |5/11 /2023

FIRE SAFETY CERTIFICATE

Certified that M/s Air Cargo Logistic Centre 2B for Shristi Cargo Warehouse Pvt. Ltd, Opposite Gate No. 1, Near ATC Tower, IGI Airport, New Delhi-110037, comprised of ground plus one upper floor, owned/occupied by Delhi International Airport Limited was issued FSC by this department vide letter No. F.6/DFS/MS/Storage/2020/SZ/440 dated 02/11/2020. The premises was re-inspected by the officers concerned of this department on 06/11/2023 in the presence of Sh. Kailash Sharma and observed that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the said building/premises is fit for occupancy class "Group-H Storage Building" with effect from \(\frac{1}{2}\)/11 /2023 for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS Rules, 2010.

Issued on 15 11/2023 at New Delhi by

(A TUL GARG)
DIRECTOR
DELHIFIRE SERVICE

Copy to: -

 Authorized Signatory, M/s Air Cargo Logistic Centre 2B for Shristi Cargo Warehouse Pvt. Ltd, Opposite Gate No. 1, Near ATC Tower, IGI Airport, New Delhi-110037

 The Chief Executive Officer, DIAL, New Udaan Bhawan, Opposite T-3, IGI Airport, New Delhi-110037

Conditions for the validity of Fire Safety Certificate:

All the means of escape/entry/exit shall be kept free from any obstruction.

- All the fire safety arrangement provided therein shall be maintained in good working conditions at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- All the staff members must know the correct method of operation of fire fighting system.
- The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules, 2010. The from is available on www.dfs.delhigovt.nic.in
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".

N-10

		ION REPORT	gistic Centre 2B, Shris	ti Cargo	
1.	Name & address of the building	Warehouse Pvt. Li	Airport, New Delhi-11		
2.	Type of Occupancy	Storage Building (Group-H)		
3.	Building Comprised of	Ground + One upper floor (Small basement for pump house)			
4.	Type of Case	Descend		102 11 2020	
5.	Details of previous NOC	E C/DES/MS/Storage/2020/SZ/440 dated 02.11.2020			
6.	Fire Safety directives/approval letter	F.6/DFS/MS/2020/BP/304 dated 21/08/2020 (C/19)			
7.	Date of inspection	06/11/2023			
8.	Name of Inspecting Officer	Manoj Kumar Sharma, DO (SD) Santosh Kumar, ADO (SJ)			
9.	Name and designation of Officer from building side	Sh. Kailash Sharma			
10.	Year of Construction	2020		22	
11.	Applicant letter No.	Outdoor Diary No	. 8262 dated 03/11/20	2.5	
S.	Minimum standards on fire	Existing Fire	Provided at site	Kemarks	
No.	prevention and fire safety U/R 33	Protection System		MR/NMR	
1.	Access of building			l » m	
	Road width	6m	15m	MR	
	Gate width	6m	10m	MR	
		6m	6m	MR	
	Width of internal road		1999		
2.	Number, width, Type & Arrangeme	ills of exits			
	a. Number of staircases	4 Nos	6 Nos	MR	
	Upper floors	NA NA	NA	NA	
	Basements	INA	.,		
	b. Width of staircases	1.12m	1.5m (each)	MR	
	Upper floors	NA NA	NA NA	NA	
	Basements	INA	Tur	1.000	
	c. Protection of exits	Required	Provided	MR	
	Fire check door		NA	NA	
	Pressurization	NA	V 4	0.077/0.77	
	d. No of continuous staircase to terra		NA	NA MR	
	e. Width of Corridor	1.12m	1.5m		
	f. Door Size	0.81m	1.5m	MR	
3.	Compartmentation	3 31		1	
	Fire check door	Required	Provided	MR	
	 Sealing of electrical shafts 	Required	Provided	MR	
	Fire Rating of shaft door	Required	Provided	MR	
	Water Curtain	NA	NA	NA	
	Fire Dampers	NA	NA	NA	
_	To the second se	- 000000		0.0007245	
4.	Smoke managements System	NA	NA	NA	
	Basements Union floors	12 ACPH	Natural ventilation	MR	
_	Upper floors Fig. Fastingwickers	12 ACFII	Thursday ventriation	MIK	
5.	Fire Extinguishers	60 Nos	60 Nos	MR	
	Total numbers	ABC/CO ₂	ABC type	MR	
	Types ISI marking	Required	Provided	MR	
	ISI marking	required	Trovided	IVIK	
6.	First - Aid Hose Reels	0 11	LION	11/0	
6.		8 Nos 30m	10 Nos 30m	MR MR	



N-11

	Type of detector	Required	Beam & Multi Criteria	M
	Location of Main Panel	Ground floor	Provided	M
-		NA	NA	N/
	Location of Repeater Panel	Required	Provided	MI
	Alternate source of power	All Areas	Provided	MF
	Hooters' Location	- 1	Provided	MF
	MOEFA	Required	Provided	MR
)	Public Address System	Required	Flovided	
0	Automatic Sprinkler System	314	NA	NA
	Basements	NA Required	Provided	MR
	Ground & Upper Floors Ground & Upper Floors Ground & Upper Floors	NA	NA	NA
	Sprinkler above false ceiling	1.0.1		
11	Internal Hydrants • Size of riser/down- comer	150mm	Provided	MR
		8 Nos	Provided	MR
	Number of hydrants per floor	8 Nos	Provided	MR
	Hose Box	01100		
12	Yard Hydrants	12 Nos	Provided	MR
	Total number of hydrants	12 Nos	Provided	MR
	Hose Box	12 1103		
13	Pumping Arrangements		J. 100	
	Ground Level	2850 LPM (Hyd	2850 LPM (Hyd)	MR
	Discharge of main pump	4500 LPM (Spk)		
	50 500 St. 12 14 14 14 14 14 14 14 14 14 14 14 14 14	100m	100m	MR
	> Head of main pump	02 Nos	02 Nos	MR
	> Number of main pumps	180 & 450 LPM	Provided	MR
	> Jockey pump out put	100m	Provided	MR
	 Jockey pump head Standby Pump out put 	4500 LPM	Provided	MR
	> Standby Pump Head	100m	Provided	MR
	> Auto Staring/Manual stopping	Required	Provided	MR
	> Pump House Access	Required	Provided	MR
	Terrace level		But The Yestern City	MR
	Discharge of pump	900 LPM	700 DI 111	MR
343	> Head of the pump	35m	33111	MR
	> Power supply	Required	11011000	MR
	> Auto starting of pump	Required	Provided	WIK
14	4 Captive water Storage for fire fighting	2.50.000 [4	2 x 1,25,000 Ltrs	MR
	Underground tank capacity	2,50,000 Ltrs Required	2 11 112010	MR
	> Draw of connection	Required	Tioridos	MR
	 Fire service inlet Access to tank 	Required		MR
	Overhead Tank capacity	20,000 Ltrs	20,000 Ltrs	MR
-		Required	Provided	MR
1:	Provision of Lifts		_idt.	
10	Pressurization of Lift Shaft	NA	1,1.1	NA .
-	Pressurization of lift lobby	NA	Tut	NA NA
	Communication in lift Car	NA	1.77	NA NA
	> Fireman's Grounding Switch	NA	7.75	NA NA
	➤ Lift Signage	NA Required		MR.
17		Required		
18	Refuge Area > Total area	NA		ΙA
	> Location	NA	NA N	IA



19.	Fire control room				
	Detector system panel	NA	NA	NA	
	➤ Flow Switch Panel	NA	NA	NA	
	> PA System Panel	NA	NA	NA	
	> Battery backup	NA	NA	NA	
	➤ Building Floor Plans	NA	NA	NA	
20.	Special Fire Protection Systems for Protection of special Risks, if any;	NA	NA	NA	

The fire protection system provided in the building were checked, tested at random and found functional at the time of inspection. The shortcomings issued by this department vide letter No. F6/DFS/MS/Storage/SZ/2023/4074 dated 25/10/2023 found complied.

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the fire safety certificate issued vide letter No. F6/DFS/MS/Storage/2020/SZ/440 dated 02/11/2020, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Manoj Kumar Sharma

Designation: DO (SD)

Signature of the Inspecting Officer

Name: Santosh Kumar Designation: ADO (S.J.)

this)

Tutter is protent for your singulare pl.

Shuman

1.11.25