FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/CGHS/ SZ/2023/ 554

Dated: 20/11/2023

FIRE SAFETY CERTIFICATE

Certified that the building of Gyan Shakti CGHS Ltd. Located at Plot No-07, Sector-06, Dwarka, New Delhi - 110075having 04 blocks comprised of stilt/ground + seven/eight upper floors was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/CGHS/2004/3107, dated 24/12/2004. The premise was re inspected by the officer concerned of this department on 10/11/2023 in the presence of. Sh. Sunil Kumar (Hon. Secretary) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Residential Building" Group A-4 with effect from 20 11/2023 for a period of five years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 20 11/2023 at New Delhi by.

Atul Garg

Delhi Fire Service,

Copy to:

1. The President, Gyan Shakti CGHS Ltd. Plot No-07, Sector-06, Dwarka, New Delhi - 110075.

2. The Joint Director (Building) DDA, Vikas Sadan, INA, Delhi-110023.

Following fire safety directives must be adhered to:-

- All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

- Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. Basement shall be used as per building bye laws.

 The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. www.dfs.delhigovt.nic.in.

 The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. Name & address of the building: Gyan Shakti CGHS Ltd. Located at Plot No-07, Sector-06, Dwarka, New Delhi - 110075.

2. Type of Occupancy : Residential Building "A" (Apartment)

3. Type of Case: Renewal 04 blocks (Stilt/Ground +Seven/Eight UF)

4. Details of previous NOC : F6/DFS/MS/CGHS/2004/3107, dated 24/12/2004

5. Fire Safety directives Letter No.: F6//DFS/MS/94/CGHS/1186, dated 09/08/1994

6. Date of inspection : 10/11/2023

7. Name of the Inspecting Officer: ADO (DWK)


8. Name and designation of Officer

from the building side : Sh. Sunil Kumar (Hon. Secretary)

9. Year of Construction : 1996 to 2004

10. Applicant's letter No. : GSCGHS/fire safety/2023/01, dated-30 /10/2023

S No	The same same of the same same same same same same same sam		As Per N/7, N/8 & N/9			Provided at site		Remarks MR/NMR		
1.	D. J. Call									
	Road width		09 mtrs Provide				ed MR			
	Gate width Width of internal road	4.5 mtrs		Provided			MR		_	
		6 mtrs		4.6m to 6 m		m	MR(Being old ca		old coss)	
2.	Number, width, Type & Arrangements of exits							old case)		
	Number of staircases									
	Upper floors		nos. each block	_	- ·					
	Basements Width of staircases				_	ovided			MR	
		NA NA			NA	A N		NA	VA.	
	Upper floors	1	25	5/20 /5			_		4-2	
	Basements		25 mtr & 0.90 r	-	1.16 m		MR	(Being	g old case)	
	Protection of exits	NA NA NA								
	Fire check door								1974	
	Pressurization No of continuous staircase to terrace Width Of Corridor	N/A			1	N/A N/A		N/A	N/A N/A	
Ш		-	N/A					N/A		
		Required			F	Provided		6 11	MR	
		N/A			N	N/A I		N/A		
	Door Size	N/			N/A	VA.	N/A			
3.	Compartmentation				TVII		14/2	1		
	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers	N/A			N	N/A		N/A		
Ш		_	Required			Provided			MR	
		_	N/A						N/A	
Ш		_	N/A			N/A			N/A	
		-	N/A			N/A		N/A		
4.	Smoke managements System				- 1			14/7		
	Basements	NA.			N	NA		NA		
	Upper floors	12				tural Ventilation			MR	
5.	Fire Extinguishers				1		ilutio:	1 14	II.	
	Total numbers Types	2 n	2 nos. each floor CO ₂ & ABC		Provided				MR	
					CO ₂ , ABC, Water Co ₂			202	MR	
	IS marking		ISI marked		Provided Provided			002	MR	
					riovided addition sale.				IVIIC	



NIB

6.	First – Aid Hose Reels Total numbers on each floor		01 No.		Provided	N	MR	
	Length of hose reel hose		30 m		30 m	N	ИR	
	Nozzle diameter		5 mm	V	5 mm	N	ΛR	
7.		larmino						
/.	Type of detectors		N/A	N.	/A		N/A	
	Location of Main Panel	N/A				N/A		
	Location of Repeater Panel	N/A N/A		N/A				
	Alternate source of power	N/A N/A			N/A			
	Hooters' Location	N/A N/A			N/A			
	CANTACTED AS COMMISSION				5,000		_ CONTROL	
8.	MOEFA		Required				MR	
9.	Public Address System		Required	l Pr	ovided		MR	
10							1	
	Basements NA			NA NA		NA NA		
	Upper Floor	N/A			N/A		N/A	
	Sprinkler above false ceiling	N/A	N/A		N/A		N/A	
11	. Internal Hydrants				101 Sept 101			
	Size of riser/down- comer		100 mm		Provided		MR	
	Number of hydrants per floor		1 No.		Provided		MR	
	Hose Box		01 No.	Provi	ded		MR	
12	Yard Hydrants	4.1	THE PARTY					
П	Total number of hydrants		Required	Pro	ovided		MR	
	Hose Box		Required	_	vided		MR	
13.			1	12.0				
	Ground Level		Γ.					
	Discharge of main pump		NA	NA NA		IN	IA.	
	Head of main pump		NA		NA NA		NA NA	
	Number of main pumps Jockey pump out put		NA NA		NA NA		NA	
	Jockey pump head						NA	
	Standby Pump out put Standby Pump Head		NA NA NA		NA NA NA		NA NA NA	
	Auto Staring/Manual stopping		NA		NA		NA	
	Pump House Access Terrace level		NA		NA	N	A	
	FIG. 1424(1) 1 (1) (1) (1) (1) (1) (1) (1) (1) (1			W.				
	Discharge of pump	9	450 lpm	Provi	ded	N	ſR ·	
	Head of the pump	- 4	-		Provided		MR	
	Power supply		Required	Provided		MR		
	Auto starting of pump		Required			MR		
4.	Captive water Storage for fire fig	phting	- toquilou	110110	-vu	IV	IIX	
••	Under ground tank capacity		000 ltrs	Provid	lad	3.00		
	Draw of connection	2,00,	óoo ma	TIOVIC	icu	MR		
	Fire service inlet	_						
	Access to tank Overhead Tank capacity Requ Requ		uired Provided		MR			
P					vided			
			equired Provided			ed MR		
	and the second second	10,00	00 ltr each block Provided			MR		
,	Exit Signage						MR	
6.								
	Pressurization of Lift Shaft	N/A N/A		N/A		NUA		
	Pressurization of lift lobby			The second secon		N/A		
	Communication in lift Car				N/A		N/A	
	Fireman's Grounding Switch Lift Signage		Required		Provided		MR ·	
			Required		Provided		MR	
-	Standby power supply		Required	Prov	/ided	MR		
.						110000000000000000000000000000000000000		

18.	Refuge Area			100
10	Total area	N/A	N/A	1.00
	Location	N/A	N/A	N/A
19.	Fire control room		1.072	N/A
	Detector system panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	PA System Panel	Required	Provided	MR
	Battery backup Building Floor Plans	Required	Provided	MR
		N/A	N/A	N/A
0.	Special Fire Protection Systems for Protection of special Risks, if any;	Required	CO2 fire extingu provided near ele	isher MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter No. F6/DFS/MS/CGHS/2004/3107, dated 24/12/2004 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer Name: Way Vie Sign

Designation: ADD DWA

CFO (52) Mugh 16 11 /2022 Director / 11/12 7

HOW when

sin ff lotter . 18

but up for Sign ble.

May 11/23