GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELIII HEADQUARTERS: DELIII FIRE SERVICE: NEW DELIII- 110001



F6/DFS/MS/CGHS/WZ/2023/ 555

Dated: 20 /11 /2023

FIRE SAFETY CERTIFICATE

Certified that the Jhulelal Sindhu Nagar Co-Operative Group Housing Society Ltd.

Located at Road No. 44, Pitampura, Delhi-110034, comprised of 07 blocks - Ground + 07 Upper Floors only, was issued Fire Safety Certificate by this department Vide Letter No. F6/MS/DFS/2005/HR/2506/Con./HV/775 dated 09/12/2005. The said premise was re-inspected by the officer concerned of this department on 17/10/2023 & 22/10/2023 in the presence of Sh. GD Sharma (President), RS Chaggar (Secretary), RK Sharma (Cashier) & RV Thakur (Manager) and found that the premises/building have deemed complied with the fire prevention and fire safety requirements in accordance with 12 bare minimum fire safety measures and that the premises/building is fit for occupancy class "Residential Building (Group A) with effect from 20/11/2023 for a period of Five years in accordance with Rule 36 unless renewed Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service, Rules, 2010, printed below.

Issued on 20/11/2023 at New Delhi by.

(Atul Garg) Director

Tel. No. 011-2341400

Copy to: -

 The Authorised Signatory, Jhulelal Sindhu Nagar Co-Op. Group Housing Society Ltd., Road No. 44, Pitampura, Delhi-110034.

Following fire safety directives must be adhered to:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building : Jhulelal Sindhu Nagar CGHS, Located at Road No. 44,

Pitampura, Delhi-110034

2. Type of Occupancy : Residential

3. Type of Case : Renewal

Details of previous NOC : F.6/MS/DFS/2005/HR/2506/Con./HV/775 dated 09/12/2005

5. Fire \$afety directives letter No : F.6/MS/DFS/88/CGHS/183 dated 09/02/1988

6. Date of inspection : 17/10/2023 & 22/10/2023

7. Name of the Inspecting Officers : Aman Kumar Lathar, ADO (JWP)

8. Name and designation of officers

Upper floors

from the building side : GD Sharma (President), RS Chaggar (Secretary), RK

Sharma (Cashier) & RV Thakur (Manager)

9. Year of Construction : 1990

10. Applicant's letter No. : outdoor diary no. 4137 dated 25/07/2023

S. No	N	complex is comprised of 07 Block linimum Standards on fire vention and fire safety U/R 33	OFS Rules	5(6)	Provided at	site		narks /NMR
1	Acces	to building					0.000	
	•	Road width	09 m		Provided		MR	
		Gate width	4.5 m		Provided		MR	
	•	Width of internal road	06 m		Provided		MR	
2	Numi	er, Width, Type & Arrangement	of Exits			rite II.		
_	a Nu	nber of staircases						
	•	II Floore	08 nos.	ВЕ	nos. Provided (02 nos. in Block & 02 nos. in Cocks & 04 nos. E,F,G Blocks			MR
			N/A	N/A	A N		N/A	
	h Wi							
	0. 11.		1.25 m	Old	l Case MR		being old case	
	922	0.0 • A1000 0.00 A1000	N/A	N/A	\	N/A		
		Basements Protection of exits Fire check door Pressurization No, of continuous staircases to terrace			A N/A		·	
	c. Pro		N/A	N/A				
	•		N/A	N/A				
	a No			Pro	ovided MR			
		dth of Corridor	1.25 m	Pro			being old cas	
		or Size	Open	Op	en MI		being	old cas
3	Com	partmentation.			- False		N/	Δ
		Fire check door	N/A		N/A		M	
		Sealing of electrical shafts	Required		Provided		M	
	•	Fire Rating of shaft door	Required		Provided		N/	200
	•	Water Curtain	N/A		N/A		N/	485
	•	Fire Dampers	N/A		N/A		14/	
4	Smo	moke Management System.						/4
		Basements	NA		N/A	THIRT	N	/A

NA

NA

Natural Ventilation

N I	_ 1	
10	~1	ı

5 1	Fire Extinguishers					
	Total numbers	130 Nos.	Provided	MR		
	Types		Provided	MR		
	Olovetic Society	ABC, CO ₂ type	Provided	MR	11-	
	IS marking	ISI marked	Tioners	1		
6	First-Aid Hose Reels.	Terror a to a	T	-	MR	
	Total numbers on each floor	01 each block	Provided Provided		MR	
	Length of hose reel hose	30 m	Provided	-	MR	
	Nozzle diameter	05 mm Provided				
7	Automatic fire detection and alarmin		1	-	N/A	
	 Type of detectors 	NA	N/A	_	N/A	
	Location of Main Panel	NA	N/A	-11	N/A	
- 1	Location of Repeater Panel	NA	N/A		N/A	
	Alternate source of power	NA	N/A	_	N/A	
	Hooters' Location	NA NA	N/A Provided		NA	
8	MOEFA	NA Provinced	Provided		MR	
9	Public Address System.	Required	Provided	-	1045	
10	Automatic Sprinkler System	Ul parameter	T	N/	/A	
	Basement	N/A	N/A	N/		
	 Upper floors 	N/A	N/A	N/		
	 Sprinkler above false ceiling 	N/A	N/A	1.4	-	
11	Decynded				MR	
	 Size of riser/down-comer 	100 mm	200	MR		
	 Number of hydrants per floor 	01 each block	Provided Provided	MR		
	Hose Box	Required	Provided	MIK		
12	2 Yard Hydrants. Provided N/A					
	 Total number of hydrants 	N/A	Provided Provided	N/A		
	Hose Box	N/A	Provided			
13	3 Pumping Arrangements					
	 Ground Level 		N/A		N/	
- 1	Discharge of main Pump	N/A	N/A		N/	
	> Head of Main pump	N/A	N/A		N/	
	Number of main pumps	N/A N/A	N/A	4	N/	
	> Jockey Pump out put	N/A	N/A		N/	
<	Jockey pump headStandby Pump out put	N/A	N/A		N/	
	Standby Pump Head	N/A	N/A	7	N/	
	> Standby Pump Head > Auto Starting/ Manual stopping	N/A	N/A		N/	
		N/A	N/A		N/	
	Pump House Access					
40	Terrace level		Provided		М	
	> Discharge of pump	450 LPM each	Tioriaca	120	ivi	
		block	Provided		M	
	Head of the pump	40 m	Provided		М	
	> Power Supply	Required			1	
	> Power Supply	Required	Provided		M	
	> Auto Starting of pump Required					
	Captive Water Storage for fire fighting 2 00,000 ltrs. Provided (30,000 ltrs.				IM	
14	Captive Capacity	2,00,000 ltrs.	each block)		1 "	

100	- A	10-14						
		ains	Required	Provided	MR			
\	P	Draw-off connection	Required	Provided	MR			
\	17	Fire service inlet	Required	Provided	MR			
7	7	Access to tank Overhead Tank capacity	10,000 ltrs. each block	Provided (12,000 ltrs. in each block)	MR			
1	, S	an 900.	Required	Provided	MR			
15	Exit Signage. Required							
16_	Provision of Lifts. Pressurization of Lift Shaft		N/A	N/A	N/A			
10	•	Pressurization of Lift lobby	N/A	N/A	N/A			
	•	Communication In lift Car	N/A	N/A	N/A			
	•	Fireman's Grounding Switch	Required	Provided	MR			
	•		Required	Provided	MR			
	•	Lift Signage	Required	Provided	MR			
17	Standby power supply							
18	Refuge Area.		N/A	N/A	N/A			
	>	Total Area	N/A	N/A	N/A			
	>	Location	N/A	INCL				
19	Fire Control Room							
		Detector System Panel	N/A	N/A				
		Flow Switch Panel	N/A	N/A	N/A			
		PA System Panel	N/A	N/A	N/A			
		Batter backup	N/A	N/A	N/A			
	289	Building Floor Plans	N/A	N/A	N/A			
20		al Fire Protection Systems for	N/A	N/A	N/A			

Protection of special Risks, if any: The fire protection systems provided in the building were checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety requirements under the rules, renewal of Fire Safety Certificate issued vide letter no. F.6/MS/DF\$/2005/HR/2506/Con./HV/775 dated 09/12/2005 is recommended under rule 37 of the Delhi Fire Service Rules, 2010 under the DFS Act 2007.

Accordingly DFA letter is prepared & put up for approval please.

Aman Kumar Lathar ADO (JWP)

u is added for migrature