

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No. F6/DFS/MS/School/WZ/2023/ 848

Dated: 28/11/2023

FIRE SAFETY CERTIFICATE

Certified that the Jhabban Lal D.A.V. Sr. Sec. Public SchoolLocated at J-Block, Paschim Vihar, New Delhi-110063, comprised of Basement + Ground + 02 Upper Floors (BL-2) & Ground + 02 Upper Floors (BL-1) owned/occupied by Jhabban Lal D.A.V. Sr. Sec. Public was issued Fire Safety Certificate by this department vide letter No. School F6/DFS/MS/School/2019/1338 Dated 26.06.2019. The said premise was re-inspected by the officer concerned of this department on 04.11.2023 in the presence of Sh. Gurbachan Singh (Accountant) and found that the premises / building have deemedcomplied with the fire prevention and fire safety requirements in accordance D.O.E., GNCT of Delhi, Circular no.3298-3398 dated 01-03-2011and that the premises/building is fit for occupancy class "Educational Building" Group B with effect from 28 11 2023 for a period of three years, subject to compliance of the conditions, printed below.

Issued on 28/11/2023 at New Delhi by.

Copy to: -

The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi – 110054.

2. The Principal, JhabbanLal D.A.V. Sr. Sec. Public School Located at J-Block, PaschimVihar,

Following fire safety directives must be adhered to:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fightingequipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its

INSPECTION REPORT

 Name and address of the building: Jhabban Lal D.A.V. Sr. Sec. Public School Located at J-Block, Paschim Vihar, New Delhi-63

2. Type of Occupancy : Educational, B+G+02 UFs (BL-2) & G+02 UFs (BL-1)

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/School/2019/1338 Dated 26.06.2019

5. Fire Safety directives Letter No.: D.O.E. Cr. No. 3298-3398 dated 01.03.2011

6. Date of inspection : 04.11.2023

7. Name of the Inspecting Officer : Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side : Sh. Gurbachan Singh (Accountant)

9. Year of Construction : G+2 - 1995 & B+G+2 - 2015

10. Applicant's letter No. : email dated 17.10.2023

S No	Minimum standards on fire prevention and fire safety U/R 33	NBC Requirements/as per FSC dated 26.06.2019	Provided at site	Remarks MR/NMR		
1.	Access of building					
	Road width Gate width	06 m	Provided	MR MR		
		4.5 m	Provided			
	 Width of internal road 	NA	NA	NA		
2.	Number, width, Type & Arrangements of exits					
T	a. Number of staircases					
	Upper floors	02 (BL-1) 01 (BL-2)	Provided	MR		
-	Basements	01	Provided	MR		
1	b. Width of staircases					
1	 Upper floors 	1.5 m each	Provided	MR		
	 Basements 	1.5 m	Provided	MR		
1	c. Protection of exits					
	 Fire check door 	NA	NA	NA		
	 Pressurization 	NA	NA	NA		
	d. No of continuous staircase to terrace	01	Provided	MR		
	e. Width Of Corridor	1.5 m	Provided	MR		
1	f. Door Size	1.0 m	Provided	MR		
3.	Compartmentation			IVIK		
	Fire check door	NA	NA	NA		
	Sealing of electrical shafts	NA	NA	NA		
	Fire Rating of shaft door Water Curtain	NA	NA	NA		
		NA	NA	NA NA		
4	Fire Dampers	NA	NA	NA		
+	Smoke managements System			INA		
	Basements	NA	NA	NIA		
5	• Upper floors	NA	NA	NA		
+	Fire Extinguishers			NA		
	Total numbers	24 nos.	Provided	MD		
	• Types	ABC & CO ₂	Provided	MR		
	IS marking	ISI marked	Provided	MR MR		

	First - Aid Hose Reels	02 in each b	alock	Provided	M	R
	Total numbers on each floor	30 m	olock_	Provided	M	R
	 Length of hose reel hose 	5 mm		Provided	M	R
	Nozzle diameter				1	
7.	Automatic fire detection and alarmi	ng system NA		NA	N	Α
	 Type of detectors 	1974		NA		Α
	 Location of Main Panel 	NA	-	NA		A
	 Location of Repeater Panel 	NA		NA		A
	 Alternate source of power 	NA		NA		IA
	 Hooters' Location 	NA			9.00	661000
8.	MOEFA	NA		NA		IA
9.	Public Address System	Require	:d	Provided	I N	1R
10.			N.		1	
10.	Basements	Required (E	3L-2)	Provided	_	1R
	Upper Floor	NA		NA		IA
	Opper Floor	, NA		NA	N	IA
_	Sprinkler above false ceiling	5				
11.	Internal Hydrants:	100 mm	n	150 mm	N	4R
	Size of riser/down-comer	Require		Provided		ИR
	 Number of hydrants per 	Require				C.
	floor	Required		Provided	N	ИR
	Hose Box	Require	·u	Trottaca	1	ON R. P.
2.		240		NIA	NIA	
9	Total number of hydrants	NA		NA	NA	
	Hose Box	NA		NA	NA	
3.						
	Ground Level					
	Discharge of main pump	NA		NA	N	Α
	> Head of main pump	NA		NA	N	IA
	> Number of main pumps	NA		NA		IA
	> Jockey pump out put	NA		NA		IA
		NA		NA		IA
	> Jockey pump head	NA	_	NA NA	_	IA
	> Standby Pump out put					
	> Standby Pump Head	NA		NA		IA
	➤ Auto Staring/Manual	NA		NA	1	IA
	stopping					
	Pump House Access	NA		NA	N	NA
	Terrace level					
	Discharge of pump	900 lpm	Pro	vided (Common		MR
	1 PPO - 2004 A - 4	·F		p for both block)	1	
	Head of the pump	45 m	Pulli			MR
				Promided		TV/LK
	> Power supply			Provided		
	> Power supply > Auto starting of nump	Required		Provided		MR
	> Auto starting of pump	Required Required				MR
١.	 Auto starting of pump Captive water Storage for fire fighti 	Required Required ng:		Provided		MR
	> Auto starting of pump	Required Required ng:		Provided		MR
	 Auto starting of pump Captive water Storage for fire fighti 	Required Required ing: NA		Provided Provided NA	-	MR MR
· .	 Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection 	Required Required Ing:		Provided Provided NA NA	1	MR MR NA
	 Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection Fire service inlet 	Required Required Ing: NA NA NA		Provided Provided NA NA NA	1	MR MR NA NA
·.	 Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection Fire service inlet Access to tank 	Required Required Ing: NA NA NA NA		Provided Provided NA NA NA NA NA	1	MR MR NA NA NA
I .	 Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection Fire service inlet 	Required Required Ing: NA NA NA	. Pı	Provided Provided NA NA NA NA NA Ovided (Commo	1	MR MR NA NA NA
	 Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity 	Required Required Ing: NA NA NA NA 15,000 ltrs		Provided Provided NA NA NA NA NA rovided (Commo	on	MR MR NA NA NA NA MR
	 Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection Fire service inlet Access to tank 	Required Required Ing: NA NA NA NA		Provided Provided NA NA NA NA NA Ovided (Commo	on	MR MR NA NA NA
	 Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage	Required Required Ing: NA NA NA NA 15,000 ltrs		Provided Provided NA NA NA NA NA rovided (Commo	on	MR MR NA NA NA MR
	 Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity 	Required Required Ing: NA NA NA NA 15,000 ltrs		Provided Provided NA NA NA NA NA rovided (Commo	on	MR MR NA NA NA MR
	 Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts 	Required Required Ing: NA NA NA NA 15,000 ltrs Require		Provided Provided NA NA NA NA rovided (Commo for both block) Provided	on	MR MR NA NA NA MR
	 ➤ Auto starting of pump Captive water Storage for fire fighti • Under ground tank capacity ➤ Draw off connection ➤ Fire service inlet ➤ Access to tank • Overhead Tank capacity Exit Signage Provision of Lifts ➤ Pressurization of Lift Shaft 	Required Required Ing: NA NA NA NA 15,000 ltrs Require		Provided Provided NA NA NA NA Ovided (Common for both block) Provided NA	on	MR MA NA NA NA MR MR
	➤ Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby	Required Required Ing: NA NA NA NA 15,000 ltrs Require		Provided Provided NA NA NA NA rovided (Commo for both block) Provided NA NA NA NA NA NA	on	MR MA NA NA MR MR
	➤ Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car	Required Required Ing: NA NA NA 15,000 ltrs Require		Provided Provided NA NA NA NA Ovided (Common for both block) Provided NA	on	MR MR NA NA NA MR MR
	➤ Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby	Required Required Ing: NA NA NA 15,000 ltrs Require		Provided Provided NA NA NA NA rovided (Commo for both block) Provided NA NA NA NA NA NA NA NA NA	on	MR NA NA NA MR MR
	➤ Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Swite	Required Required Ing: NA NA NA 15,000 ltrs Require NA		Provided Provided NA NA NA NA Tovided (Common for both block) Provided NA	on	MR MA NA NA MR MR MR
	➤ Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Swite	Required Required Ing: NA NA NA 15,000 ltrs Require		Provided Provided NA NA NA NA rovided (Commo for both block) Provided NA NA NA NA NA NA NA NA NA	on	MR MA NA NA MR MR MR
	➤ Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Swite Lift Signage	Required Required Ing: NA NA NA 15,000 ltrs Require NA	ed	Provided Provided NA NA NA NA rovided (Commo for both block) Provided NA	on	MR MA NA NA MR MR MR NA NA NA
	➤ Auto starting of pump Captive water Storage for fire fighti Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Swite	Required Required Ing: NA NA NA NA 15,000 ltrs Require NA	ed	Provided Provided NA NA NA NA Tovided (Common for both block) Provided NA	on	MR MA NA NA MR MR MR NA NA NA NA

3.	Refuge Area	NA	NA	NA.	
	Total areaLocation	NA NA	NA NA	NA	
9.	Fire control room				
	> Detector system panel > Flow Switch Panel > PA System Panel > Battery backup	NA	NA		
11		NA	NA	NA NA	
11		NA	NA	NA	
		NA	NA	NA	
		NA	NA	NΛ	
20.	Systems for Protection of special Risks, if any;	Required 02 ABC type fire extinguishers near elect, panel	Provided	MR	

Fire protection systems provided in the building were checked and found functional at the time of inspection. Shortcomings issued vide letter no. F6/DFS/MS/2022/514 dated 29.08.2022 are rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety requirements as per D.O.E. Circular no. 3298-3398 dated 01.03.2011, renewal of Fire Safety Certificate issued vide letter no. F6/DFS/MS/School/2019/1338 Dated 26.06.2019 is recommended.

Accordingly DFA is put up for approval please.

Aman Kumar Lathar ADO (JWP)

Assyswin

Assyswin

F.F. Julia is met-up for your signature p.

19114