

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No. F6/DFS/MS/WZ/2023/CNG/ 587

Dated: 07 12 (20 L3

FIRE SAFETY CERTIFICATE

Certified that the CNG Dispensing Station Located at PVC Market Tikri Kalan, New Delhi-110041, comprised of single story building, owned / occupied by Indraprastha Gas Limited, was issued Fire Safety Certificate by this department Vide Letter No. F6/DFS/MS/2021/CNG/25 Dated 14/01/2021. The said premise was re-inspected by the officer concerned of this department on 23/11/2023 in the presence of Sh. Shubham Jat, Dy. Manager, F&S, IGL and found that the premises/building have deemed complied with the fire prevention and fire safety requirements in accordance with the Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises/building is fit for occupancy class "Hazardous Building" Group - J with effect from 0 1 12 2 3 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on D.7. 12 2073. at New Delhi by.

Director

Tel. No. 011-23414000

Copy to: -

1. Sh. Ajay Khatri, GM (Fire & Safety), IGL Bhawan, Plot no. 4, Community Centre, Sector- 9, R.K. Puram, New Delhi-110022.

Conditions for the validity of Fire Safety Certificate:-

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of authorized construction or alteration (Clause of 1.4.3 of UBBL-2016), if any.
- The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

1	Address of the Puilt					
2	T	of the Building	CNG Dispensing Station at PVC Market, Tikri Kalan, New			
02.00	Ty	pe of Occupancy	Deini-110041			
3	Ty	pe of Case	Hazardous "Group- J"			
4	De	tails of Previous NOC	Renewal			
5	Fir	Safety Directives Letter No	F6/DFS/MS/2021/CNG/25 dated 14/01/2021			
6	Da	te of Inspection	N/A			
7	Na	me of the In-	23/11/2023			
8	Na	ne of the Inspecting Officers	Aman Kumar Latha	ar, ADO (JWP)		
	from	ne & Designation of Officers in the building side		y. Manager, F&S, IGL		
9	Yea	ar of construction		,		
10	Ap	plicant letter No.	2013			
S.	Min	nimum standards on Fire	IGL/F&S/2023/15/94/1 dated 26/10/2023			
No	Pre	vention and Fire Safety U/R 33	NFPA/CCOE/OIS		Remarks	
1	Acc	cess to Building.	etc. requirement	s Site	NR/NMR	
				1735		
		Road width	06 m	30 m	MR	
		Gate width	-N/A-	Direct accessible from		
		Widel		road	-14/74-	
2	N	Width of internal road	-N/A-	-N/A-	-N/A-	
_	a)	nber, width, type & arrangement	of exits.	13		
	a)	Number of Staircase	1007 - 100	min eye	1 1 2 1 24 2	
		Upper floors.	-N/A-	-N/A-	N/A	
		Basement floor.	-N/A-	-N/A-	-N/A-	
	b) '	Width of Staircase		-14//-	-N/A-	
		Upper floors	-N/A-	N/A		
		Basement floor	-N/A-	-N/A-	-N/A-	
	c) 1	rotection of exits	N/A	-N/A-	-N/A-	
		Fire check door	-N/A-	projecto) a	The state of the s	
		Pressurization	-N/A-	-N/A-	-N/A-	
	d) 1	No. of continuous staircase to		-N/A-	-N/A-	
		terrace	-N/A-	-N/A-	-N/A-	
	_	Vidth of corridor	-N/A-	N/A		
	f) I	Door size	1.0 m	-N/A-	-N/A-	
3	Con	partmentation.	1.0 III	Provided	MR	
		Fire check door.	-N/A-	distributed of		
		 Sealing of electrical shafts. 	360-00-00-00-00-00-00-00-00-00-00-00-00-0	-N/A-	-N/A-	
		 Fire rating of shaft door. 	-N/A-	-N/A-	-N/A-	
		Water curtain	-N/A-	-N/A-	-N/A-	
		Fire dampers.	-N/A-	-N/A-	-N/A-	
1.	Smal	ke Management system.	-N/A-	-N/A-	-N/A-	
+		Basement		a remarkant	-1N/A-	
		Upper floors	-N/A-	-N/A-	-	
5.	Fin 1		-N/A-	-N/A-	-N/A-	
-	rire.	Extinguishers.		· MA	-N/A-	
		Total numbers	17 nos.	Dun. 1 1		
			17 HOS.	Provided	MR	
		Types	DCR e co	, DCP 75 kg trolley-	.•11	
	3		DCP & CO ₂	04, DCP 10kg - 10 &	MD	
		ISI Marking		CO ₂ 4.5 kg -03	MR	
-			ISI marked	· Park Alex	3. 1	
8 13			Dayinii 101	Provided		
				1200000000		

irst Aid Hose Reels.		17700				
Total numbers on each floor		New William	-N/A			
 Length of hose-reel hose. 	-N/A-	-N/A-	-N/A			
Nozzle Diameter	-N/A-	-N/A-	-N/A			
Automatic fire detection & alarming sy						
Gas and flame detectors in	Required	Provided	MR			
compressor packages area	Dogwired	Described				
			MR			
•	The second secon		-N/A-			
The state of the s			MR			
COV THE STATE OF THE PROPERTY OF THE			MR			
	A 15 (27 per 2 2010) - 11 per 2		MR			
- 100 V 100	-N/A-	-N/A-	-N/A-			
		1507/8	-N/A-			
	CONTROL	-N/A-	-N/A-			
Sprinkler above false centing	-NA-	-NA-	-NA-			
Internal Hydrants.						
Size of Riser / Down-comer	-N/A-	-N/A-	-N/A-			
Number of Hydrant per floor	-N/A-	-N/A-	-N/A-			
Hose box.	-N/A-	-N/A-	-N/A-			
Yard Hydrants.			-IMA-			
Total number of hydrants.	-N/A-	-N/A-	-N/A-			
Hose box.	-N/A-	-N/A-	-N/A-			
Pumping arrangements.			1,171			
Ground Level	(8)					
Discharge of main numn	-N/A-	-N/A-	-N/A-			
	-N/A-	-N/A-	-N/A-			
Number of main pumps.	-N/A-	-N/A-	-N/A-			
Jockey Pump output.	-N/A-	DEVOCATIONAL CONTRACTOR	-N/A-			
	-N/A-		-N/A-			
			-N/A-			
	5570000	0.000 (9.00)	-N/A-			
stopping.			-N/A-			
Pump house access.			-N/A-			
	-IV/A-	-18/74-	-IVIA-			
전 시민대는 게임한 소문을 받았다.	NI/A	N/A	-N/A-			
마음이는 그, 그림사이 (1995년에 BAS) 프라틴 인터뷰의 이름을 되어 하고 그림을 하는			-N/A-			
			-N/A-			
> Auto starting of pump.	-N/A-	-N/A-	-N/A-			
	-N/A-	-N/A-	-N/A-			
 Orderground tank capacity. Draw-off connection. 	-N/A-	-N/A-	-N/A-			
Fire Service Inlet.	-N/A-	-N/A-	-N/A-			
> Access to tank.	-N/A-	-N/A-	-N/A-			
Overhead tank capacity.	-N/A-	-N/A-	-N/A-			
Fuit Signages	1228///5293	Provided	MR			
	,	0.000	V. The			
	-N/A-	-N/A-	-N/A-			
Pressurization of lift shall.		-N/A-	-N/A-			
Pressurization of fitt loody.	de la	1 1	1			
	Length of hose-reel hose. Nozzle Diameter Automatic fire detection & alarming sy Gas and flame detectors in compressor packages area Location of Main Panel Location of Repeater Panel Alternate source of power Hooter's location MOEFA Public Address System Automatic Sprinkler System Basement. Upper floors Sprinkler above false ceiling Internal Hydrants. Size of Riser / Down-comer Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box. Pumping arrangements. Ground Level Discharge of main pump. Number of main pumps. Jockey Pump output. Jockey Pump output. Jockey Pump head. Standby Pump head. Standby Pump head. Auto Starting/Manual stopping. Pump house access. Terrace Level Discharge of pump. Head of pump. Power supply. Auto starting of pump. Power supply. Auto starting of pump. Power supply. Power supply. Power supply. Power off connection. Fire Service Inlet.	• Total numbers on each floor • Length of hose-reel hose. • Nozzle Diameter • Gas and flame detectors in compressor packages area • Location of Main Panel • Location of Repeater Panel • Alternate source of power • Hooter's location MOEFA Public Address System • Hooter's location MOEFA Public Address System • Basement. • Upper floors • Sprinkler System • Size of Riser / Down-comer • Number of Hydrant per floor • Number of Hydrant per floor • Hose box. Vard Hydrants. • Total number of hydrants. • Total number of hydrants. • Total number of hydrants. • Hose box. Pumping arrangements. • Ground Level Discharge of main pump. > Head of main pump. > Number of main pumps. > Jockey Pump output. > Jockey Pump head. > Standby Pump output. > Standby Pump output. > Standby Pump output. > Standby Pump output. > Standby Pump head. > Auto Starting/Manual stopping. > Pump house access. • Terrace Level > Discharge of pump. > Head of pump. > Head of pump. > Pump house access N/A- • Terrace Level > Discharge of pump. > Head of pump. > Auto Starting of pump N/A N/A-	• Total numbers on each floor • Length of hose-reel hose. • Nozzle Diameter • N/A- • Nozzle Diameter • N/A- • N/A			

20. Si the		ecial Fire Protection System for Protection of special Risk, if any.	CO ₂ Hooding system		Provided	MR
		Flow Switch Panel. PA system Panel. Battery backup Building floor plan	-N/A-	-N/A-		-N/A-
			-N/A-	-N/A	-N/A-	
			N/A-	N/A	N/A-	
			-N/A-		-N/A-	
19.	Fire	Control Room. Detector System Panel.	-N/A-	-N/A-		-N/A-
		Location	-N/A-	-10//		
		Total area	-N/A-	-14/77-		N/A-
18.	Ref	ige Area		-N/A-		N/A-
17	Stan	dby Power Supply	-N/A-	-N/A-		N/A-
	ł	Lift signage.	-N/A-	-N/A-		N/A- N/A-
	1	Fireman's switch.	-N/A-	-N/A-		N/A-
	•	Communication in lift car.	-N/A-	-N/A-		N/A-

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In View of the deemed compliance of the minimum standards of fire prevention and fire safety requirements under the rules, renewal of FSC issued vide letter no. F6/DFS/MS/2021/CNG/25 dated 14/01/2021 is recommended under the rule 37 of the Delhi Fire Service rule, 2010 under the DFS Ac 2009.

Accordingly DFA is put up for approval and signature please.

Aman Kumar Lathar ADO (JWP)

Olin Like Market

1 121/202

Director My