



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE** NEW DELHI-110001

No. F.6/DFS/MS/School/2023/SZ/ Sp/

Dated: .[.2...]2../2023

FIRE SAFETY CERTIFICATE

Certified that the Hope Hall Foundation School, located at Sector VII, R.K Puram, New Delhi 110022 comprised of Ground plus three upper floors, But School running at Ground plus two & half upper floor only was issued NOC by this department vide letter No F6/DFS/MS/2010/3077 Dated 03/11/2010. The school premises was re-inspected by officer concerned of this department on 01/12/2023 in the presence of Mr. Bhagat and observed that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with Directorate of Education Circular No F.16//Estate/CC/Fire Safety/2011/3298 to 3398 dated 01/03/2011 issued by Director of Education, Govt. of NCT of Delhi and that the building/premises is fit for occupancy class "Educational Building" Group-B, with effect from 12 12 2023 for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 12 12 /2023 at New Delhi by

DELHI FIŘE SERV

Copy to: -

1. The Principal, Hope Hall Foundation School, located at Sector VII, R.K Puram, New Delhi 110022

2. The Directorate of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054

Conditions for the validity of Fire Safety Certificate: -

All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to nonfunctional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting

4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-

6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."



1 11	Name & Address of the Building			dation Cabool Cartor V	лі РК	
		Hope Hall Foundation School, Sector VII, R.K Puram, New Delhi 110022				
2	Type of Occupancy	Educational, Group-B (School)				
3	Building Comprised of	Ground plus three upper floors but school running at Ground plus two upper floors				
4	Type of Case	Renewal				
5	Details of Previous NOC	F6/DFS/MS/2010/3077 Dated 03-11-2010 for Ground plus two and half upper floor.				
6	Fire Safety Directives Letter No	DOE Circular 01/03/2011				
7	Date of Inspection	01/12/2023				
8	Name of the Inspecting Officers	ADO (BCP)				
9	Name & Designation of Officers from the building side	Mr. Bhagat Singh				
10	Year of construction	2004				
11	Applicant letter No.	Outdoor Diary		No. 5859 dated 11-09-2023		
S. No.	Minimum standards on Fire Prevention and Fire Safety U/R 33	Old NOC Requirements		Provided at Site	Remarks MR/NMR	
1	Access to Building.				1 MD	
-	Road width	Required Required -NA-		Accessible	MR	
-1 1	Gate width			4.50m, 6.62m & 4.32m	MR	
4.9	Width of internal road			-NA-	-NA-	
2	Number, width, type & arrangement of ex	its.		fore plant and		
7.0	a) Number of Staircase		NY.	05 Nos	MR	
100 AV	> Upper floors.	01 Nos		10/22/10/2015	-NA-	
	> Basement floor.	-NA-		-NA-	-IAV-	
	b) Width of Staircase		1645	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	MR	
	> Upper floors	1.50m -NA-		1.68m, 1.25m, 1.31m, 1.53m & 1.20m	1000 A 10	
3/4-	> Basement floor			-NA-	-NA-	
2	c) Protection of exits		NA-	-NA-	-NA-	
112	> Fire check door		NA-	-NA-	-NA-	
	> Pressurization		uired	02 No	MR	
E J	d) No. of continuous staircase to terrace		VA-	-NA-	-NA-	
11/12	e) Width of corridor	-NA-		-NA-	-NA-	
- BIV	n Door size	-1				
3	Compartmentation.	-1	NA-	-NA-	-NA-	
	Fire check door. Gulian of electrical shafts.		NA-	-NA-	-NA	
	Sealing of electrical shafts. Figure of shaft door. The shaft door.		NA-	-NA-	-NA	
300	Fire rating of shaft door.		NA-	-NA-	-NA	
	Water curtain		NA-	-NA-	-NA	
	Fire dampers.	-				
4	Smoke Management system. Basement	-NA-		-NA-	-NA	
	Upper floors		NA-	-NA-	-NA	
5	. Fire Extinguishers.	- Japan		of a fight property of		
	Total numbers	Required		10 Nos	MF	
	Types	ABO	C/CO2	ABC & CO2	MI	
	ISI Marking	ISI mark		Provided	M	
6	First Aid Hose Reels.		10		EL III I III	
	Total numbers on each floor.	1	One	Provided	M	
47			30m	Provided	M	

1- 1



	a I amount on			. जात्सव
	Length of hose-reel hose. Nozzle Diameter	5mm	Provided	MR
7	Automatic fire detection & alarming system.			
	Type of detectors	-NA-	-NA-	T NA
	 Location of Main Panel 	-NA-	-NA-	-NA-
	 Location of Repeater Panel 	-NA-	-NA-	-NA-
	 Alternate source of power 	-NA-	-NA-	-NA-
	Hooter's location	-NA-	-NA-	-NA-
8	MOEFA	-NA-	-NA-	-NA-
9	Public Address System	-NA-	-NA-	-NA-
10	Automatic Sprinkler System		-	1 -1974-
	Basement	-NA-	-NA-	-NA-
	Upper floors	-NA-	-NA-	-NA-
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11	Internal Hydrants.		- Tin-	-IVA-
	 Size of Riser/Down-comer 	-NA-	-NA-	-NA-
	Number of Hydrant per floor	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
12	Yard Hydrants.		,	-MA-
	 Total number of hydrants. 	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13	Pumping arrangements.	135.4	manage children w	1
	Ground Level	or horizontogenesia	A 90-1 010-4 1016	-
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.	-NA-	-NA-	-NA-
	Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	 Auto Starting/Manual Stopping. Pump house access. 	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
	Terrace Level			
	Discharge of pump.	450 LPM	2 x 450 LPM	MR
	> Head of pump.	40m	40 mtr each	MR
	 Power supply. Auto starting of pump. 	Required	Provided	MR
14		Required	Provided	MR
14	Captive water storage for fire fighting.	-NA-	-NA-	N/A
	 Underground tank capacity. Draw-off connection. 	-NA-	-NA-	-NA-
	> Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
	Overhead tank capacity.	10,000 Lts	15,000 ltr	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.			
	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	Communication in lift car.	-NA-	-NA-	-NA-
	Fireman's switch.	-NA-	-NA-	-NA-
	Lift signage.	-NA-	-NA-	-NA-
17	Standby Power Supply	-NA-	-NA-	-NA-
18	Refuge Area			
	Total area	-NA-	-NA-	-NA-

W



1	Location	-NA-	-NA-	-NA-
Fire (Control Room.		740,500	
1	Detector system panel.	-NA-	-NA-	-NA-
	Flow switch panel.	-NA-	-NA-	-NA-
i •	PA system panel.	-NA-	-NA-	-NA-
•	Battery backup.	-NA-	-NA-	-NA-
•	Building floor plan.	-NA-	-NA-	-NA-
Speci	al Fire Protection System for th	Protection of special	-NA-	

The fire protection system provided in the building / premises were checked, tested at random and

found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F6/DFS/MS/2010/3077 Dated 03-11-20 0, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar ADO (BCP)

approved, F.T. retter is fortist