

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No.F6/DFS/MS/School/NDZ/2023/ 938

Dated: 29/12/2023

FIRE SAFETY CERTIFICATE

Certified that the Govt. Girls Sec. School located at GH-Block, Old Seemapuri, Delhi110095, comprised of ground plus one upper floor, owned/occupied by Govt. Girls Sec. School was issued Fire Safety Certificate vide letter No. F6/DFS/MS/School/20020/NDZ/512 dated 24/11/2020. The School building was re-inspected by the officer concerned of this department on 22/12/2023 in presence of Mr. Sanjeev Kumar, Estate Manager and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with the Fire Prevention and Fire Safety requirements in accordance with Circular No. F16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.2011 issued by Director of Education and that the building is fit for occupancy class "Educational" (Group-B) with effect from 29/12-/2023 for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rule 2010. Subject to conditions printed below.

Issued on 29 12 2023 at New Delhi by.

(ATUL GARG)
DIRECTOR
DELHI FIRE SERVICE

Copy to:-

- 1. The Joint Director of Education, Director of Education, Lucknow Road, Delhi-110054
- 2. The Principal, Govt. Girls Sec. School located at GH-Block, Old Seemapuri, Delhi-110095.

Conditions for the validity of Fire Safety Certificate

- The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule(1) of rule 37] along with a copy of this certificate, six months prior to its expiry
- 2. All the means of escape shall be kept free of all the type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc. may be got verified from the authorities concerned.
- This Fire Safety Certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.

		UPA-	INSPE	CTION REPO					
1	Na	ame	& address of the building	g Govt. Girls Sec. School located at GH-Block, Old Seemapuri, Delhi-110095.					
2	Building is comprised of			Ground + 01 upper floors					
3	-	_		Educational B	uilding				
4	Type of occupancy			Denewal					
5	Type of case Details of previous FSC			F6/DFS/MS/S	chool/20020/NDZ/51	2 dated			
3	De	etan	is of previous FSC	24/11/2020					
6	Fi	re s	afety directives letter no.	F16/Estate/CC/Fire Safety/2011/3298-3398 dated 01.03.2011.					
7	D	ate o	of inspection	22.12.2023					
8			of the inspecting officers	Vashwant Singh Meena ADO (L.N)					
9	N	ame	of the designation of r from the building side	Mr. Sanjeev Kumar, Estate Manager					
••	Year of construction			2001	2001				
10				Email dated 04	1/12/2023				
5.N 0	Applicant's letter no. Minimum standard of fire prevention and fire safety U/R 33			01.03.2011 Circular requirement	Provided at site	Remarks MR/NMR			
1	A	cces	s to Building:			MR			
8	A		toad width	6.0 mtrs.	6.0 mtrs.	N/A			
	B		ate width	N/A	N/A	N/A			
	6	v	Vidth of internal road	N/A	N/A	N/A			
2	N	uml	per, Width, Type and Arran	gement of Exits	s:				
ir.tt	A	IN	lumber of staircases			1 vm			
	-	a Upper floor		01 nos.	01 nos.	MR			
		"	Opper mes						
	-	-	Basement	N/A	N/A	N/A			
	В	C	Vidth of staircases		((
	Б	a Upper floor 1.50 mtrs 1.50 mtrs, 1.		1.50 mtrs, 1.70 mtr & 1.70 mtr	MR				
		1 1			\$174	N/A			
		b	Basement	N/A	N/A	.18/75			
	C	P	rotection of exits	S7/4	N/A	N/A			
		a	70 - A - A - A - A - A - A - A - A - A -	N/A N/A	N/A	N/A			
	D	N	Pressurization o. of continuous staircases	01 nos.	01 nos.	MR			
	_		terrace	1.50 mtrs.	1.50 mtrs.	MR			
	E Width of corridor F Door size			1.0 mtrs.	1.0 mtrs.	MR			
	F			1.V mus.		10 - 5-10-2			
3	Compartmentation:			NA	NA	NA			
	A Fire check door			N/A	N/A	N/A			
	B Sealing of electrical shafts C Fire rating of shaft door			N/A	N/A	N/A			
	$\overline{}$		LE LAUTHE OF SHALL GOOL			N/A			
	C			N/A	N/A	14/14			
	C D	W	ater curtain	N/A N/A	N/A N/A	N/A			
4	C D E	W Fi	ater curtain re dampers	N/A N/A	N/A N/A	The second secon			
4	C D E	Fi oke	ater curtain			The second secon			

W

M121

	Fire Extinguisher:							
	A Total numbers		09 nos.	11 nos.	MR			
1	В	Types	CO ₂ & ABC	CO ₂ & ABC	MR			
ł	C	ISI marking	ISI Marked	Provided	MR			
-		st-Aid-Hose Reel:	101111111					
6		Total numbers of each	N/A	N/A	N/A			
	A Total numbers of each floor		11/12		Notes and			
	В	Length of hose reel hose	N/A	N/A	N/A			
	C	Nozzle diameter	N/A	N/A	N/A			
7	Automatic Fire Detection and Alarming System:							
	A	Type of detectors	N/A	N/A	N/A			
	B	Location of main panel	N/A	N/A	N/A			
	C	Location of repeater panel	N/A	N/A	N/A			
	D	Alternate source of power	N/A	N/A	N/A			
	E	Hooters	N/A	N/A	N/A			
8		DEFA:	N/A	N/A	N/A			
9	J. Dente.	blic Address System:	N/A	N/A	N/A			
10	_	tomatic Sprinkler System:	JA CANALIS	1471	1			
10	Au	Basement	N/A	N/A	N/A			
	B	Upper floor	N/A	N/A	N/A			
	KS-624	[20 - 0. 4 (4 (20 (10 (10 (10 (10 (10 (10 (10	N/A	N/A	N/A			
	C	Sprinkler above false ceiling	IN/A	IN/A	IN/A			
11	In	ternal Hydrants:			1			
	A	Size of riser/down-comer	N/A	N/A	N/A			
	B	Number of hydrants per	N/A	N/A	N/A			
	1	floor		The state of the s				
	C	Hose box	N/A	N/A	N/A			
12	Y	ard Hydrants:						
	A	Total number of hydrants	N/A	N/A	N/A			
	В		N/A	N/A	N/A			
13	Pi	Pumping Arrangements:						
1		Ground level						
741	A	Discharge of main pump	N/A	N/A	N/A			
	В	Head of main pump	N/A	N/A	N/A			
	C		N/A	N/A	N/A			
	D	Jockey pump out put	N/A	N/A	N/A			
	E	Jockey pump head	N/A	N/A	N/A			
	F	Standby pump out put	N/A	N/A	N/A			
	G	Standby pump head	N/A	N/A	N/A			
	H		N/A	N/A	N/A			
		stopping	, C	1				
	I Pump house access N/A N/A N							
2	Terrace Level							
	A		N/A	N/A	N/A			
	B	The state of the s	N/A	N/A	N/A			
	C	N M SE SE HANNESSEE	N/A	N/A	N/A			
	D	Auto starting of pump	N/A	N/A	N/A			

W

4	Cap	tive Water Storage for Fire Fightin		1,,,,	Lv.		
	A	Underground tank capacity	N/A	N/A	N/		
T	В	Draw-off connection	N/A	N/A	N/A		
T	C	Fire service inlet	N/A	N/A	N/A		
t	D	Access to tank	N/A	N/A	N/A		
H	E	Overhead tank capacity	N/A	N/A	N/A		
15			N/A	N/A	N/A		
_	Exit Signage:						
16		vision of Lifts:	N/A	N/A	N/A		
	A	Pressurization of lift shaft	N/A	N/A	N/A		
	В	Pressurization of lift lobby	N/A	N/A	N/A		
	C	Communication in lift car	N/A	N/A	N/A		
	D	Firemen's grounding switch	N/A	N/A	N/A		
	E	Lift signage	N/A	N/A	N/A		
17	Sta	Standby Power Supply: N/A N/A					
18	Re	fuge Area:	N/A	N/A			
5 261	A	Total area	N/A	N/A N/A	N/A		
	B	Location	N/A	N/A			
19	Fi	re Control Room:	100000	N/A	N/A		
-	A	Detector system panel	N/A	N/A	N/A		
	B	Flow switch panel	N/A	N/A	N/A		
	C	•	N/A	N/A	N/A		
	D		N/A	N/A	N/A		
	E	Building floor plans	N/A	N/A	N/A		
20	S	pecial Fire Protection systems for rotection of special Risks, if any:	N/A	IVA	10000		

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspections.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required in Directorate of Education Circular no F16/Estate/CC/Fire Safety/2011/3298-3398 dated 01.03.2011, the FSC issued vide letter dated 24/11/2020 is recommended to be no. F6/DFS/MS/School/20020/NDZ/512 renewed.

22 12 2023

Signature of the Inspecting Officer Yashwant Singh Meena

Name:-

Designation:- ADO (L.N)