

· FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/CGHS/SZ/2024/ 04

Dated: 03 /01/2024

Delhi Fire Servi

FIRE SAFETY CERTIFICATE

Certified that the building of Ishwar C.G.H.S. Ltd. Located at Plot No-4, Sector-12, Dwarka, New Delhi having 04 blocks comprised of stilt+ six/seven upper floors upper floors was issued No Objection Certificate by this department vide letter No. F6/DFS/MS/CGHS/2001/1541, dated 01/08/2001. The premise was re inspected by the officer concerned of this department on 26/12/2023 in the presence of. Sh. Rajesh Kr. Goyal (Treasurer) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Residential Building" Group A-4 with effect from Oldow Delhi Fire Service Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 03 01 2024 at New Delhi by.

Copy to:

1. The President, Ishwar C.G.H.S. Ltd. at Plot No-4, Sector-12, Dwarka, New Delhi.

2. The Joint Director (Building) DDA, Vikas Sadan, INA, Delhi-110023.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- The trained staff should be available round the clock.
- Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. www.dfs.delhigovt.nic.in.
- The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

 Name & address of the building: Ishwar C.G.H.S. Ltd. Located at Plot No-4, Sector-12, Dwarka, New Delhi.

2. Type of Occupancy : Residential Building "A" (Apartment)

 Type of Case: Renewal 04 block= stilt + Six/Seven upper floors Interconnected between 4th & 5th floor & 6th & 7th floor

4. Details of previous NOC : F6/DFS/MS/CGHS/2001/1541, dated 01/08/2001

Fire Safety directives L. No.: F6//DFS/MS/97/CGHS/1046, dated 22/08/1997

. 6. Date of inspection : 26/12/2023

7. Name of the Inspecting Officer: Sh. Udai vir Singh ADO (DWK)

8. Name and designation of Officer

from the building side : Sh. Rajesh Kr. Goyal (Treasurer)

9. Year of Construction : 1998

10. Applicant's letter No. : Email dated-18/12/2023

| S No | Mini | mum standards on fire ention and fire safety U/R 33 | As | Per NBC | | Prov site | vided at | Remarks MR/NMI | |
|---------|--|--|-------------------|---------------------|----------|--|---------------|-------------------|--|
| 1. | | ess of building | | | 100 | | L | TD. | |
| • | • Road width | | 09 mtrs Provide | | - | | ИR | | |
| | | Gate width | 4.5 mtrs | | Provided | | | AR (old case) | |
| | | | 6 mtrs 5m to 6r | | m M | | IR (Old Case) | | |
| 2. | Num | ber, width, Type & Arrangen | nents of ex | its | | | | - | |
| | а | a. Number of staircases Upper floors Basements b. Width of staircases Upper floors | | | | ovided | MR | | |
| | 1 19 | | I Hour cath order | | | | IA I | | |
| | | | NA | | INA | | 11 | MA. | |
| | l t | | 1.25 mtr 1.14m | | 14m | n MR(Be | | ing old case) | |
| | Basements C. Protection of exits | | NA | | NA | | 1 | | |
| | | | 147 | | | | | | |
| | | Fire check door | N/A | | | N/A N | | N/A | |
| | • | Pressurization | N/A | | | | | N/A | |
| | d. No of continuous stairca | - TI 01. T- 11. | | | Provided | | MR | | |
| | | . Width Of Corridor | N/A | | | N/A | | N/A | |
| | 10.7 | Door Size | N/A | | N/A | AT AT A STATE OF THE STATE OF T | N/A | | |
| 3. | Con | partmentation | | | | N/A | i i | | |
| | Fire check door | | N/A | | | | | N/A | |
| | | Sealing of electrical shafts | | N/A | | | | N/A | |
| | Fire Rating of shaft door Water Curtain Fire Dampers | | N/A | | | | | N/A | |
| | | | N/A | N/A | | | | N/A | |
| | | | N/A | | | N/A | | N/A | |
| 4. | Smo | ke managements System | | | | | | | |
| - | Basements Upper floors | | NA | | | NA | | NA | |
| | | | 12 a/c r | 12 a/c per hour Pro | | ovided | | MR | |

| 5. | Fire Extinguishe | are | | | • | | | | | | |
|-----|----------------------------|-------------------------------|---------|--|-----------------------------|--------|---|--------|----------|------|------|
| | Total nu | | 2. | nos. each flo | SEW - | T n | | | | | |
| | Types | moers | 4793950 | | oor | | vided | | _ | M | |
| | IS mark | na | | O ₂ & ABC I marked | 74 | | 2, ABC, W | ater C | 02 | M | _ |
| 5. | First - Aid Hos | Reels | 13 | marked | | Pro | vided | | | M | R |
| | | mbers on each fl | | 01.35 | - | - T | | | | | |
| - 1 | • Length | of hose reel hose | loor | 01 No. | | Prov | 7-1 - 1-1 - | - 1- | | M | R |
| | Nozzle / | diameter | | 30 m | | 30 n | | | 1R | 4 | L |
| 7. | Automatic fire | detection and ala | | 5 mm | | 5 mr | n | M | IR . | | |
| | Type of | detectors | rming | | | | | | | | |
| | Location | of Main Panel | | N/A | N | /A | | | N/A | | |
| | Location | of Repeater Par | | N/A | 1 | | /A | | N/A | | |
| | Alternat | e source of power | nei | N/A | _ | /A | | | N/A | | |
| | Hooters | 'Location | er | N/A | _ N | /A | | Χ. | N/A | | |
| 8. | MOEFA | Location | | N/A | | - | N/A | | N/A | | |
| 9. | Public Address | System | | Required | - | rovide | 31. | | MR | 1 | |
| 10. | Automatic Spri | nkler System | | Required | Pr | rovide | d | | MR | | |
| | Baseme | nte | NA | The state of the s | Le | | | | | | |
| | Upper F | | N/A | | N. | | | | NA | | |
| | Sprinkle | er above false | N/A | | _ | /A | | | N/A | ī | |
| | ceiling | acore raise | 11/24 | | N. | /A | | | N/A | | Ī |
| 11. | Internal Hydrar | nts | | | | - | | | | | |
| | | riser/down- come | er | 100 mm | Den | vided | | | DEC | | |
| | Number | of hydrants per | floor | 1 each blo | ck | | /ided | | MR | | |
| | Hose Be | ox | | - swell blo | CK | 110 | rided | | MR | | |
| 10 | | | | 01 No. | Provi | ided | | | 1 | N.CT | _ |
| 12. | Yard Hydrants | 71 | | | | | | | | MI | K |
| | Total nu | ımber of hydrant | s | 3 Nos. | P | rovide | d | | MR | + | |
| 12 | Hose Be | 7.2- | | Required | | ovide | | | MR | + | _ |
| 13. | Pumping Arran | | | | | | | | IVIIC | + | - |
| | Ground | | | | | | | | | H | - |
| | Dischar Head of | ge of main pump |) | NA | 14 | N | A | N | IA | | |
| | > Head of | main pump | | NA' | | | A | | A | 1 | _ |
| | > Inchar | of main pumps pump out put | | NA | | | Α | | IA | - | |
| | > Jockey | pump bead | | NA | | | A | | A | 1. | |
| | > Standby | Pump out put | | NA | | | A | N | A | | |
| | > Standby | Pump Head | | NA | N. | | A | | A | | |
| | > Auto St | aring/Manual sto | ppino | NA NA | _ | | A | | A · | | |
| | ➤ Pump H | louse Access | 5 | NA NA | | _ | A | | Α | 1 | |
| | Terrace | level | | 11/1 | | | Α | N | A | | |
| | Dischar | - is that go of pump | | | 450 lpm each block Provided | | | | | Ĩ. | RRIR |
| | > Head of | the pump | | 40m | _ | rided | Provided | | 1R | 4 | |
| | > Power s | | | Required | | ided | | | 1R | 1 | |
| | | arting of pump | | Required | _ | ided | | | IR IR | | |
| 14. | Captive water S | Storage for fire fi | ghting | 7 | 1.00 | rucu | | _ IV | 1R | | _ |
| | Under g capacity | round tank | | ,000 ltrs | Prov | rided | | MR | | | |
| | > Draw o | f connection | Regi | uired | D- | ovide | 3 | 12.5 | | 1 | |
| | > Fire ser | vice inlet | | uired | | | | MR | | 1 | |
| L | > Access | | Dan | uired | _ | ovide | | MR | | 1 | _ |
| | The second second | ad Tank capacity | | | rı | ovide | 1 | MR | | | |
| | Overne | ad rank capacity | 10.0 | 00 ltr each b | lock | Prov | ided | MI | 2 | 11 | |

| | Exil Signage | Required Provided | | MR | | | | | |
|-----|--|---|-------------------|---|----------|-----|--|--|--|
| 5 | Provision of Lifts | i-i-an of Life | | | | | | | |
| 16. | Pressurization of Lift Sha | ft N/A v N/A | | N/A | N/A | | | | |
| | > Pressurization of lift lobb | | | N/A | N/A | | | | |
| | Communication in lift Ca | A. Company | Required Provided | | MR | | | | |
| | > Fireman's Grounding Sw | Required Required Required | | Provided MF | | | | | |
| | > Lift Signage | | | Provided | MR MR | | | | |
| | Standby power supply | | | Provided | | | | | |
| 17. | Refuge Area | | | | | T | | | |
| 18. | | N/A | | N/A | | N/A | | | |
| | > Total area > Location | N/A | | N/A | | N/A | | | |
| 19. | Fire control room | | | Taxia | | N/A | | | |
| | > Detector system panel | N/A | | N/A | | N/A | | | |
| | > Flow Switch Panel | N/A Required Required Required | | N/A Provided Provided Provided | | | | | |
| | > PA System Panel | | | | | MR | | | |
| | > Battery backup | | | | | MR | | | |
| | > Building Floor Plans | | | | | MR | | | |
| 20. | Special Fire Protection Systems for Protection of special Risks, if any; | | 10 | O2 fire extinguish rovided near electr | MR | | | | |

The fire protection systems provided in the building were test checked and found functional

at the time of inspection.

in view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter No. F6/DFS/MS/CGHS/2001/1541, dated 01/08/2001 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended

Signature of the Inspecting Officer, Udas Vir Name Designation ADOLDON

py of gar by

MREURO