GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/NDZ/2024/06

Dated :04./01../2024

FIRE SAFETY CERTIFICATE

Certified that the M/S Nando's (A Unit of Nandos Karnataka Restaurants Pvt. Ltd.) located at F-29, 30A, Malhotra Building, Connaught Place, New Delhi in a building comprised of Ground + Mezzanine + 02 Upper floor, Restaurant running at Ground + Mezzanine floor only. The FSC was earlier granted by this department vide letter No. F6/DFS/MS/EH/NDZ/2020/189 dated 24.12.2020. Now, the premises was re-inspected by the officer concerned of this department on 27/12/23 in the presence of Manager and found that the said premises has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building Group D Restaurant running at Ground + Mezzanine floor only, and valid up to 31.03.2026 from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued. 04 .01. 224 at New Delhi by.

Delhi Fire Service

Copy to:- .

1. The Chief Architect, NDMC, Palika Kendra, New Delhi.

 The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID No. 2023120119056 dated 19.12.23.

3. The Manager, M/S Nando's (A Unit of Nandos Karnataka Restaurants Pvt. Ltd.), F-29, 30A, Malhotra Building, Connaught Place, New Delhi.

Conditions for the validity of Fire Safety Certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- Any deviation w.r.t. Construction, use of occupancy, height of building, electric installation, set back area etc. shall be checked & verified by the concerned authority.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

8. All flammable materials used for decorations and others shall be strictly prohibited.

INSPECTION REPORT

M/S Nando's (A Unit of Nandos Karnataka 1. Name & address of the

Restaurants Pvt. Ltd.), F-29, 30A, Malhotra Building, Connaught Place, New Delhi

Assembly Building Group-D 2. Type of occupancy:-

Gr. + Mezz. + 02 upper floor, Restaurant at Gr. +

Mezzanine floor only

Renewal 3. Type of case:-

F6/DFS/MS/EH/NDZ/2020/189 dated 24.12.2020 4. Details of previous FSC:-

5. Fire safety directives No.-N/A

27/12/2023 6. Date of inspection:-

Sh. Rajinder Atwal DO (CD) & 7. Name of the inspecting officer:-Sh. Ravinder Singh ADO/CC)

8. Name & designation of officer from the building side:-

Manager

9. Year of construction:-

Old Heritage Bldg. ID No. 2023120119056 dated 19.12.23.

10. Applicant's letter No:-

No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR
	Access to Building			MR
	1) Road width	09 mtr	16 mtr. /	N/A
	2) Gate width	N/A	N/A	
	2)Width of internal road	N/A	N/A	N/A
	Number, Width Type & Arra			
2.	A. Number of staircases			
		02 No.	02 No.	MR
	1. Upper floors	N/A	N/A	N/A
	2. Basements			
	B. Width of staircase	1.5 & 1.25 mtr.	1.5 & 1.25 mtr.	MR
	1. Upper floors	N/A	N/A	N/A
	2. Basements	N/A	N/A	N/A
	C. Protection of exits	N/A	N/A	N/A
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	01	01	MR
	D. No. of continuous	OI.	G.72	
	staircase to terrace	N/A	N/A	N/A
	E. Width of corridor	2 mtr.	02 mtr. (MR
	F. Door size	Z mu.		
3.	Compartmentation	N/A	N/A	N/A
	1) Fire check door		N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	A 1// A	
4.	Smoke Management System	1 20 ACRU	N/A	N/A
	1) Basements	30 ACFR	Natural	MR
V	2) Upper floors	12 ACPH	Ivaturar	
5.	Fire Extinguishers		18 Nos.	MR
	1) Total numbers	15 Nos.		MR
	2) Types	ABC & CO2	ABC & CO2	2,122

	3) ISI marking	Required	Provided	MR	
6.	First-Aid Hose Reel	72.		12.00	
	1) Total number of eachfloor	01	01	MR	
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR	
	3) Nozzle diameter	05 mm	05 mm	MR	
7.	Automatic Fire Detection &	Alarming Sys	stem	I M	
	1) Type of detectors	Required	Provided	MR	
	2) Location of main panel	N/A	N/A	N/A	
	3) Location of repeater panel	N/A	N/A	N/A	
	4) Alternate source of power	N/A	N/A	N/A	
	5) Hooter's Location	N/A	N/A	N/A	
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	N/A	N/A	N/A	
10.	Automatic Sprinkler System				
10.	1) Basement	N/A	N/A	N/A	
	2) Upper floors	Required	Provided	MR	
	Sprinkler above false ceiling	N/A	N/A	N/A	
11.	Internal Hydrants				
	1) Size of riser/down-comer	100 mm	100 mm	MR	
	2) Number of hydrants per floor	01	01	MR	
	3) Hose box	01	01	MR	
12.	Vard Hydrants				
Adl	1) Total number of hydrants	N/A	N/A	N/A	
	2) Hose box	N/A	N/A	N/A	
13.	Pumping Arrangement				
200	1) Ground level	N/A	N/A	N/A	
	a) Discharge of main pump	N/A	N/A	N/A	
	b) Head of main pump	N/A	N/A	N/A	
	c) Number of main pump	N/A	N/A	N/A	
	d) Jockey pump out put	N/A	N/A	N/A	
	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump output		N/A	N/A	
	g) Stand by pump head	N/A	N/A	N/A	
-	h) Auto starting/Manual stopping	N/A	N/A	N/A	
	2) Terrace level				
	a) Discharge of pump	450 LPM	450 LPM	MR	
	b) Head of pump	30 mtr.	30 mtr. /	MR	
	c) Power supply	Required	Provided	MR	
	d) Auto starting of pump		Provided		
4.	Captive Water Storage for F		Flovided	MR	
	Under ground tank	N/A	I NI/A	12/4	
	capacity		N/A	NA	
-	a) Draw-off connection	N/A	N/A	N/A	
	 b) Fire service inlet 	N/A	N/A	N/A	
	 c) Access to tank 	Required			

	d) Over head tank capacity	10,000 ltr.	10,000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided /	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any: ABC & CO2	ion of special	MR	

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved, we may renew the FSC issued vide letter no. F6/DFS/MS/EH/NDZ/2020/189 dated 24.12.2020, under rule 35(6) of the Delhi Fire Service rules 2010. Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name:- Ravinder Singh

Designation :- ADO (CC)

28/14/23

بازده المامع

o por

nota)

- MA 11/30

Any h