5

FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/CGHS/SZ/2024/47

Dated: 17 10/12024

Thi Fire Serv

FIRE SAFETY CERTIFICATE

Certified that the building of Palam C.G.H.S. Ltd. Located at Plot No-07, Sector-05, Dwarka, New Delhi having 04 blocks comprised of stilt / ground + seven upper floors was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/CGHS/2019/SZ/05, dated 02/01/2019. The premise was re inspected by the officer concerned of this department on 06/01/2024 in the presence of. Sh. Manish Kr. Batra (V. President) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Residential Building" Group A-4 with effect from 17/101/2024 for a period of five years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 17/61/2024 at New Delhi by.

Copy to:

1. The President, Palam C.G.H.S. Ltd. Located at Plot No-07, Sector-05, Dwarka, New Delhi.

The Joint Director (Building) DDA, Vikas Sadan, INA, Delhi-110023.

Following fire safety directives must be adhered to:-

- All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

The trained staff should be available round the clock.

- Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. Basement shall be used as per building bye laws.

 The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. www.dfs.delhigovt.nic.in.

 The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

 Name & address of the building: Palam C.G.H.S. Ltd. Located at Plot No-07, Sector-05, Dwarka, New Delhi.

2. Type of Occupancy : Residential Building "A" (Apartment)

3. Type of Case: Renewal 04 block= stilt/ground + Seven upper floors

4. Details of previous NOC : F6/DFS/MS/CGHS/2019/SZ/05, dated 02/01/2019

5. Fire Safety directives L. No.: F6//DFS/MS/97/CGHS/731, dated 11/06/1996

6. Date of inspection : 06/01/2024

7. Name of the Inspecting Officer: Sh. Udai vir Singh ADO (DWK)

8. Name and designation of Officer

from the building side : Sh. Manish Kr. Batra (V. President)

9. Year of Construction : 2000-2004

10. Applicant's letter No. : Nil dated-27/12/2023

0	Minimum standards on fire prevention and fire safety U/R 33		As Per N/8, N/9 & N/10				Provided at site		Remarks MR/NMR	
	Access of building			1						
	Road width		.5 mtrs		Provided Provided 5.20m to 6m M		. N			
- 1	Gate width	4.5							⁄IR	
1	Width of internal road	6 m					MR (R (Being old case)		
	Number, width, Type & Arranger	nent	s of exits			y III				
- (a. Number of staircases.									
- 1	Upper floors		1 no. each block Pro		ovided		MR			
	Basements	N	IA		NA			NA		
10	b. Width of staircases									
	Upper floors	1	.25 mtr	Pre	ovided		MR			
	Basements	N	IA	NA NA	S		NA			
	c. Protection of exits									
	Fire check door	N	N/A		N/A		TN	N/A		
	Pressurization	N	N/A					I/A		
	d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size		01 each block			Provided		MR		
			N/A			N/A		IN	N/A	
			V/A		N/A			/A	***	
3.	Compartmentation						- 1.			
	Fire check door Sealing of electrical shafts		N/A			N/A N/		A		
			Required		Provided N		N	MR		
	Fire Rating of shaft door		N/A			N/A	88	N	/A	
	Water Curtain		N/A			N/A	W	N	/A .	
	Fire Dampers		N/A		(8)	N/A		N	/A	
4.	Smoke managements System									
	Basements	1	NA		NA		NA			
	Upper floors	1	12 a/c per	hour	Na	tural	Ventila	tion	MR .	
5.	Parostoro									
	Total numbers				100000000000000000000000000000000000000	Provided			MR	
1	• Types					CO2, ABC, Water Co2			MR	
	IS marking	3			Pro	rided .			MR	

N/17

	First - Aid Hose Reels			(6)					
+									
	 Total numbers on each 		01 No.		Provid	led		-	MF
	 Length of hose reel hose 	e	30 m		30 m			IR ·	
-	Nozzle diameter		5 mm		5 mm		N	íR	
	Automatic fire detection and al	arming	system		**			nicoredate	
	 Type of detectors 		N/A	N	/A			N/A	
	 Location of Main Panel 		N/A		N/A	4		N/A	
	 Location of Repeater Pa 	anel	N/A	N	/A			N/A	
	 Alternate source of pow 		N/A	N	/A			N/A	
	Hooters' Location		N/A		1	V/A		N/A	Т
8.	MOEFA		Required	P	rovided	100		MR	7
9.	Public Address System		Required		rovided			MR	1
10.	Automatic Sprinkler System		1 1.04-1.0-	- 1000					\dagger
	Basements	ŇA			NA		NA	T	
	Upper Floor	N/A			N/A		N/A		
	Sprinkler above false ce	eiling	N/A			N/A		N/A	T
11.	Internal Hydrants			A.	12				+
	Size of riser/down- com	ner	100 mm	Pro	ovided			MR	T
	Number of hydrants per		1 each blo		Provid	led		MR	T
	Hose Box	a a constitution and a second			10000				
			01 No.	Prov	ided			N	1R
12.	Yard Hydrants			.,				1 3	1
	 Total number of hydran 	its	4 Nos.		rovided			MR	\perp
	Hose Box	Required	Pr	ovided			MR	\perp	
13.	Pumping Arrangements								╀
	Ground Level		2000000		Town		100		1
	 Discharge of main pump 		NA		NA		NA		╀
	Head of main pump	NA NA		NA					
	Number of main pumps	•	NA NA		NA NA			₽	
	Jockey pump out put		NA		NA				╀
	> Jockey pump head		NA		NA NA		N.		╀
	Standby Pump out putStandby Pump Head		NA NA		NA NA		N.		⊢
	> Auto Staring/Manual st	onning			NA		N.		╁
	> Pump House Access	opping	NA NA				NA NA		
	Terrace level		NA .		III		114		\vdash
	> Discharge of pump		450 lpm ea	ach ble	ock	Provided	M	R -	+
	➤ Head of the pump		40m	Prov	50.00		M		T
	> Power supply		Required		Provided		MR		Τ
	Auto starting of pump		Required		Provided			MR	
14.	Captive water Storage for fire f	ighting							
	Under ground tank	2,00	,000 ltrs	,000 ltrs Provided			MR		
	capacity								
	Draw of connection	Req	uired	Provided			MR		
	➤ Fire service inlet		uired Provide		ovided	ded MR			
	> Access to tank	Req	uired	_	ovided		MR		
	 Overhead Tank capacity 	10,0	00 ltr each b			ed	MR		
15	Exit Signage	Req	uired Pr	rovide	d		MR	(i) (i)	L
16.	Provision of Lifts	-72	reew.	T	1/2				_
	 Pressurization of Lift Sh 	3.50	N/A	N/			N/A		\vdash
	> Pressurization of lift lob		N/A	N/			N/A		
	Communication in lift C	The state of the s	Required	IATO SKITTINO	rided		MR		
	Fireman's Grounding St	witch	Required	100000	ovided		MR		
	Lift Signage	1	Required	Pro	ovided		MR		l .

1 / 2/

1	Standby power supply	Requi	red Provided	MR					
24	Refuge Area								
3.+	> Total area .	N/A	N/A	N/A					
	> Location	N/A	N/A	N/A					
+	ri- control room								
+	> Detector system panel	N/A	N/A	N/A					
1	> Flow Switch Panel	N/A	N/A	N/A					
	> PA System Panel	Required	Provided	MR					
	Battery backup	Required	Provided	MR					
Building Floor Plans		Required	Provided	MR					
1	Special Fire Protection Systems or Protection of special Risks, f any;	Required	CO2 fire extinguisher provided near electric panel	MR I					

The fire protection systems provided in the building were test checked and found functional

at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter No. F6/DFS/MS/CGHS/2019/SZ/05, dated 02/01/2019 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended

Signature of the Inspecting Officer
Name Uda Mr. Smith
Designation Applowed

CFO (S2) | Muf 2024 Denestar M X 120

Sirfy lealers

to port of

du 89 pl

DREUGUS

JE (1)

1