GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI- 110001

No. F.6/DFS/MS/CNG/2024/SZ/53

Dated: 23./01../2024

FIRE SAFETY CERTIFICATE

Certified that M/s Indraprastha Gas Limited Retail Outlet (CNG Pump) at R. K Puram, Sector-12, New Delhi comprised of Ground Floor only having 03 cascades (01 at ground floor & 02 at roof of the office building) 03 compressor unit & 08 Dispensing units, was granted FSC by this department vide letter no. F6/MS/DFS/CNG/2021/SZ/197 Dated 30/03/2021. The premise was re-inspected by the officer concerned of this department on 10.01.2024 in the presence of Mr. Raghu Nandan Singh (Manager) of the said filling station and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Storage (CNG Pump) as above with effect from 23/01 / 2024 for a period of three years in accordance with rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010.

Issued on <u>23/01/2024</u> at New Delhi by

DELHI FIRE SERVICE

Copy to: -

1. The Joint C.P (Lic.) First Floor, PS Defence Colony, New Delhi 110049.

2. Mr. Ajay Khatri GM (Fire & Safety) (IGL) LGL Bhawan, Plot No 4, Community Centre, R. K Puram, Sector- 09, New Delhi 110049.

Conditions for the validity of Fire Safety Certificate: -

1. All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire

fighting system.

4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration

(Clause 1.4.3 of UBBL- 2016), if any.

6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.



	Name & Adda Cd		Authoritic Phys Detect		
2	Name & Address of the Building	Indraprastha Gas Ltd, Retail outlet (CNG pump) at R.K Puram, Sector 12, New Delhi			
A.V.	Type of Occupancy	Storage (CNG pump), 03 cascades (01 at GF & 02 at			
3	Building Comprised of	roof) 03 Compressor units & 08 dispensing units Ground floor only			
4	Type of Case	Renewal			
5	Details of Previous NOC		G/2021/SZ/197 Dated 30/	100 10001	
6	Fire Safety Directives Letter No				
7	Date of Inspection		G/2000/144 dated 29/03/	/2000	
8	Name of the Inspecting Officers	Mr. Rajesh Kuma	(ADO DOD)	201	
9	Name & Designation of Officers				
	from the building side	Mr. Kaghu Nanda	an Singh (Manager)		
10	Year of construction	2000			
11	Applicant letter No.	IGL/F&S/2023/1	5/57/1 Dated 20-12-2023	3	
S. No	Minimum standards on Fire	Old NOC	Provided at Site	Remarks	
1	Prevention and Fire Safety U/R 33	Requirement	tritia ili 3800 - 4	MR/NMI	
	Access to Building.	THE PERSON NAMED IN COLUMN	VALUE OF THE OWNER O		
	Road width Gate width	09 mtr	12 mtr	MR	
	Width of internal road	-NA-	-NA-	-NA-	
2	Number, width, type and arrangements	of exits	-NA-	-NA-	
	a. Number of Staircase		200 0000		
	Upper floors	01 nos.	•	11	
	Basement floor		01 nos.	MR	
	b. Width of Staircase	-NA-	-NA-	-NA-	
	A STATE OF THE STA	spring mis	en techgiarloseta 🤝		
16	Upper floors	0.70 m	1.1 m	MR (old cas	
	Basement floor	-NA-	-NA-	-NA-	
	c. Protection of exits	hog	F Josées Pamph		
	Fire check door	-NA-	-NA-	-NA-	
Me.	Pressurization	-NA-	-NA-		
	d. No. of continuous staircase to terrace	-NA-	-NA-	-NA-	
	e. Width of corridor	B(F)	-INA-	-NA-	
		-NA-	-NA-	-NA-	
7(f. Door size	1 m quinq	Provided	MR	
3	Compartmentation.	Manual desiration	Lapitye water storage	JAI.	
	Fire check door.	-NA-	-NA-	-NA-	
	Sealing of electrical shafts.	-NA-	-NA-	-NA-	
W-	Fire rating of shaft door.	-NA-	-NA-	-NA-	
и-	Fire rating of shaft door. Water curtain	-NA-	-NA-	-NA-	
	Fire rating of shaft door. Water curtain Fire dampers.				
4.	Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system.	-NA-	# OF SEE -NA-	-NA-	
	Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement	-NA-	-NA-	-NA-	
4.	Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors	-NA-	-NA-	-NA-	
	Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement	-NA- -NA-	-NA-	-NA- -NA-	
4.	Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors	-NA- -NA-	-NA-	-NA- -NA- -NA-	
4.	Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors Fire Extinguishers. Total numbers Types	-NA- -NA- -NA-	-NANANANANA- DCP/75 kg- 13, DCP/10kg	-NA- -NA- -NA- MR	
5.	Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors Fire Extinguishers. Total numbers Types ISI Marking	-NANANA- Required	-NA- -NA- -NA- -NA- 38 Nos	-NA- -NA- -NA- -NA-	
4.	Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors Fire Extinguishers. Total numbers Types	-NANANA- Required	-NANANANANANANANA-	-NANANA- MR MR	
5.	Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors Fire Extinguishers. Total numbers Types ISI Marking	-NANANA- Required	-NANANANANANANANA-	-NANANA- MR MR MR	
5.	Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors Fire Extinguishers. Total numbers Types ISI Marking First Aid Hose Reels.	-NANANANA- Required ISI Marked	-NANANANANANANANA-	-NANANA- MR MR	

7/-		19
आज़ादी ।		1-
ગન્યુન ર	नहोत्सन 🌘	
	terior in	MASS

7	Automatic Fire Detection and Alarming	system.		-
	The Change	venio ili	Provided in compressors &	
	Type of detectors Location of Main Panel	Gas & Flame	portable gas detector with staff	MR
	Mill 13 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	-NA-	-NA-	-NA-
	Location of Repeater Panel	-NA-	-NA-	-NA-
	Alternate source of power	-NA-	-NA-	-NA-
•	Hooter's location	Required	Technician room	MR
8.	MOEFA	-NA-	-NA-	-NA-
9.	Public Address System	-NA-	NA-1/2 sull	-NA-
10.	Automatic Sprinkler System		Date of Inspection	7
	Basement	-NA-	-NA-	2
	Upper floors	/A/7/7/ 4,000		-NA-
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11.	Internal Hydrants.	-NA-	noiman-NA- In tag (-NA-
TO DE			Libbireal Thates No.	11
13(17)	Size of Riser / Down-comer	-NA-	-NA-	-NA-
	 Number of Hydrant per floor 	-NA-	-NA-	-NA-
11/	Hose box.	-NA-	-NA-	-NA-
12.	Yard Hydrants.		(they same a	
	Total number of hydrants.	-NA-	1-1-16 10 0	
	Hose box.	-NA-	-NA-	-NA-
13.	Pumping arrangements.		eminus la marino de la	-NA-
25	Ground Level		 Ugnet Beers 	
	Discharge of main pump.	NA	Total Incompagn	
	N III1-C	-NA- -NA-	M. Wid-AM. Staintea	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
16-	Jockey Pump output.	-NA-	-NA-	-NA-
	Jockey Pump head.	-NA-	DOU INSHENAL	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	➤ Auto Starting/Manual Stopping.	-NA-	aumsau-NA-	-NA-
	Terrace Level	Service and and an arrange	tz-minumenta ak ya	-NA-
	Discharge of pump.	-NA-	-NA-	
	Head of pump.	-NA-	Tobit702-NA-biv/ S	-NA-
DE .	Power supply.	-NA-	-NA-	-NA-
14.	> Auto starting of pump. Captive water storage for fire-fighting.	-NA-	-NA-1003	-NA-
-			Comportmentation.	E
Ģ	 Underground tank capacity. Draw-off connection. 	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
15.	Overhead tank capacity. No Smoking signage	-NA-	-NA-	-NA-
16.	Provision of Lifts.	Required	Provided in Hindi & English	MR
4	16A4-		· Uppa floor	
	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
K	Communication in lift car.	-NA-	-NA-	-NA-
	Fireman's switch.	-NA-	-NA-	-NA-
	Lift signage.	-NA-	-NA-	-NA-
17	Standby Power Supply	Required	Provided (DG Set)	MR
18.	Refuge Area	15 H. C. B.	(= 0 00)	IVIK
	Total area	NA.	mildening-yr *	
	• Location	-NA-	I MA-	-NA-
		-NA-	-NA-	-NA-



19.	Fire Control Room.				
	Detector System Panel.	-NA-	-NA-	-NA-	
	Flow Switch Panel.	-NA-	-NA-	-NA-	
	PA system Panel.	-NA-	-NA-	-NA-	
	Battery backup Building floor plan	-NA-	-NA-	-NA-	
		-NA-	-NA-	-NA-	
20.	Special Fire Protection System for the Protection of special Risk, if any.	NA	Co2 flooding system connected through detectors provided in each compressor unit	MR	

"No Smoking" Sign boards were found displayed both in Hindi & English at conspicuous places. No loose electric wiring was seen in the premises.

The fire protection systems provided in the building were test checked at random and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under rules, renewal of the FSC issued vide letter No. F6/MS/DFS/CNG/2021/SZ/197 Dated 30/03/2021, under rules 37 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly, DFA is put up for perusal and signature please.

Signature of the Inspecting Officer Name: MR. Rajesh Kumar

Designation: ADO (BCP)

Mylly This advance date?